

AlgoHack micro:bit



ACCELEROMETER SENSING

Authors

Niranjana Meegammana

N P Vishva Kumara



AlgoHack aims to teach Computer Science and Programming to young people, initiated by Shilpa Sayura Foundation, supported by GOOGLE RISE and Computer Society of Sri Lanka.

This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/). Shilpa Sayura Foundation (www.shilpasayura.org)




Understanding Accelerometer

Accelerometers measure *acceleration* and express this as three values which we refer to as X, Y and Z. These values are "vectors" meaning they express both a magnitude (amount) and direction.

In the case of the BBC micro:bit, with the micro:bit held flat with its LED display facing upwards and the edge connector facing toward you, the X value measures the amount of acceleration to the left and right of you.

Y measures the acceleration in the direction away from you or back towards you whilst Z measures acceleration up or down. So X and Y describe acceleration in the two horizontal planes whereas Z measures acceleration in the vertical plane.



The micro:bit uses values which are in multiples of one "milli-g" i.e. one thousandth of the acceleration due to gravity. Bitty Data Logger scales the values up to be relative to g itself.

Study following program

https://makecode.microbit.org/_aAtFoHVEVDq4

//Accelerometer Game - light of LEDs by moving microbit
//Niranjan Meegammana for AlgoHack microbit club project

```
let player: game.LedSprite = null
let xgame = new gameboard()
let px = -2
let py = -2
let started = false
basic.forever(() => {
    gx = input.acceleration(Dimension.X)
    gy = input.acceleration(Dimension.Y)
    let bxv = divdecimal(gx, seg)
    let byv = divdecimal(gy, seg)
    let bx = getLed(bxv)
    let by = getLed(byv)
    let obj = game.createSprite(bx, by)
    xgame.grid[bx][by] = true
    if ((bx == px) && (by == py)) {
        for (let i = 0; i < 3; i++) {
            obj.setBrightness(0)
            basic.pause(100)
            obj.setBrightness(255)
            basic.pause(100)
            obj.setBrightness(150)
        }
    }
    else {
        px = bx
    }
})
```

```

    py = by
    obj.setBrightness(150)
  }
  let win = gamecheck()
  if (win == true) {
    xgame.score = xgame.score + 1
    basic.pause(300)
    basic.showIcon(IconNames.Diamond)
    basic.showNumber(xgame.score)
    basic.pause(300)
    init()
  }
  else {
    basic.pause(100)
  }
  basic.pause(100)
})

```

```

let gx = 0
let gy = 0
let seg = 511

```

```

//player = game.createSprite(2, 2)
function init() {
  let player: game.LedSprite = null
  let xgame = new gameboard()
}
function getLed(bxv: number) {
  let r = 2 + bxv
  return r
}
function divdecimal(n: number, m: number) {

```

```

    let s = n % m
    let p = n - s
    let q = p / m
    if (s >= (m / 2)) {
        q = q + 1
    }
    return q
}

```

```

function gamecheck() {
    let win = true
    for (let t = 0; t < 5; t++) {
        for (let u = 0; u < 5; u++) {
            if (xgame.grid[t][u] == false) {
                win = false
                break
            }
        }
        if (win == false) {
            break
        }
    }
    return win
}

```

```

class gameboard {
    public score: number
    public grid: Array<Array<boolean>>;

    constructor() {
        this.score = 0
        this.grid = [];
    }
}

```

```
    for (let i = 0; i < 5; i++) {  
        this.grid.push([false, false, false, false, false]);  
    }  
}
```



කමෙහි විෂය
කමෙහි වෙලාවක
කමෙහි තැනක
නිදහසේ ඉගෙන ගන්න
පාඩම් සහ ප්‍රශ්න

Shilpa64.lk



AlgoHack aims to teach Computer Science and Programing to young people, initiated by Shilpa Sayura Foundation, supported by GOOGLE RISE and Computer Society of Sri Lanka.

AlgoHack micro:bit



ACCELEROMETER SENSING

Niranjan Meegammana & N P Vishva Kumara