



NOKASH API_PAYIN

Documentation



API Documentation

NOKASH Payment API

Version	Authors	Quality	Date	Comments
1	FEUDJIO LIONEL	Team Dev NOKASH	January 2023	initial Document
2	FEUDJIO LIONEL	Team Dev NOKASH	April 2023	update after api version 301 was ready
3	FEUDJIO LIONEL	Team Dev NOKASH	May 2023	adding callback url
4	FEUDJIO LIONEL	Team Dev NOKASH	July 2024	adding api payin v407

NOKASH GLOBAL
July 2024



Table of contents:

I. Initiate the payment

II. response of initiate payment

III. check status



Process of collecting payments in NOKASH

Find the link of the postman collection file here: [postman collection](#)

I. Initiate the payment

This is done via the api:

http method	POST
url	<code>https://api.nokash.app/lapas-on-trans/trans/api-payin-request/407</code>
header	- content-Type: application/json
parameters	
body	• i_space_key: the key of the integrator • app_space_key: the key of the app. • payment_type: the type of payment needed ○ for CM country, use: CM_MOBILEMONEY ○ for NG country, use: NG_BANKTRANSFER • country: the iso alpha 2 of the country (only {CM, NG} are available now) • payment_method: the payment method to use for the payment; ○ for CM country, use these: MTN_MOMO, ORANGE_MONEY ○ for NG country, use these: BANK_TRANSFER; • order_id: the unique id of the transaction in your system • amount: the amount of the transaction ○ minimum for CM country is: 1 XAF ○ minimum for NG country is: 100 NGN • callback_url (optional and only for production keys): this is an endpoint you will open in your system to let us send you the status of the request when it is changed. It is a post request with this body data: id, status, amount, phone, orderId; • user_data: the information of the payer which depend on the payment type: ○ for payment_type: CM_MOBILEMONEY, set field: ■ user_phone: the payer phone number ○ for NG_BANKTRANSFER payment_type, set fields: ■ user_email: the payer email address ■ user_name: the payer name



II. get the response of initiate payment

The structure of the response is:

- **status**: the status of your request.
possible values are:
 - REQUEST_OK: process have been initiate
 - REQUEST_BAD_INFOS: you did not send an information
 - ... others are unknown errors; you may report it to us please.
- **message**: the message of the server
- **data**: the data of the response;
 - when status is not REQUEST_OK, data is null
 - when it is REQUEST_OK, data is an object.

data object structure depend on **payment_type** used when initiating the payment:

- for payment_type **CM_MOBILEMONEY** :
 - **id**: the unique id of the payment in our system (you will use it to get the status of the payment)
 - **status**: current status of the payment; possible values are: PENDING, FAILED, CANCELED, TIMEOUT, SUCCESS
 - **amount**: the amount of the payment.
 - **orderId**: the id from your system
 - **phone**: the phone number of payer
- for payment_type **NG_BANKTRANSFER**:
 - **id**: the unique id of the payment in our system (you will use it to get the status of the payment)
 - **status**: current status of the payment; possible values are: PENDING, FAILED, CANCELED, TIMEOUT, SUCCESS
 - **amount**: the amount of the payment.
 - **orderId**: the id from your system
 - **va_bank_code**: the bank code of VA generated
 - **va_bank_name**: the bank name
 - **va_account_number**: the VA generated
 - **va_expiry_date_in_utc**: expiration data of the va in utc
 - **user_name**: the payer name
 - **user_email**: the payer email



III. check status

http method	POST
url	https://api.nokash.app/lapas-on-trans/trans/310/status-request
parameter	- transaction_id : the id of the transaction
response	● status: the status of your request. possible values are: ○ REQUEST_OK: your request was proceed. ○ REQUEST_BAD_INFOS: you did not send an information ○ ... others are unknown errors; you may report it to us please. ● message: the message of the server ● data: data of the response; when the status is REQUEST_OK, data is an object which represent the transaction: ○ amount ○ status: status of the transaction; possible values are: PENDING, FAILED, CANCELED, TIMEOUT, SUCCESS ○ statusReason: a string, which is: ■ null when status is SUCCESS ■ have value when status is FAILED ○ orderId: the order id of the transaction ○ id: the id of the transaction ○ phone: the payer phone ○ user_name ○ user_email ○ user_bank_code ○ user_bank_account