Full-Stack Web Application Planning and Architecture

The first step is to choose and define a clear project concept and its goals. For example, imagine an **online bookstore** web application. Its purpose is to let users browse, search, and purchase books from various categories, with secure user accounts and order management. Key objectives might include enabling **user registration/login**, **product catalog browsing/search**, **shopping cart and checkout**, and **order history** features. The project brief should state who the users are (customers and administrators) and what main problems the app solves (e.g. finding books easily, managing inventory).

To focus development, we write *user stories* (short, user-centered descriptions). A standard format is: *"As a [type of user], I want [goal] so that [reason]"* [1]. For example:

- *"As a shopper, I want to search for books by title or author so that I can find items quickly."*
- *"As a shopper, I want to add books to my cart so I can purchase them later."*
- *"As an admin, I want to add or remove products so that the inventory stays up-to-date."*

User stories keep the focus on user value [2] [1] and form the basis for planning features. They also drive *acceptance criteria*, ensuring that each story is testable. In agile planning, stories are broken down into smaller tasks (often as part of epics/themes) [3].

Functional and Nonfunctional Requirements

Next, we list system requirements. **Functional requirements** describe *what* the system should do (features and operations) [4]. For our bookstore example, functional requirements might include:

- **User authentication:** Users must be able to register, log in/out, and reset passwords.
- **Product catalog:** Users can browse and search book listings, view details (title, author, price, description).
- **Shopping cart and checkout:** Users can add/remove items in a cart, enter payment/shipping info, and place orders.
- **Admin functions:** Admins can create, update, or delete book listings and view all orders.

In contrast, **non-functional requirements** (NFRs) describe *how well* the system performs these functions – qualities like performance, security, and reliability [4]. Typical NFRs might include:

- **Performance:** Pages should load within 2 seconds under normal traffic.
- **Scalability:** The system should handle surges (e.g. 10,000 concurrent users) without failure.
- **Security:** All sensitive data (passwords, payments) must use encryption (e.g. HTTPS/TLS) and follow industry standards.
- **Usability:** The UI should be intuitive and responsive (mobile-friendly).
- **Reliability:** Uptime should be ≥99%, with error monitoring and alerts.

For example, in an online shopping system, functional requirements include user login and order placement, while non-functional requirements include performance, security, and scalability [5]. We document these clearly, often using **bullet lists** or tables, and ask questions like "How fast should actions respond? How secure must it be?" to flesh out the details [6] [7].

Technology Stack Selection

Choosing a **technology stack** is critical and shapes how fast the app can be built and how well it will run [8]. A "tech stack" is the layered combination of tools, frameworks, languages, and platforms used to build and deploy the application [8]. Common layers include the *frontend (UI framework)*, *backend (server framework)*, *database*, and *infrastructure/hosting* [9] [10].

There are many popular stacks. For example, the **MERN stack** (MongoDB, Express.js, React, Node.js) and **MEAN stack** (Angular instead of React) are widely used JavaScript-centric stacks [11] [12]. The **LAMP stack** (Linux, Apache, MySQL, PHP) is another classic option [11]. Factors influencing stack choice include team expertise, community support, performance needs, and licensing cost [13]. For instance, MERN's advantage is a "Uniform Language" (JavaScript) across frontend and backend, simplifying development and hiring [14].

A typical stack for a web app might be:

- **Frontend:** React, Angular, or Vue.js for dynamic UI (these work with HTML/CSS and modern JS) [15] [10].
- **Backend:** Node.js/Express or Python (Django/Flask) or Java (Spring Boot) to handle business logic, API endpoints, and server-side processing [16] [10].
- **Database:** A relational DB like MySQL/PostgreSQL or a NoSQL DB like MongoDB, chosen based on data needs (e.g. structured orders vs flexible catalogs) [17] [10].
- **Infrastructure:** Cloud hosting (AWS, Azure, Google Cloud) or platform services (Heroku, Vercel) to deploy.
- **Development Tools:** Build tools (webpack, npm), version control (Git), and CI/CD pipelines (GitHub Actions, Jenkins) for team workflow [10] [18].

We might list the above as bullet points or a table. Ultimately, the stack is justified by project goals: e.g., a cloud-native approach for scalability, or an all-JavaScript stack for rapid prototyping. We document **why** each choice is made, e.g. MERN for full-stack JS, or PostgreSQL for ACID transactions. When assessing a stack, critical considerations include scalability (can it grow?), maintainability, performance, security, developer availability, and cost [13].

User Flowcharts and Wireframes

To design the user experience, we create **user flow diagrams** and **wireframes**. A **user flow** (or flowchart) is a *visual roadmap of the user's journey* through the app [19]. It lays out the steps a user takes to complete a task (from the entry point to the end), including decision points (e.g. login vs. guest, add to cart vs. continue shopping). According to Figma's UX guidelines, a user flow "lays out the steps [the user] takes to complete a specific task… from the first spark of 'I need this' to the final 'I'm done'" [19]. Flows are often drawn with standard symbols: *rectangles* for user actions (like "click button"), *diamonds* for decisions, and *arrows* to indicate sequence [20] [21].



Figure: Example wireflow combining interface mockups (left) with decision blocks (right) to visualize user interactions. A **wireflow** (combining "wireframe" + "flow") merges page layouts with flowchart symbols to give a holistic view. In the figure above (adapted from Visily), the green boxes represent UI screens and the yellow diamonds decision points. This shows, for example, a user named Emma starting on a search page, selecting a flight (yes/no), and proceeding to payment if confirmed [22] [20] .

We also create **wireframes** of the key pages (a low-fidelity UI sketch showing element layout). A wireframe is the "skeleton of your digital project" [23] : it defines where headers, buttons, text fields, images, etc. go, without styling details. Wireframes help **clarify structure** and communicate the interface design in simple sketches [24] . For example, we might wireframe the homepage (with a search bar and category list), a product detail page, a shopping cart page, and an order confirmation page. These wireframes can be drawn by hand or using digital tools (Figma, Sketch, Balsamiq, etc.) and should include annotations or labels for key components.

Flowcharts and wireframes often inform each other: the flowchart defines what screens and paths exist, and the wireframes define what those screens look like. In practice, we would iterate on these diagrams. For instance, if a flow shows a "Checkout" decision, we ensure our wireframe has all the necessary checkout fields and error messages. As the author of one UX blog notes, creating a flow diagram "became an invaluable guide" to ensure the UI design aligned with the intended user journey [25] .

Technical Architecture and API Design

Next we design the high-level system architecture. An **architecture diagram** is essentially a *blueprint of the software system*, showing its main components, how they connect, and how data flows [26] . Typically, a full-stack web app uses a **three-tier architecture** [27] :

- **Frontend (Client layer):** The user interface running in the browser or mobile app. It could be a React/Angular SPA or a server-rendered UI. It handles displaying pages and making HTTP requests to the backend.

- **Backend (Application layer):** The server side (e.g. Node.js/Express) that implements business logic and API endpoints. It processes requests from the frontend, applies rules (auth, validation), and interacts with databases or external services.
- **Database (Storage layer):** A persistent datastore. For example, a PostgreSQL or MongoDB instance holding user accounts, products, orders, etc.

Other components might include a **cache** (e.g. Redis) between the app and database for performance, an **authentication service** (OAuth provider, JWT issuer), or **external APIs** (payment gateway, email service). A load balancer or cloud server could sit in front of the backend for scalability. All these are depicted in an architecture diagram.



Figure: Simplified web application architecture diagram showing user devices (laptop/mobile) connecting to a backend server with cache and database layers [26]. In this example, clients send requests to the **backend server**, which may use a **cache server** (to speed up repeated reads) before querying the **database**. Arrows represent data/HTTP flows. The diagram clearly separates concerns: the UI is decoupled from the data layer.

When documenting the architecture, we explain each component. For instance, we might note that "a Redis cache is used between the server and database to reduce query load and improve performance." We also describe **connectors**: the diagram's arrows represent protocols (e.g. HTTPS between client and API, SQL/ODBC between app and database) [28]. As vFunction emphasizes, architecture diagrams help stakeholders grasp the system's organization and dependencies, serving as important documentation for development and maintenance [29]. They also aid planning for scalability and security by showing where bottlenecks or sensitive data flows might occur [29] [30].

We also define **API endpoints** (the backend routes the frontend will call). Following RESTful best practices, endpoints are resource-based nouns with standard HTTP verbs (per Azure guidelines) [31]. For example, our bookstore might have endpoints like:

- `POST /api/auth/register` and `POST /api/auth/login` for user authentication.

- `GET /api/books` (list all books) and `GET /api/books/{id}` (book details).
- `POST /api/cart` (add items to cart) and `GET /api/cart/{userid}` (view user's cart).
- `POST /api/orders` (place an order) and `GET /api/orders/{orderId}` (check order status).
- `GET /api/users/{id}/orders` (list orders for a user), demonstrating a nested resource path [32].

Each endpoint's functionality is documented (parameters, request/response schema). We would specify which are public versus requiring authorization (e.g. login creates a JWT token for secured routes). Clear API documentation (even auto-generated via tools like Swagger) is part of the deliverable rationale, ensuring that frontend and backend teams can coordinate.

Database Schema Design

We design a database schema that supports the data needs identified by our use cases. Common entities for an e-commerce app include **User**, **Product (Book)**, **Order**, and possibly **Cart**. Using a relational database (e.g. PostgreSQL), we draw an ERD or class diagram. For example, based on typical models:

- **User** table: `UserID (PK), Name, Email, PasswordHash, Address, etc.`
- **Product** table: `ProductID (PK), Title, Author, Price, Description, InventoryCount, etc.`
- **Order** table: `OrderID (PK), UserID (FK→User.UserID), OrderDate, TotalAmount, etc.`
- **OrderItem** table: `OrderItemID (PK), OrderID (FK→Order.OrderID), ProductID (FK→Product.ProductID), Quantity, PriceAtPurchase`.
- **CartItem** table (if using persistent carts): `CartItemID (PK), UserID (FK), ProductID (FK), Quantity`.

These relationships capture facts like: each **User** can have many **Orders** (one-to-many), and each **Order** can include multiple products (via the OrderItem linking table), reflecting a many-to-many between orders and products [33]. For example, the `Order` table might be defined in SQL as:

```
CREATE TABLE Order (
  OrderID INT PRIMARY KEY,
  UserID INT NOT NULL,
  OrderDate TIMESTAMP,
  -- other fields --
  FOREIGN KEY (UserID) REFERENCES User(UserID)
);
```

And an `OrderItem` table:

```
CREATE TABLE OrderItem (
  OrderItemID INT PRIMARY KEY,
  OrderID INT NOT NULL,
  ProductID INT NOT NULL,
```

```
  Quantity INT,
  PriceAtPurchase DECIMAL(10,2),
  FOREIGN KEY (OrderID) REFERENCES Order(OrderID),
  FOREIGN KEY (ProductID) REFERENCES Product(ProductID)
);
```

[34].

We document these tables and their fields. Key relationships include User–Order (1-to-many), Order–OrderItem (1-to-many), and Product–OrderItem (1-to-many) [33]. If using a NoSQL database instead (like MongoDB), we would design collections (e.g. embedding cart items in a user document), but for this example we assume a relational design.

Best practices in schema design are noted. We apply **normalization** to eliminate redundant data (e.g. not storing user data in every order row) [35]. We plan **indexes** on columns frequently queried (e.g. `ProductID` or `UserID`) to speed up lookups [35]. We also consider data integrity: foreign keys enforce relationships. For scalability, we might plan caching layers or even sharding if needed. Security measures (parameterized queries, no plaintext passwords) are documented. As GFG advises, we include **backup/replication** strategy, logging, and monitoring to ensure resilience [35]. A well-designed schema supports the app's functionality, maintainability, and performance.

Compilation and Rationale

Finally, we compile all written plans and diagrams into one organized document (PDF or DOCX). It should begin with the **project brief** (purpose, scope, features) and move through each section: user stories, requirements, flows, wireframes, architecture, and database. Each diagram (flowchart, wireframe, architecture diagram, ERD) should be clearly labeled (e.g. "Figure 1: User Signup Flow") and briefly explained in the text. For every major design decision, we include a rationale. For example, we justify the chosen tech stack ("We selected React/Node due to the team's JS expertise and its large ecosystem" [14]), or an architecture pattern ("Using a separate cache server reduces database load during peak searches").

Clarity of presentation is crucial: use headings, bullet lists, and tables to make the document easy to scan. Each section flows logically, building from concept to detailed design. According to best practices, architecture diagrams serve as vital documentation and reference [29], so we ensure ours are neat and accurate. In summary, the submission will demonstrate a well-thought-out concept, detailed and labeled diagrams (user flows, UI wireframes, system architecture, and ERD), plus clear explanations of how each part supports the project's goals.

Sources: We based these recommendations on agile and UX design guides [2] [19], software architecture best practices [26] [29], and database design tutorials [34] [35] to ensure a comprehensive, industry-aligned approach.

---

[1] [2] [3] User stories with examples and a template | Atlassian
https://www.atlassian.com/agile/project-management/user-stories

[4] [5] [6] [7] Functional and Non Functional Requirements - GeeksforGeeks
https://www.geeksforgeeks.org/software-engineering/functional-vs-non-functional-requirements/

[8] [9] [10] [13] [18] What are Tech Stacks? Choosing the Right One - GeeksforGeeks
https://www.geeksforgeeks.org/blogs/what-are-tech-stacks-choosing-the-right-one/

[11] [14] MEAN vs MERN vs LAMP: Full Stack Comparison for Web Dev
https://appinsnap.com/blogs/mean-vs-mern-vs-lamp

[12] MERN Stack vs. Other Stacks: A Comparative Analysis - GeeksforGeeks
https://www.geeksforgeeks.org/mern/mern-stack-vs-other-stacks-a-comparative-analysis/

[15] [16] [17] [27] Common Architectural Patterns in Full-Stack Web Development | by Mai | Medium
https://medium.com/@vmaineng/common-architectural-patterns-in-full-stack-web-development-24b6adbeadd6

[19] What Is a User Flow? | Figma
https://www.figma.com/resource-library/user-flow/

[20] [25] How I used Wireframes & User Flow Diagrams to Plan My First Web App | by nicki.dev | Medium
https://medium.com/@op_the_eye/how-i-used-wireframes-user-flow-diagrams-to-plan-my-first-web-app-c8310a032b3c

[21] [22] Wireflow: Examples, Benefits & Wireflow vs. Wireframe Guide - Visily
https://www.visily.ai/blog/wireflow-streamline-design-process/

[23] [24] What is a wireframe? A guide for non-designers
https://balsamiq.com/blog/what-are-wireframes/

[26] [28] [29] [30] Architecture Diagram Basics & Best Practices - vFunction
https://vfunction.com/blog/architecture-diagram-guide/

[31] [32] Web API Design Best Practices - Azure Architecture Center | Microsoft Learn
https://learn.microsoft.com/en-us/azure/architecture/best-practices/api-design

[33] [34] [35] How to Design a Database for Web Applications - GeeksforGeeks
https://www.geeksforgeeks.org/dbms/how-to-design-a-database-for-web-applications/