```
#Q1:
# To find the ultimate moment carrying capacity of singly r/f beam
fck = float(input("Enter the value of characteristics compressive strength:"))
fy= float(input("Enter the grade of steel:"))
Es = float(input("Enter the value of Modulus of Elasticity of steel:"))
b= float(input("Enter the value of width:"))
d= float(input("Enter the value of effective depth:"))
d1 = float(input("Enter the value of bar diameter (d1):"))
d2 = float(input("Enter the value of bar diameter (d2):"))
n=int(input("Enter the number of bars:"))
Ast1= (n*0.7854*d1*d1)
Ast2= (n*0.7854*d2*d2)
print("The value of area of steel (Ast1):", Ast1)
print("The value of area of steel (Ast2):", Ast2)
# Total area of steel
Ast = Ast1 + Ast2
print("The value of area of steel (Ast):", Ast)
# Neutral Axis factor
ku = 0.0035/(0.0055 + (fy/(1.15*Es)))
print("The value of Neutral axis factor (ku):", ku)
# Moment of Resistance factor
Ru= 0.36*fck*ku*(1-(0.42*ku))
print("The value of Moment of Resistance factor (Ru):", Ru)
# Maximum Neutral Axis
xumax = ku*d
print("The value of maximum neutral axis (xumax):", xumax)
xu = (0.87*fy*Ast)/(0.36*fck*b)
print("The value of Actual Neutral Axis (xu):", xu)
if xumax>xu:
    print("UNDER REINFORCED")
else:
    print("OVER REINFORCED")
# By Comparing
x = float(input("Enter the value of Neutral Axis:"))
# Moment of Resistance
Mu = 0.36*fck*x*b*(d-(0.42*x))*10**6
print("The value of Moment of Resistance is:", Mu)
```

```
Enter the value of characteristics compressive strength:20
Enter the grade of steel:415
Enter the value of Modulus of Elasticity of steel:200000
Enter the value of width:230
Enter the value of effective depth:400
Enter the value of bar diameter (d1):20
Enter the value of bar diameter (d2):16
Enter the number of bars:2
The value of area of steel (Ast1): 628.32
The value of area of steel (Ast2): 402.1248
The value of area of steel (Ast): 1030.4448
The value of Neutral axis factor (ku): 0.4791666666666667
The value of Moment of Resistance factor (Ru): 2.7556874999999996
The value of maximum neutral axis (xumax): 191.66666666666669
The value of Actual Neutral Axis (xu): 224.66100086956521
OVER REINFORCED
Enter the value of Neutral Axis:191.666667
The value of Moment of Resistance is: 101409300131927.98
```

TEJAS KHOMANE (21CV044)

```
#Q2:
# Design of Slab
# Given Data
# Effective span is already given in question
span= float(input("Enter the value of effective span in meters:"))
b= float(input("Enter the value of width of slab in mm:"))
bs= float(input("Enter the value of Support width in meters:"))
fck = float(input(" Enter the value of Characteristics Compressive Strength:"))
fy = float(input("Enter the value of grade of steel:"))
Es = float(input("Enter the value of Modulus of Elasticity is:"))
LL = float(input("Enter the value of live load:"))
FF = float(input("Enter the value of Floor finish:"))
Density = float(input("Enter the value of Density of RCC:"))
# Design Constants
# Neutral Axis factor
ku = 0.0035 / ((0.0055) + (fy / (1.15 * Es)))
print("The value of Neutral Axis Factor (ku) is:", ku)
# Moment of Resistance Facor
Ru= 0.36*fck*ku*(1-(0.42*ku))
```

```
print("The value of Moment Resistance factor (Ru) is:", Ru)
# Assuming pt 0.5 from fig 4 from IS 456 2007 page no.38
fs=float(input("Enter the value of Steel Stress of Service:"))
# From ... find out the Modification Factor
MF= float(input("Enter the value of Modification Factor:"))
# ... Select span/d Ratio
... =float(input("Enter the value of span/d ratio:"))
# Correction factors
k1=float(input("Enter the value of correction factor if span> 10m (k1):"))
k2= float(input("Enter the value of Tension r/f correction factor (k2):"))
k3= float(input("Enter the value of Compression r/f correction factor (k3):"))
k4= float(input("Enter the value of correction factor in case of flanged section (k4):"))
# Effective depth
d1= (span*1000)/(... *k1*k2*k3*k4)
print("The value of effective depth as per deflection criteria is:", d1)
# Define Effective depth and overall depth Assuming value of cover
d = float(input("Enter the value of effective depth in mm (d):"))
D= float(input("Enter the value of overall depth in mm (D):"))
# Load Calculations
# Self weight of slab
DL = D*Density/1000
print("The Dead Load is ", DL)
# Total load is
Factor=float(input("Enter the value of partial Safety factor is:"))
TL = DL + LL + FF
print("The value of total load is:", TL)
Wu=Factor*TL
print("Wu=", Wu)
# Bending Moment Calculations (Mu)
Mu= Wu*span*span/8
print("The Value of Bending Moment (Mu) is ", Mu)
# Check for effective depth
d2= (Mu*1000000/(Ru*b))**0.5
print("The value of Effective depth as per Moment criteria:", d2)
if d2>d:
    print("Revise the Depth.")
else:
    print("SAFE")
d = float(input ("Enter the value of Effective depth in mm (d):"))
print("Minimum Steel Calculations")
Astmin = 0.12*b*D/100
print("The value of Minimum steel is:", Astmin)
print("Main Steel calculations")
Ast=((0.5*fck*b*d)/(fy))*(1-((1-((4.6*Mu*1000000)/(fck*b*d*d)))**0.5))
print("Ast:", Ast)
print("Check for Ast")
if Ast<Astmin:
    print("Take Ast=Astmin")
else:
    print("Ast>Astmin, Hence SAFE")
dia1 = float(input("Enter the value of bar diameter for main steel:"))
dia2 = float(input(" Enter the value of bar diameter for Distribution steel:"))
#Area of bar
ao1 = 0.7854* dia1* dia1
print("The Value of Area of main steel bar (ao1):", ao1)
ao2= 0.7854* dia2*dia2
print("The Value of Area of main steel bar (ao2):", ao2)
# Sapcing Calculations
Spacing1 = ao1*b/Ast
print("The sapcing for main steel bars is:", Spacing1)
Spacing2 = ao2*b/Astmin
print("The sapcing for distribution steel bars is:", Spacing2)
print("Check 1 for main steel")
if Spacing1>300:
    print("UNSAFE")
else:
    print("SAFE")
    print("Check 2 for main steel")
if Spacing1> 3*d:
    print("UNSAFE")
else:
    print("SAFE")
    print("Check 1 for Distribution steel")
if Spacing1>300:
    print("UNSAFE")
else:
    print("SAFE")
```

```
    print("Check 2 for Distribution steel")
if Spacing1> 5*d
    print("UNSAFE")
else
    print("SAFE")
    print ("Approximated values of Spacing")
s1=float(input("Enter the value of spacing of main bars "))
s2=float(input("Enter the value of spacing of distribution bars "))
Astprovided=Ab*B/s1
print("The provided steel area for main bars at section in mm^2 is:", Astprovided)
Astprodist=Ab2*B/s2
print("The provided steel area for distribution bars at section in mm^2 is: ", Astprodist
# Check for Shear
Vu = (wu*span/2)-(wu*((bs/2)+d/1000))
print("The value of Sf at a Section is:", Vu)
Sstress = (Vu*1000)/(B*d)
print("The value of shear stress is :", Sstress)
# from table 20 IS 456 :2007 page 73
Sstressmax = float(input("Enter the value of maximum shear stress: "))
if Sstress>Sstressmax
    print("Crushing will happen")
else
    print("SAFE")
#Percentage Steel
pt =(100*Ast)/(B *d*120
print("Enter the value of percentage steel is :", pt)
# from table 19 IS 456 :2007 page 73
Ss= float(input("Enter the value of Shear Stress is:"))
k= float(input("Enter the value of Depth factor:"))
Shear=k*Ss
print("The value of shear at section is", Shear)
if Sstress>Shear:
    print("Shear Reinforcement Required")
else:
    print("Shear Reinforcement not Required, SAFE")
# Check for Deflection
ActDEF = span*1000/d
print("The value of span/d is:", ActDEF)
# Actual Deflection
MaxDEF = 5*MF*k1*k2*k3*k4
print("The permissible deflection is:", MaxDEF)
if MaxDEF>5.d:
    print("SAFE")
else:
    print("UNSAFE")
# Check for Anchorage Length
M1 = 0.87*fy*Ast*(d*(fy*Ast)/(fck*b))
print("The value of Moment (M1)", M1)
lo = 8*dia1
La = 1.3*(M1/Vu)+lo
print("The value of Anchorage length is:", La)
# Development Length
bonds = float(input("Enter the value of Bond Stress:"))
Ld = 0.87*fy*dia1/4*bonds*1.6
print("The value of Development length is:", Ld)
if La>Ld:
    print("SAFE")
```

```
Enter the value of effective span in meters:3
Enter the value of width of slab in mm:1000
Enter the value of Support width in meters:0.23
 Enter the value of Characteristics Compressive Strength:20
Enter the value of grade of steel:415
Enter the value of Modulus of Elasticity is:200000
Enter the value of live load:4
Enter the value of floor Finish:1.8
Enter the value of Density of RCC:25
The value of Neutral Axis Factor (ku) is: 0.4791666666666667
The value of Moment Resistance Factor (Ru) is: 2.7556874999999996
Enter the value of Steel Stress of Service:240
Enter the value of Modification Factor:1.2
Enter the value of span/d ratio:20
Enter the value of Correction Factor if span> 10m (k1):1
 Enter the value of Tension r/f correction factor (k2):1
Enter the value of Compression r/f correction factor (k3):1
 Enter the value of correction factor in case of flanged section (k4):1
The value of effective depth as per deflection criteria is: 125.0
Enter the value of Effective depth in mm (d):130
Enter the value of Overall depth in mm (D):150
```

```
The Dead load is: 3.75
Enter the value of partial Safety factor is: 1.5
The value of total load is: 9.55
Wu= 14.325000000000001
The Value of Bending Moment (Mu) is: 16.115625
The value of Effective depth as per Moment criteria: 24.182918883998223
SAFE
Enter the value of Effective depth in mm (d):130
Minimum Steel Calculations
The value of Minimum steel is: 180.0
Main Steel calculations
Ast: 1909.7862604263207
Check for Ast
Ast>Astmin, Hence SAFE
Enter the value of bar diameter for main steel:10
 Enter the value of bar diameter for Distribution steel:8
The Value of Area of main steel bar (am1): 78.54
The Value of Area of main steel bar (am2): 50.2656
The sapcing for main steel bars is; 41.125020065679 98
The sapcing for distribution steel bars is; 279.25333333333333
Check 1 for main steel
SAFE
Check 2 for main steel
SAFE
Check 1 for Distribution steel
SAFE
Check 2 for Distribution steel
SAFE
Approximated values of Sapcing:
Enter the value of spacing of main bars:210
Enter the value of spacing of distribution bars:270
The provided steel area for main bars at section in mm^2 is: 374.0
The provided steel area for distribution bars at section in mm^2 is:  186.16888888889
The value of SF at a Section is: 21.702375
The value of shear stress is: 0.16694134615384615
Enter the value of maximum Shear stress:2.8
SAFE
```

(21CV044)