
UPI API

Integration Kit

#	API Name	Description	Response Pattern
1. Utility API			
1.1	List PSP	Retrieve list of Payment Service Providers	Synchronous — direct response
1.2	List Bank (List Account Providers)	Retrieve supported banks and UPI versions	Synchronous — direct response
1.3	List Key	Retrieve cryptographic key list for PSP	Synchronous — direct response
1.4	List Verified Entity	Retrieve list of verified entity addresses (VAE)	Synchronous — direct response
2. Account Management			
2.1	Account List	Fetch bank accounts linked to a payer VPA	Async — Ack + Callback
2.2	OTP Request	Trigger OTP for UPI PIN setup or account linking	Async — Ack + Callback
2.3	VPA creation	Create VPA for customer	Async — Ack + Callback
2.4	Reg Mobile	Register a mobile device for UPI transactions	Async — Ack + Callback
2.5	Set Credentials	Set or update UPI PIN / credentials for an account	Async — Ack + Callback
2.6	VPA Credentials	Create a UPI Virtual Payment Address (VPA)	Async — Ack + Callback
3. Transaction API			
3.1	collectPayeeVPA	Send collect request to payee VPA	Async — Ack + Callback
3.2	collectPayeeAccount	Send collect request using account number + IFSC	Async — Ack + Callback
3.3	Requestpay (Pre-approval)	Initiate pre-approved pay request (approvedFlag=A)	Async — Ack + Callback
3.4	Requestpay	Initiate push payment with MPIN authorisation	Async — Ack + Callback
3.5	Confirm / Reject	Confirm or reject a pre-approved payment	Async — Ack + Callback
3.6	Intent Payment	Initiate UPI payment via intent (app-to-app redirect)	Synchronous — direct response
3.7	Dynamic QR	Generate a dynamic QR code for UPI payment	Synchronous — direct response
3.8	Refund (raiseRefund)	Raise a refund for a completed transaction	Async — Ack + Callback
3.9	Balance Enquiry	Query account balance for a UPI registered account	Async — Ack + Callback
3.10	VPA Validate (reqValAddr)	Validate a UPI Virtual Payment Address	Async — Ack + Callback
4. Mandate Management			
4.1	Initiate Mandate	Create a new UPI mandate (recurring debit instruction)	Async — Ack + Callback

#	API Name	Description	Response Pattern
4.2	Get Pending Mandate	Retrieve pending mandates awaiting approval by payer	Synchronous — direct response
4.3	Approve / Reject Mandate	Approve or reject a pending mandate request	Async — Ack + Callback
4.4	Get All Mandates	Retrieve all mandates (active/paused/revoked) for a payer VPA	Synchronous — direct response

1. Utility API

1.1 List PSP

Request Parameters

Key: **Y** = **Mandatory** **N** = Non-Mandatory **N*** = *Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
type	Y	String	Fixed	Type of list requested	Value: PspList

Sample Request Body

```
{
  "requestId": "REQDEV10001",
  "tpapId": "M000025",
  "type": "PspList"
}
```

Response Parameters

Field	Datatype	Description
PspList.Psp[].name	String	Display name of the PSP (e.g. HDFC, ICICI)
PspList.Psp[].active	String	Active status of PSP; Y = Active, N = Inactive
PspList.Psp[].codes	String	Comma-separated PSP handle codes (e.g. hdfcgold,hdfcsilver)
PspList.Psp[].url	String	URL of the PSP
PspList.Psp[].spocName	String	Name of the PSP SPOC contact
PspList.Psp[].spocEmail	String	Email address of the PSP SPOC
PspList.Psp[].spocPhone	String	Phone number of the PSP SPOC
PspList.Psp[].lastModifiedTs	String	Timestamp of last modification; null if not available
PspList.Psp[].VersionSupported[].no	String	UPI version number (e.g. 1.0, 2.0, 2.1)
PspList.Psp[].VersionSupported[].description	String	Description of the UPI version
PspList.Psp[].VersionSupported[].mandatory	Boolean	true if version is mandatory; null if optional
Status	String	Response status; SUCCESS or FAILURE
requestId	String	Echo of the requestId sent in the request
responseCode	String	Response code; 00 = Success
responseMessage	String	Human-readable response message

Sample Response

```
{
  "PspList": {
    "Psp": [
      {
        "VersionSupported": [
          { "description": "UPI 1.0 BASE VERSION", "mandatory": true, "no": "1.0" },
          { "description": "UPI 2.0", "mandatory": true, "no": "2.0" },
        ]
      }
    ]
  }
}
```

```

    { "description": "MANDATE", "mandatory": null, "no": "2.1" },
    { "description": "REFUND", "mandatory": null, "no": "2.2" },
    { "description": "AADHAAR", "mandatory": null, "no": "2.3" }
  ],
  "active": "Y",
  "codes": "hdfcgold,hdfcsilver",
  "lastModifiedTs": null,
  "name": "HDFC",
  "spocEmail": "support@hdfc.com",
  "spocName": "HDFC Support",
  "spocPhone": "9876543210",
  "url": "https://hdfc.com"
}
},
"Status": "SUCCESS",
"requestId": "REQDEV10001",
"responseCode": "00",
"responseMessage": "Get Psp List Successful"
}

```

1.2 List Bank (List Account Providers)

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
type	Y	String	Fixed	Type of list requested	Value: BankList

Sample Request Body

```

{
  "requestId": "REQDEV10001",
  "tpapId": "M000025",
  "type": "BankList"
}

```

Response Parameters

Field	Datatype	Description
BankDetail	Array	List of bank objects
BankDetail.AccProvName	String	Account provider (bank) name
BankDetail.IIN	String	Issuer Identification Number
BankDetail.ifsc	String	IFSC code of the bank
BankDetail.mobRegFormat	String	Mobile registration format (nullable)
BankDetail.versupported	Array	List of supported UPI versions
BankDetail.versupported.version	String	UPI version number
BankDetail.versupported.description	String	Description of the version
Status	String	Overall status of the response
requestId	String	Echo of the requestId sent in the request
responseCode	String	Response code (e.g. 00 = Success)
responseMessage	String	Human-readable response message

Sample Response

```
{
  "BankDetail": [{
    "AccProvName": "HDFC",
    "IIN": "901345",
    "ifsc": "11111",
    "mobRegFormat": null,
    "versupported": [
      { "version": "1.0", "description": "UPI 1.0 BASE VERSION" },
      { "version": "2.0", "description": "UPI 2.0: ALL TAG LEVEL CHANGES" },
      { "version": "2.1", "description": "MANDATE" }
    ]
  }],
  "Status": "SUCCESS",
  "requestId": "REQDEV10001",
  "responseCode": "00",
  "responseMessage": "Get Banks List Successful"
}
```

1.3 List Key

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
type	Y	String	Fixed	Type of list requested	Value: KeyList

Sample Request Body

```
{
  "requestId": "REQDEV10001",
  "tpapId": "M000025",
  "type": "KeyList"
}
```

Response Parameters

Field	Datatype	Description
KeyList.keyList[].code	String	Short identifier for the key (e.g. K1, K2)
KeyList.keyList[].keyValue	String	Actual key value string
KeyList.keyList[].ki	String	Key index or version identifier
KeyList.keyList[].owner	String	Owner/issuer of the key (e.g. HDFC, ICICI)
KeyList.keyList[].type	String	Encryption type; AES or RSA
Status	String	Response status; SUCCESS or FAILURE
requestId	String	Echo of the requestId sent in the request
responseCode	String	Response code; 00 = Success
responseMessage	String	Human-readable response message

Sample Response

```
{
  "KeyList": {
    "keyList": [
      { "code": "K1", "keyValue": "ABCD1234EFGH5678", "ki": "1", "owner": "HDFC", "type": "AES" },
      { "code": "K2", "keyValue": "XYZ9876LMNOP4321", "ki": "2", "owner": "ICICI", "type": "RSA" }
    ]
  },
}
```

```

"Status": "SUCCESS",
"requestId": "REQDEV10001",
"responseCode": "00",
"responseMessage": "Get Key List Successful"
}

```

1.4 List Verified Entity

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
type	Y	String	Fixed	Type of list requested	Value: VerifiedEntityList

Sample Request Body

```

{
  "requestId": "REQDEV10001",
  "tpapId": "M000025",
  "type": "VerifiedEntityList"
}

```

Response Parameters

Field	Datatype	Description
VaeList.VaeList[].addr	String	UPI VPA of the verified entity (e.g. lic@hdfc)
VaeList.VaeList[].name	String	Display name of the verified entity
VaeList.VaeList[].logo	String	Logo identifier or image reference for the entity
VaeList.VaeList[].url	String	URL of the verified entity; may be empty
VaeList.VaeList[].key.code	String	Key owner code (e.g. NPCI)
VaeList.VaeList[].key.keyValue	String	Base64-encoded public key value
VaeList.VaeList[].key.ki	String	Key index/date identifier (e.g. 20260325)
VaeList.VaeList[].key.type	String	Key type; PKI
Status	String	Response status; SUCCESS or FAILURE
requestId	String	Echo of the requestId sent in the request
responseCode	String	Response code; 00 = Success
responseMessage	String	Human-readable response message

Sample Response

```

{
  "Status": "SUCCESS",
  "VaeList": {
    "VaeList": [
      {
        "addr": "lic@hdfc",
        "key": {
          "code": "NPCI",
          "keyValue": "BASE64VALUE123",
          "ki": "20260325",
          "type": "PKI"
        },
        "logo": "image",
        "name": "LIC",
        "url": ""
      }
    ]
  }
}

```

```
}  
},  
"requestId": "REQDEV10001",  
"responseCode": "00",  
"responseMessage": "Get verifiedEntities List Successful"  
}
```


2. Account Management

2.1 Account List

Checksum Logic (SHA-256)

Concatenate the following fields separated by pipe (|):

Checksum Formula

```
requestId | linkValue | ifsc | tpapId  
Example: REQ55323294|9886543110|ICUC0001534|M000025
```

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
payerAddr	N	String	Variable	UPI virtual payment address of payer	Format: localpart@handle
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY
payerCode	Y	String	Fixed	Payer bank/institution code	Exactly 4 digits
aadhaarConsent	Y	String	Fixed	Aadhaar data-sharing consent flag	Y or N
ifsc	Y	String	Fixed	Bank branch IFSC code	^[A-Z]{4}0[A-Z0-9]{6}\$ (e.g. HDFC0001234)
signature	Y	String	Variable	Request integrity signature	SHA-256 checksum
timestamp	Y	String	Variable	Request timestamp	Format: yyyy-MM-dd'T'HH:mm:ss; not future; not older than 30 min
linkType	N	String	Fixed	Type of linking identifier	MOBILE or AADHAAR
linkValue	N	String	Variable	Value of linking identifier	MOBILE: 10 digits; AADHAAR: 12 digits
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "requestId": "REQ32323234",
  "tpapId": "M000025",
  "payerAddr": "",
  "payerType": "PERSON",
  "payerCode": "0000",
  "aadhaarConsent": "Y",
  "ifsc": "ICIC0001234",
  "signature": "5DEPwW0h6TzAMASbiAXp9MHJ6d+y2YBt44j7FO63IN8=",
  "timestamp": "2026-03-23T11:35:30",
  "linkType": "MOBILE",
  "linkValue": "9876543210",
  "deviceInfo": {
    "mobile": "9876543210",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE987654321",
    "app": "com.upi.app",
    "capability": "UPI",
    "telecom": "AIRTEL"
  },
  "adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}
```

Callback Response

Field	Datatype	Description
reqType	String	Type of request; always ListAccount
msgId	String	Unique callback message ID
reqMsgId	String	Echo of the original requestId
status	String	Overall status of the operation
respCode	String	Response code from NPCI
accounts	Array	List of bank account objects
accounts.name	String	Account holder full name
accounts.maskedAccount	String	Masked bank account number
accounts.accType	String	Bank account type
accounts.ifsc	String	IFSC code of the bank branch
accounts.aeba	String	Aadhaar Enabled Bank Account flag
accounts.aadhaarNo	String	Masked Aadhaar number (if applicable)
accounts.credsAllowed	Array	Credentials allowed for this account
accounts.credsAllowed.type	String	Credential type
accounts.credsAllowed.subType	String	Credential sub-type

Sample Callback Response

```
{
  "reqType": "ListAccount",
  "msgId": "123OTAWFNALGV2026032311512235934441",
  "CustomerId": "C00043",
  "accounts": [
    {
      "aadhaarNo": "XXXX XXXX 9012",
      "mmid": "9056014",
      "name": "John Doe",
      "maskedAccount": "XXXXXXXXXXXX",
      "accType": "SAVINGS",
      "ifsc": "ICIC0001111",
      "aeba": "Y",
      "credsAllowed": [{ "dType": "NUM", "dLength": "4", "subType": "ATMPIN", "type": "PIN" }]
    }
  ],
  "respCode": "000",
  "reqMsgId": "REQ5323294",
  "status": "SUCCESS"
}
```

2.2 OTP Request

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory C = Conditionally Mandatory

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
linkType	Y	String	Fixed	Type of linking identifier	MOBILE AADHAAR
linkValue	Y	String	Variable	Value corresponding to linkType	MOBILE: 10-digit; AADHAAR: 12-digit UID

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
payerAddr	N	String	Variable	UPI VPA of the payer	Format: localpart@handle
payerName	N	String	Variable	Full name of the payer	
payerSeqNum	Y	String	Variable	Sequence number assigned to the payer	Numeric string; e.g. 1
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY
payerCode	Y	String	Fixed	Payer bank/institution code	Exactly 4 digits
addrType	Y	String	Fixed	Type of address used for OTP request	AADHAAR ACCOUNT MOBILE
ifscValue	C	String	Fixed	IFSC code of the bank branch	Mandatory if addrType=ACCOUNT
acType	C	String	Fixed	Type of bank account	Mandatory if addrType=ACCOUNT; SAVINGS CURRENT DEFAULT NRE NRO CREDIT
acNum	C	String	Variable	Bank account number	Mandatory if addrType=ACCOUNT; numeric digits
aadhaarlin	C	String	Variable	Aadhaar IIN	Mandatory if addrType=AADHAAR
aadhaarUidNum	C	String	Variable	Aadhaar UID number	Mandatory if addrType=AADHAAR; 12-digit UID
mmid	C	String	Variable	Mobile Money Identifier	Mandatory if addrType=MOBILE
mobileNumber	C	String	Variable	Mobile number linked to bank account	Mandatory if addrType=MOBILE; 10 digits
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "requestId": "REQ3542345236",
  "tpapId": "M000025",
  "linkType": "MOBILE",
  "linkValue": "9876543210",
  "payerAddr": "roshan45@upi",
  "payerName": "Roshan Doe",
  "payerSeqNum": "1",
  "payerType": "PERSON",
  "payerCode": "0000",
  "addrType": "ACCOUNT",
  "ifscValue": "ICIC0001234",
  "acType": "SAVINGS",
  "acNum": "123456789012",
  "aadhaarIn": "",
  "aadhaarUidNum": "",
  "mmid": "",
  "mobileNumber": "",
  "deviceInfo": {
    "mobile": "9876543210",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE987654321",
    "app": "com.upi.app",
    "capability": "UPI",
    "telecom": "AIRTEL"
  },
  "adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}
```

Callback Response

Field	Datatype	Description
reqType	String	Type of request; always Otp
msgId	String	Unique callback message ID
reqMsgId	String	Echo of the original requestId
status	String	Overall status of the OTP operation
respCode	String	Response code from NPCI
securePinUrl	String	URL for setting the UPI PIN (returned on success)

Sample Callback Response

```
{
  "reqType": "Otp",
  "msgId": "REQ3542345236",
  "respCode": "026",
  "securePinUrl": "https://secure.npci.org/upi/setpin",
  "reqMsgId": "REQ3542345236",
  "status": "SUCCESS"
}
```

2.3 VPA creation

Request Parameters

Key: **Y** = Mandatory N = Non-Mandatory *C* = Conditionally Mandatory

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
customerId	Y	String	Fixed	Type of linking identifier	Verify from DB
mobileMobNum	Y	String	Variable	Value corresponding to linkType	10-digit mobile number
payerAddr	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	

adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00051",
  "requestId": "REQ7876510",
  "tpapId": "TPSM000080",
  "mobileMobNum": "9898963932",
  "payerAddr": "ashish5@upi",

  "deviceInfo": {
    "mobile": "9898963932",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE18232346758",
    "app": "com.upi.app",
    "capability": "SMS,OTP,GPS",
    "telecom": "AIRTEL"
  },

  "adf1": "",
  "adf2": "",
  "adf3": "",
  "adf4": "",
  "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00051",
  "deviceId": "DEVICE18232346758",
  "mobileNumber": "9898963932",
  "requestId": "REQ7876510",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "TPSM000080"
}
```

Callback Response

Field	Datatype	Description
-------	----------	-------------

Field	Datatype	Description
reqType	String	Type of request; always ReqRegMob
msgId	String	Unique callback message ID
reqMsgId	String	Echo of the original requestId
VpaAddress	String	VPA address which created
respCode	String	Response code from NPCI
status	String	Response message

Sample Callback Response

```
{
  "VpaAddress": "ashish85@upi",
  "reqType": "ValAdd",
  "msgId": "123EZKBCJMKV2026050513320057644596",
  "respCode": "000",
  "reqMsgId": "REQ7876510",
  "status": "VPA Created Successfully"
}
```


2.4 Reg Mobile

Request Parameters

Key: **Y** = **Mandatory** N = Non-Mandatory C = *Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	After otp reg getting customer id pass
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
addrType	Y	String	Fixed	Address type for registration	AADHAAR ACCOUNT MOBILE
aadhaarIin	C	String	Variable	Aadhaar IIN number	Mandatory if addrType == AADHAAR
aadhaarUidNum	C	String	Variable	Aadhaar UID number	Mandatory if addrType == AADHAAR; 12 digits
accountIfsc	C	String	Fixed	Bank branch IFSC code	Mandatory if addrType == ACCOUNT
accountAcType	C	String	Fixed	Bank account type	Mandatory if addrType == ACCOUNT; SAVINGS CURRENT DEFAULT NRE NRO CREDIT
accountAcNum	C	String	Variable	Bank account number	Mandatory if addrType == ACCOUNT
mobileMmid	C	String	Variable	Mobile Money Identifier (MMID)	Mandatory if addrType == MOBILE
mobileMobNum	C	String	Variable	Mobile number for MOBILE address type	Mandatory if addrType == MOBILE; 10 digits
payerAddr	Y	String	Variable	UPI virtual payment address of payer	Format: localpart@handle Check in Database according to customerId and account
payerName	Y	String	Variable	Full name of the payer	
payerSeqNum	Y	String	Variable	Payer sequence number	Numeric string

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY
payerCode	Y	String	Fixed	Payer bank/institution code	Exactly 4 digits
regDetailsType	N	String	Fixed	Registration detail format type	FORMAT1 FORMAT2 ATM_REDIRECT
regDetailsMobile	N	String	Variable	Mobile number for registration details	10-digit mobile number
regDetailsCardDigits	N	String	Variable	Last 4 digits of debit/credit card	Exactly 4 numeric digits
regDetailsExpDate	N	String	Fixed	Card expiry date	Format: MMY
credType	Y	String	Fixed	Credential type used for authentication	CARD OTP PIN
credSubType	Y	String	Fixed	Credential sub-type	CARDDetails SMS EMAIL HOTP TOTP MPIN ATMPIN
dataNodeCode	N	String	Fixed	Data node identifier code	
dataNodeKi	N	String	Variable	Key index for encrypted data	16-character string
dataNodeValue	N	String	Variable	Encrypted credential/card data value	Encrypted string; max length 512
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	N	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	N	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	N	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	N	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	N	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00043",
  "requestId": "REQ2343765343",
  "tpapId": "M000025",
  "addrType": "ACCOUNT",
  "accountIfsc": "ICIC0001234",
  "accountAcType": "SAVINGS",
  "accountAcNum": "123456789012",
  "mobileMmid": "1234567",
  "mobileMobNum": "9876543210",
  "payerAddr": "user43@upi",

```

```

"payerName": "John Doe",
"payerSeqNum": "1",
"payerType": "PERSON",
"payerCode": "0000",
"regDetailsType": "FORMAT1",
"regDetailsMobile": "9876543210",
"regDetailsCardDigits": "1234",
"regDetailsExpDate": "1226",
"credType": "OTP",
"credSubType": "SMS",
"dataNodeCode": "OTP",
"dataNodeKi": "key123",
"dataNodeValue": "123456",
"deviceInfo": {
  "mobile": "9876543210",
  "os": "ANDROID",
  "appVersion": "2.3.1",
  "type": "MOBILE",
  "geoCode": "19.0760,72.8777",
  "location": "Mumbai",
  "ip": "49.205.45.12",
  "id": "DEVICE987654321",
  "app": "com.upi.app",
  "capability": "UPI",
  "telecom": "AIRTEL"
},
"adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}

```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```

{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}

```

Callback Response

Field	Datatype	Description
reqType	String	Type of request; always ReqRegMob
msgId	String	Unique callback message ID
reqMsgId	String	Echo of the original requestId

Field	Datatype	Description
status	String	Overall status of the operation
respCode	String	Response code from NPCI

Sample Callback Response

```
{
  "reqType": "ReqRegMob",
  "msgId": "123CVWUHEYFEJ2026031111442094528916",
  "respCode": "000",
  "reqMsgId": "REQ2343765343",
  "status": "SUCCESS"
}
```

2.5 Set Credentials

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	Customer id while get in mobile reg
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
addrType	Y	String	Fixed	Address type for account resolution	ACCOUNT MOBILE
accountIfsc	<i>N*</i>	String	Fixed	IFSC code of the bank branch	Mandatory if addrType == ACCOUNT
accountType	<i>N*</i>	String	Fixed	Bank account type	Mandatory if addrType == ACCOUNT; SAVINGS CURRENT DEFAULT NRE NRO CREDIT
accountNumber	<i>N*</i>	String	Variable	Bank account number	Mandatory if addrType == ACCOUNT
mobileMmid	<i>N*</i>	String	Variable	Mobile Money Identifier (MMID)	Mandatory if addrType == MOBILE; 7-digit numeric
mobileNumber	<i>N*</i>	String	Variable	Mobile number of the payer	Mandatory if addrType == MOBILE; 10-digit numeric
credType	Y	String	Fixed	Type of existing credential	PIN
credSubType	Y	String	Fixed	Sub-type of existing credential	MPIN
credData	Y	String	Variable	Existing credential data (encrypted)	Base64-encoded encrypted value; max 512 chars
newCredType	Y	String	Fixed	Type of new credential to set	PIN
newCredSubType	Y	String	Fixed	Sub-type of new credential	MPIN
newCredData	Y	String	Variable	New credential data (encrypted)	Base64-encoded encrypted value; max 512 chars
payerAddr	Y	String	Variable	UPI VPA of payer	Format: localpart@handle
payerName	Y	String	Variable	Full name of the payer	Max 99 characters
payerSeqNum	Y	String	Variable	Sequence number of the payer account	Numeric string
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
payerCode	Y	String	Fixed	Payer bank/institution code	Exactly 4 digits
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\.[0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00043",
  "requestId": "REQ13454364",
  "tpapId": "M000025",
  "addrType": "ACCOUNT",
  "accountIfsc": "ICIC0001234",
  "accountType": "SAVINGS",
  "accountNumber": "123456789012",
  "mobileMmid": "1234567",
  "mobileNumber": "9876543210",
  "credType": "PIN",
  "credSubType": "MPIN",
  "credData": "encryptedOldPin",
  "newCredType": "PIN",
  "newCredSubType": "MPIN",
  "newCredData": "encryptedNewPin",
  "payerAddr": "user@upi",
  "payerName": "John Doe",
  "payerSeqNum": "1",
  "payerType": "PERSON",
  "payerCode": "0000",
  "deviceInfo": {
    "mobile": "9876543210",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE987654321",
    "app": "com.upi.app",
    "capability": "UPI",
    "telecom": "AIRTEL"
  },
}
```

```
"adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}
```

Callback Response

Field	Datatype	Description
reqType	String	Type of request; always SetCre
msgId	String	Unique callback message ID generated by NPCI
respCode	String	Response code from NPCI (e.g. 00 = Success)
reqMsgId	String	Echo of the original requestId
status	String	Overall status of the operation (e.g. SUCCESS)

Sample Callback Response

```
{
  "reqType": "SetCre",
  "msgId": "123B0V07QP2X5PTPUT8F6E43X27M6RX6TBS",
  "respCode": "00",
  "reqMsgId": "REQ13454364",
  "status": "SUCCESS"
}
```

2.6 VPA Credentials

Request Parameters

Key: Y = Mandatory N = Non-Mandatory N* = Conditionally Mandatory

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 25

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
mobileMobNum	Y	String	Variable	Mobile number of the payer	10-digit mobile number
payerAddr	Y	String	Variable	UPI VPA to create	Format: localpart@handle
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	N	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	N	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	N	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	N	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	N	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00043",
  "requestId": "REQ3453456",
  "tpapId": "M000025",
  "mobileMobNum": "9876543210",
  "payerAddr": "user43@upi",
  "deviceInfo": {
    "mobile": "9876543210",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE987654321",
    "app": "com.upi.app",
    "capability": "UPI",
    "telecom": "AIRTEL"
  },
  "adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system

Field	Datatype	Description
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}
```

VPA Callback Response

Field	Datatype	Description
VpaAddress	String	The newly created VPA
reqType	String	Type of request; always ValAdd
msgId	String	Unique callback message ID
respCode	String	Response code
reqMsgId	String	Echo of the original requestId
status	String	Status message of the VPA creation

Sample VPA Callback Response

```
{
  "VpaAddress": "user43@upi",
  "reqType": "ValAdd",
  "msgId": "123FFJHGLNGRP2026032306521185601796",
  "respCode": "000",
  "reqMsgId": "REQ3453457",
  "status": "VPA Created Successfully"
}
```


3. Transaction API

3.1 collectPayeeVPA

Checksum Logic (SHA-256)

Checksum Formula

merchantTxnId + auth_id + amount + payer.addr + payee.addr

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
merchantTxnId	Y	String	Var	Merchant transaction ID	Unique per transaction
auth_id	Y	String	Var	Merchant authentication ID	MerchantId Shared with Onboarding credentials
sid	N	String	Var	Store ID	Max 15 chars
tid	N	String	Var	Terminal ID	Max 15 chars
checkSum	Y	String	Var	SHA-256 integrity checksum	See Checksum Logic section
reseller_auth_id	N	String	Var	Reseller authentication ID	Default NA
txn_timestamp	Y	String	Var	Transaction timestamp	yyyy-MM-dd HH:mm:ss
amount	Y	Decimal	Var	Transaction amount	Positive value
currencyCode	Y	String	Fix	Currency code	INR
customerID	N	String	Var	Customer identifier	Optional
mobile	Y	String	Fix	Mobile number with country code	E.g. +919999999999
geocode	N	String	Var	Geo coordinates	lat,long
location	N	String	Var	Location description	Optional
ip	N	String	Var	Client IP address	IPv4 format
remark	N	String	Var	Transaction remark	Optional
expiryTimeUp	N	String	Var	Expiry time in minutes	Default 5 mins
type	N	String	Var	Device type	Default NA
id	N	String	Var	Device ID	Optional
os	N	String	Var	Device OS	E.g. Android 13
app	N	String	Var	App name	Optional
capability	N	String	Fix	Device capability bitmap	E.g. 011001
telecom	N	String	Var	Telecom operator	Optional
returnUrl	Y	String	Var	Callback URL	Valid HTTPS URL
seqId	Y	String	Var	Sequence ID	12-digit unique
channelcode	N	String	Var	Channel code	Optional
mcccode	N	String	Fix	Merchant category code	4-digit code
verifypayeeracc	N	String	Fix	Verify payee account flag	Y / N
merchanttype	N	String	Var	Merchant type	SMALL / LARGE
payer[].addr	Y	String	Var	Payer UPI VPA	E.g. user@bank
payer[].name	Y	String	Var	Payer name	Max 50 chars
payer[].accountNumber	N	String	Var	Payer account number	Numeric

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
payer[].ifsc	N	String	Fix	Payer IFSC code	11 chars
payee[].addr	Y	String	Var	Payee UPI VPA	E.g. merchant@bank validated from onboarded Merchant details
payee[].name	Y	String	Var	Payee name	Max 50 chars
payee[].accountNumber	N	String	Var	Payee account number	Numeric validated from onboarded Merchant details
payee[].ifsc	N	String	Fix	Payee IFSC code	11 chars validated from onboarded Merchant details
adf1	N	String	Var	Additional data field 1	
adf2	N	String	Var	Additional data field 2	
adf3	N	String	Var	Additional data field 3	
adf4	N	String	Var	Additional data field 4	
adf5	N	String	Var	Additional data field 5	

Sample Request Body

```
{
  "merchantTxnId": "2454546546547567568",
  "auth_id": "M000062",
  "sid": "M000062",
  "tid": "M000062",
  "adf1": "NA", "adf2": "NA", "adf3": "NA", "adf4": "NA", "adf5": "NA",
  "checksum": "02e834050fdf4afe187e3720f67c2e91646ab18ac6aa1e5a2a721f9f8ba2d169",
  "reseller_auth_id": "NA",
  "txn_timestamp": "2026-04-01 16:37:45",
  "amount": 100.00,
  "currencyCode": "INR",
  "customerID": "hdgd",
  "mobile": "+916987456321",
  "geocode": "19.0760,72.8777",
  "location": "Mumbai, IND",
  "ip": "192.168.1.10",
  "remark": "Payment remark",
  "expiryTimeUp": 5,
  "type": "NA",
  "id": "DEVICE1344543523",
  "os": "Android 13",
  "app": "NA",
  "capability": "011001",
  "telecom": "Airtel",
  "returnUrl": "https://merchant.com/callback",
  "seqId": "123456789010",
  "channelcode": "NA",
  "mcccode": "6543",
  "verifypayeeracc": "Y",
  "merchanttype": "SMALL",
  "payer": [{ "addr": "customer@icici", "name": "Customer Name" }],
  "payee": [{ "addr": "merchant@icici", "name": "ABC Store", "accountNumber": "123456789012", "ifsc": "ICIC0001234" }]
}
```

Sample Acknowledgement Response

```
{
  "merchantTxnId": "TXN123456",
  "refId": "REF987654321",
  "auth_id": "M0000062",
  "amount": "500.00",
  "payeevpa": "merchant@upi",
  "responseCode": "U52",
  "responseMessage": "PSP ORGID NOT FOUND"
}
```

Callback Response

Field	Datatype	Description
responseCode	String	Final response code (00 = Success)
bankRRN	String	Bank Reference Number for this transaction
upiTranlogId	String	UPI transaction log ID (may be empty)
customerId	String	Internal customer identifier
authId	String	Echo of auth_id from the original request
requestId	String	Echo of the merchantTxnId from the original request
note	String	Transaction note or remark
amount	Decimal	Actual amount processed
payeeVa	String	UPI VPA of the payee
type	String	Transaction type identifier
payeeName	String	Name of the payee
payerVa	String	UPI VPA of the payer
payerName	String	Name of the payer
direction	String	Direction of payment; SENT RECEIVED
status	String	Final transaction status; SUCCESS FAILURE PENDING

Sample Callback Response

```
{
  "responseCode": "00",
  "bankRRN": "Ref20260325060153655GJYQ",
  "upiTranlogId": "",
  "customerId": "38",
  "authId": "M000062",
  "requestId": "PP12783348272895127",
  "note": "Payment for order 1234",
  "amount": 100.00,
  "payeeVa": "merchant@icici",
  "type": "COLLECT",
  "payeeName": "ABC Store",
  "payerVa": "customer@okhdfcbank",
  "payerName": "Rahul Sharma",
  "direction": "SENT",
  "status": "SUCCESS"
}
```

3.2 collectPayeeAccount

Checksum Logic (SHA-256)

Checksum Formula

merchantTxnId + auth_id + amount + payer.addr + payee.addr

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
merchantTxnId	Y	String	Var	Merchant transaction ID	Unique per transaction
auth_id	Y	String	Var	Merchant authentication ID	MrchantId shared with onboarding credentials
sid	N	String	Var	Store ID	Max 15 chars
tid	N	String	Var	Terminal ID	Max 15 chars
checkSum	Y	String	Var	SHA-256 integrity checksum	See Checksum Logic section
reseller_auth_id	N	String	Var	Reseller authentication ID	Default NA
txn_timestamp	Y	String	Var	Transaction timestamp	yyyy-MM-dd HH:mm:ss
amount	Y	Decimal	Var	Transaction amount	Positive value
currencyCode	Y	String	Fix	Currency code	INR
customerID	N	String	Var	Customer identifier	Optional
mobile	Y	String	Fix	Mobile number with country code	E.g. +919999999999
geocode	N	String	Var	Geo coordinates	lat,long
location	N	String	Var	Location description	
ip	N	String	Var	Client IP address	IPv4 format
remark	N	String	Var	Transaction remark	
expiryTimeUp	N	String	Var	Expiry time in minutes	Default 5 mins
type	N	String	Var	Device type	Default NA
id	N	String	Var	Device ID	
os	N	String	Var	Device OS	E.g. Android 13
app	N	String	Var	App name	
capability	N	String	Fix	Device capability bitmap	NA, SMS, OTP, GPS, NFC, BIOMETRIC
telecom	N	String	Var	Telecom operator	
returnUrl	Y	String	Var	Callback URL	Callback URI Whitelisted in Database
seqId	Y	String	Var	Sequence ID	12-digit unique
payer[].addr	Y	String	Var	Payer UPI VPA	E.g. user@bank
payer[].name	Y	String	Var	Payer name	Max 50 chars

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
payee[].addr	Y	String	Var	Payee UPI VPA	E.g. merchant@bank validated from onboarded Merchant details
payee[].name	Y	String	Var	Payee name	Max 50 chars
payee[].accountNumber	Y	String	Var	Payee account number	Numeric; mandatory for Account Collect validated from onboarded Merchant details
payee[].ifsc	Y	String	Fix	Payee IFSC code	11 chars; mandatory for Account Collect validated from onboarded Merchant details
adf1	N	String	Var	Additional data field 1	
adf2	N	String	Var	Additional data field 2	
adf3	N	String	Var	Additional data field 3	
adf4	N	String	Var	Additional data field 4	
adf5	N	String	Var	Additional data field 5	

Sample Request Body

```
{
  "merchantTxnId": "2454546546547567567",
  "auth_id": "M000062",
  "sid": "M000062",
  "tid": "M000062",
  "adf1": "NA", "adf2": "NA", "adf3": "NA", "adf4": "NA", "adf5": "NA",
  "checksum": "e4ea46fbc3bb6c0dccf41381e07059b3392ddf9eba4ce733238d7449b5847ac4",
  "reseller_auth_id": "NA",
  "txn_timestamp": "2026-04-01 13:03:45",
  "amount": 100.00,
  "currencyCode": "INR",
  "customerID": "hdgd",
  "mobile": "+916987456321",
  "geocode": "19.0760,72.8777",
  "location": "Mumbai, IND",
  "ip": "192.168.1.10",
  "remark": "Payment remark",
  "expiryTimeUp": "5",
  "type": "NA",
  "id": "DEVICE12345678",
  "os": "Android 13",
  "app": "NA",
  "capability": "011001",
  "telecom": "Airtel",
  "returnUrl": "https://merchant.com/callback",
  "seqId": "123456789012",
  "payer": [{ "addr": "customer@icici", "name": "Customer Name" }],
  "payee": [{ "addr": "merchant@icici", "name": "ABC Store", "accountNumber": "123456789012", "ifsc": "ICIC0001234" }]
}
```

Sample Acknowledgement Response

```
{
  "merchantTxnId": "TXN123456",
  "refId": "REF987654321",
  "auth_id": "M0000062",
  "amount": "500.00",
  "payeevpa": "merchant@upi",
  "responseCode": "U52",
  "responseMessage": "PSP ORGID NOT FOUND"
}
```

Callback Response

Field	Datatype	Description
responseCode	String	Final response code (00 = Success)
bankRRN	String	Bank Reference Number for this transaction
upiTranlogId	String	UPI transaction log ID (may be empty)
customerId	String	Internal customer identifier
authId	String	Echo of auth_id from the original request
requestId	String	Echo of the merchantTxnId from the original request
note	String	Transaction note or remark
amount	Decimal	Actual amount processed
payeeVa	String	UPI VPA of the payee
type	String	Transaction type identifier
payeeName	String	Name of the payee
payerVa	String	UPI VPA of the payer
payerName	String	Name of the payer
direction	String	Direction of payment; SENT RECEIVED
status	String	Final transaction status; SUCCESS FAILURE PENDING

Sample Callback Response

```
{"responseCode":"00",
"bankRRN":"Ref20260325060153655GJYQ","upiTranlogId":"","customerId":"38","authId":"M000062","requestId":"PP12783348272895127",
"note":"Payment for order 1234","amount":100.00,"payeeVa":"merchant@icici","type":"COLLECT","payeeName":"ABC Store",
"payerVa":"customer@okhdfcbank","payerName":"Rahul Sharma","direction":"SENT","status":"SUCCESS"}
```

3.3 PayRequestPay (Pre-approval)

Checksum Logic (SHA-256)

Checksum Formula

merchantTxnId + auth_id + amount + payer.payerAddr + payee.payeeAddr

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
seqnum	Y	String	Var	Unique sequence number	18-character hexadecimal value
merchantTxnId	Y	String	Var	Merchant transaction ID	Must be unique per transaction
Checksum	Y	String	Var	SHA-256 integrity checksum	Generated using checksum formula
mpin	N	String	Var	MPIN (Base64 encoded)	Use NA for pre-approval request
payer.mobile	Y	String	Fix	Payer mobile number	Must be 10 digits
payer.accountNumber	Y	String	Var	Payer bank account number	Numeric value validated from onboarded merchant details
payer.ifscCode	Y	String	Fix	Payer IFSC code	Must be 11 characters
payer.accountType	Y	String	Var	Payer account type	Allowed values: SAVINGS, CURRENT
payer.payerAddr	Y	String	Var	Payer UPI VPA	Example: user@bank
payer.payerName	Y	String	Var	Payer name	Maximum 50 characters
payer.payerMCC	N	String	Fix	Payer MCC code	4-digit MCC value
payer.payerType	Y	String	Var	Payer entity type	Allowed values: ENTITY, PERSON
payee.payeeAddr	Y	String	Var	Payee UPI VPA	Example: merchant@bank
payee.payeeName	Y	String	Var	Payee name	Maximum 50 characters
payee.payeeMCC	N	String	Fix	Payee MCC code	4-digit MCC value
payee.payeeType	Y	String	Var	Payee entity type	Allowed values: ENTITY, PERSON
transaction.amount	Y	Decimal	Var	Transaction amount	Must be greater than 0
transaction.currencyCode	Y	String	Fix	Currency code	Must be INR
transaction.txnType	Y	String	Var	Transaction type	Allowed values: P2P, P2M
transaction.remark	N	String	Var	Transaction remark	Maximum 50 characters
transaction.approvedFlag	Y	String	Fix	Approval flag	Must be A for pre-approval flow

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
device.mobile	Y	String	Fix	Device mobile number	Must be 10 digits
device.type	Y	String	Var	Device type	Allowed values: MOBILE, WEB
device.id	Y	String	Var	Device identifier	Unique device ID
additionalInfo.auth_id	Y	String	Var	Merchant authentication ID	Assigned by PSP
additionalInfo.reseller_auth_id	N	String	Var	Reseller authentication ID	Default value NA
additionalInfo.customerID	N	String	Var	Customer identifier	Optional field
callbackUrl	Y	String	Var	Merchant callback URL	Must be valid HTTPS URL
qrDetails.referenceId	N	String	Var	QR reference ID	Optional
qrDetails.globalVpa	N	String	Var	Global VPA	Optional
qrDetails.qrAmount	N	String	Var	QR amount	Optional
qrDetails.referenceUrl	N	String	Var	QR reference URL	Valid HTTPS URL
qrDetails.merchantId	N	String	Var	QR merchant ID	Optional
qrDetails.merchantTxnId	N	String	Var	QR merchant transaction ID	Optional
qrDetails.subMerchantId	N	String	Var	QR sub-merchant ID	Optional
qrDetails.terminalId	N	String	Var	QR terminal ID	Optional
qrDetails.ver	N	String	Fix	QR version	Example: 1
qrDetails.qrMode	N	String	Fix	QR mode	Example: 01
qrDetails.purpose	N	String	Fix	QR purpose code	Example: 00
qrDetails.category	N	String	Fix	QR category	Example: 01
qrDetails.qrThrough	N	String	Fix	QR source channel	Example: 01
qrDetails.qrExpireDate	N	String	Var	QR expiry timestamp	Format: yyyy-MM-dd HH:mm:ss

Sample Request Body

```
{
  "seqnum": "AABBCCDDEEFF112233",
  "merchantTxnId": "132123345343",
  "mpin": "NA",
  "Checksum":"218c718c35f1e4bd906d4056cc6fbfb112dc51807d4663f1df791682d73904ee",
  "payer": {
    "mobile": "9999499899",
    "accountNumber": "34408015821",
    "ifscCode": "SBIN0017118",
    "accountType": "CURRENT",
    "payerAddr": "sani21@upi",
    "payerName": "dsdsdd",
    "payerMCC": "6543",
    "payerType": "PERSON"
  },
  "payee": {
```



```
"payeeAddr": "drishti@okicici",
"payeeName": "dsdsdd",
"payeeMCC": "6789",
"payeeType": "ENTITY"
},

"transaction": {
  "amount": 100.00,
  "currencyCode": "INR",
  "txnType": "P2M",
  "remark": "pay for shopping",
  "approvedFlag": "A"
},

"qrDetails": {
  "referenceId": "sasaassa",
  "globalVpa": "test@paytm",
  "qrAmount": "234",
  "referenceUrl": "https://www.google.com",
  "merchantId": "M000062",
  "merchantTxnId": "34343434",
  "subMerchantId": "33344343",
  "terminalId": "34343434",
  "ver": "1",
  "qrMode": "01",
  "purpose": "00",
  "category": "01",
  "qrThrough": "01",
  "qrExpireDate": "2026-05-11 17:54:45"
},

"gstDetails": {
  "gst": "svalue",
  "billNo": "323223",
  "billDate": "11-05-2026",
  "billName": "me1"
},

"device": {
  "mobile": "9999999999",
  "geocode": "19.0760,72.8777",
  "location": "Mumbai, IND",
  "ip": "192.168.1.10",
  "type": "MOBILE",
  "id": "DEVICE123",
  "os": "Android",
  "app": "PayApp 2.0",
  "capability": "GPS",
  "telecom": "Airtel"
},

"additionalInfo": {
  "auth_id": "TPSM000082",
  "reseller_auth_id": "NA",
  "customerID": "C00047",
  "adf1": "NA",
  "adf2": "NA",
  "adf3": "NA",
  "adf4": "NA",
```

```
"adf5": "NA"
},

"callbackUrl": "https://merchant.com/callback"
}
```

Acknowledgement Response

Field	Datatype	Description
code	String	Acknowledgement response code (00 = Accepted, U52 = PSP Org ID Not Found)
message	String	Human-readable description of the acknowledgement code
data	String	Additional data; empty string on acknowledgement

Sample Acknowledgement Response

3.4 Requestpay

Checksum Logic (SHA-256)

Checksum Formula

merchantTxnId + auth_id + amount + payer.payerAddr + payee.payeeAddr

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
seqnum	Y	String	Var	Unique sequence number	Must be 18-character hexadecimal value
merchantTxnId	Y	String	Var	Merchant transaction ID	Must be unique per transaction
Checksum	Y	String	Var	SHA-256 integrity checksum	Generated using checksum logic
mpin	Y	String	Var	Base64 encoded encrypted MPIN	Mandatory for MPIN-based payment (approvedFlag = M)
payer.mobile	Y	String	Fix	Payer mobile number	Must be 10 digits
payer.accountNumber	Y	String	Var	Payer bank account number	Numeric value validated from onboarded merchant details
payer.ifscCode	Y	String	Fix	Payer IFSC code	Must be 11 characters
payer.accountType	Y	String	Var	Payer account type	Allowed values: SAVINGS, CURRENT
payer.payerAddr	Y	String	Var	Payer UPI VPA	Example: user@bank
payer.payerName	Y	String	Var	Payer name	Maximum 50 characters
payer.payerType	Y	String	Var	Payer entity type	Allowed values: ENTITY, PERSON
payee.payeeAddr	Y	String	Var	Payee UPI VPA	Example: merchant@bank
payee.payeeName	Y	String	Var	Payee name	Maximum 50 characters
payee.payeeType	Y	String	Var	Payee entity type	Allowed values: ENTITY, PERSON
transaction.amount	Y	Decimal	Var	Transaction amount	Must be greater than 0
transaction.currencyCode	Y	String	Fix	Currency code	Must be INR
transaction.txnType	Y	String	Var	Transaction type	Allowed values: P2P, P2M
transaction.remark	N	String	Var	Transaction remark	Maximum 50 characters
transaction.approvedFlag	Y	String	Fix	Approval flag	M = MPIN authorized, A = Pre-approval flow
device.mobile	Y	String	Fix	Device mobile number	Must be 10 digits
device.type	Y	String	Var	Device type	Allowed values: MOBILE, WEB
device.id	Y	String	Var	Device identifier	Unique device ID
additionalInfo.auth_id	Y	String	Var	Merchant authentication ID	Assigned by PSP

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
additionalInfo.reseller_auth_id	N	String	Var	Reseller authentication ID	Default value NA
callbackUrl	Y	String	Var	Merchant callback URL	Must be valid HTTPS URL
qrDetails.referenceId	N	String	Var	QR reference ID	Optional
qrDetails.globalVpa	N	String	Var	QR global VPA	Optional
qrDetails.qrAmount	N	String	Var	QR amount	Optional
qrDetails.referenceUrl	N	String	Var	QR reference URL	Must be valid HTTPS URL
qrDetails.merchantId	N*	String	Var	Merchant ID	Mandatory when TPAP is mapped with Merchant ID
qrDetails.merchantTxnId	N	String	Var	QR merchant transaction ID	Optional
qrDetails.subMerchantId	N	String	Var	Sub-merchant ID	Optional
qrDetails.terminalId	N	String	Var	Terminal ID	Optional
qrDetails.ver	N	String	Fix	QR version	Example: 1
qrDetails.qrMode	N	String	Fix	QR mode	Example: 01
qrDetails.purpose	N	String	Fix	QR purpose code	Example: 00
qrDetails.category	N	String	Fix	QR category	Example: 01
qrDetails.qrThrough	N	String	Fix	QR transaction channel	Example: 01
qrDetails.qrExpireDate	N	String	Var	QR expiry timestamp	Format: yyyy-MM-dd HH:mm:ss

Sample Request Body

```
{
  "seqnum": "AABBCCDDEEFF112233",
  "merchantTxnId": "88237362876322332",
  "mpin": "MTIzNDU2Nzg5",
  "Checksum": "806c98def492381ecdbc92eafe982ddd056da589e4396773ef81bc0cdf02590e",
  "payer": {
    "mobile": "9999499899",
    "accountNumber": "34408015821",
    "ifscCode": "SBIN0017118",
    "accountType": "CURRENT",
    "payerAddr": "sani21@upi",
    "payerName": "dsdsdd",
    "payerMCC": "6543",
    "payerType": "PERSON"
  },
  "payee": {
    "payeeAddr": "drishti@okicici",
    "payeeName": "dsdsdd",
    "payeeMCC": "6789",
    "payeeType": "ENTITY"
  },
  "transaction": {
```

```

"amount": 100.00,
"currencyCode": "INR",
"txnType": "P2M",
"remark": "pay for shopping",
"approvedFlag": "M"
},

"qrDetails": {
  "referenceId": "",
  "globalVpa": "test@paytm",
  "qrAmount": "",
  "referenceUrl": "",
  "merchantId": "M000082",
  "merchantTxnId": "",
  "subMerchantId": "",
  "terminalId": "",
  "ver": "",
  "qrMode": "",
  "purpose": "",
  "category": "",
  "qrThrough": "",
  "qrExpireDate": ""
},

"gstDetails": {
  "gst": "svalue",
  "billNo": "323223",
  "billDate": "10-02-2025",
  "billName": "mel"
},

"device": {
  "mobile": "9999999999",
  "geocode": "19.0760,72.8777",
  "location": "Mumbai, IND",
  "ip": "192.168.1.10",
  "type": "MOBILE",
  "id": "DEVICE123",
  "os": "Android",
  "app": "PayApp 2.0",
  "capability": "GPS",
  "telecom": "Airtel"
},

"additionalInfo": {
  "auth_id": "TPSM000082",
  "reseller_auth_id": "NA",
  "customerID": "C00047",
  "adf1": "",
  "adf2": "",
  "adf3": "",
  "adf4": "",
  "adf5": ""
},

"callbackUrl": "https://merchant.com/callback"
}

```

Sample Acknowledgement Response

```
{
  "merchantTxnId": "TXN123456",
  "refId": "REF987654321",
  "auth_id": "AUTH1001",
  "amount": "500.00",
  "payeevpa": "merchant@upi",
  "responseCode": "U25",
  "responseMessage": "PSP ORGID NOT FOUND"
}
```

Callback Response

Field	Datatype	Description
responseCode	String	Final response code (00 = Success)
bankRRN	String	Bank Reference Number for this transaction
upiTranlogId	String	UPI transaction log ID (may be empty)
customerId	String	Internal customer identifier
authId	String	Echo of auth_id from the original request
requestId	String	Echo of the merchantTxnId from the original request
note	String	Transaction note or remark
amount	Decimal	Actual amount processed
payeeVa	String	UPI VPA of the payee
type	String	Transaction type identifier
payeeName	String	Name of the payee
payerVa	String	UPI VPA of the payer
payerName	String	Name of the payer
direction	String	Direction of payment; SENT RECEIVED
status	String	Final transaction status; SUCCESS FAILURE PENDING

Sample Callback Response

```
{"responseCode":"00","bankRRN":"Ref20260325060153655GJYQ","upiTranlogId":"","customerId":"38","authId":"M000062","requestId":
"PP12783348272895127","note":"Payment for order
1234","amount":100.00,"payeeVa":"merchant@icici","type":"COLLECT","payeeName":"ABC
Store","payerVa":"customer@okhdfcbank","payerName":"Rahul Sharma","direction":"SENT","status":"SUCCESS"}
```

3.5 Confirm / Reject

Checksum Logic (SHA-256)

Checksum Formula

merchantTxnId + auth_id + amount + payer.payerAddr + payee.payeeAddr

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
seqNum	Y	String	Var	Original sequence number received during pre-approval	Must match the original pre-approval seqNum
txnId	Y	String	Var	NPCI transaction ID	Transaction ID received from NPCI during transaction initiation
ReqId	Y	String	Var	Merchant request ID	Must be unique for each confirmation request
CustomerId	Y	String	Var	Customer identifier	Validated from DB and mapped against TPAP
authId	Y	String	Var	TPAP authentication ID	Received during TPAP onboarding
Checksum	Y	String	Var	SHA-256 integrity checksum	Generated using checksum logic
payer.ifsc	Y	String	Fix	Payer IFSC code	Must be valid 11-character IFSC
payer.accountNumber	Y	String	Var	Payer account number	Numeric value
payer.addr	Y	String	Var	Payer UPI VPA	Must match original request
payee.addr	Y	String	Var	Payee UPI VPA	Must match original request
transaction.amount	Y	Decimal	Var	Original transaction amount	Must match original transaction amount
transaction.approvedAmount	Y	Decimal	Var	Approved transaction amount	Must match approved amount
transaction.currency	Y	String	Fix	Currency code	Must be INR
transaction.note	Y	String	Var	Transaction note	Maximum 50 characters
transaction.action	Y	String	Fix	Action type	A = Accept, R = Reject
transaction.approvedFlag	Y	String	Fix	Approval flag	Must be M for final confirmation
credentials.type	Y	String	Fix	Credential type	Must be PIN
credentials.subType	Y	String	Fix	Credential subtype	Must be MPIN

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
credentials.data	Y	String	Var	Base64 encoded MPIN	Required for final authorization
device.mobile	Y	String	Fix	Device mobile number	Must be 10 digits
device.geocode	N	String	Var	Device geolocation coordinates	Format: latitude,longitude
device.location	N	String	Var	Device location	Example: Mumbai, IN
device.ip	N	String	Var	Device IP address	Valid IPv4/IPv6 address
device.type	Y	String	Var	Device type	Allowed values: MOBILE, WEB
device.id	Y	String	Var	Device identifier	Unique device ID
device.os	N	String	Var	Device operating system	Example: Android 13
device.app	N	String	Var	Application name/version	Example: PayApp 2.0
device.capability	N	String	Var	Device capability code	Example: 011001

Sample Request Body

```
{
  "seqNum": "ef1e92b4a01d4618a0eca5fdecc37ff23f3",
  "txnId": "20260411153919263A25G",
  "ReqId": "302923472394674",
  "CustomerId": "C00047",
  "authID": "TPSM000082",
  "Checksum": "13bf96cef7f193dc6181c12e25e854376b4e501d0fa9226409871d465f414bfc",
  "adf1": "NA",
  "adf2": "NA",
  "adf3": "NA",
  "adf4": "NA",
  "payer": {
    "addr": "sani21@upi",
    "accountNumber": "34408015821",
    "ifsc": "SBIN0017118"
  },
  "payee": {
    "addr": "drishti@okicici"
  },
  "transaction": {
    "amount": 800.00,
    "approvedAmount": 800.00,
    "currency": "INR",
    "note": "taxi-bill",
    "action": "A",
    "approvedFlag": "M"
  },
  "credentials": {
    "type": "PIN",
    "subType": "MPIN",
    "data": "<base64encodedString>"
  },
  "device": {
    "mobile": "9999999999",
    "geocode": "19.0760,72.8777",
    "location": "Mumbai, IN",

```



```
"ip": "192.168.1.10",
"type": "MOBILE",
"id": "DEVICE123",
"os": "Android 13",
"app": "PayApp 2.0",
"capability": "011001",
"telecom": "Airtel"
}
}
```

Sample Acknowledgement Response

```
{
  "merchantTxnId": "TXN123456",
  "refId": "REF987654321",
  "auth_id": "AUTH1001",
  "amount": "500.00",
  "payeevpa": "merchant@upi",
  "responseCode": "U25",
  "responseMessage": "PSP ORGID NOT FOUND"
}
```

3.6 Intent Payment

Checksum Logic (SHA-256)

Checksum Formula

authId | merchantTxnId | amount | payKey
Example: M000062 | 111023745747141 | 150.00 | drishtinYtx@okicici

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
merchantTxnId	Y	String	Variable	Unique merchant transaction ID	Alphanumeric; max 35 chars; unique per transaction
auth_id	Y	String	Variable	Merchant authentication ID	Merchant Id with shared the merchant credentials over the mail
txn_timestamp	Y	String	Variable	Transaction timestamp	Format: yyyy-MM-dd HH:mm:ss
txn_type	Y	String	Fixed	Transaction type	Value: Intent
txn_ver	Y	String	Variable	Transaction version number	Numeric string; e.g. 111
initiation_mode	Y	String	Fixed	Payment initiation channel	00-Default, 01-QR Code, 02-Secure QR Code, 03-Bharat QR Code, 04-Intent, 05-Secure Intent, 06-NFC, 07-BLE, 08-UHF, 09-Aadhaar, 10-SDK, 11-UPI-Mandate, 12-FIR, 13-QR Mandate, 14-BBPS
checksum	Y	String	Variable	SHA-256 integrity checksum	See Checksum Logic section
purpose_code	Y	String	Fixed	Transaction purpose code	01-SEBI, 02-AMC, 03-Travel, 04-Hospitality, 05-Hospital, 06-Telecom, 07-Insurance, 08-Education, 09-Gifting, 10-BBPS, 11-Global UPI, 12-Metro ATM QR, 13-Non-metro ATM QR, 14-Standing Instruction, 15-Corporate Disbursement
note	N	String	Variable	Remarks or note for the transaction	Max 50 chars
callbackUrl	Y	String	Variable	URL to receive async payment status	Must be a valid with the URL whitelisted in Database
expiresIn	Y	Integer	Variable	Payment link expiry time in minutes	Positive integer; typically, 5-60
amount	Y	Decimal	Variable	Transaction amount in INR	Positive number; max 2 decimal places; min 1.00
pay_key	Y	String	Variable	UPI VPA of the payee (merchant)	Format: localpart@handle
txn_medium	Y	String	Fixed	Medium of transaction initiation	WEB MOBILE
customer.name	Y	String	Variable	Customer full name	Max 50 chars

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customer.email	N	String	Variable	Customer email address	Valid email format; max 100 chars
customer.phone	Y	String	Variable	Customer mobile number with country code	Format: +91XXXXXXXXXX
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "merchantTxnId": "6873683668453",
  "auth_id": "M000062",
  "txn_timestamp": "2026-05-12 17:22:45",
  "txn_type": "Intent",
  "txn_ver": "111",
  "initiation_mode": "00",
  "checksum": "ab349adaaa4ce5a579f024f68c9443db2ad20df091583d32c181f9840d1696b9",
  "purpose_code": "01",
  "note": "Payment for order 1234",
  "callbackUrl": "https://merchant.com/callback",
  "expiresIn": 10,
  "amount": 100.00,
  "reseller_auth_id": "000000",
  "reseller_txn_id": "00000000000000",
  "autoCapture": true,
  "pay_key": "drishtinYtx@okicici",
  "description": "Payment via Intent",
  "txn_medium": "WEB",
  "customer": {
    "name": "John Doe",
    "email": "john.doe@example.com",
    "phone": "+919234567890"
  }
}
```

Response Parameters

Field	Datatype	Description
status	String	Status of payment creation; CREATED on success
gateway_ref_id	String	Unique payment reference ID generated by the gateway
merchant_txn_id	String	Echo of the merchantTxnId sent in the request
payment_expiry	String	Payment link expiry timestamp in ISO 8601 format
action_url	String	URL to redirect customer to the payment page
payment_methods.intent	Array	List of intent payment objects for UPI apps
payment_methods.intent[].app	String	UPI app name (e.g. BHIM, GOOGLE_PAY)
payment_methods.intent[].intentUri	String	Deep-link URI to launch the UPI app for payment
payment_methods.qrPayload	String	QR payload (null for Intent)

Sample Response

```
{
  "status": "CREATED",
  "gateway_ref_id": "202602191057278325E26",
  "merchant_txn_id": "111023745747141",
  "payment_expiry": "2026-02-19T11:07:27.847507792Z",
  "action_url": "https://pay.mockupi.com/202602191057278325E26",
  "payment_methods": {
    "intent": [
      { "app": "BHIM", "intentUri": "upi://pay?pa=drishtinYtx@okicici&am=150.00&cu=INR" },
      { "app": "GOOGLE_PAY", "intentUri": "upi://pay?pa=drishtinYtx@okicici&am=150.00&cu=INR" }
    ],
    "qrPayload": null
  }
}
```

3.7 Dynamic QR

Checksum Logic (SHA-256)

Checksum Formula

auth_id | merchantTxnId | amount | pay_key
Example: M000062 | 113726348764823 | 150.00 | drishtinYtx@okicici

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Same as Intent Payment (API 3.6) with the following difference:

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
txn_type	Y	String	Fixed	Transaction type	Value: Dynamic QR

Sample Request Body

```
{
  "merchantTxnId": "364527364532",
  "auth_id": "M000062",
  "txn_timestamp": "2026-05-11 15:39:45",
```

```

"txn_type": "Dynamic QR",
"txn_ver": "111",
"initiation_mode": "00",
"checksum": "2abf7f7b859cf34941b60e9cca4c3e048d8779b5307f69b7fdf1128ffe5f2311",
"purpose_code": "01",
"note": "Payment for order 1234",
"callbackUrl": "https://merchant.com/callback",
"expiresIn": 10,
"amount": 100.00,
"reseller_auth_id": "000000",
"reseller_txn_id": "00000000000000",
"autoCapture": true,
"pay_key": "drishtinYtx@okicici",
"description": "rqtwyreytqwrytqw",
"txn_medium": "WEB",
"customer": {
  "name": "John Doe",
  "email": "john.doe@example.com",
  "phone": "+919234567890"
}
}

```

Response Parameters

Field	Datatype	Description
status	String	Status of QR creation; CREATED on success
gateway_ref_id	String	Unique payment reference ID generated by the gateway
merchant_txn_id	String	Echo of the merchantTxnId sent in the request
payment_expiry	String	Payment link expiry timestamp in ISO 8601 format
action_url	String	URL to redirect customer to the payment page
payment_methods.intent	String	null for Dynamic QR transactions
payment_methods.qrPayload	String	Base64-encoded PNG image of the QR code; render as on client

Sample Response

```

{
  "status": "CREATED",
  "gateway_ref_id": "20260219133001663VRM2",
  "merchant_txn_id": "113726348764823",
  "payment_expiry": "2026-02-19T13:40:01.677827416Z",
  "action_url": "https://pay.mockupi.com/20260219133001663VRM2",
  "payment_methods": {
    "intent": null,
    "qrPayload": "data:image/png;base64,<BASE64_ENCODED_QR_IMAGE>"
  }
}

```

3.8 Refund (raiseRefund)

Checksum Logic (SHA-256)

Checksum Formula

auth_id | merchant_txn_id | refund_amount
Example: M000062 | 1132323482732895127 | 100.00

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
merchant_txn_id	Y	String	Variable	Original merchant transaction ID to be refunded	Must match a previously completed transaction
auth_id	Y	String	Variable	Merchant authentication ID	Must exist in PSP master repository
valiaddress	Y	String	Variable	Validated address reference	Must match a prior validated address token
reason	Y	String	Variable	Reason for the refund	Max 100 chars
checkSum	Y	String	Variable	SHA-256 integrity checksum	See Checksum Logic section
reseller_auth_id	N	String	Variable	Reseller authentication ID	Use 000000 if not applicable
reseller_txn_id	N	String	Variable	Reseller transaction ID	Use 00000000000000 if not applicable
ref_timestamp	Y	String	Variable	Refund request timestamp	Format: yyyy-MM-dd HH:mm:ss
saleOrgTxnDate	Y	String	Variable	Date of the original sale transaction	Format: yyyy-MM-dd
txnVer	Y	String	Variable	Transaction version	e.g. 1.0
reqType	Y	String	Fixed	Request type	Value: REFUND
refund_type	Y	String	Fixed	Type of refund	PR = Partial Refund FR = Full Refund
saleRequestId	N*	String	Variable	Original PSP request ID of the sale	Mandatory for partial refunds (refund_type=PR)
salePSPRequestId	N*	String	Variable	Original PSP-level request ID of the sale	Mandatory for partial refunds (refund_type=PR)
refund_amount	N*	Decimal	Variable	Amount to be refunded	Mandatory for PR; must be <= original sale amount
saleTxnAmount	Y	Decimal	Variable	Original sale transaction amount	Positive number; must match the original transaction
currency	Y	String	Fixed	Currency code	Value: INR
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "merchant_txn_id": "1132323482732895127",
  "auth_id": "M000062",
  "valiaddress": "MSG1234",
  "reason": "Customer requested refund",
  "checkSum": "5ae95905e8d01b8d1e32243437b0f793663b6cf645331d75f562326a5d92d9ca",
  "reseller_auth_id": "000000",
  "reseller_txn_id": "00000000000000",
}
```

```

"ref_timestamp": "2026-02-10 12:34:45",
"saleOrgTxnDate": "2026-02-10",
"txnVer": "1.0",
"reqType": "REFUND",
"refund_type": "PR",
"saleRequestId": "",
"salePSPRequestId": "",
"refund_amount": 100.00,
"saleTxnAmount": 100.00,
"currency": "INR",
"adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}

```

Acknowledgement Response

Field	Datatype	Description
code	String	Acknowledgement response code (00 = Accepted, U52 = PSP Org ID Not Found)
message	String	Human-readable description of the acknowledgement code
data	String	Additional data; empty string on acknowledgement

Sample Acknowledgement Response

```

{
  "code": "00",
  "message": "Request Accepted",
  "data": ""
}

```

Callback Response

Field	Datatype	Description
responseCode	String	Final response code (00 = Success)
bankRRN	String	Bank Reference Number for this transaction
upiTranlogId	String	UPI transaction log ID (may be empty)
customerId	String	Internal customer identifier
authId	String	Echo of auth_id from the original request
requestId	String	Echo of the merchantTxnId from the original request
note	String	Transaction note or remark
amount	Decimal	Actual amount processed
payeeVa	String	UPI VPA of the payee
type	String	Transaction type identifier
payeeName	String	Name of the payee
payerVa	String	UPI VPA of the payer
payerName	String	Name of the payer
direction	String	Direction of payment; SENT RECEIVED
status	String	Final transaction status; SUCCESS FAILURE PENDING

Sample Callback Response

```

{
  "responseCode": "00",
  "bankRRN": "Ref20260325060153655GJYQ",
  "upiTranlogId": "",
  "customerId": "38",
  "authId": "M000062",
  "requestId": "TXN005",
  "note": "Reversal",
  "amount": 100.00,
}

```

```

"payeeVa": "merchant@icici",
"type": "REFUND",
"payeeName": "ABC Store",
"payerVa": "customer@okhdfcbank",
"payerName": "Rahul Sharma",
"direction": "SENT",
"status": "SUCCESS"
}

```

3.9 Balance Enquiry

Request Parameters

Key: Y = Mandatory N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Internal customer identifier	Alphanumeric; must exist in system
requestId	Y	String	Variable	Unique request identifier	Alphanumeric only; max length 35
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
addrType	Y	String	Fixed	Address type for account lookup	AADHAAR ACCOUNT MOBILE
aadhaarIin	N*	String	Variable	Aadhaar IIN number	Mandatory if addrType = AADHAAR
aadhaarUidNum	N*	String	Variable	Aadhaar UID number	Mandatory if addrType = AADHAAR
accountIfsc	N*	String	Variable	Bank IFSC code	Mandatory if addrType = ACCOUNT
accountAcType	Y	String	Fixed	Bank account type	SAVINGS CURRENT DEFAULT NRE NRO CREDIT
accountAcNum	N*	String	Variable	Bank account number	Mandatory if addrType = ACCOUNT; max 18 chars
mobileMmid	N*	String	Variable	Mobile Money Identifier	Mandatory if addrType = MOBILE
mobileMobNum	N*	String	Variable	Mobile number for MOBILE address	Mandatory if addrType = MOBILE; 10-digit
payerAddr	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle
payerName	Y	String	Variable	Full name of the payer	Max 50 chars
payerSeqNum	Y	String	Variable	Payer sequence number	Numeric string; e.g. 1
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY
payerCode	Y	String	Fixed	Payer bank institution code	Exactly 4 digits; e.g. 0000
credType	Y	String	Fixed	Credential type for authentication	CARD OTP PIN
credSubType	Y	String	Fixed	Credential sub-type	CARDDETAILS SMS EMAIL HOTP TOTP MPIN ATMPIN
dataNodeValue	Y	String	Variable	Encrypted or plain credential data	Value depends on credType/credSubType
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system of the device	ANDROID IOS

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\.[0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application package name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Comma-separated device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00043",
  "requestId": "REQ234366643",
  "tpapId": "M000025",
  "addrType": "ACCOUNT",
  "accountIfsc": "ICIC0001234",
  "accountAcType": "SAVINGS",
  "accountAcNum": "123456789012",
  "aadhaarlin": "",
  "aadhaarUidNum": "",
  "mobileMmid": "",
  "mobileMobNum": "",
  "payerAddr": "user43@upi",
  "payerName": "John Doe",
  "payerSeqNum": "1",
  "payerType": "PERSON",
  "payerCode": "0000",
  "credType": "OTP",
  "credSubType": "SMS",
  "dataNodeValue": "123456",
  "deviceInfo": {
    "mobile": "9876543210",
    "os": "ANDROID",
    "appVersion": "2.3.1",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "49.205.45.12",
    "id": "DEVICE987654321",
    "app": "com.upi.app",
    "capability": "UPI",
    "telecom": "AIRTEL"
  },
  "adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	String	Internal customer ID assigned by the system
deviceId	String	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId": "123ARHKDKSHIS2026032705445588198757",
  "customerId": "C00043",
  "deviceId": "DEVICE987654321",
  "mobileNumber": "9876543210",
  "requestId": "REQ123456",
  "responseCode": "E09",
  "responseMessage": "Failed At NPCI Side",
  "tpapId": "M000025"
}
```

Callback Response

Field	Datatype	Description
resp.result	String	Final result of balance enquiry; SUCCESS or FAILURE
resp.errCode	String	Error code; 00 = Success
resp.reqMsgId	String	Echo of the requestId from the original request
payer.code	String	Payer bank institution code
payer.seqNum	String	Payer sequence number
payer.name	String	Name of the payer
payer.addr	String	UPI VPA of the payer
payer.bal.data	String	Base64-encoded encrypted balance data; decrypt using AES-256-GCM
payer.type	String	Payer entity type; PERSON or ENTITY

Sample Callback Response

```
{
  "resp": {
    "result": "SUCCESS",
    "errCode": "00",
    "reqMsgId": "REQ234366643"
  },
  "payer": {
    "code": "0000",
    "seqNum": "1",
    "name": "John Doe",
    "addr": "user43@upi",
    "bal": { "data": "BASE64_ENCRYPTED_BALANCE_DATA" },
    "type": "PERSON"
  }
}
```

3.10 VPA Validate (reqValAddr)

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
deviceId	Y	String	Variable	Device ID is a unique identifier of the user's device. It is used by the NPCI Common Library during,Challenge/Token generation,MPIN encryption and validation.	Alphanumeric; max 50 chars
seqNo	Y	String	Variable	Unique sequence number for this request	Alphanumeric; max 50 chars; unique per session
virtualAddress	Y	String	Variable	UPI VPA of the payee to be validated	Format: localpart@handle; e.g. xyz@psp
payeeName	Y	String	Variable	Name associated with the payee VPA	Max 50 chars
devicemobile	Y	String	Variable	Mobile number registered with the device	Format: 91XXXXXXXXXX (with country code, no +)
deviceGeoCode	Y	String	Variable	GPS coordinates of the device	Format: latitude,longitude
deviceLocation	Y	String	Variable	Human-readable device location	Max 100 chars
deviceIp	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceType	Y	String	Fixed	Type of device	MOB TAB PC
deviceOS	Y	String	Variable	Operating system of the device	e.g. Android9, iOS16
deviceApp	Y	String	Variable	Application package name or identifier	e.g. com.upi.npci
deviceCapability	Y	String	Fixed	Comma-separated device capability flags	e.g. 011001
deviceTeleCom	Y	String	Variable	Telecom operator of the device SIM	e.g. AIRTEL, JIO
payerAddr	Y	String	Variable	UPI VPA of the payer initiating the request	Format: localpart@handle
payerName	Y	String	Variable	Full name of the payer	Max 50 chars
payerSeqNum	Y	String	Variable	Sequence number assigned to the payer	Numeric string; e.g. 1
payerType	Y	String	Fixed	Type of payer entity	PERSON ENTITY
payerCode	Y	String	Fixed	Payer's bank institution code	Exactly 4 digits
txnId	Y	String	Variable	Unique transaction ID for this validation request	Alphanumeric; max 35 chars
identityId	N	String	Variable	Identity document number (e.g. PAN)	Format based on identitytype
identitytype	N	String	Fixed	Type of identity document provided	PAN AADHAAR DRIVING_LICENSE
verifiedName	N	String	Variable	Name as per the identity document	Max 50 chars
isAddrVerified	Y	String	Fixed	Indicates if address was pre-verified	true false
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "deviceId": "84521654864135",
  "seqNo": "ef1e92b4a01d4618a0eca5fdecc37ff23f3",
  "virtualAddress": "xyz@psp",
  "payeeName": "Rohit Patekar",
  "devicemobile": "919136086373",
  "deviceGeoCode": "91.9819,23.9404",
  "deviceLocation": "HYDERABAD",
  "deviceIp": "10.25.205.68",
  "deviceType": "MOB",
  "deviceOS": "Android9",
  "deviceApp": "com.upi.npci",
  "deviceCapability": "011001",
  "deviceTeleCom": "AIRTEL",
  "payerAddr": "rohit@upi",
  "payerName": "Rohit Patekar",
  "payerSeqNum": "1",
  "payerType": "PERSON",
  "payerCode": "0000",
  "txnId": "TXN123456789",
  "identityId": "ABCDE1234F",
  "identitytype": "PAN",
  "verifiedName": "Rohit Patekar",
  "isAddrVerified": "true",
  "adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}
```

Acknowledgement Response

Field	Datatype	Description
code	String	Acknowledgement response code (e.g. 00 = Success, U52 = PSP Org ID Not Found)
message	String	Human-readable description of the acknowledgement code
data	String	Additional data; empty string on acknowledgement

Sample Acknowledgement Response

```
{
  "code": "00",
  "message": "Request Accepted",
  "data": ""
}
```

Callback Response

Field	Datatype	Description
responseCode	String	Final response code from NPCI (00 = Success)
bankRRN	String	Bank Reference Number assigned to this transaction
upiTranlogId	String	UPI transaction log ID (may be empty)
customerId	String	Internal customer identifier
authId	String	Echo of auth_id from the original request
requestId	String	Echo of the request identifier
virtualAddress	String	The VPA that was validated
payeeName	String	Registered name of the VPA holder returned from NPCI

Field	Datatype	Description
status	String	Final status of the validation; SUCCESS FAILURE

Sample Callback Response

```
{
  "responseCode": "00",
  "bankRRN": "Ref20260325060153655GJYQ",
  "upiTranlogId": "",
  "customerId": "38",
  "authId": "M000062",
  "requestId": "PP12783348272895127",
  "virtualAddress": "xyz@psp",
  "payeeName": "ABC Store",
  "status": "SUCCESS"
}
```

4. Mandate Management

4.1 Initiate Mandate

Request Parameters

Key: **Y** = **Mandatory** N = Non-Mandatory *N** = *Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	Must exist in system
requestId	Y	String	Variable	Unique request identifier	Alphanumeric; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
seqNo	Y	String	Variable	Unique sequence number	Alphanumeric
preApproved	Y	String	Fixed	Pre-approval type	M = MPIN required; A = Pre-approved
profileId	Y	String	Variable	Profile identifier	
payerVa	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle Validated from database vpa against TPAP Id
payeeVa	Y	String	Variable	UPI VPA of the payee	Format: localpart@handle; must exist and be active
action	Y	String	Fixed	Mandate action	CREATE Update revoke
mode	Y	String	Fixed	Mandate mode	PAY Collect
ifsc	Y	String	Fixed	IFSC code of payer's bank	^[A-Z]{4}0[A-Z0-9]{6}\$
accountNumber	Y	String	Variable	Payer's bank account number	Must match customerId records
accountProvider	Y	String	Variable	Payer's bank / account provider	
amount	Y	String	Variable	Maximum mandate amount	Positive numeric value
amountRule	Y	String	Fixed	Amount rule for the mandate	MAX EXACT
note	N	String	Variable	Note or description for the mandate	Max 50 chars
mandateName	Y	String	Variable	Name of the mandate	
startDate	Y	String	Variable	Mandate start date	Format: dd-MM-yyyy
endDate	Y	String	Variable	Mandate end date	Format: dd-MM-yyyy; must be after startDate
frequency	Y	String	Fixed	Debit frequency	DAILY WEEKLY FORTNIGHTLY MONTHLY BIMONTHLY QUARTERLY HALFYEARLY YEARLY ASPRESENTED
debitDay	N	String	Variable	Day of the month for debit	01-31 (applicable for MONTHLY frequency)
debitRule	Y	String	Fixed	Debit rule	ON BEFORE AFTER
mpin	Y	String	Variable	Encrypted MPIN for authorisation	Encrypted using NPCI Common Library
notifyFlag	N	String	Fixed	Enable/disable notifications	true false

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
revokeable	Y	String	Fixed	Whether mandate can be revoked by payer	Y N
shareToPayee	Y	String	Fixed	Share mandate details with payee	Y N
blockFund	Y	String	Fixed	Block funds for mandate	Y N
expireAfter	N	String	Variable	Number of months after which mandate expires	Numeric string
umn	C	String	Variable	Unique Mandate Number	Assigned by NPCI (Not mandatory if create)
payeeName	N	String	Variable	Name of the payee	
payerName	N	String	Variable	Name of the payer	
mandateNickName	N	String	Variable	Nickname for the mandate	
purpose	Y	String	Variable	Purpose code for the mandate	2-digit numeric code
mcc	N	String	Variable	Merchant Category Code	4-digit numeric code
merchantType	N	String	Fixed	Merchant type	ONLINE OFFLINE
mid	N	String	Variable	Merchant ID	
msid	N	String	Variable	Merchant Store ID	
mtid	N	String	Variable	Merchant Terminal ID	
brand	N	String	Variable	Brand name	
legal	N	String	Variable	Legal name	
franchise	N	String	Variable	Franchise name	
ownershipType	N	String	Fixed	Ownership type	PRIVATE PUBLIC
customerType	N	String	Fixed	Customer type	PERSON ENTITY
signature	Y	String	Variable	signature	requestId seqNo accountNumber tpapId
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\.[0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must not already exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00047",
  "requestId": "REQ1000111",
  "tpapId": "TPSM000080",
  "deviceInfo": {
    "mobile": "8080173945",
    "os": "Android",
    "appVersion": "1.0.0",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "192.168.1.1",
    "id": "DEVICE18776656445",
    "app": "MyUPIApp",
    "capability": "UPI",
    "telecom": "JIO"
  },
  "seqNo": "SEQ123456",
  "preApproved": "A",
  "profileId": "12345",
  "umn": "UMN100000001",
  "payeeVa": "nitesh98@upi",
  "payerVa": "sani21@upi",
  "action": "UPDATE",
  "mode": "PAY",
  "ifsc": "ICIC0005678",
  "accountNumber": "99995343665666",
  "accountProvider": "ICIC",
  "amount": "400",
  "amountRule": "MAX",
  "note": "NetFlix",
  "mandateName": "NetFlix Subscription",
  "startDate": "14052026",
  "endDate": "14052028",
  "frequency": "MONTHLY",
  "debitDay": "1",
  "debitRule": "ON",
  "mpin": "",
  "notifyFlag": "false",
  "revokeable": "Y",
  "shareToPayee": "Y",
  "blockFund": "N",
  "expireAfter": "1",
  "payeeName": "Merchant Name",
  "payerName": "sani",
  "mandateNickName": "AutoPay",
  "purpose": "01",
  "mcc": "1243",
  "merchantType": "LARGE",
  "mid": "MID123456",
  "msid": "MSID123",
  "mtid": "MTID123",
  "brand": "BRANDX",
  "legal": "LEGALNAME",
}
```



```
"franchise": "NA",  
"ownershipType": "PRIVATE",  
"customerType": "PERSON",  
"signature": "JVPkW3qJPEv1gZankeA6nch9tGG5IBTyduZ10DqOsHg=",  
"adf1": "",  
"adf2": "",  
"adf3": "",  
"adf4": "",  
"adf5": ""  
}
```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	Integer	Internal customer ID assigned by the system
deviceId	String	Device identifier echoed from request
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```
{
  "MessageId" : "123OTAWFNALGV2026032311512235934441",
  "customerId" : "C00043",
  "mobileNumber" : "9876543210",
  "requestId" : "REQ55323294",
  "responseCode" : "E09",
  "responseMessage" : "Failed At NPCI Side",
  "tpapId" : "M000025"
}
```

4.2 Get Pending Mandate

Request Parameters

Key: **Y** = **Mandatory** N = Non-Mandatory *N** = *Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	Must exist in system
requestId	Y	String	Variable	Unique request identifier	Alphanumeric; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
seqNo	Y	String	Variable	Unique sequence number	Alphanumeric
payerVa	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle
signature	Y			signature	tpapId seqNo customerId requestId
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system	ANDROID IOS

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\.[0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00047",
  "requestId": "REQ343442232",
  "tpapId": "TPSM000080",
  "seqNo": "SEQ123453",
  "payerVa": "sani21@upi",
  "signature": "78AN5vXhSqKpRrNJzmmAdRJhSoGoYz2pw4vuP2iJOuw=",
  "deviceInfo": {
    "mobile": "8080173945",
    "os": "Android",
    "appVersion": "1.0.0",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "192.168.1.1",
    "id": "DEVICE18776656445",
    "app": "MyUPIApp",
    "capability": "UPI",
    "telecom": "JIO"
  },
  "adf1": "",
  "adf2": "",
  "adf3": "",
  "adf4": "",
  "adf5": ""
}
```

Response Parameters

Field	Datatype	Description
customerId	String	Unique customer identifier
mandateData[].amount	String	Mandate amount
mandateData[].deviceId	String	Device identifier associated with the mandate
mandateData[].endDate	String	Mandate end date in DDMMYYYY format
mandateData[].frequency	String	Debit frequency; e.g. MONTHLY
mandateData[].mandateName	String	Name/label of the mandate
mandateData[].payeeVa	String	UPI VPA of the payee
mandateData[].requestId	String	Unique request identifier for the mandate
mandateData[].startDate	String	Mandate start date in DDMMYYYY format
mandateData[].status	String	Current status of the mandate; e.g. INITIATED, Send to NPCI
payerVa	String	UPI VPA of the payer
responseCode	String	Response code; 00 = Success
responseMessage	String	Human-readable response message

Sample Response

```
{
  "customerId": "C00047",
  "mandateData": [
    {
      "amount": "5000",
      "deviceId": "DEVICE18776656445",
      "endDate": "08082027",
      "frequency": "MONTHLY",
      "mandateName": "OTT Subscription",
      "payeeVa": "nitesh@upi",
      "requestId": "REQ1000001",
      "startDate": "08042026",
      "status": "INITIATED"
    },
    {
      "amount": "5000",
      "deviceId": "DEVICE18776656445",
      "endDate": "08082027",
      "frequency": "MONTHLY",
      "mandateName": "OTT Subscription",
      "payeeVa": "nitesh@upi",
      "requestId": "REQ1000004",
      "startDate": "08042026",
      "status": "Send to NPCI"
    },
    {
      "amount": "2100",
      "deviceId": "DEVICE18776656445",
```

```

    "endDate" : "08082027",
    "frequency" : "MONTHLY",
    "mandateName" : "OTT Subscription",
    "payeeVa" : "roshan@upi",
    "requestId" : "REQ1000005",
    "startDate" : "08042026",
    "status" : "Send to NPCI"
  },
  {
    "amount" : "2100",
    "deviceId" : "DEVICE18776656445",
    "endDate" : "08082027",
    "frequency" : "MONTHLY",
    "mandateName" : "OTT Subscription",
    "payeeVa" : "roshan@upi",
    "requestId" : "REQ1000006",
    "startDate" : "08042026",
    "status" : "Send to NPCI"
  }
],
"payerVa" : "sani21@upi",
"responseCode" : "00",
"responseMessage" : "Mandate Fetch Successful"
}

```

4.3 Approve / Reject Mandate

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	Must exist in system
requestId	Y	String	Variable	Unique request identifier	Alphanumeric; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository
msgId	Y	String	Variable	MsgId Id	MsgId validate from Databases if exists.
seqNo	Y	String	Variable	Unique sequence number	Alphanumeric
preApproved	Y	String	Fixed	Pre-approval type	M = MPIN required; A = Pre-approved
payerVa	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle
payeeVa	Y	String	Variable	UPI VPA of the payee	Must exist and be active; throw error if not present
action	Y	String	Fixed	Action to perform	APPROVE REJECT
mode	Y	String	Fixed	Mandate mode	COLLECT
ifsc	Y	String	Fixed	IFSC code of payer's bank	^[A-Z]{4}0[A-Z0-9]{6}\$
accountNumber	Y	String	Variable	Payer's bank account number	Must match customerId records
accountProvider	Y	String	Variable	Payer's bank / account provider	
amount	Y	String	Variable	Mandate amount	Positive numeric value
frequency	Y	String	Fixed	Debit frequency	DAILY WEEKLY MONTHLY YEARLY ASPRESENTED

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
debitRule	Y	String	Fixed	Debit rule	ON BEFORE AFTER
mpin	Y	String	Variable	Encrypted MPIN for authorisation	Encrypted using NPCI Common Library
revokeable	Y	String	Fixed	Whether mandate can be revoked by payer	Y N
shareToPayee	Y	String	Fixed	Share mandate details with payee	Y N
blockFund	Y	String	Fixed	Block funds for mandate	Y N
umn	Y	String	Variable	Unique Mandate Number	Must match existing pending mandate
signature	Y	String	Variable	Signature format SHA256	tpapId seqNo accountNumber requestId
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\.[0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00047",
  "requestId": "REQ1234345776",
  "tpapId": "TPSM000082",
  "seqNo": "SEQ123456",
  "preApproved": "M",
  "payerVa": "user@upi",
  "payeeVa": "merchant@upi",
  "action": "APPROVE",
  "mode": "PAY",
  "ifsc": "HDFC0001234",
  "accountNumber": "123456789012",
  "accountProvider": "HDFC",
  "amount": "5000",
  "frequency": "MONTHLY",
  "debitRule": "ON",
  "mpin": "encrypted-mpin-value",
  "revokeable": "Y",
}
```

```

"shareToPayee": "Y",
"blockFund": "N",
"umrn": "UMN123456789",
"deviceInfo": {
  "mobile": "8080173945",
  "os": "Android",
  "appVersion": "1.0.0",
  "type": "MOBILE",
  "geoCode": "19.0760,72.8777",
  "location": "Mumbai",
  "ip": "192.168.1.1",
  "id": "DEVICE18776656445",
  "app": "MyUPIApp",
  "capability": "UPI",
  "telecom": "JIO"
},
"adf1": "", "adf2": "", "adf3": "", "adf4": "", "adf5": ""
}

```

Acknowledgement Response

Field	Datatype	Description
MessageId	String	Unique message ID generated by the system
customerId	Integer	Internal customer ID assigned by the system
deviceId	String	Device identifier echoed from request
mobileNumber	String	Mobile number associated with the device
requestId	String	Echo of the requestId sent in the request
responseCode	String	Acknowledgement status code
responseMessage	String	Human-readable response message
tpapId	String	TPAP ID associated with the request

Sample Acknowledgement Response

```

{
  "MessageId" : "123OTAWFNLGV2026032311512235934441",
  "customerId" : "C00043",
  "mobileNumber" : "9876543210",
  "requestId" : "REQ55323294",
  "responseCode" : "E09",
  "responseMessage" : "Failed At NPCI Side",
  "tpapId" : "M000025"
}

```

4.4 Get All Mandates

Request Parameters

Key: **Y = Mandatory** N = Non-Mandatory *N* = Conditionally Mandatory*

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
customerId	Y	String	Variable	Unique customer identifier	Must exist in system
requestId	Y	String	Variable	Unique request identifier	Alphanumeric; max length 25
tpapId	Y	String	Variable	Third-party app provider ID	Must exist in PSP master repository

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
seqNo	Y	String	Variable	Unique sequence number	Alphanumeric
payerVa	Y	String	Variable	UPI VPA of the payer	Format: localpart@handle
mandateMode	N	String	Fixed	Filter by mandate mode	A = All P = Pending C = Created R = Revoked
mandateId	N	String	Variable	Filter by specific mandate reference number (UMN)	UMN Number
signature	Y	String	Variable	signature	tpapId seqNo customerId requestId
deviceInfo.mobile	Y	String	Variable	Mobile number of the device	10-digit mobile number
deviceInfo.os	Y	String	Fixed	Operating system	ANDROID IOS
deviceInfo.appVersion	Y	String	Variable	Version of the UPI application	^[0-9]+(\\. [0-9]+){1,2}\$
deviceInfo.type	Y	String	Fixed	Device type	MOBILE TABLET WEB
deviceInfo.geoCode	Y	String	Variable	Geographic coordinates of the device	Format: latitude,longitude
deviceInfo.location	Y	String	Variable	Human-readable location name	Only alphabets are allowed
deviceInfo.ip	Y	String	Variable	IP address of the device	Valid IPv4 address
deviceInfo.id	Y	String	Variable	Unique device identifier	Must exist in NPCI device config
deviceInfo.app	Y	String	Variable	Application name	^[a-zA-Z0-9._-]{3,30}\$
deviceInfo.capability	Y	String	Variable	Device capabilities	"UPI", "NFC", "BIOMETRIC"
deviceInfo.telecom	Y	String	Variable	Telecom operator name	"JIO", "AIRTEL", "VI", "BSNL"
adf1	N	String	Variable	Additional data field 1	
adf2	N	String	Variable	Additional data field 2	
adf3	N	String	Variable	Additional data field 3	
adf4	N	String	Variable	Additional data field 4	
adf5	N	String	Variable	Additional data field 5	

Sample Request Body

```
{
  "customerId": "C00047",
  "requestId": "REQ235623232",
  "tpapId": "TPSM000080",
  "seqNo": "SEQ123436",
  "payerVa": "sani21@upi",
  "mode": "COLLECT",
  "mandateMode": "",
  "mandateRefNo": "",
  "signature": "zAf+4siqwdf8PrWsPisGyX0BnxxSal5dzEKkshtl1Ns=",
  "deviceInfo": {
    "mobile": "8080173945",
    "os": "Android",
    "appVersion": "1.0.0",
    "type": "MOBILE",
    "geoCode": "19.0760,72.8777",
    "location": "Mumbai",
    "ip": "192.168.1.1",
    "id": "DEVICE18776656445",
    "app": "MyUPIApp",
    "capability": "UPI",
  }
}
```



```
"telecom": "JIO"
},
"adf1": "",
"adf2": "",
"adf3": "",
"adf4": "",
"adf5": ""
}
```

Response Parameters

Field	Datatype	Description
customerId	String	Unique customer identifier
mandateData[].amount	String	Mandate amount
mandateData[].deviceId	String	Device identifier associated with the mandate
mandateData[].endDate	String	Mandate end date in DDMMYYYY format
mandateData[].frequency	String	Debit frequency; e.g. MONTHLY
mandateData[].mandateName	String	Name/label of the mandate
mandateData[].payeeVa	String	UPI VPA of the payee
mandateData[].requestId	String	Unique request identifier for the mandate
mandateData[].startDate	String	Mandate start date in DDMMYYYY format
mandateData[].status	String	Current status of the mandate; e.g. INITIATED, Send to NPCI
payerVa	String	UPI VPA of the payer
responseCode	String	Response code; 00 = Success
responseMessage	String	Human-readable response message

Sample Response

```
{
  "customerId": "C00047",
  "mandateData": [
    {
      "amount": "34000",
      "deviceId": "DEVICE18776656445",
      "endDate": "07082027",
```

```
"frequency" : "MONTHLY",
"mandateName" : "OTT Collect Mandate",
"payeeVa" : "khush1@upi",
"requestId" : "REQ3653245112",
"startDate" : "07042026",
"status" : "INITIATED"
},
{
  "amount" : "34000",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "07082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Collect Mandate",
  "payeeVa" : "Ashu1@upi",
  "requestId" : "REQ5123245112",
  "startDate" : "07042026",
  "status" : "INITIATED"
},
{
  "amount" : "34000",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "07082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Collect Mandate",
  "payeeVa" : "Ashu1@upi",
  "requestId" : "REQ514564562",
  "startDate" : "07042026",
  "status" : "INITIATED"
},
{
  "amount" : "5000",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "08082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Subscription",
  "payeeVa" : "nitesh@upi",
  "requestId" : "REQ1000001",
  "startDate" : "08042026",
  "status" : "INITIATED"
},
{
  "amount" : "5000",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "08082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Subscription",
  "payeeVa" : "nitesh@upi",
  "requestId" : "REQ1000004",
  "startDate" : "08042026",
  "status" : "Send to NPCI"
},
{
  "amount" : "2100",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "08082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Subscription",
  "payeeVa" : "roshan@upi",
  "requestId" : "REQ1000005",
  "startDate" : "08042026",
  "status" : "Send to NPCI"
},
{
  "amount" : "2100",
  "deviceId" : "DEVICE18776656445",
  "endDate" : "08082027",
  "frequency" : "MONTHLY",
  "mandateName" : "OTT Subscription",
  "payeeVa" : "roshan@upi",
  "requestId" : "REQ1000006",
```

```
    "startDate" : "08042026",  
    "status" : "Send to NPCI"  
  },  
  ],  
  "payerVa" : "sani21@upi",  
  "responseCode" : "00",  
  "responseMessage" : "Mandate Fetch Successful"  
}
```

5. Encryption / Decryption API

This API is used to encrypt and decrypt sensitive data (such as MPIN and account details) using AES-256-GCM. The PSP provides an AuthId for authentication.

5.1 Request Parameters

Field	M/NM	Datatype	Fix/Var	Description	Rule / Validation
AuthId	Y	String	Variable	Authentication ID	Provided by PSP
Reqbody	Y	String	Variable	Encrypted request body / data to encrypt or decrypt	Base64-encoded AES-256-GCM encrypted string

Sample Request

```
{
  "encDate": "B4UErTvB7UliOPNReBP6GspAXm9Mvap6Cqdiy+oAFNf47swes/2UyTM8GllC6dbw
PxipfcezOxWHldmwhkPZeM1Omu8rrcPfhAooKy0Jj0WV9YwyGfAoSkTp1ALn3Ggr
OWCR1CgOzhs9PHEBXukfhfsuQeU6frjNR/Mwm90wDXfTV3crVdm+uw1LTDXTfk1
... (truncated for readability)",
  "AuthId": "M000025"
}
```

5.2 Response Parameters

Field	Datatype	Description
AuthId	String	Authentication ID received from PSP
EncResponse	String	Encrypted response data (Base64-encoded AES-256-GCM)

Sample Response

```
{
  "AuthId": "M000025",
  "EncResponse": "Ge9gQld5fEEnmjp7ZaZwjE5i94t9QYW7NQPFvudJI0z/ImCsMqJmdnljAC4t233T
m+W3SWvMvyWITBUERRPUQyRZp1b1vqsklQqFjkXLW6QOprRSfZfoZ2MR6DkER3v
... (truncated for readability)"
}
```

5.3 Encryption Logic (Java — AES-256-GCM)

Encryption Implementation

```
public String encrypt(String plainText, String keyString) throws Exception {
    byte[] keyBytes = keyString.getBytes(StandardCharsets.UTF_8);
    if (keyBytes.length != 32) {
        throw new IllegalArgumentException("AES-256 key must be 32 bytes");
    }
    SecretKeySpec keySpec = new SecretKeySpec(keyBytes, "AES");
    byte[] iv = new byte[12]; // 12 bytes for GCM
    new SecureRandom().nextBytes(iv);
    Cipher cipher = Cipher.getInstance("AES/GCM/NoPadding");
    GCMParameterSpec spec = new GCMParameterSpec(128, iv);
    cipher.init(Cipher.ENCRYPT_MODE, keySpec, spec);
    byte[] encrypted = cipher.doFinal(plainText.getBytes(StandardCharsets.UTF_8));
    byte[] encryptedWithIv = new byte[iv.length + encrypted.length];
    System.arraycopy(iv, 0, encryptedWithIv, 0, iv.length);
    System.arraycopy(encrypted, 0, encryptedWithIv, iv.length, encrypted.length);
    return Base64.getEncoder().encodeToString(encryptedWithIv);
}
```

5.4 Decryption Logic (Java — AES-256-GCM)

Decryption Implementation

```
public static String decrypt(String cipherText, String keyString) throws Exception {
    byte[] keyBytes = keyString.getBytes(StandardCharsets.UTF_8);
    if (keyBytes.length != 32) {
        throw new IllegalArgumentException("AES-256 key must be 32 bytes");
    }
    SecretKeySpec keySpec = new SecretKeySpec(keyBytes, "AES");
    byte[] iv = new byte[12]; // 12 bytes for GCM
    new SecureRandom().nextBytes(iv);
    Cipher cipher = Cipher.getInstance("AES/GCM/NoPadding");
    GCMParameterSpec spec = new GCMParameterSpec(128, iv);
    cipher.init(Cipher.DECRYPT_MODE, keySpec, spec);
    byte[] encryptedWithIv = Base64.getDecoder().decode(cipherText);
    System.arraycopy(iv, 0, encryptedWithIv, 0, iv.length);
    byte[] encrypted = new byte[encryptedWithIv.length - iv.length];
    System.arraycopy(encryptedWithIv, iv.length, encrypted, 0, encrypted.length);
    return new String(cipher.doFinal(encrypted), StandardCharsets.UTF_8);
}
```

```

    }
    SecretKeySpec keySpec = new SecretKeySpec(keyBytes, "AES");
    byte[] decoded = Base64.getDecoder().decode(cipherText);
    byte[] iv = new byte[12];
    byte[] encrypted = new byte[decoded.length - 12];
    System.arraycopy(decoded, 0, iv, 0, 12);
    System.arraycopy(decoded, 12, encrypted, 0, encrypted.length);
    Cipher cipher = Cipher.getInstance("AES/GCM/NoPadding");
    GCMParameterSpec spec = new GCMParameterSpec(128, iv);
    cipher.init(Cipher.DECRYPT_MODE, keySpec, spec);
    byte[] decrypted = cipher.doFinal(encrypted);
    return new String(decrypted, StandardCharsets.UTF_8);
}

```

5.5 Signature Logic (SHA-256)

SHA-256 Signature Implementation

```

public static String sha256(String input) throws Exception {
    MessageDigest digest = MessageDigest.getInstance("SHA-256");
    byte[] hash = digest.digest(input.getBytes("UTF-8"));
    return Base64.getEncoder().encodeToString(hash);
}

```

5.6 Checksum Logic (SHA-256)

SHA-256 Checksum Implementation

```

public static String generateSHA256(String input) {
    try {
        MessageDigest digest = MessageDigest.getInstance("SHA-256");
        byte[] hash = digest.digest(input.getBytes(StandardCharsets.UTF_8));

        StringBuilder hexString = new StringBuilder();

        for (byte b : hash) {
            String hex = Integer.toHexString(0xff & b);

            if (hex.length() == 1) {
                hexString.append('0');
            }

            hexString.append(hex);
        }

        return hexString.toString();
    } catch (Exception e) {
        throw new RuntimeException("Error generating checksum", e);
    }
}

```

