



Sunbeam Institute of Information Technology

Pune and Karad

PreCAT

Module – Data Structures

Trainer - Devendra Dhande

Email – devendra.dhande@sunbeaminfo.com




Stack and Queue - Introduction

Stack

- Stack is Last-In-First-Out structure.
- Stack Operations:

- push()
- pop()
- peek()
- is_empty()
- is_full()



- Both Stack and Queue can be implemented using array and linked lists.

Stack Applications

- Parenthesis balancing
- Expression conversion and evaluation
- Function calls
- Used in advanced data structures for traversing
- **Expression conversion and evaluation:**
 - Infix to postfix
 - Infix to prefix
 - Postfix evaluation
 - Prefix evaluation
 - Prefix to postfix
 - Postfix to infix



Infix to Postfix Conversion

- Process each element of infix expression from left to right
- If element is Operand
 - Append it to the postfix expression
- If element is Operator
 - If priority of topmost element (Operator) of stack is greater or equal to current element (Operator), pop topmost element from stack and append it to postfix expression
 - Repeat above step if required
 - Push element on stack
- Pop all remaining elements (Operators) from stack one by one and append them into the postfix expression
- e.g. $a * b / c * d + e - f * h + i$



Infix to Prefix Conversion

- Process each element of infix expression from right to left
- If element is Operand
 - Append it to the prefix expression
- If element is Operator
 - If priority of topmost element of stack is greater than current element (Operator), pop topmost element from stack and append it to prefix expression
 - Repeat above step if required
 - Push element on stack
- Pop all remaining elements (Operators) from stack one by one and append them into the prefix expression
- Reverse prefix expression
- e.g. $a * b / c * d + e - f * h + i$



Prefix to Postfix

- Process each element of prefix expression from right to left
- If element is an Operand
 - Push it on to the stack
- If element is an Operator
 - Pop two elements (Operands) from stack, in such a way that
 - Op1 – first popped element
 - Op2 – second popped element
 - Form a string by concatenating Op1, Op2 and Opr (element)
 - String = “Op1+Op2+Opr”, push back on to the stack
- Repeat above two steps until end of prefix expression.
- Last remaining on the stack is postfix expression
- e.g. $* + a b - c d$



Postfix to infix

- Process each element of postfix expression from left to right
- If element is an Operand
 - Push it on to the stack
- If element is an Operator
 - Pop two elements (Operands) from stack, in such a way that
 - Op2 – first popped element
 - Op1 – second popped element
 - Form a string by concatenating Op1, Opr (element) and Op2
 - String = “Op1+Opr+Op2”, push back on to the stack
- Repeat above two steps until end of postfix expression.
- Last remaining on the stack is infix expression
- E.g. a b c - + d e - f g - h + / *





Thank you!

Devendra Dhande

<devendra.dhande@sunbeaminfo.com>

