

1. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog one two three

```
/* myprog.c */
#include<stdio.h>

int main(int argc, char **argv)
{
    printf("%c\n", **++argv);
    return 0;
}
```

- A. myprog one two three
- B. myprog one
- C. o
- D. two

Answer: Option C

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

2. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog one two three

```
/* myprog.c */
#include<stdio.h>
#include<stdlib.h>

int main(int argc, char **argv)
{
    printf("%s\n", **++argv);
    return 0;
}
```

- A. myprog
- B. one
- C. two
- D. three

Answer: Option B

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

3. What will be the output of the program (sample.c) given below if it is executed from the command line (Turbo C in DOS)?

cmd> sample 1 2 3

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    int j;
    j = argv[1] + argv[2] + argv[3];
    printf("%d", j);
    return 0;
}
```

- A. 6
- B. sample 6
- C. Error
- D. Garbage value

Answer: Option C

Explanation:

Here `argv[1]`, `argv[2]` and `argv[3]` are string type. We have to convert the string to integer type before perform arithmetic operation.

Example: `j = atoi(argv[1]) + atoi(argv[2]) + atoi(argv[3]);`

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

4. What will be the output of the program (sample.c) given below if it is executed from the command line (turbo c under DOS)?

cmd> sample Good Morning

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%d %s", argc, argv[1]);
    return 0;
}
```

- A. 3 Good
- B. 2 Good
- C. Good Morning
- D. 3 Morning

Answer: Option A

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

5. What will be the output of the program

```
#include<stdio.h>
void fun(int);

int main(int argc)
{
    printf("%d ", argc);
    fun(argc);
    return 0;
}
void fun(int i)
{
    if(i!=4)
        main(++i);
}
```

- A. 1 2 3
- B. 1 2 3 4
- C. 2 3 4
- D. 1

Answer: Option B

6. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample "*.c"

```
/* sample.c */
#include<stdio.h>

int main(int argc, int *argv)
{
    int i;
    for(i=1; i<argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

- A. *.c
- B. "*.c"
- C. sample *.c
- D. List of all files and folders in the current directory

Answer: Option A

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

7. What will be the output of the program if it is executed like below?

cmd> sample

```
/* sample.c */
#include<stdio.h>

int main(int argc, char **argv)
{
    printf("%s\n", argv[argc-1]);
    return 0;
}
```

- [A.](#) 0
- [B.](#) sample
- [C.](#) samp
- [D.](#) No output

Answer: Option B

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

8. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample friday tuesday sunday

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%c", **++argv);
    return 0;
}
```

- [A.](#) s
- [B.](#) f
- [C.](#) sample
- [D.](#) friday

Answer: Option B

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

9. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog friday tuesday sunday

```
/* myprog.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%c", *++argv[1]);
    return 0;
}
```

- A. r
- B. f
- C. m
- D. y

Answer: Option A

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

10. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample one two three

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    int i=0;
    i+=strlen(argv[1]);
    while(i>0)
    {
        printf("%c", argv[1][--i]);
    }
    return 0;
}
```

- A. three two one
- B. owt
- C. eno
- D. eerht

Answer: Option C

11. What will be the output of the program in Turbo C?

```
#include<stdio.h>

int main(int argc, char *argv, char *env[])
{
    int i;
    for(i=1; i<argc; i++)
        printf("%s\n", env[i]);
    return 0;
}
```

- A.** List of all environment variables
- B.** List of all command-line arguments
- C.** count of command-line arguments
- D.** Error: cannot have more than two arguments in `main()`

Answer: Option A

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

12. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample Jan Feb Mar

```
/* sample.c */
#include<stdio.h>
#include<dos.h>

int main(int arc, char *arv[])
{
    int i;
    for(i=1; i<_argc; i++)
        printf("%s ", _argv[i]);
    return 0;
}
```

- A.** No output
- B.** sample Jan Feb Mar
- C.** Jan Feb Mar
- D.** Error

Answer: Option C

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

13. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample monday tuesday wednesday thursday

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    while(--argc>0)
        printf("%s", *++argv);
    return 0;
}
```

- A. sample monday tuesday wednesday thursday
- B. monday tuesday wednesday thursday
- C. monday tuesday thursday
- D. tuesday

Answer: Option B

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

14. If the following program (myproc.c) is present in the directory "C:\TC" then what will be output of the program if run it from DOS shell?

```
/* myproc.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%s", argv[0]);
    return 0;
}
```

- A. SAMPLE.C
- B. C:\TC\MYPROC.EXE
- C. C:\TC
- D. Error

Answer: Option B

Explanation:

In order to execute it from DOS shell, we have to run the created EXE file by entering the exe file name as C:\TC>myproc <enter>.

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

15. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog one two three

```
/* myprog.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    int i;
    for(i=1; i<argc; i++)
        printf("%c", argv[i][0]);
    return 0;
}
```

- A. oot
- B. ott
- C. nwh
- D. eoe

Answer: Option B

16. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample 1 2 3

cmd> sample 2 2 3

cmd> sample 3 2 3

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%s\n", argv[0]);
    return 0;
}
```

- A. sample 3 2 3
- B. sample 1 2 3
- C. sample
- D. Error

Answer: Option C

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss](#) in Forum [Workspace Report](#)

17. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog 1 2 3

```
/* myprog.c */
#include<stdio.h>
#include<stdlib.h>

int main(int argc, char **argv)
{
    int i, j=0;
    for(i=0; i<argc; i++)
        j = j+atoi(argv[i]);
    printf("%d\n", j);
    return 0;
}
```

- A. 123
- B. 6
- C. Error
- D. "123"

Answer: Option B

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

18. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample friday tuesday sunday

```
/* sample.c */
#include<stdio.h>

int main(int sizeofargv, char *argv[])
{
    while(sizeofargv)
        printf("%s", argv[--sizeofargv]);
    return 0;
}
```

- A. sample friday tuesday sunday
- B. sample friday tuesday
- C. sunday tuesday friday sample
- D. sunday tuesday friday

Answer: Option C

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

19. What will be the output of the program (sample.c) given below if it is executed from the command line?

cmd> sample friday tuesday sunday

```
/* sample.c */
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("%c", *++argv[2] );
    return 0;
}
```

A. s

B. f

C. u

D. r

Answer: Option C

Explanation:

No answer description available for this question. [Let us discuss.](#)

[View Answer](#) [Discuss in Forum](#) [Workspace Report](#)

20. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog 10 20 30

```
/* myprog.c */
#include<stdio.h>

int main(int argc, char **argv)
{
    int i;
    for(i=0; i<argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

A. 10 20 30

B. myprog 10 20

C. myprog 10 20 30

D. 10 20

Answer: Option C

21. What will be the output of the program (myprog.c) given below if it is executed from the command line?

cmd> myprog one two three

```
/* myprog.c */
#include<stdio.h>
#include<stdlib.h>

int main(int argc, char **argv)
{
    int i;
    for(i=1; i<=3; i++)
        printf("%u\n", &argv[i]);
    return 0;
}
```

If the first value printed by the above program is 65517, what will be the rest of output?

- A. 65525 65531
- B. 65519 65521
- C. 65517 65517
- D. 65521 65525