


Detailed Level Design (DLD)

1. Overview

The program is structured around `Game` class which orchestrates both interface and game logic. `Game` class includes `Player` , `Dealer` , `Card_deck` classes.

2. UML Class Diagram



3. Class Details

Card_deck

Attribute	Type	Visibility	Description
deck	Card[52]	private	All 52 playing cards
deck_size	int	private	Remaining cards (0-52)

Method	Return	Responsibility
shuffle()	void	Randomize deck using Fisher-Yates algorithm; O(n)
reset()	void	Reset deck_size to 52 for new round
deal()	Card	Return next card and decrement counter

Constraint	Notes
Initialization	Cards populated in constructor (0-51 mapped to suite/value)
Shuffle Timing	Called at start of each round after reset()

Player

Attribute	Type	Visibility	Description
hand	Card[MAX_HAND]	protected	Current 2-11 cards
hand_size	int	protected	Number of cards held
funds	int	private	Available funds

Method	Return	Responsibility
receive_card(Card)	void	Add card to hand if space available
hand_sum() const	int	Calculate hand value
has_blackjack() const	bool	True if exactly 2 cards summing to 21
is_bust() const	bool	True if hand_sum() > 21

Method	Return	Responsibility
place_bet(int)	int	Validate and deduct bet; return 1 if valid, 0 if invalid
add_win(int)	void	Add payout amount to funds
clear_hand()	void	Reset hand_size to 0

Validation	Notes
Bet validation	bet > 0 AND bet ≤ current funds
Hand limit	Cannot exceed MAX_HAND (11 cards)

Dealer

Attribute	Type	Visibility	Description
(inherited from Player)			Uses hand and hand_size only

Method	Return	Responsibility
should_hit()	bool	Return true if hand_sum() < 17 (dealer hits on 16 and below)

Game

Attribute	Type	Visibility	Description
deck	Card_deck	private	Managed shuffled deck
player	Player	private	Player state and funds
dealer	Dealer	private	Dealer state
current_bet	int	private	Current round's bet amount

Method	Return	Responsibility
run()	void	Main game loop: init_funds → while(has_funds) play_round → ask_play_again
play_round()	void	Single round: place_bet → reset/shuffle deck → deal → player_turn → dealer_turn →

Method	Return	Responsibility
		determine_outcome → apply_payout
display() const	void	Show current game state (funds, bet, both hands)
init_funds()	void	Input validation loop for starting funds
place_bet()	int	Input validation loop for bet placement
deal_initial_cards()	void	Deal 2 cards to each player/dealer
check_bj()	bool	Evaluate blackjack; return true if found and round ends
player_turn()	bool	Loop hit/stand decisions; return true if bust
dealer_turn()	void	Auto-deal while should_hit() is true
determine_outcome()	GameOutcome	Compare hands and return the game outcome
calculate_payout() const	int	Return total payout
apply_payout()	void	Display result message and update player.funds

Separation of Concerns	Notes
Logic Methods	determine_outcome(), calculate_payout()
Display Methods	display(), display_round_start(), display_round_result()
UI Methods	place_bet(), ask_play_again()

4. Key Algorithms

Player::hand_sum() - Ace Handling

Algorithm: Calculate blackjack hand value and take into account the Ace value conversion

```

int Player::hand_sum() const {
    int sum = 0;
    int aces = 0;
    for (int i = 0; i < hand_size; i++) {
        sum += card_points(hand[i]);
        if (hand[i].value == 12) {
            aces++;
        }
    }

    while (sum > 21 && aces > 0) {
        sum -= 10;
        aces--;
    }

    return sum;
}

```

Examples:

[5, 6] → 11

[K, 5] → 15

[A, K] → 21 (Ace as 11)

[A, 5, 5] → 11 (Ace as 1, avoid bust)

[K, Q, 5] → 25 (BUST)

Card_deck::shuffle() - Fisher-Yates Algorithm

Algorithm: Randomize deck of cards

```

void Card_deck::shuffle() {
    static std::default_random_engine generator(std::random_device{}());
    for (int i = deck_size - 1; i > 0; i--) {
        std::uniform_int_distribution<int> distribution(0,i);
        int j = distribution(generator);
        swap(&deck[i], &deck[j]);
    }
}

```

Complexity: O(n) time, O(1) space

Called at round start after reset() to get fresh 52-card deck

Game::determine_outcome() - Hand Comparison

Algorithm: Compare final hands and determine winner

```
Game::GameOutcome Game::determine_outcome() {  
    int player_score = player.hand_sum();  
    int dealer_score = dealer.hand_sum();  
  
    if (player_score > 21) {  
        return GameOutcome::PLAYER_BUST;  
    }  
    else if (dealer_score > 21) {  
        return GameOutcome::DEALER_BUST;  
    }  
    else if (player_score > dealer_score) {  
        return GameOutcome::PLAYER_WIN;  
    }  
    else if (player_score == dealer_score) {  
        return GameOutcome::PUSH;  
    }  
    else {  
        return GameOutcome::DEALER_WIN;  
    }  
}
```

Game::calculate_payout() - Payout Table

Input: outcome (GameOutcome enum)

Output: Total amount returned to player

Outcome	Payout	Example (bet=\$50)
PLAYER_BLACKJACK	BET + BET×1.5	\$125
PLAYER_WIN	BET × 2	\$100
DEALER_BUST	BET × 2	\$100
PUSH	BET	\$50
DEALER_WIN	0	\$0
PLAYER_BUST	0	\$0

Game::play_round() - Round Flow

Algorithm: Execute one complete blackjack round

- 1. Clear both hands
- 2. Get valid bet from player
- 3. Reset & shuffle deck
- 4. Deal 2 cards to each
- 5. Display initial state
- 6. IF blackjack found: apply payout & end
- 7. Player turn: loop hit/stand until stand or bust
- 8. IF player not bust:
 - Dealer deals while hand sum < 17
- 9. Display final state
- 10. Compute outcome
- 11. Apply payout and display result

5. Validation & Constraints

Component	Constraint	Validation
Player Funds	Must be > 0	set_funds() rejects ≤ 0
Bet Amount	$0 < \text{bet} \leq \text{available_funds}$	place_bet() deducts and returns success/failure
Hand Size	Max 11 cards	receive_card() ignores overflow
Dealer Rules	Hits on <17, stands on ≥ 17	should_hit() enforces rule
Deck	52 unique cards	Reset to 52 per round, Fisher-Yates shuffle
Input	Integer validation + range checking	Input loops with retry on invalid

6. Design Tradeoffs

Decision	Rationale	Trade-off
Inheritance: Dealer < Player	Reuse hand/funds logic	Dealer doesn't use funds field, minor waste of memory
Integer funds only	Avoid floating-point bugs	Cannot represent fractional cents