



# ATOLL BLOCK PPR

## PRODUCT DESCRIPTION ANTIBLOCKING AGENT

### PRODUCT SPECIFICATION

It prevents laminated paper products from sticking together due to the humidity in the environment while they are stacked or rolled up in the warehouse. It is an excellent internal antiblocking agent for water-based resin systems. It does not change the chemical and physical properties of urea/melamine-formaldehyde resins. It is completely water based. It does not contain oils such as silicone and paraffin.

### CHEMICAL SPECIFICATION

<b>Physical Condition:</b>	Liquid
<b>Color:</b>	White emulsion
<b>Smell:</b>	Specific
<b>Ph:</b>	4.0 - 7.0
<b>Melting/Freezing:</b>	< 0 C
<b>Boiling Point:</b>	> 100 C
<b>Flash Point:</b>	No Data
<b>Evaporation Rate:</b>	Low
<b>Flammability:</b>	Not flammable
<b>Vapor Pressure:</b>	No Data
<b>Density(20°C):</b>	0.95 – 1.05 g/cm <sup>3</sup>
<b>Dissolution:</b>	Totally soluble in water.

### USAGE AREAS

It can be used as an anti stick – blocking agent, in all kinds of paper impregnation.

### INSTRUCTION

It is used directly without dilution. It is added to the mixture at a rate of 0.1-0.5% according to the amount of resin.

### PACKAGING TYPE

1.000 KG IBC