



ATOLL WET PPR

PRODUCT DESCRIPTION WETTING AGENT

PRODUCT SPECIFICATION

It is a general wetting agent used in impregnation processes, for urea formaldehyde, melamine-formaldehyde and mix-type resins.. It facilitates the absorption of the resin by the paper by reducing the surface tension. It increases the performance of the hardener, does not adversely affect the resin utilization time. It reduces the amount of resin usage by decreasing the surface tension of the resin and increasing the fluidity. It is used in both of the baths.

CHEMICAL SPECIFICATION

Physical Condition:	Liquid
Color:	Clear, colorless
Smell:	Specific
Ph:	6 - 8 [concentration. (% w/w): 100%]
Melting/Freezing:	< 0 C
Boiling Point:	> 100 C
Flash Point:	No Data
Evaporation Rate:	Low
Flammability:	Not flammable
Vapor Pressure:	No Data
Density:	1.00 – 1,10 g/ml
Dissolution:	Totally soluble in water.

USAGE AREAS

It can be used as a wetting agent, in all kinds of paper impregnation.

INSTRUCTION

It is used directly without dilution. It is added to the mixture at a rate of 0.1-0.5% at room temperature.

PACKAGING TYPE

1.000 KG IBC

MARKETED BY: - PHOENIX ADDITIVES CHEMICALS

Unit NO.12, Borivali Ganjawala CHS. LTD., S.V.Road, Borivali (W)
Mumbai-400092

www.phoenixadditiveschemicals.com

pacindia@hotmail.com