Activation Survival, Language Association, and Causal Effects under Weight Quantization: A Multilingual SAE Study

Hemang Joshi and Eashaan Thakur and Shardul Joshi and Nikhita Ravi
International Institute of Information Technology, Hyderabad

Abstract

Quantization changes sparse autoencoder (SAE) activations, but an activation change need not imply a loss of language association or causal contribution. We examine these distinctions in Gemma-2-2B using a frozen layer-12 Gemma Scope SAE, 27 FLORES-200 languages, and round-to-nearest weight quantization from INT8 to INT4. Of 8,086 development-selected features, 82.4% reproduce their original language peak in full precision; among these, 70.8% retain it at INT4. Removing top-64 language groups increases next-token loss beyond activity-matched controls in all 27 languages, and this dependence persists through INT5. However, the frozen Belebele comprehension test does not establish a corresponding group effect. Individual intervention effects drift at lower precision, but matched alternative directions drift similarly. Graded feature scaling suggests a small INT4 improvement at a 1.1 multiplier, without supporting a simple activation-shrinkage explanation. A minimum check on Llama-3.2-1B with a different SAE finds the dependence in 21 of 27 languages (24 were required) and flat through INT6, but no INT4 amplification (pre-specified verdict: not consistent; model and dictionary are confounded). Apart from the Belebele family, all analyses are exploratory. These results qualify the interpretation of feature survival and do not establish selective-feature destruction as the mechanism of multilingual quantization damage.

1 Introduction

Weight quantization reduces the numerical precision required to store language-model parameters. Its effects need not be uniform across languages or tasks: multilingual evaluations find that automatic metrics can underestimate degradation that human evaluation reveals, most for non-Latin-script languages (Marchisio et al., 2024). This motivates examining internal representations alongside model performance. An internal measurement is useful, however, only if its interpretation is explicit. Calling a feature "lost" can refer to a change in its activation pattern, preferred language, or effect on predictions. These are different outcomes.

Sparse autoencoders decompose a model activation into a sparse combination of learned directions (Cunningham et al., 2023). Language-associated SAE features have been identified and manipulated in full-precision models (Deng et al., 2025). Separately, Duan (2026) measure activation correlations before and after weight quantization using a frozen SAE. Neither observation, by itself, establishes that quantization removes language-specific functionality. The representation can change while a contribution remains, or an intervention can change because the downstream model changes.

We initially investigated whether language-selective features were more vulnerable than non-selective controls and whether that difference explained resource-tier disparities. After implementation audits and negative primary contrasts, we expanded the project to test the measurement assumptions directly. This report presents the completed investigation, including hypotheses that were not supported, rather than treating every additional analysis as confirmation of the original question.

We address three questions. **RQ1:** how do activation preservation and language-association retention compare? **RQ2:** do selected language groups contribute to prediction and reading comprehension, and how do those contributions change with precision? **RQ3:** do individual intervention effects and graded group manipulations support an interpretation of feature-specific functional damage? **RQ4:** does the group dependence appear on a second model with a different SAE?

Our empirical contribution is a controlled case study combining per-language response profiles, native interventions, donor patches, and effect fingerprints across weight precisions. We also doc-

ument the sensitivity of the initial replication to beginning-of-sequence (BOS) handling. We make no claim that ablation, activation patching, or feature-effect fingerprints are new methods. The main outcome is a set of distinctions and counterexamples to an overly broad interpretation of activation survival, within the main model and measurement basis.

2 Related Work

Multilingual quantization. Marchisio et al. (2024) evaluate multilingual model compression and show that task, language, and evaluation method affect the observed degradation. Their behavioural evidence motivates our language panel but does not identify SAE features as its mechanism. Resource categories provide a useful descriptive grouping (Joshi et al., 2020); our coarse tiers are not controlled interventions on training-data availability.

Language-associated features. Deng et al. (2025) identify language-specific SAE features and use ablation and steering. Thus, demonstrating an own-language loss effect in full precision is supporting evidence, rather than a standalone novelty claim. Gemma Scope supplies open SAEs across Gemma 2 layers (Lieberum et al., 2024). A frozen dictionary offers consistent coordinates across precision states but does not guarantee that each coordinate is an invariant mechanism.

Compression and causal interpretation. Duan (2026) measure feature survival under round-to-nearest quantization using activation correlation. A pruning study already distinguishes geometric survival from causal importance (Borobia et al., 2026); changing the compression operator alone does not establish a new general principle. Chang et al. (2025) use activation patching to localize quantization errors, while Hoang et al. (2026) analyze the geometry of intervention-induced logit changes. We use these ideas to compare measurements across precision and add controls for generic downstream drift. Belebele supplies a separate reading-comprehension outcome (Bandarkar et al., 2024).

3 Experimental Setting and Research History

3.1 Model, dictionary, and quantization

We use the Gemma-2-2B base model (Gemma Team et al., 2024) and a 16,384-feature JumpReLU (Rajamanoharan et al., 2024) Gemma Scope SAE at the layer-12 post-block residual stream. Model inference uses bfloat16; SAE encoding uses float32. The same dictionary is used in every condition. We apply the vendored reference round-to-nearest (RTN) quantization functions, restoring the original weights before each state. RTN uses output-channel scaling, with the reference implementation's shared indexing across heads for attention query, key, and value tensors. We do not claim to evaluate integer-kernel speed or memory savings: quantized values are represented in the inference model's floating-point storage.

The main precision ladder is full precision (FP), INT8, INT7, INT6, INT5, and INT4. INT0 denotes the restore-only identity condition, not zero-bit quantization. INT16 and INT12 are near-lossless rounding references, not exact FP identities: re-rounding bfloat16 weights can still change them. For the individual-effect study, INT16 supplies the numerical reference. One BOS token is prepended; BOS and padding are excluded from statistics and edits.

3.2 Languages and data separation

The panel contains 27 parallel FLORES-200 (NLLB Team et al., 2022) languages in three descriptive resource tiers of nine languages each (Appendix A). Feature discovery uses the development split. The original correlation and association studies use equal-budget sampling of 27,036 content-token positions per language on devtest, alongside an all-token sensitivity. Equalizing token counts controls sample size; it does not remove all tokenizer or linguistic confounds.

The functional loss evaluation uses 300 fixed, aligned devtest sentence identifiers per language. Development-selected feature groups therefore do not use those evaluation sentences. Nevertheless, devtest had already been examined in the earlier studies, so all FLORES functional analyses are exploratory. The graded-gain extension uses 562 reserve sentences not scored in earlier intervention runs; it remains an exploratory follow-up motivated by the main results.

Belebele passages originate from FLORES. We

split its items by passage origin into dev-origin calibration and devtest-origin evaluation, avoiding a random item split that could put a passage on both sides. Full-precision calibration selects the letter-answer format and 18 languages whose accuracy lower bound exceeds chance plus 0.05. The frozen evaluation uses 385 items per language. Coverage is a property of this model, format, and rule; it is not a classification of whether a language is generally supported.

3.3 Analysis status and implementation audit

An initial independent implementation was retired after a code and reporting audit. Its numerical outputs and paper claims are not used as current findings. We reproduced the reference code, validated the new runner, and retained dated decisions, artifact hashes, and evaluation freezes. The historical proposal-level tests are reported as planned tests; an external OSF registration was not verified. We do not describe them as externally preregistered. We call a rule *pre-specified* if it was committed to the repository before the data it judges were scored; none was registered externally.

For functional validation, the only confirmatory family is the held-out Belebele family frozen before evaluation scoring. Its first statement requires a positive FP macro effect; the five precision-retention statements use 99% intervals for multiplicity control. Other results remain exploratory even where the analysis rules were written before a particular run. Additional analyses were not retroactively promoted to confirmation.

4 Measurements and Interventions

4.1 Activation and language association

Let $a_f^b(t)$ be feature f's activation at token t in precision state b. The activation-preservation score is

$$c_f^b = \mathrm{corr}_t(a_f^{\mathrm{FP}}(t), a_f^b(t)). \tag{1}$$

The historical survival cutoff is $c_f^b > 0.9$. This measures agreement on the original language's tokens, not the identity of the peak language after quantization.

Language selectivity uses firing rates $r_{\ell f}$ and score $S_f = \max_\ell r_{\ell f} / \mathrm{mean}_\ell\, r_{\ell f}$. Discovery requires the score to exceed the 95th-percentile shuffled-language null (50 permutations; cutoff about 1.83), at least 50 positive peak-language tokens, panel rate at least 10^{-5}, and the same peak in at least 80 of 100 resamples using 90% of sentences. The dev-selected cohort contains 8,086 features. A feature is *established* on devtest if its original language is the unique firing-rate peak with the support safeguards; it is *retained* at b if that peak remains unique and supported. Retention conditions on FP establishment: non-establishment before quantization is not compression damage.

We also analyze the FP margin between the original language's firing rate and its strongest competitor. This tests whether a changed argmax mostly reflects a previously close contest. Rate-based association, mean activation, and token correlation are reported as distinct views.

4.2 Language groups and activity controls

For language ℓ, G_ℓ contains its 64 highest-mean-activation selective features on dev. K16 and the entire selective group are size sensitivities. Controls come from 2,860 supported, non-selective features. Greedy matching uses the target language's log firing rate and log mean activation, sampling uniformly among the three nearest unused candidates for each group member. There is no replacement within a draw. There are five draws for the main K64 analysis and three for Study G.

Matching is imperfect. Across 81 language–size cases, 75 group/control activation ratios fall within $[0.8, 1.25]$. At K64 the important exceptions include Thai (0.78), Yoruba (1.47), and Lao (1.48). Draws overlap because the pool is finite. They provide a reference comparison, not an independent null population. Effects can reflect remaining differences in the amount of activation removed, so activity matching is not an identification argument for language specificity itself.

4.3 Native edits and donor patches

Let x be a residual, a its SAE encoding, and d_f a decoder row. We preserve the recipient's reconstruction error by editing only selected terms:

$$x' = x + \sum_{f \in G} (a'_f - a_f) d_f. \tag{2}$$

Zero ablation sets $a'_f = 0$; scaling sets $a'_f = \alpha a_f$. A resampling sensitivity replaces the group with a co-activation vector from other-language dev text. Identity and sham edits check the intervention path. Native interventions use each model's own activations, allowing changes in contribution to be distinguished from donor-patch recovery.

For the rescue experiment, the recipient is quantized and a'_f is the FP activation at the same input position. We separately patch the language group, matched controls, all reconstructed features, the reconstruction error, and the whole residual. These patches need not have additive effects because the downstream computation is nonlinear.

4.4 Effects, retention, and uncertainty

For precision b and intervention I, harm is its change in negative log-likelihood relative to the same state's unedited prediction. The language-group effect is

$$E^b_\ell = h^b_\ell(G_\ell) - \frac{1}{R}\sum_{r=1}^{R} h^b_\ell(C_{\ell r}). \qquad (3)$$

Loss-task units are nats per token. Belebele uses negative log-probability of the correct answer normalized over the four candidates, in nats per item, with accuracy as a secondary measurement. Negative harm denotes improvement and is never clipped.

For languages with a clearly positive FP effect, functional retention is $E^b_\ell / E^{\mathrm{FP}}_\ell$. The macro statistic averages these per-language ratios, rather than dividing two macro means. Ratios are undefined when the FP denominator is not established. The proposed retention band is $[0.75, 1.33]$; an interval entirely inside it is classified as preserved, rather than inferring preservation from a nonsignificant difference.

Loss-task intervals use 2,000 paired cluster-bootstrap draws over aligned sentence identifiers, preserving the dependence between translations; Belebele resamples passages. Association intervals use 1,000 paired sentence-bootstrap draws; because resampling can flip near-tied peaks, they can be shifted relative to the observed estimate, which we report.

4.5 Individual effect fingerprints

For 1,487 features stratified by language and role, we select up to 16 dev contexts with strong FP activation. At the FP-active positions we ablate the feature and measure its output-logit change. Define

$$D_b(f) = \frac{1}{|T_f|}\sum_{t \in T_f} \mathrm{center}(z'_{bt} - z_{bt}), \qquad (4)$$

where centering subtracts the vocabulary mean at each position. The write-side similarity is $W^b_f = \cos(D_{\mathrm{FP}}(f), D_b(f))$. It is a context-averaged intervention measurement, not a complete description of a feature's meaning. Float32 editing and output calculations reduce round-off artifacts; sham and forward-parity gates check the modified path.

We compare W with the fifth percentile of INT16 similarities, $\tau = 0.9489$. This is an empirical numerical reference, not semantic ground truth. A separate 404-feature control subtracts another matched decoder direction at the original feature's positions and amplitudes. Comparing each such direction with itself across precision tests whether declining similarity is specific to the selected feature or shared by arbitrary perturbations. Fixed-FP-amplitude and 8/32-context sensitivities address further measurement choices.

5 Replication and Initial Hypothesis Tests

5.1 The BOS-dependent reference regime

The vendored WikiText replication matches the published reference table closely: INT7 survival is 81.19% versus 81.26%, and INT6 is 51.15% versus 51.30%. However, the no-BOS unquantized perplexity is 458.4. On the same content windows, adding BOS and masking its position reduces perplexity to about 16.1 and yields INT6 survival near 97.5%. TransformerLens and Hugging Face implementations agree closely when aligned.

This establishes sensitivity to the input regime, not that every reported reference result is invalid. The active-feature populations can differ between regimes, and the diagnostic does not identify all causes of BOS dependence. We therefore use BOS-masked evaluation for ongoing experiments and preserve the no-BOS study only as historical evidence.

5.2 Selective features and resource tiers

In the rebuilt primary regime, none of the three original planned tests rejects after Holm correction. The selective-minus-control survival contrasts are -0.28 percentage points at INT7 and -1.44 at INT6 (adjusted $p = 0.514$ and 0.128). A stricter, post hoc selectivity threshold produces an INT6 disadvantage near -7.16 points; additionally matching activation magnitude reverses the contrast to $+4.58$ points. The selective-feature penalty is therefore not robust to this comparison choice.

There is a broad language disparity under the correlation metric: mean INT6 survival is 69.4/90.6/95.1% in low/mid/high tiers. The tier

State	Corr. (%)	Assoc. (%)	Effect ratio
INT8	100.00	98.1	1.01
INT7	99.97	97.5	1.03
INT6	94.94	94.7	1.04
INT5	59.00	89.1	1.13
INT4	13.75	70.8	2.14

Table 1: Different measurements across precision. Correlation survival pools active features; association retention conditions on 6,663 established selective features; the effect ratio averages 27 language-group ratios. Their denominators and meanings differ. All three analyses are exploratory.

slope changes from $+12.3$ to -0.81 points per step after conditioning on activation scale ($p = 0.667$). This attenuation is correlational, is partly mechanically related to activation scale, and does not establish tokenization or activation scale as the cause of multilingual damage.

6 Association and Functional Results

6.1 Language peaks persist beyond correlation survival

Only 6,663 of the 8,086 dev-selected features (82.4%) establish their original peak on FP devtest. Among these, association retention falls gradually to 70.8% at INT4 (Table 1). The INT16/INT12 reference already loses 56 features, retaining 99.2%. No established feature becomes globally inactive; most lost associations reflect a different peak language, ties, or insufficient peak support.

Correlation and association disagree on individual features. At INT6, 75.8% of association-lost features still exceed the correlation cutoff; at INT4, 79% of association-retained features do not. These within-cohort comparisons show why a changed activation pattern cannot simply be read as a changed language label. The pooled all-active correlation fraction and selective-cohort retention in Table 1 have different denominators and are not paired estimates of the same event.

Within-language FP margin predicts association loss with AUROC 0.90, 0.81, and 0.75 at INT6/5/4. At INT6, the most borderline fifth loses its association in 20.7% of cases, against 0.1% in the least borderline fifth. Excluding English gives the same qualitative pattern. This supports sensitivity to near ties; it does not rule out meaningful changes among clearly separated features, especially at INT4.

6.2 Language-group dependence persists on text loss

Zeroing a language's K64 group increases own-text loss beyond controls in all 27 languages at FP and every tested precision. The FP macro effect is 0.704 nats/token, with a 95% interval $[0.684, 0.723]$; the median is 0.262. Macro effect retention is near one through INT6, 1.13 at INT5, and 2.14 at INT4 ($[2.04, 2.50]$). The latter is a mean of ratios: the ratio of macro effects is only 1.33, illustrating why the aggregation must be specified.

These results concern dependence on the selected group in an ablation experiment. A larger effect in a damaged INT4 model does not mean improved language ability or a better preserved representation. K16, whole-group, and resampling sensitivities retain the qualitative own-text dependence. The result also holds separately in the 18 Belebele-covered languages and the other nine, so it is not driven solely by languages with no measured comprehension headroom.

6.3 Patching localizes little damage to the groups

At INT4, restoring the language group recovers 2.6% of the loss gap, versus 1.2% for controls, 17.4% for all SAE features, and 39.3% for the whole residual. At INT5/6 the language-group recovery is approximately zero. Whole-residual recovery is 29.7/35.0% there; INT6 fractions apply only to the 12 languages with a clearly positive baseline gap. The group effect and patch recovery answer different questions: necessity within a model need not imply responsibility for the difference between models.

Matching association-lost and association-retained subsets on native activity does not reveal a systematic harm difference: median lost-minus-retained effects (26 of 27 languages) are $+0.0006$, $+0.0007$, and $+0.0002$ nats/token at INT4/5/6. Some macro means are dominated by Lao. We describe the observed small contrasts, rather than asserting universal equivalence or absence of any functional association.

6.4 The confirmatory comprehension statement is not met

On frozen Belebele evaluation, the FP macro group effect is -0.0001 nats/item, with interval $[-0.0035, +0.0031]$. Accuracy is 0.426 unedited, 0.426 after group ablation, and 0.425 after control

ablation. No covered language has a clearly positive FP effect. Statement S0 is not met; the five retention statements are undefined because their denominator condition fails. INT4 accuracy is 0.236, leaving no useful above-chance headroom.

The exploratory whole-group sensitivity also has an interval spanning zero: $+0.0007$ nats/item, $[-0.0030, +0.0042]$. Random-set positive controls show that the edit path can affect accuracy: sets of 1,024–2,860 features reduce it by 1.2–6.0 percentage points, while sham edits change nothing. At 256 random features, the decrease is 0.7–0.8 points, placing the own-group decrease (0.5 points) in the range of similarly sized random interventions; the null therefore cannot exclude group effects of about half a point.

An independent prompt check compares our frozen format with the lm-evaluation-harness format on 250 calibration items per covered language. The frozen format reproduces stored calibration exactly and scores higher in all 18 languages (point estimates; the margin rule labels 3 clearly and 15 inconclusive); harness-minus-frozen accuracy is -0.100 on average, with interval $[-0.110, -0.090]$. This rules out a handicap relative to that alternative, not all possible prompt effects. These calibration accuracies are not directly comparable to the separate held-out evaluation accuracy or published harness scores.

6.5 Individual effects drift, but directions drift too

Across 1,487 tested features, median write-side similarity is 0.997/0.988/0.961/0.839 at INT8/6/5/4. The fraction above the INT16 reference is 94.0/89.7/66.5/0.3%. Yet each feature's quantized effect remains much closer to its own FP fingerprint than to other features': top-1 identity retrieval is 0.997–1.000. Recognizable identity and numerical similarity are different outcomes.

The 404-feature matched-direction comparison is essential (Figure 1). At INT4, feature and control median similarities are 0.842 and 0.828; at INT8/6/5 the differences of medians are only 0.004/0.006/0.007. Fixing amplitudes to FP gives INT4 similarities 0.846 and 0.838. Therefore, most measured drift is also present for alternative perturbation directions; the data do not isolate feature-specific destruction. We have not established statistical equivalence of the directions from these medians.

At INT5, about 31% of features above the write-side reference fail activation survival. This is disagreement with an operational reference, not a semantic false-negative rate. Association status has descriptive AUROC 0.506 ($[0.469, 0.543]$) for INT4 write-side similarity. The FP margin is much better at predicting association loss than functional change: on the same samples, INT6 AUROCs are 0.86 and 0.58, respectively. Thus, label stability and causal-effect stability should not be conflated.




Figure 1: Median fingerprint similarity on the same 404 features and matched directions. Bars show interquartile ranges, not confidence intervals. The numerical drift is largely shared by alternative perturbations.

7 Graded Feature Scaling

7.1 Dose response across precision

Study G varies α in Equation 2 for the same K64 groups. A separate 100-sentence FP pilot calibrates three down multipliers, 0.3536/0.1768/0.0884, to target increasing fractions of zero-ablation harm; up multipliers are their reciprocals, 2.8284/5.6569/11.3137. Fine increases of 1.1 and 1.2 are specified separately. The main evaluation uses 300 sentences, 27 languages, and three control draws.

In FP, median net harm increases from 0.0223 to 0.0902 to 0.1687 to 0.2624 as the group is suppressed more strongly and finally zeroed. The down-dose ordering holds in all 27 languages; 26 have a positive lower interval bound at the deepest nonzero down multiplier. Strong amplification also raises harm. The curves are similar from FP through INT5, with an INT4 increase (Figure 2). The predefined strict precision-monotonicity rule is not met because a small intermediate decrease exceeds its tolerance. A post hoc relaxed tolerance is not substituted for that result.

7.2 A small INT4 benefit and two checks

The main sample suggests a small benefit from fine amplification at INT4 but is underpowered




Figure 2: Median net harm under suppression, from the completed Study G curves. Net harm subtracts controls scaled by the same multiplier. The strongest precision change occurs at INT4.




Figure 3: Reserve-sentence follow-up: median net harm at small amplification ratios. Bars are the stored 97.5% language-bootstrap intervals for the primary ratios. Negative values denote improvement relative to matched controls.

for that effect. The larger follow-up evaluates FP/INT6/INT5/INT4 on 562 reserve sentences per language, with five control draws and fixed primary multipliers 1.1 and 1.2. At INT4, 1.1 yields median net harm -0.00135 nats/token, with a 97.5% interval $[-0.00197, -0.00032]$, and improves 20 of 27 languages. The 1.2 interval spans zero and its predefined rule is not met (Figure 3). The same amplification slightly raises the loss at FP, INT6, and INT5 (+0.0004 to +0.0014), so its sign depends on precision (INT4 minus FP: -0.0024 and -0.0041 for the two multipliers). The matched controls do not show a clear corresponding decrease. The effect is approximately 0.05% of loss, too small and narrowly evaluated to support a practical repair claim.

Two follow-ups test the interpretation. First, selecting each state's own top-64 language features changes membership substantially (INT4 Jaccard 0.49 with the FP selection), but the dose-response curves remain similar. State-defined groups are not more consequential than the FP reference: the median deepest-down net-harm difference at INT4 is -0.0098 nats/token. This supports robustness to group selection at this resolution, not identity of the underlying feature sets.

Second, the language-specific gain minimizing INT4 group harm is reproducible across sentence halves (reliability 0.917). Its rank correlation with inverse group-activation shrinkage is nevertheless -0.170 (one-sided permutation $p = 0.804$). The smooth estimator agrees qualitatively. Therefore, a simple compensation explanation is not supported, even though the aggregate optimum and shrinkage can look compatible. We did not search many alternative predictors for a successful explanation.

8 A Second-Model Check

Design. To ask whether the Gemma-2-2B picture is peculiar to one model and dictionary, we ran a minimum consistency check on Llama-3.2-1B (Grattafiori et al., 2024) with the public TopK (Gao et al., 2024) SAE `seonglae/Llama-3.2-1B-sae` (FineWeb, $k = 48$, 14,336 features) at the residual stream entering block 12. The rest is the frozen Gemma pipeline through an adapter: the same 27 languages and sentence identifiers, selectivity rule, K64 groups, matched controls (three draws), Study G multipliers (not recalibrated), 300 held-out sentences, and states FP, INT8, INT6, INT5, and INT4. Five predictions and a verdict function were fixed before any Llama run (Table 2): *consistent* needs P1, P2b, and P3a; *partly consistent* P1 and P3a; *limited* P1 only; *not consistent* follows if P1 fails; P2a and P3b never change the verdict. All 27 languages had the 16 selective features required for testing.

Result. The verdict is *not consistent*. The group effect exists in most languages but is small: the median effect is 0.048 nats/token (Gemma: 0.262), positive in 21 of 27 languages when 24 are required. It is large in German, Yoruba, and Amharic (1.16, 1.50, 1.21) and negative in Russian, Chinese, Japanese, Korean, Hindi, and Kannada. As on Gemma, the dependence is flat through INT6 (P2a). The INT4 amplification is not found: the frozen mean retention is -3.57 because one language with a tiny FP effect (Tamil, $E = 0.0027$) has a ratio of -88.9; the post hoc median of the ratios is 0.86 $[0.74, 1.03]$ at INT4, below its INT6 value of 1.08. The graded ordering holds in 20 of 27 languages at FP and 15 of 27 at INT4.

Prediction (fixed beforehand)	Llama-3.2-1B	Gemma-2-2B	Met
P1: median $E > 0$ with its interval above 0 and $E > 0$ in ≥ 24 of 27 languages	median 0.048 $[0.018, 0.173]$; 21 of 27	median 0.262; 27 of 27	no
P2a: macro retention in $[0.85, 1.15]$ at INT8 and INT6	1.010, 1.024	1.006, 1.038	yes
P2b: INT4 retention $\geq$ INT6 $+0.30$ and the largest	INT5 0.14, INT4 -3.57 (median of ratios 0.86)	1.13, 2.14 (median 1.54)	no
P3a: down-dose ordering (H-G1) in ≥ 24 of 27 languages and in the median, at FP and INT4	20 of 27 at FP, 15 of 27 at INT4	met (Study G)	no
P3b (reported only): the deepest down multiplier costs more at INT4 in ≥ 20 of 27 and the median ratio exceeds 1.3	14 of 27; median ratio 1.17	ratio 1.91	no
Verdict	not consistent (P1 fails)		

Table 2: Pre-specified predictions and outcomes for the Llama-3.2-1B check. E is the group effect of Equation 3 (nats/token); retention is the mean of per-language ratios $E^b_\ell / E^{\mathrm{FP}}_\ell$ over languages with a clearly positive FP effect (21 of 27). The median of the ratios is post hoc and not used for the verdict.

Robustness, post hoc. The control draws are heavy-tailed: for Japanese they cost 0.07, 0.20, and 3.72 nats/token against a group harm of 0.095. With the median of the three draws, $E > 0$ in 23 of 27 languages at FP (24 required), and the group harm exceeds every single draw in 17. At INT4 the zeroed groups and their controls no longer perturb the residual equally (relative norm of the group against its controls 0.12 against 0.19; 0.18 against 0.17 at FP), so a control harm above the group harm there is partly a property of the matching. These tables cannot change the verdict.

What it does and does not show. Model family, SAE architecture (TopK against JumpReLU) and training data, layer depth (12 of 16 against 12 of 26), and tokenizer all differ. This dictionary also labels 91% of its supported features language-selective (about three quarters for Gemma Scope) and leaves only 898 candidate controls (Gemma: 2,860), which suggests a less discriminating selectivity criterion (specificity was not measured). The check therefore does not show that the Gemma findings fail on other models and is not a replication; a larger model of the same family and SAE type would separate model from dictionary and has not been run here.

9 Discussion and Conclusion

The original selective-destruction account is not established. Its primary contrasts were weak, its apparent threshold-dependent disadvantage changed after magnitude matching, and donor patches attributed little quantization loss to the selected language groups. Functional dependence on those groups persists on own-text prediction, but a frozen comprehension test does not establish the same dependence.

The main methodological lesson is to specify what a survival measurement preserves: a correlation cutoff describes activation agreement, a peak-language label depends on the margin to competing languages, and a logit fingerprint describes a sampled intervention in a changing downstream model. The matched-direction control limits the reading of functional drift: effects change at low precision, but also for perturbations that are not the feature's own direction.

The second-model check adds a caution: on Llama-3.2-1B with a TopK dictionary the dependence is present in most languages and flat through INT6, but smaller and without the INT4 amplification or the graded ordering. Because model and dictionary differ together, we attribute this to neither; the Gemma results are findings about one model and one dictionary until a same-family replication exists.

The outcome is a reproducible investigation that rejects parts of its motivating account and narrows others: persistent group dependence, disagreement between survival views, and a small INT4 scaling benefit without a supported compensation mechanism. These findings motivate better-calibrated compression audits; they do not establish a new quantization algorithm or broad multilingual capability recovery.

Limitations, Challenges, and Future Work

The main analyses use one base model, layer, frozen SAE, and rounding scheme, which limits generalization. Dictionary fidelity can deteriorate after compression. Zero ablation can be off-distribution and does not establish unique necessity, sufficiency, or semantic identity. Imperfect matching and overlapping control draws constrain interpretation.

Most results are exploratory. Language tiers confound script, tokenization, training distribution, and competence. Bootstrap intervals condition on the selected sample; discrete peak labels introduce resampling bias. The numerical threshold is an operational choice, and averaged fingerprints can hide context dependence.

The second-model check confounds model family, SAE architecture and training data, depth, and tokenizer, and its control pool was smaller; a same-family larger model (Gemma-2-9B with Gemma Scope) was planned as a cleaner test and is not part of this report. A designed but unrun study would separate the effect of a fixed feature intervention into context, downstream weights, and their interaction by crossing full-precision and quantized prefixes and suffixes.

Challenges included replacing the initial pipeline, accelerator memory limits, hardware heterogeneity, and CUDA failures. Future work should replicate the measurements across models and quantizers, assess dictionary variability, use task interventions with calibrated headroom, and prospectively test predictors of useful gains. These extensions are not completed results.

References

Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabsa. 2024. The belebele benchmark: a parallel reading comprehension dataset in 122 language variants. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 749–775, Bangkok, Thailand. Association for Computational Linguistics.

Hector Borobia, Elies Seguí-Mas, and Guillermina Tormo-Carbó. 2026. How pruning reshapes features: Sparse autoencoder analysis of weight-pruned language models. *arXiv preprint arXiv:2603.25325*.

Ting-Yun Chang, Muru Zhang, Jesse Thomason, and Robin Jia. 2025. Why do some inputs break low-bit LLM quantization? In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 3410–3429, Suzhou, China. Association for Computational Linguistics.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*.

Boyi Deng, Yu Wan, Baosong Yang, Yidan Zhang, and Fuli Feng. 2025. Unveiling language-specific features in large language models via sparse autoencoders. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4563–4608, Vienna, Austria. Association for Computational Linguistics.

Evan Duan. 2026. Perplexity can miss SAE feature damage under quantization. *arXiv preprint arXiv:2606.03002*.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. 2024. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093*.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, et al. 2024. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Phu Gia Hoang, Anwoy Chatterjee, Tanmoy Chakraborty, Iryna Gurevych, and Subhabrata Dutta. 2026. Sparse autoencoders encode both concepts and functions: The downstream geometry of feature effects. *arXiv preprint arXiv:2607.24645*.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6282–6293, Online. Association for Computational Linguistics.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, Janos Kramar, Anca Dragan, Rohin Shah, and Neel Nanda. 2024. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. In *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pages 278–300, Miami, Florida, US. Association for Computational Linguistics.

Kelly Marchisio, Saurabh Dash, Hongyu Chen, Dennis Aumiller, Ahmet Üstün, Sara Hooker, and Sebastian Ruder. 2024. How does quantization affect multilingual LLMs? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15928–15947, Miami, Florida, USA. Association for Computational Linguistics.

NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, et al. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.

Senthooran Rajamanoharan, Tom Lieberum, Nicolas Sonnerat, Arthur Conmy, Vikrant Varma, János Kramár, and Neel Nanda. 2024. Jumping ahead: Improving reconstruction fidelity with JumpReLU sparse autoencoders. *arXiv preprint arXiv:2407.14435*.

A Language Panel and Reproduction

Tier	Languages (FLORES-200 codes)
High	eng_Latn, deu_Latn, spa_Latn, fra_Latn, por_Latn, rus_Cyrl, zho_Hans, jpn_Jpan, kor_Hang
Mid	hin_Deva, ben_Beng, tam_Taml, tur_Latn, vie_Latn, ind_Latn, tha_Thai, pol_Latn, ukr_Cyrl
Low	kan_Knda, tel_Telu, yor_Latn, sun_Latn, amh_Ethi, ibo_Latn, hau_Latn, khm_Khmr, lao_Laoo

Table 3: The fixed 27-language roster in the order English, German, Spanish, French, Portuguese, Russian, Chinese, Japanese, Korean; Hindi, Bengali, Tamil, Turkish, Vietnamese, Indonesian, Thai, Polish, Ukrainian; Kannada, Telugu, Yoruba, Sundanese, Amharic, Igbo, Hausa, Khmer, Lao. Tiers are descriptive groupings, not equal training exposure.

The repository is https://github.com/TH4KUR/always-late; its results summary and figure index map the headline numbers to their source files, and the evidence map in the report folder lists the tables behind each numerical block. The private artifact dataset is https://huggingface.co/datasets/karma-skz/always-late-artifacts; newer item-level files are recorded by location and checksum and are not all archived there. The Weights & Biases project https://wandb.ai/karma-skz-/anlp-project holds the 19 earlier replication runs and 15 runs (`v2-*`) uploaded after the fact, one per result family, with headline numbers, tables, and figures read from the committed files (design: `reports/wandb_schema_v2.md`); no weights or item-level files are uploaded. Software: Python 3.10, PyTorch 2.14.1 (CUDA 12.6), TransformerLens 3.9.0, SAE Lens 6.54.5, Transformers 5.19.0. Jobs ran on 11 GB RTX 2080 Ti GPUs: about 3 GPU hours per precision state for the Gemma-2-2B functional and Study G runs, 1.5 for Llama-3.2-1B, and two GPUs for about four hours for the replication baseline.

Regeneration checks: the Phase 1 reproduction compared 89 output files against cached inputs (all identical); the Study G and prompt-check reproduction compared 45 outputs (zero differences), and the five Llama outputs were regenerated identically. These regenerate analyses; they are not independent repetitions of model inference. Freezes, sentence identifiers, matching manifests, run metadata, and SHA-256 checksums identify the runs; test suites, mutation checks, sham gates, and restore-only identities check the implementation, not the scientific interpretation.

B Pre-specified Rules and Outcomes

The upper part of Table 4 lists the rules of Study G and its three extensions (B, C, D) as written before the data were scored, with their outcomes; the unsupported ones are named below it.

Hypotheses That Were Not Supported

The original selective-versus-control tests (primary regime), the frozen Belebele statement S0 (making S1–S5 undefined), strict Study G precision monotonicity, the main-study repair rules (before the larger follow-up, which supported only the 1.1 multiplier), state-defined groups being more consequential, inverse shrinkage predicting the optimal gain, and on Llama-3.2-1B the predictions P1, P2b, P3a, and P3b were not met. They are reported as outcomes and were not converted by changing thresholds.

C Result Inventory and Status

The lower part of Table 4 lists every result block of the report with its headline numbers and its status (confirmatory, frozen, or exploratory). The repository's results summary numbers the same results as claims 1 to 17.

Rule	Condition fixed beforehand (languages counted out of 27)	Outcome	Verdict
H-G1, 2	net harm strictly ordered over the three down multipliers and zero ablation (FP), in ≥ 24 and in the median; lower bound above 0 at the deepest one, in ≥ 24	27, medians 0.0223, 0.0902, 0.1687, 0.2624; 26	met
H-G3	group harm increasing over the up multipliers in ≥ 24 and net harm above 0 at the largest in ≥ 20 (FP)	27 and 24	met
H-G4	tau > 0 at the deepest down multiplier in ≥ 24 and the median not falling by more than one bootstrap error	27; median clause false	not met
H-G5	INT4 generic repair (control harm below 0 at 1.1 or 1.2); group-specific repair (net-harm upper bound below 0 in ≥ 14); optimal gain against inverse shrinkage, rank correlation above 0.3	controls 0.0000 and 0.0002; 12; -0.034	not met
H-G6	net harm positive at the deepest down multiplier in ≥ 24 in every state; rank correlation FP against INT4 > 0.5	27 in every state; 0.936	met
H-Gc1	INT4 repair on fresh sentences: median net-harm interval below 0 and ≥ 19 negative	1.1: -0.0013 $[-0.0020, -0.0003]$, 20 (met); 1.2: -0.0017 $[-0.0031, 0.0003]$, 18 (not met)	met (1.1)
H-Gc2, 3	INT4 minus FP paired difference below 0 at both multipliers; matched controls not falling too at INT4	-0.0024, -0.0041; controls -0.0002, $+0.0001$	met
R-D1	same correlation, fresh sentences: $\rho \geq 0.30$, one-sided $p < 0.05$, reliability ≥ 0.30	$\rho = -0.170$, $p = 0.804$; reliability 0.917	not supported
H-Gb1	contributing features move with precision (Jaccard with FP smaller at INT4 than at INT6 in ≥ 24)	27; 0.488 against 0.855	met
H-Gb2	state-defined minus FP-defined net harm positive in ≥ 18 and in the median (INT4)	11; median -0.0098	not met
H-Gb3, 4	dose-response of state-defined groups (3); generic repair (4a); group-specific repair (4b)	met; 4a not met; 4b: 16 of 27	3, 4b met; 4a not met

Block	Headline result	Status
Association retention	6,663 of 8,086 selected features established; 70.8% retain their peak at INT4; correlation survival at INT4 13.75%	exploratory
Original tests	no rejection after Holm (-0.28, -1.44 points at INT7, INT6); tier slope $+12.3$ to -0.81 after conditioning on scale	historical, not externally registered
Group dependence on loss	macro effect 0.704 nats/token $[0.684, 0.723]$, 27 of 27; retention 1.01–1.04 through INT6, 1.13 at INT5, 2.14 at INT4	exploratory, frozen setting
Patching	language group recovers 2.6% of the INT4 loss gap, whole residual 39.3%	exploratory
Association versus function	lost-minus-retained medians (26 languages) $+0.0006$, $+0.0007$, $+0.0002$; margin AUROC for association loss 0.90/0.81/0.75; F5 sample: 0.86 for association loss, 0.58 for function (INT6)	exploratory
Belebele	S0 not met: macro effect -0.0001 $[-0.0035, +0.0031]$; whole group $+0.0007$; frozen prompt above harness prompt in 18 of 18 (point estimates)	S0 confirmatory; rest exploratory
Individual effects	median cosine 0.997/0.988/0.961/0.839 at INT8/6/5/4; matched other direction 0.828 against 0.842 at INT4	exploratory
Graded scaling	H-G1 to H-G3, H-G6 met; H-G4, repair rules not met	exploratory
Fine amplification	1.1 at INT4: net harm -0.00135 $[-0.00197, -0.00032]$, 20 of 27 languages; 1.2 not met	exploratory, fresh sentences
Optimum and groups	optimum reliable (0.92), not related to shrinkage in this sample (-0.17); state-defined groups not more consequential (-0.0098)	exploratory, post hoc in origin
Second model	Llama-3.2-1B: P1 not met (21 of 27), flat through INT6, no INT4 amplification; verdict not consistent	exploratory, pre-specified rule

Table 4: Upper part: pre-specified rules of Study G and its extensions with outcomes (net harm: group harm minus matched controls scaled by the same multiplier, nats per token). Lower part: every result block with its status ("frozen": fixed in a committed file before scoring; "confirmatory": fixed in advance, reported whatever the outcome).