Do Interventions on Language Features Survive Weight Quantization? Context, Weights, and Activation Survival in Gemma-2-2B

Hemang Joshi and Eashaan Thakur and Shardul Joshi and Nikhita Ravi
International Institute of Information Technology, Hyderabad

Abstract

Quantization changes sparse autoencoder (SAE) activations, but an activation change need not change what an intervention on that feature does. In Gemma-2-2B with a frozen layer-12 Gemma Scope SAE, 27 FLORES-200 languages and round-to-nearest weight quantization, we first show that activation survival, language-association retention and causal contribution are different outcomes: 70.8% of established language features keep their peak language at INT4, removing 64-feature language groups raises own-text loss beyond matched controls in all 27 languages, and individual feature effects drift as much for matched other directions. We then cross the two things quantization changes, the activations before an intervention (context) and the weights after it, for a fixed feature ablation. At INT6 the effect changes little (cosine 0.98, an error of about two numerical floors, above the rounding floor). At INT4 the group-level harm is amplified (median net harm 0.85 against 0.26 for the fixed full-precision edit); the context term of that edit is about three times the weight term ($|C| = 0.31$, $|W| = 0.10$), but with the quantized state's own activation the harm (0.43) is that of the weights alone, and the effect vector of single features is rotated (cosine 0.77) with the larger norm in the weight term, a substantial interaction, and largely the same rotation for other directions. Averaged fingerprints overstate transfer (+0.126 cosine). The sensitivity to other directions predicts the held-out error (21.5% reduction at INT4, an interval including zero at INT6, and a similar gain in a rounding-only state); on eligible items at INT4 neither activation survival nor gradient attribution adds measurably. A six-language Wikipedia panel repeats the INT4 statements; at INT6 its group-level weight term is the larger one and the prediction criterion is met. Apart from one family, all analyses are exploratory; one model, one SAE, simulated quantization.

1 Introduction

Weight quantization reduces the numerical precision of language-model parameters, and its effects need not be uniform across languages or tasks (Marchisio et al., 2024). Internal measurements can complement task metrics, but only if their interpretation is explicit. Calling a sparse autoencoder (SAE) feature "lost" can mean a changed activation pattern, a changed preferred language, or a changed effect on predictions. SAEs decompose an activation into sparse directions (Cunningham et al., 2023); language-associated features have been identified and manipulated in full precision (Deng et al., 2025); and Duan (2026) measure activation correlations before and after weight quantization with a frozen SAE, leaving open whether interventions built on those features survive. The representation can change while a contribution remains, or an intervention can change because the downstream model changes.

We began by asking whether language-selective features were more vulnerable than non-selective controls and whether that explained resource-tier disparities. After implementation audits and negative primary contrasts we expanded the project to test the measurement assumptions directly, and then to its main question. This report presents the whole investigation, including hypotheses that were not supported. **RQ1:** how do activation preservation and language-association retention compare? **RQ2:** do selected language groups contribute to prediction and comprehension, and how does that change with precision? **RQ3:** do individual intervention effects support an interpretation of feature-specific damage? **RQ4:** does the group dependence appear on a second model? **RQ5 (main):** does the effect of a *fixed* intervention survive quantization, and is a change due to the context, the weights, or their interaction; can it be predicted for held-out features?

Our contribution is a controlled case study: native interventions, donor patches and effect fingerprints across weight precisions (Sections 4, 6 and 8), and a crossed context–weights design for a fixed feature intervention with matched and random directions, a numerical floor, a held-out prediction target and an external-text check (Section 7). Ablation, patching and fingerprints are not new methods; the outcome is a set of distinctions and counterexamples to reading activation survival as functional survival, within one model and one measurement basis.

2 Related Work

Multilingual quantization. Marchisio et al. (2024) show that task, language and evaluation method affect the observed degradation; their behavioural evidence motivates our language panel but does not identify SAE features as its mechanism. Resource categories are a descriptive grouping (Joshi et al., 2020), not controlled interventions on training data.

Language-associated features. Deng et al. (2025) identify language-specific SAE features and use ablation and steering, so an own-language loss effect in full precision is supporting evidence, not a novelty claim. Gemma Scope supplies open SAEs across Gemma 2 layers (Lieberum et al., 2024). A frozen dictionary gives consistent coordinates across precision states without guaranteeing that each coordinate is an invariant mechanism.

Compression and causal interpretation. Duan (2026) measure feature survival under round-to-nearest quantization by activation correlation. A pruning study already separates geometric survival from causal importance (Borobia et al., 2026). Chang et al. (2025) use activation patching to localize quantization error and compare the loss recovered by patching activations with that recovered by restoring weights (their Section 6), which is why a context-dominated result alone is not our contribution; Hoang et al. (2026) analyze the geometry of intervention-induced logit changes; and Vaidyanathan et al. (2026) show that the effect estimated by activation patching contains an interaction term that is a diagnostic rather than noise, small when the model is locally affine. We add a crossed design for a fixed SAE intervention under quantization, controls for generic drift, and a held-out prediction target. Belebele (Bandarkar et al., 2024) supplies a separate comprehension outcome.

3 Setting and Research History

We use Gemma-2-2B (Gemma Team et al., 2024) and a 16,384-feature JumpReLU (Rajamanoharan et al., 2024) Gemma Scope SAE at the layer-12 post-block residual stream; the model runs in bfloat16, the SAE and all edits in float32, and the same dictionary serves every condition. Quantization uses the vendored reference round-to-nearest (RTN) functions (output-channel scaling), restoring the original weights before each state; values stay in floating-point storage, so we do not evaluate integer kernels. States are full precision (FP), INT8 to INT4, and INT16 and INT12 as near-lossless rounding references (re-rounding bfloat16 weights still changes them). One BOS token is prepended; BOS and padding are excluded from statistics and edits.

The panel is 27 parallel FLORES-200 (NLLB Team et al., 2022) languages in three descriptive tiers of nine (Appendix A). Features are discovered on the development split; association studies use 27,036 content tokens per language on devtest; the loss evaluation uses 300 aligned devtest sentences per language. Devtest had been examined earlier, so all FLORES functional analyses are exploratory. Belebele items are split by passage origin into calibration and evaluation; calibration selects the answer format and 18 languages with accuracy above chance plus 0.05, and the frozen evaluation has 385 items per language.

An initial implementation was retired after an audit; its outputs are not used. A rule is *pre-specified* if committed to the repository before the data it judges were scored; none was registered externally. The only confirmatory family is the Belebele family (its first statement needs a positive FP macro effect; 99% intervals for the five retention statements); everything else is exploratory.

4 Measurements and Interventions

Activation and association. With $a_f^b(t)$ the activation of feature f at token t in state b, the preservation score is $c_f^b = \mathrm{corr}_t(a_f^{\mathrm{FP}}(t), a_f^b(t))$ and the historical survival cutoff is $c_f^b > 0.9$. Language selectivity uses firing rates $r_{\ell f}$ and $S_f = \max_\ell r_{\ell f} / \mathrm{mean}_\ell r_{\ell f}$, with a shuffled-language null (95th percentile, 50 permutations), at least 50 peak tokens, a panel rate of at least 10^{-5} and the same peak in 80 of 100 resamples; the cohort

has 8,086 features. A feature is *established* on devtest if its original language is the unique supported firing-rate peak, and *retained* at b if that stays so; retention conditions on FP establishment. We also analyze the FP margin to the strongest competing language.

Groups, controls and edits. G_ℓ is the 64 highest-activation selective features of language ℓ on dev. Controls are matched greedily on log firing rate and log mean activation from 2,860 supported non-selective features (five draws; three in Study G). Matching is imperfect (75 of 81 language–size ratios within $[0.8, 1.25]$; Thai, Yoruba and Lao outside at K64), so activity matching is not an identification argument for language specificity. With x a residual, a its SAE encoding and d_f a decoder row, edits preserve the reconstruction error:

$$x' = x + \sum_{f \in G} (a'_f - a_f) d_f, \qquad (1)$$

zero ablation sets $a'_f = 0$ and scaling $a'_f = \alpha a_f$; identity and sham edits check the path. For donor patches the recipient is quantized and a'_f is the FP activation at the same position.

Effects and uncertainty. Harm is the change of the negative log-likelihood against the same state's unedited prediction (nats per token; Belebele nats per item). The group effect is

$$E^b_\ell = h^b_\ell(G_\ell) - \frac{1}{R} \sum_{r=1}^{R} h^b_\ell(C_{\ell r}), \qquad (2)$$

negative harm is improvement and never clipped. Retention is $E^b_\ell / E^{\mathrm{FP}}_\ell$ for languages with a clearly positive FP effect, averaged per language (a mean of ratios; it differs from the ratio of means). Loss intervals are 2,000 paired cluster-bootstrap draws over aligned sentence identifiers; Belebele resamples passages; association intervals use 1,000 sentence resamples and can be shifted by near-tied peaks.

5 Replication and Initial Tests

The vendored WikiText replication matches the published table closely (INT7 81.19% against 81.26%; INT6 51.15% against 51.30%), but the no-BOS FP perplexity is 458.4; with BOS added and masked it is about 16.1 and INT6 survival on WikiText is near 97.5%. This shows sensitivity to the input regime, not that every published result is invalid, so we use BOS-masked evaluation and keep the no-BOS study as history. In that primary regime none of the three planned tests rejects after Holm correction (selective-minus-control survival -0.28 and -1.44 points at INT7 and INT6; adjusted $p = 0.514, 0.128$); a stricter post hoc threshold gives -7.16 at INT6, and matching activation magnitude reverses it to $+4.58$. The tier disparity (INT6 survival 69.4/90.6/95.1% for low/mid/high) attenuates from $+12.3$ to -0.81 points per step after conditioning on activation scale ($p = 0.667$), which is correlational and does not identify the cause of multilingual damage.

State	Corr. (%)	Assoc. (%)	Effect ratio
INT8	100.00	98.1	1.01
INT7	99.97	97.5	1.03
INT6	94.94	94.7	1.04
INT5	59.00	89.1	1.13
INT4	13.75	70.8	2.14

Table 1: Different measurements across precision. Correlation survival pools active features; association retention conditions on 6,663 established features; the effect ratio is the mean of 27 per-language ratios. Denominators and meanings differ; all exploratory.

6 Association and Functional Results

Peaks persist beyond correlation survival. Only 6,663 of 8,086 selected features (82.4%) establish their peak on FP devtest; among them, retention falls gradually to 70.8% at INT4 (Table 1); the INT16 reference loses 56 features (99.2% retained) and no established feature becomes inactive. Correlation and association disagree: at INT6, 75.8% of association-lost features still exceed the correlation cutoff; at INT4, 79% of retained ones do not. The FP margin predicts association loss within a language (AUROC 0.90, 0.81, 0.75 at INT6/5/4; most borderline fifth against least at INT6: 20.7% against 0.1%), so much of the loss is sensitivity to near ties.

Group dependence on loss, and little localized damage. Zeroing a language's K64 group raises own-text loss beyond controls in all 27 languages at every precision: FP macro effect 0.704 nats/token $[0.684, 0.723]$ (median 0.262), retention near one through INT6, 1.13 at INT5 and 2.14 at INT4 $[2.04, 2.50]$ (the ratio of macro effects is only 1.33). This is dependence of a damaged model on the

group, not better language ability. Restoring the group with FP activations at INT4 recovers 2.6% of the loss gap (controls 1.2%; all SAE features 17.4%; whole residual 39.3%), and about nothing at INT5 and INT6: necessity within a model is not responsibility for the difference between models. Matching association-lost and retained features on native activity shows no systematic harm difference (median lost-minus-retained $+0.0006$, $+0.0007$, $+0.0002$ nats/token at INT4/5/6).

The comprehension statement is not met. On frozen Belebele the FP macro group effect is -0.0001 nats/item $[-0.0035, +0.0031]$; accuracy is 0.426 unedited, 0.426 with the group ablated and 0.425 with controls. No covered language has a clearly positive FP effect, so statement S0 is not met and S1–S5 are undefined; the whole group ($+0.0007$ $[-0.0030, +0.0042]$) agrees. Random sets of 1,024–2,860 features lower accuracy by 1.2–6.0 points while sham edits change nothing, so the edit path is sensitive and the null cannot exclude group effects of about half a point. Our frozen prompt scores above the lm-evaluation-harness prompt in all 18 languages (point estimates).

Individual effects drift, but directions drift too. For 1,487 features the median cosine between FP and quantized effect fingerprints is 0.997/0.988/0.961/0.839 at INT8/6/5/4 (fraction above the INT16 reference 94.0/89.7/66.5/0.3%), yet each feature's effect stays far closer to its own FP fingerprint than to others' (retrieval 0.997–1.000). In the 404-feature control that subtracts another matched decoder direction at the same positions and amplitudes the medians are 0.842 and 0.828 at INT4 (differences of medians 0.004–0.007 at INT8/6/5), so most drift is shared by arbitrary perturbations. About 31% of features above the write-side reference fail the activation-survival cutoff at INT5, and association status has descriptive AUROC 0.506 for INT4 effect similarity (at INT6 on the F5 sample the FP margin predicts association loss at 0.86 but function change at 0.58): label stability and causal-effect stability are different.

7 Intervention Transfer under Quantization

Design. The comparisons above change activations and weights together. We instead ask how the effect of a *fixed* intervention changes when the model is quantized, and whether the change




Figure 1: Median fingerprint similarity on the same 404 features and matched directions. Bars show interquartile ranges, not confidence intervals. The numerical drift is largely shared by alternative perturbations.

comes from the context (the residual and SAE activations before the edit), the weights (the layers after it) or their interaction. At the positions where a feature is active in FP we subtract its FP decoder contribution (float32; every cell subtracts its own unedited baseline; a zero edit is exactly zero). Let $D[p, s]$ be the mean centered change of the output logits with prefix state p and suffix state s, each FP or quantized (Q). Then $C = D[\mathrm{Q}, \mathrm{FP}] - D[\mathrm{FP}, \mathrm{FP}]$, $W = D[\mathrm{FP}, \mathrm{Q}] - D[\mathrm{FP}, \mathrm{FP}]$, $I = D[\mathrm{Q}, \mathrm{Q}] - D[\mathrm{Q}, \mathrm{FP}] - D[\mathrm{FP}, \mathrm{Q}] + D[\mathrm{FP}, \mathrm{FP}]$, and $D[\mathrm{Q}, \mathrm{Q}] - D[\mathrm{FP}, \mathrm{FP}] = C + W + I$ exactly. A fifth cell uses the quantized state's own activation (native amplitude).

Controls, floor, populations. Each edit is repeated along a matched swapped direction (another feature's decoder row) and three random norm-matched orthogonal directions. Because the model runs in bfloat16, even INT16 changes the logits; per direction kind the numerical floor is the 95th percentile of the INT16 error over calibration features (28.7 for the real direction), and an item is *eligible* if its FP effect norm exceeds five floors. The normalized error is $\|D[\mathrm{Q}, \mathrm{Q}] - D[\mathrm{FP}, \mathrm{FP}]\| / (\|D[\mathrm{FP}, \mathrm{FP}]\| + \text{floor})$. The feature level has 404 features with up to 16 contexts each (6,464 feature–context pairs; 2,203 eligible real-direction items of 235 features), split by a hash of the feature id into calibration and held-out halves; the group level ablates each language's K64 group and three matched control groups on the 300 evaluation sentences of the 27 languages and decomposes the net harm of Equation 2. Intervals are 2,000-replicate crossed bootstraps over features and source-sentence clusters (group level: sentences only). Pre-declared: A3, the expectation that the context term dominates the weight term at

the group level; H1, that the error is not explained by a rescaling of the FP effect or by the quantized state's own activation; H2 (descriptive), that C, W, I reproduce between the calibration and the held-out half; H3, that the generic sensitivity (below) predicts the error beyond activation measurements; H4, that the averaged fingerprint transfers differently from its single contexts. The design, thresholds and hypotheses were frozen and hashed before the first quantized run; amendments made after a 12-feature instrument run and before the full runs concern a gate threshold, the form of the gradient baseline and one extra baseline column, and the claim rules were tightened once after an independent code review and before the outcomes were read (Appendix B).

Group level. At INT6 the terms are small and equal (median $|C| = 0.0091$ $[0.0056, 0.0114]$, $|W| = 0.0092$ $[0.0061, 0.0133]$; the context term is larger in 12 of 27 languages), about 3.5% of the FP net harm and about 19 and 35 times the rounding-only values, so the group effect changes little (net harm 0.281 against 0.263). At INT4 the median net harm is 0.85 with the fixed FP edit, and for that edit the context term is about three times the weight term ($|C| = 0.310$ $[0.258, 0.334]$, $|W| = 0.104$ $[0.094, 0.122]$, $|I| = 0.071$); the interval of the median $|C| - |W|$ is $[+0.022, +0.073]$ (the context term is larger in 19 languages, as in the rounding-only state, so the count is not evidence; the interval is). The expectation that context dominates (A3) is supported at INT4 for this edit and undecided at INT6. A caveat matters for the reading: the median net harm of the four cells is 0.263 (FP/FP), 0.684 (quantized context, FP weights), 0.428 (FP context, quantized weights) and 0.848 (both), and with the quantized state's own activation it is 0.433, within 8% of the weights-only cell. For the natural intervention the amplification is therefore that of the weights; the context term of the fixed edit comes from subtracting a full-precision-sized contribution in a context where the feature's activation has changed.

Feature level. At INT6 the effect vector is rotated little (cosine 0.984, normalized error 0.165, 1.9 floors: small, but above the rounding floor); at INT4 it is rotated strongly (cosine 0.768) with a slightly larger norm (ratio 1.09) and a normalized error of 0.664 $[0.647, 0.680]$, 7.7 floors. The error is almost orthogonal to the FP effect (97–99% at every state, 99.7% at INT16) and using the quantized state's own activation leaves 97% of it, so neither a rescaling nor an activation change explains it (H1: the shares alone say nothing because they are equal in the rounding-only state, hence the requirement that the error clears the floor). Unlike the group-level loss, the *weight* term has the larger norm in the effect vector (relative norms 0.145 against 0.100 at INT6, 0.560 against 0.359 at INT4; $\|C\| > \|W\|$ in 6% and 10% of items; exploratory, the terms are not additive), and the interaction is a third of the change at INT4. The two readings differ in what they measure: the norm of a mean logit change against a signed loss summed over a group. Most of the error is not specific to the feature's direction: matched and random directions give terms and errors of similar size, with small differences in both directions (INT4: the real direction's normalized error is above its controls by $+0.019$ $[0.009, 0.032]$; the controls are not eligibility-filtered, so this mixes scale and specificity: in the 144 pairs with matched FP effect size the real direction's error norm is $\times 1.12$ (INT6) and $\times 1.14$ (INT4) that of its swapped direction ($\times 1.00$ at INT16): a modest specific part, post hoc).

Averages hide the contexts. The cosine of a feature's *averaged* fingerprint exceeds the mean cosine of its single contexts by 0.126 $[0.121, 0.131]$ at INT4, 0.024 at INT6 and 0.0145 $[0.011, 0.017]$ in the rounding-only state, where a positive gap is expected if numerical noise is independent across contexts (Figure 2c); the averaged fingerprint also has the lower normalized error in all 404 features, in every state. The contexts of a feature agree in FP only with coherence 0.59. Averaged fingerprints therefore overstate how well an intervention transfers (H4).

Prediction. We fit ridge models on the calibration half and score the held-out features (feature-held-out: their contexts share source sentences with the calibration half). A uses activation measurements (cosine of FP and quantized activations, log activation, firing share, log effect and residual norms), G adds the loss gradient at the edited rows, B adds the generic sensitivity measured with the *other* four directions at the same context. B reduces the held-out error against the strongest baseline (A+G at INT4, A at INT6, chosen on the calibration half) by 21.5% $[12.7, 29.4]$ at INT4, so the 10% criterion is met, but by 10.9% $[-1.2, 21.4]$ at INT6, where the interval includes zero and the baselines are not better than the calibration median;

State	Group level (27 languages, nats/token)				Feature level (2,203 eligible items)					
	net harm	$\|C\|$	$\|W\|$	$\|I\|$	cosine	error	floors	C	W	I
INT16 (rounding)	0.262	0.0005	0.0003	0.0002	0.998	0.056	0.71	0.055	0.053	0.074
INT6	0.281	0.009	0.009	0.001	0.984	0.165	1.9	0.100	0.145	0.086
INT4	0.848	0.310	0.104	0.071	0.768	0.664	7.7	0.359	0.560	0.315

Table 2: Main results of the transfer study. Group level: median net harm with the FP edit (FP: 0.263) and median absolute terms over 27 languages. Feature level: medians over eligible real-direction items of the cosine between the quantized and FP effect vectors, the normalized error, the error in numerical floors, and the norms of C, W, I relative to the FP norm plus floor. INT16 is the rounding-only reference.




Figure 2: (a) Median relative norm of the context, weight and interaction terms of the effect vector, real direction (with 95% interval) and the four control directions. (b) Group-level absolute context and weight terms of the net harm, one point per language. (c) Cosine of the averaged fingerprint minus the mean cosine of its contexts, with the rounding-only state as reference; the interval resamples features only.




Figure 3: Relative reduction of the held-out error of the model with the generic sensitivity (A+B) against the strongest baseline, with crossed-bootstrap intervals, for the eligible items of the real direction (blue; the primary analysis) and for all items (grey; secondary). Dashed: the 10% criterion.

on all 6,464 items, a secondary analysis with the floor-normalized error (grey in Figure 3), the INT6 reduction is 37.1% $[30.7, 43.0]$. The pre-specified utility criterion needs both states on eligible items and is not met. The same model reduces the error by 23.4% $[15.1, 30.8]$ in the rounding-only INT16 state, so the INT4 gain cannot be attributed to a quantization-specific mechanism: B also predicts pure rounding error, plausibly because it measures how noise-prone a context is. On eligible items at INT4 neither gradient attribution (held-out error 0.124 against 0.125, no interval) nor the Pearson survival of the feature adds to A or to B (survival: -0.4% $[-1.8, 0.7]$ and -0.6% $[-4.3, 3.4]$); at INT6 adding survival to B is slightly worse (-6.5% $[-12.0, -1.6]$).

External panel. We ran the same design once on 1,800 Wikipedia passages (300 each in English, Hindi, Russian, Spanish, Yoruba and Chinese; 402 of the 404 features; same rules, floor recomputed: 1,444 of 6,406 items eligible). INT4 repeats the main result: the effect vector is rotated (cosine 0.754, normalized error 0.679), the weight term has the larger norm, the averaged fingerprint hides the error (cosine gap $+0.132$ $[0.125, 0.140]$ against $+0.027$ in the rounding-only state; H4 supported),

the context term of the fixed edit exceeds the weight term ($+0.053$ $[+0.040, +0.064]$, 4 of 6 languages; A3 supported), and B reduces the held-out error by 19.4% $[5.1, 31.8]$ (20.6% $[9.3, 31.2]$ when fitted on the FLORES calibration features, no refit). INT6 differs: the weight term is larger at the group level (-0.0049 $[-0.0060, -0.0031]$; A3 reversed), H4 is inconclusive, and the reduction is 23.4% $[12.8, 32.5]$ (against the calibration median, which beats both activation baselines at INT6, the FLORES-fitted cross-corpus reduction is 15.8% $[-2.7, 28.7]$), so the utility criterion is met here though not on FLORES; the rounding-only state is predicted as well (28.9%). With six languages and a smaller eligible population this is an external-validity check, not a replication.

8 Graded Feature Scaling

Study G varies α in Equation 1 for the K64 groups with three down multipliers (0.3536, 0.1768, 0.0884) and their reciprocals, calibrated on a 100-sentence FP pilot, on 300 sentences, 27 languages and three control draws. In FP the median net harm rises 0.0223, 0.0902, 0.1687, 0.2624 as the group is suppressed more strongly and then zeroed (ordered in all 27 languages; 26 with a positive lower bound at the deepest down multiplier); strong amplification also raises harm; the curves are similar from FP through INT5 with an INT4 increase. The strict precision-monotonicity rule is not met and no relaxed tolerance is substituted. A follow-up on 562 reserve sentences with five control draws finds a small INT4 benefit of amplifying by 1.1 (median net harm -0.00135 nats/token, 97.5% interval $[-0.00197, -0.00032]$, 20 of 27 languages; 1.2: not met), with a small harm at FP, INT6 and INT5. State-defined groups (Jaccard with the FP group 0.49 at INT4) are not more consequential (-0.0098), and the language-specific optimal gain is reproducible (reliability 0.917) but not explained by inverse activation shrinkage (rank correlation -0.170, $p = 0.804$): a simple compensation explanation is not supported.

9 A Second-Model Check

We ran a minimum consistency check on Llama-3.2-1B (Grattafiori et al., 2024) with a public TopK (Gao et al., 2024) SAE (14,336 features, residual entering block 12) through an adapter around the frozen Gemma pipeline (same languages, sentences, selectivity rule, K64 groups, three control draws, Study G multipliers, 300 sentences; FP, INT8, INT6, INT5, INT4), with predictions fixed beforehand (Table 3). The verdict is *not consistent*: the group effect exists but is small (median 0.048 nats/token against 0.262; positive in 21 of 27 languages, 24 required; large in German, Yoruba and Amharic, negative in six languages); it is flat through INT6 (P2a met) but without INT4 amplification (the frozen mean retention is -3.57 because one language with $E = 0.0027$ has a ratio of -88.9; the post hoc median is 0.86, against 1.54 on Gemma), and the down-dose ordering holds in 20 of 27 languages at FP and 15 at INT4. Control draws are heavy-tailed, so post hoc robustness variants cannot change the verdict. Model family, SAE architecture, depth and tokenizer all differ, and this dictionary labels 91% of its supported features selective with only 898 candidate controls, so the check does not show that the Gemma findings fail elsewhere.




Figure 4: Median net harm under suppression, from the completed Study G curves. Net harm subtracts controls scaled by the same multiplier. The strongest precision change occurs at INT4.

10 Discussion and Conclusion

The original selective-destruction account is not established: primary contrasts were weak, the threshold-dependent disadvantage reversed with magnitude matching, and donor patches attributed little quantization loss to the selected groups. The main methodological lesson is to say what a survival measurement preserves: a correlation cutoff describes activation agreement, a peak label depends on a margin, and a logit fingerprint describes a sampled intervention in a changing downstream model.

The crossed design adds three findings. First, whether an intervention keeps its effect depends strongly on the precision (cosine 0.98 at INT6, 0.77 at INT4): at INT6 it changes little (about two floors,

Prediction (fixed beforehand)	Llama-3.2-1B	Gemma-2-2B	Met
P1: median $E > 0$ with its interval above 0 and $E > 0$ in ≥ 24 of 27 languages	median 0.048 $[0.018, 0.173]$; 21 of 27	median 0.262; 27 of 27	no
P2a: macro retention in $[0.85, 1.15]$ at INT8 and INT6	1.010, 1.024	1.006, 1.038	yes
P2b: INT4 retention $\geq$ INT6 $+0.30$ and the largest	INT5 0.14, INT4 -3.57 (median of ratios 0.86)	1.13, 2.14 (median 1.54)	no
P3a: down-dose ordering (H-G1) in ≥ 24 of 27 languages and in the median, at FP and INT4	20 of 27 at FP, 15 of 27 at INT4	met (Study G)	no
P3b (reported only): the deepest down multiplier costs more at INT4 in ≥ 20 of 27 and the median ratio exceeds 1.3	14 of 27; median ratio 1.17	ratio 1.91	no
Verdict	not consistent (P1 fails)		

Table 3: Pre-specified predictions and outcomes for the Llama-3.2-1B check. E is the group effect of Equation 2 (nats/token); retention is the mean of per-language ratios $E^b_\ell / E^{\mathrm{FP}}_\ell$ over languages with a clearly positive FP effect (21 of 27). The median of the ratios is post hoc and not used for the verdict.

above the rounding floor) and at INT4 the effect vector is rotated rather than shrunk. Second, the answer to "context or weights" depends on the quantity and on the edit: for the fixed full-precision edit the group-level loss is amplified mostly through the context term, but with the quantized state's own activation the harm is that of the weights alone, and the effect vector has its larger norm in the weight term; the interaction is never negligible at INT4, so a single split would mislead. Third, most of the transfer error is shared with other directions and the sensitivity to them predicts it (it also predicts the rounding-only error, so this is not shown to be quantization-specific); activation survival and, on eligible items at INT4, gradient attribution add nothing measurable; and averaged fingerprints hide it. Together with the earlier result that activation survival and association status are not reliable proxies for functional change, this argues against using activation survival as a proxy for the survival of interventions; it does not show that a better proxy is unavailable.

Limitations, Challenges, and Future Work

All analyses use one base model, layer, frozen SAE and simulated round-to-nearest weights (not deployed integer kernels); dictionary fidelity can deteriorate after compression. Zero ablation can be off-distribution and does not establish unique necessity or semantic identity; matching is imperfect and control draws overlap. Language tiers confound script, tokenization, training data and competence. Most results are exploratory, and bootstrap intervals condition on the selected sample.

For the transfer study: the numerical floor is large (bfloat16 execution), so INT6 effects are only about two floors; "held-out" means held-out features (88% of held-out source sentences also occur among calibration contexts); the group-level interval resamples sentences only and the averaged-fingerprint interval features only; the control directions of the specificity contrast are not eligibility-filtered; the ridge strength chosen was the largest of the three tried; the generic-sensitivity model also works in the rounding-only state, so its INT4 gain must not be read as quantization-specific; the gradient baseline is the scalar loss-attribution form, not the effect-vector form (post hoc, $r = 0.63$ with the signed loss change, 0.58 with its INT4 shift); and the six-language external panel is a validity check, not a replication of the 27-language study (its INT6 statuses differ and one language dominates its medians). The second-model check confounds model family, dictionary, depth and tokenizer; Gemma-2-9B with Gemma Scope was handed to another team and is not part of this report.

Challenges included replacing the initial pipeline, accelerator memory limits, hardware heterogeneity (one node with different float results, one that ran on the CPU; both caught by gates and log checks), and CUDA failures. Future work should replicate across models and quantizers (including integer kernels and activation quantization), test behavioural steering with calibrated headroom, and test the generic-sensitivity predictor against a quantization-specific alternative. These are not completed results.

References

Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabsa. 2024. The belebele benchmark: a parallel reading comprehension dataset in 122 language variants. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 749–775, Bangkok, Thailand. Association for Computational Linguistics.

Hector Borobia, Elies Seguí-Mas, and Guillermina Tormo-Carbó. 2026. How pruning reshapes features: Sparse autoencoder analysis of weight-pruned language models. *arXiv preprint arXiv:2603.25325*.

Ting-Yun Chang, Muru Zhang, Jesse Thomason, and Robin Jia. 2025. Why do some inputs break low-bit LLM quantization? In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 3410–3429, Suzhou, China. Association for Computational Linguistics.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. Sparse autoencoders find highly interpretable features in language models. *arXiv preprint arXiv:2309.08600*.

Boyi Deng, Yu Wan, Baosong Yang, Yidan Zhang, and Fuli Feng. 2025. Unveiling language-specific features in large language models via sparse autoencoders. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4563–4608, Vienna, Austria. Association for Computational Linguistics.

Evan Duan. 2026. Perplexity can miss SAE feature damage under quantization. *arXiv preprint arXiv:2606.03002*.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. 2024. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093*.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, et al. 2024. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Phu Gia Hoang, Anwoy Chatterjee, Tanmoy Chakraborty, Iryna Gurevych, and Subhabrata Dutta. 2026. Sparse autoencoders encode both concepts and functions: The downstream geometry of feature effects. *arXiv preprint arXiv:2607.24645*.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6282–6293, Online. Association for Computational Linguistics.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, Janos Kramar, Anca Dragan, Rohin Shah, and Neel Nanda. 2024. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. In *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pages 278–300, Miami, Florida, US. Association for Computational Linguistics.

Kelly Marchisio, Saurabh Dash, Hongyu Chen, Dennis Aumiller, Ahmet Üstün, Sara Hooker, and Sebastian Ruder. 2024. How does quantization affect multilingual LLMs? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15928–15947, Miami, Florida, USA. Association for Computational Linguistics.

NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, et al. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.

Senthooran Rajamanoharan, Tom Lieberum, Nicolas Sonnerat, Arthur Conmy, Vikrant Varma, János Kramár, and Neel Nanda. 2024. Jumping ahead: Improving reconstruction fidelity with JumpReLU sparse autoencoders. *arXiv preprint arXiv:2407.14435*.

Sankaran Vaidyanathan, David Arbour, Aaron Mueller, Scott Niekum, and David Jensen. 2026. The curse of multiple mediators: Hidden interaction effects in activation patching. *arXiv preprint arXiv:2606.27510*.

A Language Panel and Reproduction

Tier	Languages (FLORES-200 codes)
High	eng_Latn, deu_Latn, spa_Latn, fra_Latn, por_Latn, rus_Cyrl, zho_Hans, jpn_Jpan, kor_Hang
Mid	hin_Deva, ben_Beng, tam_Taml, tur_Latn, vie_Latn, ind_Latn, tha_Thai, pol_Latn, ukr_Cyrl
Low	kan_Knda, tel_Telu, yor_Latn, sun_Latn, amh_Ethi, ibo_Latn, hau_Latn, khm_Khmr, lao_Laoo

Table 4: The fixed 27-language roster in the order English, German, Spanish, French, Portuguese, Russian, Chinese, Japanese, Korean; Hindi, Bengali, Tamil, Turkish, Vietnamese, Indonesian, Thai, Polish, Ukrainian; Kannada, Telugu, Yoruba, Sundanese, Amharic, Igbo, Hausa, Khmer, Lao. Tiers are descriptive groupings, not equal training exposure.

The repository is https://github.com/TH4KUR/always-late; its results summary and figure index map the headline numbers to their source files, and the evidence map in the report folder lists the tables behind each numerical block. The private artifact dataset is https://huggingface.co/datasets/karma-skz/always-late-artifacts; newer item-level files are recorded by location and checksum and are not all archived there. The Wikipedia text of the external panel is pinned by dataset revision and per-passage checksums in reports/intervention_transfer/freeze_external.json and is not in the repository (CC BY-SA). The Weights & Biases project https://wandb.ai/karma-skz-/anlp-project holds the 19 earlier replication runs and 15 runs (v2-⋆) uploaded after the fact, one per result family (the transfer study is not among them), with headline numbers, tables, and figures read from the committed files (design: reports/wandb_schema_v2.md); no weights or item-level files are uploaded. Software: Python 3.10, PyTorch 2.14.1 (CUDA 12.6), TransformerLens 3.9.0, SAE Lens 6.54.5, Transformers 5.19.0. Jobs ran on 11 GB RTX 2080 Ti GPUs: about 3 GPU hours per precision state for the Gemma-2-2B functional and Study G runs, 1.5 for Llama-3.2-1B, about 3 to 5 for each of the six main transfer runs and 1.5 to 8 for the six external ones.

Regeneration checks: the Phase 1 reproduction compared 89 output files against cached inputs (all identical); the Study G and prompt-check reproduction compared 45 outputs (zero differences), and the five Llama outputs were regenerated identically. These regenerate analyses; they are not independent repetitions of model inference. Freezes, sentence identifiers, matching manifests, run metadata, and SHA-256 checksums identify the runs; test suites (about 300 for the transfer study), mutation checks, an independent read-only code review, sham gates, and restore-only identities check the implementation, not the scientific interpretation. The transfer analysis ran once on the six validated main runs; its claim rules were tightened once, after the review and before any outcome was read (H1 also needs the error above the numerical floor, H4 must separate from the rounding-only state, A3 needs both readings of its wording, an unrun or unfittable state is not a failed criterion, incomplete runs stop the analysis).

B Pre-specified Rules and Outcomes

The upper part of Table 5 lists the rules of Study G and its three extensions (B, C, D) as written before the data were scored, with their outcomes; the unsupported ones are named below it.

Hypotheses That Were Not Supported

The original selective-versus-control tests (primary regime), the frozen Belebele statement S0 (making S1–S5 undefined), strict Study G precision monotonicity, the main-study repair rules (before the larger follow-up, which supported only the 1.1 multiplier), state-defined groups being more consequential, inverse shrinkage predicting the optimal gain, on Llama-3.2-1B the predictions P1, P2b, P3a, and P3b, and in the transfer study the utility criterion on FLORES (met at INT4, not at INT6; met on the external panel) and the context-dominance expectation at INT6 (undecided on FLORES, reversed on the external panel). They are reported as outcomes and were not converted by changing thresholds.

C Result Inventory and Status

The lower part of Table 5 lists every result block of the report with its headline numbers and its status (confirmatory, frozen, or exploratory). The repository's results summary numbers the same results as claims 1 to 18.

Rule	Condition fixed beforehand (languages counted out of 27)	Outcome	Verdict
H-G1, 2	net harm strictly ordered over the three down multipliers and zero ablation (FP), in ≥ 24 and in the median; lower bound above 0 at the deepest one, in ≥ 24	27, medians 0.0223, 0.0902, 0.1687, 0.2624; 26	met
H-G3	group harm increasing over the up multipliers in ≥ 24 and net harm above 0 at the largest in ≥ 20 (FP)	27 and 24	met
H-G4	tau > 0 at the deepest down multiplier in ≥ 24 and the median not falling by more than one bootstrap error	27; median clause false	not met
H-G5	INT4 generic repair (control harm below 0 at 1.1 or 1.2); group-specific repair (net-harm upper bound below 0 in ≥ 14); optimal gain against inverse shrinkage, rank correlation above 0.3	controls 0.0000 and 0.0002; 12; -0.034	not met
H-G6	net harm positive at the deepest down multiplier in ≥ 24 in every state; rank correlation FP against INT4 > 0.5	27 in every state; 0.936	met
H-Gc1	INT4 repair on fresh sentences: median net-harm interval below 0 and ≥ 19 negative	1.1: -0.0013 $[-0.0020, -0.0003]$, 20 (met); 1.2: -0.0017 $[-0.0031, 0.0003]$, 18 (not met)	met (1.1)
H-Gc2, 3	INT4 minus FP paired difference below 0 at both multipliers; matched controls not falling too at INT4	-0.0024, -0.0041; controls -0.0002, $+0.0001$	met
R-D1	same correlation, fresh sentences: $\rho \geq 0.30$, one-sided $p < 0.05$, reliability ≥ 0.30	$\rho = -0.170$, $p = 0.804$; reliability 0.917	not supported
H-Gb1	contributing features move with precision (Jaccard with FP smaller at INT4 than at INT6 in ≥ 24)	27; 0.488 against 0.855	met
H-Gb2	state-defined minus FP-defined net harm positive in ≥ 18 and in the median (INT4)	11; median -0.0098	not met
H-Gb3, 4	dose-response of state-defined groups (3); generic repair (4a); group-specific repair (4b)	met; 4a not met; 4b: 16 of 27	3, 4b met; 4a not met

Block	Headline result	Status
Association retention	6,663 of 8,086 selected features established; 70.8% retain their peak at INT4; correlation survival at INT4 13.75%	exploratory
Original tests	no rejection after Holm (-0.28, -1.44 points at INT7, INT6); tier slope $+12.3$ to -0.81 after conditioning on scale	historical, not externally registered
Group dependence on loss	macro effect 0.704 nats/token $[0.684, 0.723]$, 27 of 27; retention 1.01–1.04 through INT6, 1.13 at INT5, 2.14 at INT4	exploratory, frozen setting
Patching	language group recovers 2.6% of the INT4 loss gap, whole residual 39.3%	exploratory
Association versus function	lost-minus-retained medians (26 languages) $+0.0006$, $+0.0007$, $+0.0002$; margin AUROC for association loss 0.90/0.81/0.75; F5 sample: 0.86 for association loss, 0.58 for function (INT6)	exploratory
Belebele	S0 not met: macro effect -0.0001 $[-0.0035, +0.0031]$; whole group $+0.0007$; frozen prompt above harness prompt in 18 of 18 (point estimates)	S0 confirmatory; rest exploratory
Individual effects	median cosine 0.997/0.988/0.961/0.839 at INT8/6/5/4; matched other direction 0.828 against 0.842 at INT4	exploratory
Graded scaling	H-G1 to H-G3, H-G6 met; H-G4, repair rules not met	exploratory
Fine amplification	1.1 at INT4: net harm -0.00135 $[-0.00197, -0.00032]$, 20 of 27 languages; 1.2 not met	exploratory, fresh sentences
Optimum and groups	optimum reliable (0.92), not related to shrinkage in this sample (-0.17); state-defined groups not more consequential (-0.0098)	exploratory, post hoc in origin
Second model	Llama-3.2-1B: P1 not met (21 of 27), flat through INT6, no INT4 amplification; verdict not consistent	exploratory, pre-specified rule
Transfer, group level	net harm 0.85 against 0.26 at INT4; $\lvert C\rvert = 0.310$, $\lvert W\rvert = 0.104$ (difference $[+0.022, +0.073]$, context larger in 19 of 27); INT6 0.0091 and 0.0092	A3 supported at INT4, undecided at INT6
Transfer, feature level	2,203 eligible items; cosine 0.984 and 0.768, normalized error 0.165 and 0.664 at INT6 and INT4, 97–99% orthogonal to the FP effect; weight term larger; real direction close to its controls ($+0.019$ at INT4); averaged-fingerprint gap $+0.126$ at INT4 ($+0.0145$ at INT16)	H1 and H4 supported; rest exploratory
Transfer, external panel	six languages, 1,444 eligible items; INT4 cosine 0.754, error 0.679, context larger ($+0.053$), gap $+0.132$; INT6 weight larger (-0.0049); error reduction 19.4% and 23.4%, cross-corpus 20.6% and 19.7%	H1, H3 supported, A3 and H4 mixed, utility met; exploratory
Prediction	error reduction 21.5% $[12.7, 29.4]$ at INT4, 10.9% $[-1.2, 21.4]$ at INT6 (all items 37.1%), 23.4% at INT16; gradient and survival add nothing at INT4	H3 mixed; utility not met

Table 5: Upper: pre-specified rules of Study G and its extensions with outcomes (net harm: group minus matched controls, nats per token). Lower: every result block with its status.