



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No.9
Aim: To implement Non-Restoring division algorithm using c-programming
Name: AKSHAT AVINASH VYAS
Roll no: 61
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim - To implement Non-Restoring division algorithm using c-programming.

Objective -

1. To understand the working of Non-Restoring division algorithm.
2. To understand how to implement Non-Restoring division algorithm using cprogramming.


Theory:

In each cycle content of the register, A is first shifted and then the divisor is added or subtracted with the content of register A depending upon the sign of A. In this, there is no need of restoring, but if the remainder is negative then there is a need of restoring the remainder. This is the faster algorithm of division.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science



Perform $8 \div 3$ by non-restoring division technique.

	A Register	Q Register	
Initially	0 0 0 0 0	1 0 0 0	
Shift	0 0 0 0 1	0 0 0 □	
Subtract	1 1 1 0 1		First Cycle
Set Q ₀	1 1 1 1 0	0 0 0 0	
Shift	1 1 1 0 0	0 0 0 □	
Add	0 0 0 1 1		Second Cycle
Set Q ₀	1 1 1 1 1	0 0 0 0	
Shift	1 1 1 1 0	0 0 0 □	
Add	0 0 0 1 1		Third Cycle
Set Q ₀	0 0 0 0 1	0 0 0 1	
Shift	0 0 0 1 0	0 0 1 □	
Subtract	1 1 1 0 1		Fourth Cycle
Set Q ₀	1 1 1 1 1	0 0 1 0	
Add	1 1 1 1 1		Quotient
	0 0 0 1 1		
	0 0 0 1 0		
			Remainder

Program -

```
#include <stdio.h>
```

```
void binaryPrint(int n, int bits) {
    for (int i = bits - 1; i >= 0; i--) {
        printf("%d", (n >> i) & 1);
    }
    printf("\n");
}
```



```
int main() { int M, Q, A;
A = 0; count; int n;
printf("Enter the divisor (M): ");
scanf("%d", &M); printf("Enter
the dividend (Q): "); scanf("%d",
&Q); printf("Enter the number of
bits: "); scanf("%d", &n); count =
n;
```

```
printf("\nInitial values:\n");
printf("A: ");
binaryPrint(A, n);
printf("Q: ");
binaryPrint(Q, n);
printf("M: ");
binaryPrint(M, n);
printf("\n");
```

```
while (count > 0) {
    A = (A << 1) | ((Q >> (n - 1)) & 1);
    Q = Q << 1;
```

```
    printf("After left shift:\n");
    printf("A: "); binaryPrint(A,
n); printf("Q: ");
    binaryPrint(Q, n);
```

```
    if (A >= 0) { A = A - M; printf("After
    subtraction (A >= 0):\n");
    } else {
        A = A + M; printf("After addition
        (A < 0):\n");
    }
}
```

```
printf("A: "); binaryPrint(A,
n);
```

```
if (A >= 0) {
    Q = Q | 1;
} else {
    Q = Q & ~(1);
}
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
printf("After      updating
Q0:\n");      printf("A:  ");
binaryPrint(A, n); printf("Q:
");      binaryPrint(Q,  n);
printf("\n");

count--;
}

if (A < 0) { A = A + M; printf("Final correction (if
A < 0, add M to A):\n"); printf("A: ");
binaryPrint(A, n);
}

printf("\nFinal quotient (Q):
");      binaryPrint(Q,  n);
printf("Final remainder (A):
");      binaryPrint(A, n);
return 0;
}
```

Output:



```
Enter the divisor (M): 4
Enter the dividend (Q): 2
Enter the number of bits: 4
```

Initial values:

```
A: 0000
Q: 0010
M: 0100
```

After left shift:

```
A: 0000
Q: 0100
```

After subtraction ($A \geq 0$):

```
A: 1100
```

After updating Q0:

```
A: 1100
Q: 0100
```

After left shift:

```
A: 1000
Q: 1000
```

After addition ($A < 0$):

```
A: 1100
```

After updating Q0:

```
A: 1100
Q: 1000
```

After left shift:

```
A: 1001
Q: 0000
```

After addition ($A < 0$):

```
A: 1101
```

After updating Q0:

```
A: 1101
Q: 0000
```

Final correction (if $A < 0$, add M to A):

```
A: 0010
```

Final quotient (Q): 0000

Final remainder (A): 0010



Conclusion -

In this experiment, we successfully implemented the Non-Restoring Division Algorithm in C to divide two unsigned integers represented in binary form. The algorithm effectively demonstrates the process of binary arithmetic, including addition, subtraction, and bitwise shifting. Through stepby-step execution, we observed how the quotient and remainder are derived based on the initial dividend and divisor. This implementation not only reinforces the understanding of binary operations but also highlights the efficiency of Non-Restoring Division in handling division tasks without requiring restoration in every step. Overall, the experiment provides valuable insights into algorithm design and binary number manipulation in programming.