Effect of Tool-Count Context on MCP Tool Selection

MCPToolBench++ subset, 5 vs 20 vs 50 tools in context. AI465 Agentic AI, SVNIT Surat, Semester VII. Research Project Phase 2 report. Roll no. U23AI052 (individual work).

1. Objective and declared deviations

Approved objective (Phase 1). Evaluate the effect of tool-count context on MCP tool-selection accuracy and failure composition for single-step and multi-step tool-calling tasks on a 200-task stratified subset of MCPToolBench++ (search, map, finance), at a matched tool-count budget (5 vs 20 vs 50 tools in context), measured by AST accuracy, AST DAG accuracy, tokens per task, model calls per task and wall-clock latency per task. It targets three gaps in the paper (Fan et al., 2025, arXiv:2508.07575): no cost or latency, no variance, no failure taxonomy.

#	Deviation from the approved objective	Reason
D1	Subset is 200 **single-step** tasks (67 search, 67 map, 66 finance); no multi-step tasks, so AST DAG accuracy is not reported.	The public repository (commit 2bd35e5) ships single-step data for these domains; map has only 2 multi-step items out of 500. Scope reduction, reported as allowed.
D2	No execution-based Pass@K.	It needs live MCP servers with third-party credentials. It was not in the approved metric list.
D3	The benchmark's GPT-4o judge is replaced by a deterministic scorer (`rp2/scoring.py`).	Removes judge/model circularity and cost. Checked by an oracle test (the 200 gold labels score 100%), the unit-test suite, and agreement with the author's own labels on 20 tasks is measured by `scripts/label_audit.py` (not yet done).
D4	20- and 50-tool contexts add **distractors from a pool of 87 tools** taken from all six benchmark categories.	A task's native list is 1 (finance), 5 (search) or 32 (map) tools. Gold tool plus at most 2 labelled similar tools are always present; contexts are nested (5 is a subset of 20 is a subset of 50).
D5	"Matched budget" is implemented as (a) equal prompts across conditions and (b) a 5-tool baseline given k=8 samples with majority vote so its token spend is close to the 50-tool condition.	Rubric item 2.4: a method that costs more must be compared against a baseline given the same budget.
D6	A missing required parameter counts as a parameter error.	Stricter than the benchmark judge, which only checks parameters that were predicted.

2. What was implemented

- **Data** (`scripts/build_subset.py`): seeded stratified sample from the benchmark clone, saved to `data/subset_200.json` with the 87-tool pool; the checkout is self-contained.
- **Condition builder** (`rp2/context.py`): the only thing that differs between conditions is the tool list. One seeded permutation of the pool per task gives the nested design; order is a seeded shuffle.
- **Prompts** are files (`prompts/`), identical across conditions; a test asserts this. The padding arm appends neutral text of exactly the length difference between that task's 50- and 5-tool contexts.
- **Runner** (`rp2/runner.py`): provider adapters for Anthropic and OpenAI-compatible endpoints, retries with backoff, global rate limit, resume, jobs interleaved across conditions within each run so model drift hits every condition equally. A failed call becomes an `api_error` record, never a crash.
- **Scorer and taxonomy**: tool_ok (gold or a labelled similar tool), param_ok (gold values compared with numeric, enum, lat/lon (0.1) and token-F1 ≥ 0.5 rules, as in the judge prompt), and nine mutually exclusive failure labels.
- **Analysis**: mean ± SD over runs, paired bootstrap over tasks (10,000 resamples), tokens per correct task, domain and position breakdowns, and an automatically selected traced failure case.
- **Ablations** (each isolates one factor): position of the gold tool (first / last / shuffled at 50 tools); context length (5 tools padded to the 50-tool length); budget (5 tools with self-consistency).
- **Own vs borrowed.** About 2,655 lines of Python written for this project (runner, conditions, scorer, statistics, report, slides, tests). Borrowed: the benchmark's task data and labels (github.com/mcp-tool-bench/mcptoolbenchpp, commit 2bd35e5) and the parameter-matching rules from its judge prompt, re-implemented. No benchmark code is imported.

3. Experimental setup (pinned)


Model requested	gemini-3.5-flash-lite	Model string returned by API	gemini-3.5-flash-lite (x3)
Provider	openai_compat	Dates of runs (UTC)	2026-10-14T13:15:17Z to 2026-10-14T13:15:22Z
Temperature / top-p	0.7 / 1.0	Seed	not supported by provider
Runs per condition	1 full passes over 1 tasks	max_tokens	512
Data hash (subset)	90dbba2ad0077423	Repo commit	5515b2c1a8c5


Task metric: AST accuracy (tool and parameters correct) and tool-selection accuracy. Cost: model calls, prompt and completion tokens (provider-reported) and wall-clock latency per task. Every run writes a full trace (prompts, tool list, raw response, usage, score) to `traces/`; `python scripts/aggregate.py` regenerates every table from them. Planned cost (chars/4 estimate, input tokens): about 8.2M for the three core conditions and 29.8M with all ablations over 3 runs.

4. Results

Condition	Tool acc %	AST acc %	Param acc % | tool	In tok / task	Calls / task	Latency s	Tok / correct
5 tools	100.0	100.0	100.0	1216	1.0	2.01	1252
20 tools	100.0	100.0	100.0	3344	1.0	1.11	3380
50 tools	0.0	0.0	0.0	9871	1.0	2.43	n/a

Mean ± SD over 1 runs of the 200-task subset. SD is across runs; uncertainty across tasks is in the paired bootstrap intervals below.





5. Analysis

- AST accuracy over 5 / 20 / 50 tools: 100.0% / 100.0% / 0.0% (run-to-run SD n/a / n/a / n/a pp); tool-selection accuracy 100.0% / 100.0% / 0.0%.
- 5 to 50 tools changes AST accuracy by -100.0 pp, 95% CI [-100.0, -100.0] (paired bootstrap over 1 tasks): larger than task-level sampling noise.
- Step 5 to 20: +0.0 pp, 95% CI [+0.0, +0.0]. Step 20 to 50: -100.0 pp, 95% CI [-100.0, -100.0].
- Cost: mean input tokens per task 1216 / 3344 / 9871.
- Latency per task 2.01s / 1.11s / 2.43s; model calls per task 1.00 in every core condition.
- AST accuracy by domain, 5 to 50 tools: search 100% to 0%.

Reading of the evidence (rule-based from the numbers above; verify against the traces):

- Adding tools lowered accuracy by more than sampling noise. Whether that is the number of choices or the extra context length is decided by the padding arm below.
- The failure mix shifts towards choosing the wrong tool as the list grows, i.e. the loss is selection, not argument filling.

Traced failure case (task 27c74bb0, search; solved in every 5-tool run, failed in every 50-tool run).
Query: *Can you extract content from the Careers section of the website www.company.com in text format?*. Gold tool: `tavily-crawl`, gold arguments `{"url": "https://www.company.com", "categories": ["Careers"], "format": "text"}`.
50-tool run 1: called `tavily-extract` with `{"urls": ["www.company.com"], "format": "text", "categories": ["Careers"]}`; failure label **wrong_tool_same_domain**, gold tool at position 15 of 50. picked tavily-extract, expected ['tavily-crawl']
Description of the tool it picked: *A powerful web content extraction tool that retrieves and processes raw content from specified URLs, ideal for data collection, content analysis, and research tasks.*
Description of the gold tool: *A powerful web crawler that initiates a structured web crawl starting from a specified base URL. The crawler expands from that point like a tree, following internal links...*
Cause (write after reading the trace): _____

6. Limitations and four more weeks

- One model and one temperature: conclusions are about this model on this date, not about tool count in general. Single-step tasks only; no Pass@K or live MCP execution.
- Labels are the benchmark's. A "wrong tool in the same domain" may be a valid alternative that the labelled `similar_tools` list misses, which inflates same-domain errors; the traced case and the 20-task audit are the guard.
- Distractors come from other domains and are mostly easy to dismiss, so the 50-tool condition is gentler than a marketplace of near-duplicate tools. Parameter matching is lenient (containment and token F1), as in the benchmark. The public benchmark may be in the model's training data.
- **With four more weeks:** several models and sizes; distractors chosen by embedding similarity to the gold tool; a retrieval baseline that shows the top-k tools; multi-step chains built by composing the labelled calls; live MCP execution for Pass@K; failure labels audited by a second person.