

Task

Hint

AI Assistant

56:52

QUESTION 1 OF 5

First create a redis database container called `redis`, image `redis:alpine`.

if you are unsure, check the hints section for the exact commands.

Check

Next →

redis container running?

Terminal 1

+

Click-Counter

Stop Lab

~ → docker run -d --name redis redis:alpine
3941bdcc85e708505e25f5340a9e619a7639510504af88d63dc77422a9873b8
~ →

Task

Hint

AI Assistant

54:53

QUESTION 2 OF 5

Next, create a simple container called `clickcounter` with the image `kodekloud/click-counter`, link it to the `redis` container that we created in the previous task and then expose it on the host port `8085`.

The `clickcounter` app run on port `5000`.
if you are unsure, check the hints section for the exact commands.

Check

Next →

clickcounter exposed on the correct HostPort?
clickcounter linked to the redis container ?

Terminal 1

+

Click-Counter

Stop Lab

~ → docker run -d --name=clickcounter --link redis:redis -p 8085:5000 kodekloud/click-counter
Unable to find image 'kodekloud/click-counter:latest' locally
latest: Pulling from kodekloud/click-counter
540db60ca938: Pull complete
a7ad1a75a999: Pull complete
37ce6546d5dd: Pull complete
ec9e91bed5a2: Pull complete
767433e1b0b0: Pull complete
156f000493cb: Pull complete
3fe82d8a2401: Pull complete
4a41f7c94204: Pull complete
473063430a4f: Pull complete
452c68a16ccd: Pull complete
Digest: sha256:530e4532a718e8f5cbda05844a6c0638ebe8898fa4c4307ee6afb5dd5d1f213db
Status: Downloaded newer image for kodekloud/click-counter:latest
8fbb7f6208523edfc65eb244e99d787ad39837669d3a88fa72df19e666b7fdb1
~ →

Task

Hint

AI Assistant

46:01

QUESTION 4 OF 5

Let's clean up the actions carried out in previous steps. Delete the `redis` and the `clickcounter` containers.

Check

Next →

clickcounter container deleted?
redis container deleted?

Terminal 1

+

Click-Counter

Stop Lab

~ → docker ps
CONTAINER ID IMAGE NAMES COMMAND CREATED STATUS PORTS
8fbb7f620852 kodekloud/click-counter "Flask run" 8 minutes ago Up 8 minutes 0.0.0.0:8085->5000/tcp, :::8085->5000/tcp clickcounter
3941bdcc85e redis:alpine "docker-entrypoint.s..." 10 minutes ago Up 10 minutes 6379/tcp redis
~ → docker stop 8f 39
8f
39
~ → docker rm 8f 39
8f
39
~ →

Task

Solution

AI Assistant

30:02

QUESTION 5 OF 5

Create a `docker-compose.yml` file under the directory `/root/clickcounter`. Once done, run `docker-compose up`.

The compose file should have the exact specification as follows -

1. `redis` service specification - Image name should be `redis:alpine`.

2. `clickcounter` service specification - Image name should be `kodekloud/click-counter`, app is run on port `5000` and expose it on the host port `8085` in the compose file.

Check

Next →

Terminal 1

+

Click-Counter

Stop Lab

~/clickcounter → cat docker-compose.yml
version: '3.8'

services:
 redis:
 image: redis:alpine
 restart: always

 clickcounter:
 image: kodekloud/click-counter
 ports:
 - "8085:5000"
 depends_on:
 - redis
 restart: always

~/clickcounter → docker-compose up -d
[*] Running 2/3
✓ Network clickcounter_default Created 0.1s
✓ Container clickcounter-redis-1 Started 0.5s
Container clickcounter-clickcounter-1 Starting 0.5s
Error response from daemon: driver failed programming external connectivity on endpoint clickcounter-clickcounter-1 (ec7bb0b0b6e64ea5c15519086676c9dfac55c01fc0329cb7198fa8fb61038): Bind for 0.0.0.0:8085 failed: port is already allocated

Task

Hint

Solution

AI Assistant

57:32

QUESTION 2 OF 6

What is the `ENTRYPOINT` configured on the `mysql` image?

NO ENTRYPOINT CONFIGURED

mysqld

/usr/local/bin

docker-entrypoint.sh

Terminal 1

```
~ → ls
Dockerfile-mysql      Dockerfile-ubuntu    app
Dockerfile-python     Dockerfile-wordpress

~ → cat Dockerfile-mysql | grep -i entry
RUN mkdir /docker-entrypoint-initdb.d
COPY docker-entrypoint.sh /usr/local/bin/
RUN ln -s /usr/local/bin/docker-entrypoint.sh /entrypoint.sh # backwards compat
ENTRYPOINT ["docker-entrypoint.sh"]

~ →
```

Task

Hint

Solution

AI Assistant

56:19

QUESTION 3 OF 6

What is the `CMD` configured on the `wordpress` image?

docker-entrypoint.sh

wordpress

apache2-foreground

Terminal 1

```
~ → ls
Dockerfile-mysql      Dockerfile-ubuntu    app
Dockerfile-python     Dockerfile-wordpress

~ → cat Dockerfile-wordpress | grep -i cmd
CMD ["apache2-foreground"]

~ →
```

Task

Hint

Solution

AI Assistant

55:00

QUESTION 4 OF 6

Preview only — answers can't be changed or retried here.

What is the final command run at startup when the `wordpress` image is run. Consider both `ENTRYPOINT` and `CMD` instructions

docker-entrypoint.sh

docker-entrypoint.sh wordpress

docker-entrypoint.sh apache2-foreground

Terminal 1

```
~ → ls
Dockerfile-mysql      Dockerfile-ubuntu    app
Dockerfile-python     Dockerfile-wordpress

~ → cat Dockerfile-wordpress | grep -i cmd
CMD ["apache2-foreground"]

~ → cat Dockerfile-wordpress | grep -i entry
COPY docker-entrypoint.sh /usr/local/bin/
ENTRYPOINT ["docker-entrypoint.sh"]

~ →
```

☐ ☐ ☐ ☐ ☒ ☐

11

Run it in detached mode.

Next →


```

~ ➔ ls
Dockerfile-mysql      Dockerfile-ubuntu    app
Dockerfile-python     Dockerfile-wordpress

~ ➔ cat Dockerfile-ubuntu | grep -i cmd
CMD ["bash"]

~ ➔ docker run -d ubuntu sleep 1000
a3b94827850b2944e42f1de46f26c03ebfd7a30af1d998ecb82516851f4136fa

~ ➔

```