The Gi1 Prime Card: printer brief

Send this page with FRONT.png, BACK.png, and both FOIL plates.





Size and files

Item	Spec
Trim size	88.9 x 50.8 mm (3.5 x 2 in). Art is 2912 x 1673 px, about 830 dpi.
Bleed	The *_bleed files add 3 mm each side (colour extends, nothing important there).
Safe zone	3 mm inside the trim. The thin gold frame sits 2.2 mm in. Ask for a precise die cut or laser cut.
Corners	3 mm radius, rounded.
Colour	Navy base. Please match the navy and the gold to the proof. Ask for a hard proof before the full run.

Recommended build (best to good)

Option	Material and finish
A. Premium	0.8 mm brushed black or navy stainless steel, laser engraved plus gold PVD fill, NFC inlay under the TAP mark.
B. Strong and cheaper	600 gsm soft-touch laminated card, navy matte. Hot-foil GOLD using the foil plates. Spot UV on the logo and "Gi1 Prime App". Rounded corners.
C. Budget	400 gsm matte laminated card, metallic gold ink look (no foil).

Foil plates

Files named FOIL_FRONT and FOIL_BACK: black = hot gold foil, white = no foil. Use as the foil layer. The logo is printed in colour with a foil frame; QR stays dark blue on white (do not foil the QR).

NFC chip

Chip	NTAG215 or NTAG216 (works on every phone). Keep it away from metal: use a ferrite layer if the card is metal.
Position	Behind the "TAP OR SCAN" mark, top right of the front.
Content	One URL record. We write it ourselves (see README step 4).

QR

The QR on the back is final. Do not resize below 22 mm. Keep the white quiet margin. Test-scan the proof with two phones.