

ECR-2 Counter-Current Simulation Report

Frozen calculation snapshot for preliminary engineering review

RUN #845

WARNING / PRELIMINARY ENGINEERING

Calculated 24 Aug 2026, 4:21:28 PM | Revision 8 | IIX-ecr-simulator v2.1.0
Three accepted preliminary D/H trials; two smaller trials dependency-blocked.

Executive result

Run #845 used the current Stage 4 Process Design basis: 50 deg C extraction temperature, RRBO composition 85/5/5/5 wt%, RRBO feed 3,448 kg/h, NMP feed 4,024 kg/h, and a 10 mol% hydrocarbon-only raffinate aromatic target.

Interpretation

The run is warning-status because $D = 0.30$ m and $D = 0.45$ m fail the K&H 1995 holdup physical-validity check. $D = 0.60$ m, 0.80 m, and 1.00 m each converged and passed mass balance.

Best preliminary trial (not a final selection)

Diameter	0.60 m
Required active height	0.279375 m
RRBO recovery	90.3339%
Raffinate aromatics	9.9989% hydrocarbon-only mol fraction
BVP / mass balance	converged / passed

ECR-2 generates the complete feasible preliminary (D,H) set. It does not select a final diameter.

1. Frozen inputs and calculation basis

Frozen Run #845 input snapshot

Operating temperature	50 deg C (Stage 4 Extraction Temperature)
RRBO feed	3448.000 kg/h
NMP feed	4024.000 kg/h
S/O ratio	1.167053 mass basis
Phase configuration	NMP continuous / RRBO dispersed
Theoretical stages, N_T	1 (calculated)
Raffinate target	10 mol% aromatics, hydrocarbon-only physical outlet basis

RRBO feed composition

Component	Mass fraction	Feed flow
Saturates	85 wt%	2930.800 kg/h
Mono-aromatics	5 wt%	172.400 kg/h
Di-aromatics	5 wt%	172.400 kg/h
Poly-aromatics	5 wt%	172.400 kg/h
Total aromatics	15 wt%	517.200 kg/h
RRBO total	100 wt%	3448.000 kg/h

ECR-2 generated sizing basis

Specific agitation psi	0.1000 W/kg
d32 route	DIRECT_TURBULENCE_D32_PRELIMINARY
d32 result	0.976126 mm (C = 0.39)
C sensitivity	0.901 to 1.076 mm d32
Diameter trials	0.30, 0.45, 0.60, 0.80, 1.00 m
Height method	Progressive full-BVP trials with conservative upper bracket endpoint
Numerical mesh	Maximum delta-z = 0.25 m; physical height is independent of mesh size

Equation basis: $d_{32} = C * (\gamma / \rho_c)^{0.6} * \epsilon^{(-0.4)}$, with $\epsilon = \text{psi} = 0.1 \text{ W/kg}$. The direct-turbulence d32 is preliminary, not pilot validated, and separate from K&H 1996.

2. Diameter and height search

Generated diameter trials

Each diameter is evaluated independently. Every physical-height trial reruns the full counter-current BVP; no local NRTL, holdup, d32, or transfer value is reused between height trials.

Diameter	Trial status	Required H	Product aromatics	Cells	Iter.	F evals	Total balance
0.30 m	DEPENDENCY BLOCKED	NOT CALCULATED	—	—	0	0	—
0.45 m	DEPENDENCY BLOCKED	NOT CALCULATED	—	—	0	0	—
0.60 m	FEASIBLE PRELIMINARY	0.279375 m	9.9989%	2	11	232	2.5074e-9 kg/h
0.80 m	FEASIBLE PRELIMINARY	0.385625 m	9.9984%	2	11	232	2.4026e-9 kg/h
1.00 m	FEASIBLE PRELIMINARY	0.412500 m	9.9999%	2	11	232	1.3630e-8 kg/h

Height-sizing method

For accepted trials, the target bracket is refined until the product-quality condition is met. The conservative upper bracket endpoint is selected as the required active extraction height. The selected heights below are physical equipment heights, not numerical cell counts or delta-z values.

D (m)	Selected H (m)	Bracket / selection note
0.60	0.279375	Target bracket refined to [0.2788, 0.2794] m; conservative upper bound selected.
0.80	0.385625	Target bracket refined to [0.3850, 0.3856] m; conservative upper bound selected.
1.00	0.412500	Target bracket refined to [0.4119, 0.4125] m; conservative upper bound selected.

3. Accepted BVP calculations

Accepted preliminary trial diagnostics

The following BVP results satisfy convergence and total mass-balance acceptance for the individual diameter trial. They remain preliminary and are not release-eligible.

D = 0.60 m | H = 0.279375 m

Product aromatics	9.9989% (target 10 mol%)
BVP status	converged; mass balance passed
Solver diagnostics	11 iterations; 232 function evaluations; final residual norm 1.3766e-12
Total mass balance	2.5074e-9 kg/h
RRBO recovery	90.3339%

D = 0.80 m | H = 0.385625 m

Product aromatics	9.9984% (target 10 mol%)
BVP status	converged; mass balance passed
Solver diagnostics	11 iterations; 232 function evaluations; final residual norm 1.0331e-12
Total mass balance	2.4026e-9 kg/h
RRBO recovery	89.7098%

D = 1.00 m | H = 0.412500 m

Product aromatics	9.9999% (target 10 mol%)
BVP status	converged; mass balance passed
Solver diagnostics	11 iterations; 232 function evaluations; final residual norm 4.1178e-12
Total mass balance	1.3630e-8 kg/h
RRBO recovery	89.5699%

RRBO recovery calculation

RRBO recovery = (Saturates + Mono-aromatics + Di-aromatics + Poly-aromatics in raffinate) / RRBO feed x 100. NMP is excluded from RRBO recovery.

Diameter	RRBO raffinate	RRBO transferred to extract	RRBO recovery
0.60 m	3114.712 kg/h	333.288 kg/h	90.3339%
0.80 m	3093.196 kg/h	354.804 kg/h	89.7098%
1.00 m	3088.370 kg/h	359.630 kg/h	89.5699%

4. Outlet composition and component calculations

Accepted raffinate outlet component flows

Component order is Saturates / Mono-aromatics / Di-aromatics / Poly-aromatics / NMP. Product-quality aromatics are calculated on the hydrocarbon-only physical raffinate basis; NMP is excluded from both numerator and denominator.

Component	Feed kg/h	Raffinate kg/h	Extract kg/h
Saturates	2930.800	2694.199	236.601
Mono-aromatics	172.400	134.974	37.426
Di-aromatics	172.400	138.984	33.416
Poly-aromatics	172.400	146.555	25.845
NMP	4003.880	31.109	3972.771

D = 0.60 m product quality

9.9989% aromatics (hydrocarbon-only)

Component	Feed kg/h	Raffinate kg/h	Extract kg/h
Saturates	2930.800	2675.535	255.265
Mono-aromatics	172.400	133.799	38.601
Di-aromatics	172.400	138.097	34.303
Poly-aromatics	172.400	145.765	26.635
NMP	4003.880	32.408	3971.472

D = 0.80 m product quality

9.9984% aromatics (hydrocarbon-only)

Component	Feed kg/h	Raffinate kg/h	Extract kg/h
Saturates	2930.800	2671.283	259.517
Mono-aromatics	172.400	133.546	38.854
Di-aromatics	172.400	137.921	34.479
Poly-aromatics	172.400	145.620	26.780
NMP	4003.880	32.849	3971.031

D = 1.00 m product quality

9.9999% aromatics (hydrocarbon-only)

5. Warnings, acceptance and release status

Run-level status

Overall run status	WARNING
Governed transfer values	UNAVAILABLE
Release status	NOT_RELEASE_ELIGIBLE

Primary dependency blocker

The $D = 0.30$ m and $D = 0.45$ m initial BVPs are blocked because K&H 1995 returns $\phi_{\text{raw}} = 10.4189$, which is physically inadmissible because holdup must be below 1. The simulator fails closed and does not clamp or substitute the value.

Why governed transfer output is unavailable

The accepted local transfer arrays are preliminary solver results only. The direct-turbulence d32 route and local K&H transfer physics are not pilot validated or release eligible. In addition, the primary/global BVP is dependency-blocked by the smaller diameter trial. Therefore the report retains diagnostic data for accepted trials but does not present governed transfer performance as a final design result.

Additional warnings

- NRTL at 50 deg C is outside its calibrated range; equilibrium targets are extrapolated pending validation.
- Interfacial tension uses an unchanged 70 deg C source anchor at the selected 50 deg C condition under a preliminary constant-over-range basis.
- Physical RRBO molecular weights and SN300 EPD tabular values are assumed/provisional.
- NMP purity is retained as a physical plant-boundary input; canonical fresh NMP is used for the C2 thermodynamic coordinate.
- $d_{32} = 0.976$ mm is DIRECT_TURBULENCE_D32_PRELIMINARY and must not be attributed to K&H 1996.
- Sulfur/DBT prediction is not implemented and must not be inferred from aromatic-transfer results.

6. Engineering interpretation

Summary of calculated results

Run #845 is a preliminary forward-model evaluation on the current Stage 4 feed basis. The feasible preliminary design set returned by the generated diameter search is:

Diameter	Required physical height	RRBO recovery	Raffinate aromatics
0.60 m	0.279375 m	90.3339%	9.9989% mol fraction
0.80 m	0.385625 m	89.7098%	9.9984% mol fraction
1.00 m	0.412500 m	89.5699%	9.9999% mol fraction

Use limitation

These results are suitable for preliminary engineering review and comparison of generated diameter/height trials only. The simulator does not select a final diameter, does not establish a release-grade transfer design, and does not provide sulfur or DBT prediction.

The complete frozen source for this report is ECR-2 calculation Run #845, Revision 8. Any change to Stage 4 temperature, feed, composition, solvent ratio, or governed evidence requires a new simulation run and a new report.