

Theoretical-stage comparison

Stage 2 | All product targets | Existing saved calculation

MINIMUM SAVED ACCEPTED N_t: 4

Meets the original saved targets below. This is not a determination of economic optimum.

N _t	Recovery ≥85%	NMP ≤20 wt%	Saturates ≥92.5 wt%	Total arom. ≤7 wt%	Polar arom. ≤0.5 wt%	Sulfur* ≤1,500 ppm	Numerical checks	Saved acceptance
1	91.32 ✓	11.96 ✓	89.57 ×	9.33 ×	1.10 ×	2,399.6 ×	PASS	NOT ACCEPTED
2	88.81 ✓	9.98 ✓	91.41 ×	7.87 ×	0.71 ×	1,834.9 ×	PASS	NOT ACCEPTED
3	87.63 ✓	9.12 ✓	92.31 ×	7.18 ×	0.51 ×	1,563.9 ×	PASS	NOT ACCEPTED
4	87.00 ✓	8.68 ✓	92.80 ✓	6.81 ✓	0.38 ✓	1,414.3 ✓	PASS	ACCEPTED
5	86.64 ✓	8.45 ✓	93.09 ✓	6.61 ✓	0.30 ✓	1,324.5 ✓	PASS	ACCEPTED
6	86.43 ✓	8.31 ✓	93.26 ✓	6.50 ✓	0.24 ✓	1,267.2 ✓	PASS	ACCEPTED
7	86.30 ✓	8.22 ✓	93.37 ✓	6.43 ✓	0.20 ✓	1,228.8 ✓	PASS	ACCEPTED
8	86.22 ✓	8.17 ✓	93.44 ✓	6.40 ✓	0.17 ✓	1,201.9 ✓	PASS	ACCEPTED
9	86.16 ✓	8.14 ✓	93.48 ✓	6.38 ✓	0.14 ✓	N/C	FAIL	NOT ACCEPTED
10	86.13 ✓	8.12 ✓	93.52 ✓	6.37 ✓	0.12 ✓	1,167.9 ✓	PASS	ACCEPTED

✓ PASS × FAIL N/C Not calculable

BASIS Recovery is NMP-free hydrocarbon recovery. Saturates and aromatics are wt% on an NMP-free raffinate basis; NMP is wt% on a total-raffinate basis. Values are rounded for display; indicators reproduce the saved checks.

* SULFUR Model-predicted; not independently demonstrated sulfur compliance.

ACCEPTANCE N_t = 9 failed numerical checks; sulfur is not calculable. Product-target passes alone do not establish acceptance.

TARGETS Original saved limits are shown—not the later discussed >93 wt% saturates / <1,200 ppm sulfur scenario.