PRODUCT REFERENCE

YP-Raksha Gateway and Browser AI Guard Product Datasheet

Capabilities, interfaces, platform support, data handling and prerequisites

Document information

Version 1.0 | source-derived planning pack

Prepared 24 October 2026

Audience Enterprise architecture, security and operations teams

Release status Validate against the selected product release before procurement or production use

Product capability and sizing statements are labelled by evidence and assumption. Confirm release-specific support and commercial terms with the product owner.

Contents and document index

Section page numbers include the cover page. Headings are listed in reading order.

Product summary 3
Product composition 3
Common deployment use cases 3
Capability overview 4
Interfaces and request types 5
- Gateway routes 5
- Request families 5
- Authentication patterns 5

Provider and integration coverage 5
Data and persistence 6
Security and deployment model 6
Platform support matrix 6
Capacity and service level statement 7
Deployment prerequisites 7
Product boundaries and confirmation register 7
References 8

Product: YP-Raksha Gateway and Browser AI Guard

Audience: enterprise architecture, information security, infrastructure, application and procurement teams

Document status: product capability reference based on the current repository; release-specific support and commercial terms require confirmation

Related documents: Technical Documentation; On-Premises Deployment Architecture for DC, DR and UAT

Product summary

YP-Raksha is a self-hostable platform for governing application-to-model traffic and browser-based use of AI services. The YP-Raksha Gateway sits between approved applications and configured model endpoints. It provides a common API surface, authentication, policy enforcement, provider selection, usage controls and operational records. Browser AI Guard steers selected browser traffic through a local endpoint proxy or an optional internal shared proxy, evaluates configured rules and reports policy events to the Gateway.

The platform can be deployed in bank-controlled infrastructure. Residency is an architecture and operations outcome: provider, telemetry, email, update, licensing and support paths must use internal destinations or be disabled, and network egress must be enforced at the bank boundary. See the companion architecture document for the 120,000-endpoint reference design and verification process.

Product composition

Component	Function	Deployment and responsibility
YP-Raksha Gateway	Serves the administration UI, management APIs, inference APIs, integrations, policy and observability routes	Container or Kubernetes deployment on bank-operated Linux infrastructure; production ingress, persistence, secrets and HA are platform-owner responsibilities
Gateway core	Normalizes requests, selects configured provider/model routes, invokes provider adapters and returns model results	Runs within Gateway process; model execution is remote to a configured provider endpoint, including a bank-hosted endpoint in a sovereign design
Browser AI Guard endpoint agent	Provides local proxy/PAC steering, policy evaluation, health/heartbeat and event/configuration exchange	Packaged endpoint agent exists for Windows and macOS; deploy through the bank endpoint-management system and validate release-specific OS versions
Optional shared Guard proxy	Provides centrally managed proxy-mode inspection for selected network/browser traffic	Separate internal service; deployment, identity mapping, throughput and HA require independent validation
ConfigStore	Stores configuration, workspace identities, roles, virtual keys, provider/model configuration and related settings	Relational database layer; PostgreSQL is the recommended production planning baseline in this pack
LogsStore	Stores and aggregates inference, MCP, audit and Browser AI records	Relational database layer; define payload capture, access, retention, archival and backup before production
Optional supporting services	Cache, vector store, metrics/tracing, object store, email and connectors	Choose bank-operated equivalents for a no-egress environment; enable only the services needed by the approved design

Common deployment use cases

- **Governed internal AI access:** internal applications authenticate to the Gateway with virtual keys and use approved private model endpoints.

- **Model consolidation:** applications use a shared gateway API while the platform team configures one or more provider adapters and routing rules.
- **Usage administration:** platform owners assign keys to users, teams, customers or business units and apply configured budgets, rate limits and access profiles.
- **Browser AI policy:** endpoint or shared-proxy traffic to configured AI destinations is evaluated against browser guard rules and policy settings.
- **Operational review:** administrators review Gateway, audit, MCP and Browser AI records and monitor internal health and metrics endpoints.
- **MCP tool governance:** where enabled, administrators manage MCP connections, tool groups, sessions and related credentials.

These are functional patterns, not a statement that every provider implements every endpoint or that every browser/VDI combination is certified.

Capability overview

Capability area	Product function	Configuration or scope note
Model API gateway	OpenAI-compatible inference routes and provider-specific pass-through routes	Request/response feature coverage depends on the selected provider adapter and model
Provider adapters	Adapter packages cover commercial, cloud and self-hosted provider families	Credentials and outbound destinations are configured by administrators; use private endpoints for strict residency
Model selection	Configured models, provider key selection, routing rules, fallback and circuit-breaker components	Routing behavior and fallback targets must be reviewed against data classification and locality requirements
Identity and access	Users, teams, customers/business units, virtual keys, system roles and custom RBAC	Resource-level operations and section grants are enforced in the application; integrate bank identity/SCIM where configured
Usage governance	Budgets, rate limits, access profiles and audit records	Limits are configuration-driven; confirm enforcement scope in release acceptance tests
Gateway guardrails	Optional guardrail plugin and policy integrations on inference traffic	Enabled checks, failure behavior and third-party/model dependencies must be documented per deployment
Browser AI Guard	Target websites, rule management, endpoint fleet, policy configuration and event/log views	Rule actions are BLOCK, REDACT or WARN; unmatched traffic follows configured policy behavior
Prompt and skills repositories	Managed prompt/skill content and related workspace functionality	Access scope follows configured role and workspace grants
MCP Gateway	MCP clients/servers, tool groups, sessions and OAuth-related flows	Optional feature; each remote MCP destination is an egress path and must be approved or disabled
Observability	Health endpoint, Prometheus metrics, application logs, audit/log views and optional tracing/connectors	Keep scrape targets and exporters internal for a sovereign deployment
Deployment packaging	Docker/Compose examples and Kubernetes Helm charts	Examples contain defaults intended for development/evaluation; replace public endpoints and sample credentials before bank use

Interfaces and request types

Gateway routes

Route family	Typical purpose
`/v1/*`	Inference and related API operations
`/api/*`	Administration, governance, configuration, reporting and Browser AI control plane
`/openai/*`, `/anthropic/*`, `/genai/*`, `/bedrock/*`, `/cohere/*`, `/cursor/*`, `/litellm/*`, `/langchain/*`, `/pydanticai/*`	Provider/client-compatible pass-through integration surfaces present in the server
`/ws`, `/v1/realtime`	WebSocket and realtime transports where supported by the selected route/provider
`/health`	Service health check
`/metrics`	Metrics endpoint; restrict to internal scrapers
`/pprof`	Development profiling route; do not expose in production

Routes are examples from the implementation surface, not a promise that every operation is enabled for every tenant or provider. See the technical manual and release API definitions for exact request schemas.

Request families

Provider code includes adapter implementations for combinations of chat/completions, text completions, responses, embeddings, reranking, image generation, speech, transcription, OCR, video, batch, file, container and realtime operations. The provider capability matrix is not uniform. Validate each application's required operation, streaming behavior, upload limits, model parameters, error mapping and cancellation behavior with its selected provider before production.

Authentication patterns

- Inference clients use a Gateway virtual key or an administrator-configured provider key through supported request authentication headers.
- Administrators use dashboard sessions and role-based authorization.
- Browser Guard agents use the configured fleet secret and agent identity path, separate from an interactive dashboard session.
- Service-to-service identity, SSO/SCIM, TLS termination and key rotation depend on the bank deployment configuration.

Provider and integration coverage

The repository contains provider adapter packages for: Anthropic, Azure, Amazon Bedrock, Bedrock Mantle, Cerebras, Cohere, DeepSeek, ElevenLabs, Fireworks, Gemini, Groq, Hugging Face, Mistral, Nebius, Ollama, OpenAI, generic OpenAI-compatible endpoints, OpenCode, OpenRouter, Parasail, Perplexity, Replicate, Runware, Runway, SGL, Vertex, vLLM and xAI.

Adapter presence indicates an implementation path; it does not imply feature parity, a current commercial certification, a vendor support agreement, or that all request families are implemented. In a bank deployment, configure only internal/private destinations if data must remain within the bank and India. Review per-provider capabilities and network destinations for the exact release.

Data and persistence

Record family	Examples	Design treatment
Configuration and identity	Users, roles, workspace objects, virtual keys, providers, models, routing and settings	Restrict write access to administrators; back up consistently with secrets and encryption-key recovery procedures
Inference records	Request metadata, usage and, depending on settings, request/response content	Treat as sensitive; decide payload logging, redaction, retention and deletion before rollout
Browser AI records	Agent inventory/heartbeat, detected events, policy verdicts, search and event details	Treat captured prompts or content as sensitive; constrain field access and retention
MCP records	Tool/server configuration, sessions and logs	Treat tool input/output and credentials as sensitive; approve remote MCP destinations individually
Audit records	Mutating management actions and actor/context metadata	Retain under bank policy and ensure audit storage is included in backup and review controls
Metrics and traces	Operational service and request measurements; traces when configured	May contain identifiers or attributes; inspect configuration and keep collectors/exporters internal
Attachments and packages	Files or Guard distribution artifacts where used	Restrict object-store access; use internal encrypted storage and verify backup/retention behavior

The code supports PostgreSQL, MySQL and SQLite storage drivers in the relevant layers. This reference architecture selects PostgreSQL for production planning. A specific enterprise support or certification matrix for database versions must be confirmed for the release.

Security and deployment model

The Gateway is commonly placed behind an internal load balancer or WAF, with the application process separated from user and database networks. Use TLS for client-to-ingress and service/database links according to bank standards, trusted proxy allow-lists when forwarding headers, least privilege for management roles, strong secrets, encrypted storage, key rotation and audited administrative changes.

The application includes session-cookie controls, authentication throttles, RBAC checks, audit middleware, optional database-secret encryption and Guard fleet authentication controls. These are components of a control set; they do not by themselves establish a bank security certification or guarantee a particular regulatory posture. Review the exact release, threat model, configuration and operational evidence with bank security owners.

A zero-egress design requires the bank to disable external providers/exporters/connectors, configure private services, use internal DNS/NTP/IAM/SMTP and image/package mirrors, and block all unapproved outbound traffic at the network layer. See the deployment architecture for flows and verification steps.

Platform support matrix

The table separates implementation/package evidence from formal version certification. Exact release builds must be checked before procurement or rollout.

Area	Evidence and current statement	Validation required
Gateway host	Container and Helm deployment paths are present for Linux-based infrastructure	Match the bank Kubernetes/container platform, OS, ingress, database and storage versions to the product release

Area	Evidence and current statement	Validation required
Browser Guard on Windows	Windows executable and installer build paths exist	Confirm Windows editions/builds, endpoint-management deployment, certificate installation and update behavior
Browser Guard on macOS	macOS application/package build paths exist	Confirm exact macOS releases, signing/notarization, permissions and certificate deployment
Browser Guard on Linux	A Linux endpoint installer is not documented in the repository	Do not include Linux endpoints in the supported Guard-agent population without separate release evidence
Chrome and Edge	PAC/system proxy and OS certificate trust are used by the design	Candidate browsers only; test exact enterprise versions, policy and update channel
Firefox	No versioned certification matrix is documented	Candidate only; validate PAC and browser-specific CA trust distribution
Safari	No versioned certification matrix is documented	Candidate only on macOS; validate system proxy and CA behavior
VDI	No named VDI vendor certification matrix is documented	Citrix, VMware Horizon, Azure Virtual Desktop and other VDI targets require UAT for persistent/non-persistent identity, agent lifecycle, proxy and certificate handling

Do not describe the browser or VDI candidates as certified until the relevant version-level test evidence and support statement exist.

Capacity and service level statement

This pack contains a planning envelope for 120,000 managed endpoints, derived from explicit endpoint activity, event-rate and inference-rate assumptions. It is not a product maximum, measured benchmark, performance guarantee or service-level commitment. Private model CPU/GPU capacity is not included in Gateway sizing. Payload capture, streaming, large uploads, retention, provider latency, database I/O and Guard heartbeat/event behavior can change required resources.

Commercial licensing, support hours, warranty, SLA, release lifecycle, security certification and product-version entitlements are not established by the repository material used here. Obtain these terms separately from the product owner before procurement.

Deployment prerequisites

- Bank-operated container/Kubernetes platform and internal image/Helm repository for production deployment.
- Production database topology, storage, backup and restore plan; PostgreSQL is the reference planning choice.
- Internal DNS, NTP, certificate authority, secrets management, identity and optional SMTP relay.
- Private model service(s) reachable from the Gateway over approved internal routes.
- Internal log, metrics and tracing collectors if enabled; endpoint agents must reach the internal Gateway ingress.
- Endpoint-management method for installing Guard packages and distributing proxy/certificate configuration.
- Firewall and DNS policy that blocks direct access to unapproved public AI, telemetry and package destinations.
- Separate UAT identities, secrets, database and synthetic or masked test data.

Product boundaries and confirmation register

The following points must be settled for the selected release and bank design; this document does not invent them:

Item	Current status in source material	Required evidence/decision
Browser/VDI version certification	No complete versioned matrix found	Product-owner compatibility statement plus bank UAT results
Certified endpoint maximum or benchmark	No independently measured result included	Agreed workload profile and signed load-test report
Database version certification	Drivers are present; version certification not stated	Product support matrix and bank DBA approval
Linux endpoint Guard package	Not documented	Product-owner confirmation before including in endpoint count
Cross-site automatic DR guarantee	Not implied by application cluster support	Bank-operated database/infra design and exercised DR evidence
Offline licence activation/update	Not confirmed by repository evidence	Product-owner confirmation and successful disconnected UAT
Commercial SLA, support and certification	Not included in source files	Contract and release documentation

References

- Technical Documentation
- On-Premises Deployment Architecture
- Server and Deployment Documentation
- Administrator Guide
- Repository source architecture note