CLIENT PACK · DOCUMENT 00

# Documentation index

Every document to hand to the client

Audience: the client project owner. Hand over this folder as the full set.

This pack describes the product as it is built: the UnifAI website, the Gateway Guard laptop agent, and the YP-Raksha browser extension. Sample names, emails, and passwords are examples for training. Replace them with your company values. Do not reuse the sample passwords.

Give the client this folder. Each PDF stands alone. Sample passwords inside are for training and must be replaced.

| | | |
|---|---|---|
| 00_Documentation_Index.pdf | Project owner | List of the pack and who should read which file. |
| 01_Website_User_Manual.pdf | All website users | Sign up, every login type, sign out, menus, and how to fill the main screens. |
| 02_Administrator_Operations_Manual.pdf | Admins | Users, roles, virtual keys, providers, Browser AI rules, uninstall key. |
| 03_Technical_Reference.pdf | Technical team | Architecture, ports, authentication, RBAC, laptop paths. |
| 04_Process_Flows_and_Sample_Data.pdf | Trainers | Join, reset, block, warn, redact, API key, install, leaver, investigation. |
| 05_Gateway_Guard_and_YP-Raksha.pdf | Employees and IT | What a correct install looks like, and how uninstall works. |
| 06_Every_Website_Screen.pdf | Admins and trainers | Every menu: what to do, what it connects to, and a filled example. |
| 07_Scope_Specification.pdf | QA & Auditors | Formal product scope, testable requirement statements, and verification criteria. |
| 08_Enterprise_Connected_System_Flows.pdf | Architects, Admins & Leads | Master system flow, why each entity exists, how User-Team-Customer-Key-Providers connect, and full dashboard click-map. |
| 09_Non_Technical_Business_Guide.pdf | Executives & Business Owners | Plain English & everyday analogies guide: What work each part does, zero technical jargon, and manager cheat sheet. |

# How to read them

- Every PDF in this folder contains the same connection flow and every website section, with the inputs, how to use it, and how it connects.
- Project sponsor: this index, then document 04. Flow 0 is the order. Do not start at Flow 1.
- Every employee: document 01 and document 05.
- Administrators: document 02 section 1 is the same order as document 04 Flow 0. Document 06 is the field detail for every screen, including SMTP, Proxy, Alert Channels, MCP Auth Config, and Prompt Deployments.
- Technical team: document 03, including the extra paths in section 8.

## Product names used in this pack

| | |
|---|---|
| UnifAI | The website and the AI gateway. |
| Gateway Guard | The program installed on each laptop. |
| YP-Raksha | The browser extension Gateway Guard turns on. |

# Connection flow and every website section

Do the steps in this order. Logs stay empty until a provider and a virtual key exist. Sample values are for training.

| Order | Do this first |
|---|---|
| 1 | Settings → Security: save SMTP and confirm the test mail. |
| 2 | Settings → Client Settings. Leave Proxy off unless the server needs an office proxy. |
| 3 | Models → Model Providers, then Model Catalog. |
| 4 | Governance → Teams, Users, then Virtual Keys. |
| 5 | Routing Rules, Budgets & Limits, Pricing. Then Guardrails for API text. |
| 6 | One API call, then Observability → LLM Logs. |
| 7 | Browser AI: Target Websites, Guard Rules, Setup, then Guard Agents and Prompt Logs. |
| 8 | MCP Catalog, MCP Auth Config, and Tool Groups only if a tool server is required. |
| 9 | Prompt Repository, then Prompt Deployments. Skills Repository when you publish a skill. |
| 10 | Alert Channels after a budget or circuit breaker exists. Connectors when logs must leave the server. |

An API call connects like this: virtual key, then budget, then routing, then guardrails, then the model provider, then LLM Logs. A browser prompt connects like this: target website, then the laptop agent, then the guard rule, then Prompt Logs. That path does not use a virtual key.

## Do not mix these up

| Two things with similar names | Which one to use |
|---|---|
| Observability Dashboard and Adaptive Routing Dashboard | Observability shows cost and tokens. Adaptive Routing shows how calls are split across provider keys. |
| Guardrails Rules and Browser AI Guard Rules | Guardrails check API calls that use a virtual key. Guard Rules check prompts typed on public AI websites. |
| Settings → Proxy and Gateway Guard | Settings → Proxy is the office proxy for the server. Gateway Guard is the program on the laptop. |
| Settings → API Keys and Governance → Virtual Keys | API Keys are the vendor secrets. Virtual Keys are what applications send. |
| Connectors and Alert Channels | Connectors copy full logs. Alert Channels send one short notice for a budget or a circuit breaker. |
| MCP Library and MCP Catalog | The library is a template list. The catalog is the live server connection. |
| Users role and Allowed sections | The role is what the API allows. Allowed sections are which menus appear after login. |

## Website logins. There is one Sign In page. The role decides the menu.

| Login | Sample | After sign-in |
|---|---|---|
| admin | priya.admin / Priya#Admin24 | Every menu, including provider keys and Settings. |
| sub_admin | ravi.security / Ravi#Secure24 | Users, keys, logs, Browser AI. Not master provider keys. |
| user | anitha.user / Anitha#User24 | Only the allowed sections ticked on the user. |
| Custom role | meena.audit / Meena#Audit24 | Only the resources ticked on that role. |
| SCIM user | Created in Azure AD or Okta | Same Sign In. Inactive in the identity provider means disabled here. |
| Virtual key | Not a website login | Sent by an application as Authorization: Bearer. |

Password rule for every website account: at least 8 characters, one uppercase letter, one lowercase letter, one number, and one special character. A session lasts about 24 hours. Sign out from the account menu. Sign out does not stop Gateway Guard or YP-Raksha.

Sign-up is always role user. Open /signup with username, email, password, and confirm password. If SMTP is already tested, enter the 6-digit code. Status stays pending until an admin approves the user. Forgot password and forgot username are on the Sign In page. The code lasts 10 minutes.

# 1. Observability

## Dashboard

Open: /workspace/dashboard

### What this is used for

Shows company totals for API traffic: requests, tokens, cost, and latency.

### Inputs you fill

| Input | What you enter |
|---|---|
| Date range | Last 7 days |
| No create fields | This page is read-only |

### How to use it

Open it after at least one virtual-key call has succeeded. Read the cards. A high cost sends you to LLM Logs for that model or key.

### How it connects

Reads LLM Logs. Cost uses Pricing Overrides and Model Settings. Empty means Model Providers and Virtual Keys are not in use yet.

## LLM Logs

Open: /workspace/logs

### What this is used for

One row for every API call made with a virtual key.

### Inputs you fill

| Input | What you enter |
|---|---|
| Date | Today |
| Virtual key | Support bot — production |
| Model | gpt-4.1-mini |
| Status | success or error |

### How to use it

Filter, open a row, and read the prompt, answer, tokens, cost, and latency. Export if you need a sheet. Clear logs or recalculate cost only when an admin means to.

### How it connects

A row is written after Virtual Keys, Routing, Guardrails, and Model Providers finish a call. A 401 points at the provider key. A budget error points at Virtual Keys or Budgets & Limits.

## MCP Logs

Open: /workspace/mcp-logs

### What this is used for

One row for every tool call made through MCP Gateway.

### Inputs you fill

| Input | What you enter |
|---|---|
| Client | docs-server |
| Tool | search_docs |
| User | anitha.user |
| Time | Today |

### How to use it

Filter and open the row to see the tool arguments and the result.

### How it connects

Appears only after MCP Catalog is connected, MCP Auth Config is saved, a Tool Group allows the tool, and the feature flag mcp.tool_execution is on.

## Connectors

Open: /workspace/observability

### What this is used for

Copies logs and metrics to a system the company already runs.

### Inputs you fill

| Input | What you enter |
|---|---|
| Connector | Datadog, BigQuery, Kafka, Pub/Sub, New Relic, Prometheus, or OpenTelemetry |
| URL or site | The vendor endpoint |
| API key or dataset | The secret from that vendor account |

### How to use it

Add connector, paste the vendor values, save, and send one test chat. Confirm the same request in LLM Logs and in the vendor.

### How it connects

Source is LLM Logs and metrics. This does not send the short budget alerts. Those go to Alert Channels.

## Logs Settings

Open: /workspace/config/logging

### What this is used for

Chooses what API log text is stored and for how long.

### Inputs you fill

| Input | What you enter |
|---|---|
| Content logging | On for a pilot, off if prompts must not be stored |
| Retention days | 30 |

### How to use it

Set the two values and save. New LLM Log rows follow this. Old rows stay until retention deletes them.

### How it connects

Controls LLM Logs and the Observability Dashboard. It does not control Browser AI Prompt Logs.

# 2. Browser AI

## Overview

Open: /workspace/browser-ai?tab=overview

### What this is used for

Counts monitored sites, active rules, recent agents, and recent decisions.

### Inputs you fill

| Input | What you enter |
|---|---|
| No create fields | Read the counts after the other Browser AI tabs are filled |

### How to use it

Use it as the check that the rollout is alive. Zero monitored sites means Target Websites is empty. Zero agents means Setup has not reported a laptop.

### How it connects

Summarises Target Websites, Guard Rules, Prompt Logs, and Guard Agents.

## Target Websites

Open: /workspace/browser-ai?tab=targets

### What this is used for

The public AI sites the laptop is allowed to watch.

### Inputs you fill

| Input | What you enter |
|---|---|
| Domain | chatgpt.com |
| Platform name | ChatGPT |
| Host role | ui, chat, or file |
| Monitored | Yes |
| Block entire website | No |
| Status | MONITORED |

### How to use it

Add one row or import a CSV with those columns. Add the chat and file hosts when the vendor uses more than one domain. Pause with status PAUSED.

### How it connects

Gateway Guard downloads this list. A Guard Rule does nothing on a domain that is not here.

## Guard Rules

Open: /workspace/browser-ai?tab=rules

### What this is used for

What the laptop does when a prompt or upload on a target site matches.

### Inputs you fill

| Input | What you enter |
|---|---|
| Rule name | India PAN |
| Rule type | regex, or ai_bot typed in the screen |
| Pattern | [A-Z]{5}[0-9]{4}[A-Z] |
| Severity | CRITICAL, HIGH, or MEDIUM |
| Action | BLOCK, WARN, or REDACT |
| Warning message | Personal ID numbers cannot be sent to a public AI site. |

| Input | What you enter |
|---|---|
| Active | TRUE |

### How to use it

Create or import. BLOCK stops the send. WARN shows the message and sends the original. REDACT shows the message and sends the match as [REDACTED]. Test an ai_bot rule before Active is TRUE. AI bot rules cannot be imported.

### How it connects

Runs on text sent to a Target Website. The result is a Prompt Log. This is not Guardrails. Guardrails check API calls.

## Prompt Logs

Open: /workspace/browser-ai?tab=logs

### What this is used for

Every browser prompt the agent checked.

### Inputs you fill

| Input | What you enter |
|---|---|
| Date | Today |
| Action | Blocked, Warned, Redacted, Allowed, SiteBlocked, or Bot Answered |
| Search | The laptop hostname |

### How to use it

Filter and open the row. You see the prompt, the rule, the action, and the device.

### How it connects

Written by Gateway Guard after a Guard Rule runs. Match the hostname on Guard Agents.

## Search Logs

Open: /workspace/browser-ai?tab=search-logs

### What this is used for

Search queries the agent recorded, including private windows.

### Inputs you fill

| Input | What you enter |
|---|---|
| Engine | Google |
| Browser | Chrome, Edge, or Brave |
| Private window | Yes or no |
| Query | The text the employee searched |

### How to use it

Filter and open a row for the query and any result that was opened.

### How it connects

Same laptop agent as Prompt Logs. It is not an LLM Log.

## Setup

Open: /workspace/browser-ai?tab=setup

### What this is used for

Download the laptop package and publish Guard code updates.

### Inputs you fill

| Input | What you enter |
|---|---|
| Package | Gateway_Guard_Setup.exe for Windows, or the Mac package |

| Input | What you enter |
|---|---|
| Rebuild | Use Rebuild and Publish only after Guard code on the server changed |

### How to use it

Download the package and give it to IT. IT runs it once per laptop and leaves start at login checked.

### How it connects

The package installs Gateway Guard, which force-installs YP-Raksha and then appears under Guard Agents.

## Guard Agents

Open: /workspace/browser-ai?tab=agents

### What this is used for

Every laptop and every office proxy that has reported in.

### Inputs you fill

| Input | What you enter |
|---|---|
| Search | DESKTOP-EXAMPLE |
| Contact email | it@example.com |
| Uninstall key | A secret kept in the IT vault, not in email |

### How to use it

Confirm status active and a recent last-seen time. Remote uninstall moves the device to uninstall_pending, then uninstalled.

### How it connects

The agent appears only after Setup has run and the laptop can reach this server. Prompt Logs use the same hostname.

## Guard Insights

Open: /workspace/browser-ai?tab=telemetry

### What this is used for

Totals of allowed, blocked, warned, and redacted events per laptop.

### Inputs you fill

| Input | What you enter |
|---|---|
| No create fields | Read the totals, then open Prompt Logs for the loudest hostname |

### How to use it

Use a high Blocked count as a reason to open that laptop’s Prompt Logs before you edit the rule.

### How it connects

Adds up Prompt Logs. It does not change Guard Rules.

# 3. Models

## Model Providers

Open: /workspace/providers

### What this is used for

Attaches the company’s account at OpenAI, Anthropic, Azure, Bedrock, Gemini, or another vendor. Admin only for the secret.

### Inputs you fill

| Input | What you enter |
|---|---|
| Provider | OpenAI |
| Key name | openai-prod-1 |
| API key | The vendor key |
| Azure or Bedrock extras | Endpoint or cloud credentials, only if that form asks |

### How to use it

Add provider, paste the key, save. You may store more than one key for the same vendor. A keyless provider needs no key.

### How it connects

Model Catalog lists models from these keys. Routing sends calls here. The virtual key never contains this vendor key.

## Model Catalog

Open: /workspace/model-catalog

### What this is used for

The models UnifAI is allowed to offer.

### Inputs you fill

| Input | What you enter |
|---|---|
| Model | gpt-4.1-mini |
| Enabled | Yes for models under contract, no for the rest |

### How to use it

Search, enable, and disable. Open a model to see its price.

### How it connects

Fed by Model Providers. Virtual Keys and Routing Rules should name only enabled models.

## Budgets & Limits

Open: /workspace/model-limits

### What this is used for

A spend cap and a request rate on one model, separate from a virtual-key budget.

### Inputs you fill

| Input | What you enter |
|---|---|
| Model | gpt-4.1-mini |
| Budget | 500 |
| Rate | 60 requests per minute |

### How to use it

Open the model, set the ceiling, save. The first ceiling that is hit stops the call.

### How it connects

Checked with the Virtual Key, the Team, and the Business Unit. The error is in LLM Logs.

# Complexity Router

Open: /workspace/complexity-router

## What this is used for

Sends an easy prompt to a cheaper model and a hard prompt to a stronger model.

## Inputs you fill

| Input | What you enter |
|---|---|
| Enabled | Yes |
| Low complexity model | gpt-4.1-mini |
| High complexity model | gpt-4.1 |
| Feature flag | routing.complexity on |

## How to use it

Save the map. Send a short hello and confirm LLM Logs shows the small model.

## How it connects

Runs before the provider call. Routing Rules can still force one model. Both models must be enabled in the catalog.

# Routing Rules

Open: /workspace/routing-rules

## What this is used for

Company policy: which provider and model for a team, user, key, or model name.

## Inputs you fill

| Input | What you enter |
|---|---|
| Condition | Team is Support |
| Target model | gpt-4.1-mini |
| Order | Specific rule above the general rule |

## How to use it

Add the rule and save. Send a Support-key call and confirm the model in LLM Logs.

## How it connects

Reads the virtual key, user, and team. Sends the call to a Model Provider. Use Complexity Router for automatic difficulty. Use this screen for a fixed policy.

# Circuit Breaker

Open: /workspace/circuit-breaker

## What this is used for

Stops sending traffic to a provider that is failing.

## Inputs you fill

| Input | What you enter |
|---|---|
| Failures before open | 5 in a minute |
| Wait before retry | 30 seconds |
| Feature flag | routing.circuit_breaker on |

## How to use it

Save. You need a second provider key if traffic must continue while one vendor is paused.

## How it connects

Watches errors from Model Providers. Adaptive Routing and Routing Rules should use the healthy provider. LLM Logs show the errors that opened it.

# Pricing Overrides

Open: /workspace/custom-pricing/overrides

## What this is used for

Your contract price, used instead of the default price.

## Inputs you fill

| Input | What you enter |
|---|---|
| Model | gpt-4.1-mini |
| Input price | Your contract price per million tokens |
| Output price | Your contract price per million tokens |

## How to use it

Save. After a change, an admin can recalculate cost from LLM Logs.

## How it connects

Dashboard, LLM Logs, and budgets use this price when it is set. It wins over Model Settings when both exist.

# Model Settings

Open: /workspace/custom-pricing

## What this is used for

Default parameters and the base price for a model.

## Inputs you fill

| Input | What you enter |
|---|---|
| Model | gpt-4.1-mini |
| Temperature | 0.2 for a stable support answer |
| Base price | Set here only if you are not using a Pricing Override |

## How to use it

Open the model, set the defaults, save.

## How it connects

Applied on the way to the provider unless the client sends its own value. Pricing Overrides win on price.

# 4. MCP Gateway

## MCP Catalog

Open: /workspace/mcp-registry

### What this is used for

The MCP servers UnifAI will dial.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | docs-server |
| URL or command | https://mcp.example.com/sse |

### How to use it

Add the client, save, and reconnect if the first dial fails. Status should become connected.

### How it connects

Tool Groups pick tools from here. MCP Auth Config stores the header. MCP Logs show the calls. Flag mcp.tool_execution must be on.

## MCP Library

Open: /workspace/mcp-registry/library

### What this is used for

A ready list of known MCP servers. It is a template, not a live connection.

### Inputs you fill

| Input | What you enter |
|---|---|
| Server | The documented server you need |
| Sync | Refresh the list if it looks stale |

### How to use it

Add the chosen server into MCP Catalog, then fill the real URL and credentials there.

### How it connects

Library does not dial anything. Catalog does.

## Tool Groups

Open: /workspace/mcp-tool-groups

### What this is used for

A named set of tools one virtual key may call.

### Inputs you fill

| Input | What you enter |
|---|---|
| Group name | Support tools |
| Tools | search_docs only |
| Attached to | The Support virtual key |

### How to use it

Create the group, tick only those tools, and attach it to the key.

### How it connects

A key without the group cannot call the tool. Calls appear in MCP Logs.

## Auth Sessions

Open: /workspace/mcp-sessions

### What this is used for

Live sign-ins between a person and an MCP server.

### Inputs you fill

| Input | What you enter |
|---|---|
| User | anitha.user |
| Server | docs-server |
| State | success or the failure reason |

### How to use it

Open a session to see who connected. Disconnect a session that should stop.

### How it connects

Created after MCP Auth Config and, when required, OAuth Grants. Feature flag mcp.oauth_grants turns on the consent screen.

## OAuth Grants

Open: /workspace/oauth-grants

### What this is used for

The consent a person gave an MCP server to use an external account.

### Inputs you fill

| Input | What you enter |
|---|---|
| User | anitha.user |
| Server | docs-server |
| Action | Revoke on the day the person leaves |

### How to use it

Review the list. Revoke instead of leaving a grant in place.

### How it connects

Sits between the user and the external service. Auth Sessions show whether the sign-in worked.

## MCP Settings

Open: /workspace/mcp-settings

### What this is used for

Gateway-wide timeouts and switches for every MCP server.

### Inputs you fill

| Input | What you enter |
|---|---|
| Timeout | Raise it only when a known server is slow |

### How to use it

Change the value and save. Then reconnect the client from MCP Catalog.

### How it connects

Applies to every Catalog server. The URL of each server stays on the catalog entry.

## Plugins

Open: /workspace/plugins

### What this is used for

Turns the processing steps on the API path on or off, and sets their order.

## Inputs you fill

| Input | What you enter |
|---|---|
| Keep on | governance and logging |
| Leave off | Any plugin you do not recognise |

## How to use it

Enable, disable, and reorder only when you know which step must run first. Send one test chat and confirm LLM Logs still has a row.

## How it connects

Governance off stops budget checks. Guardrails off stops API guardrail rules. This page is not the laptop Guard.

# 5. Governance

## Virtual Keys

Open: /workspace/governance/virtual-keys

### What this is used for

The secret an application sends. It is not a website login and it is not the vendor key.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Support bot — production |
| Team or user | Support |
| Budget | 200 |
| Rate | 120 per minute |
| Models | gpt-4.1-mini |

### How to use it

Create, copy the key once into the application secret store, and rotate it when staff leave.

### How it connects

The app calls /v1/chat/completions with Authorization: Bearer and this key. Budgets, Routing, Guardrails, and Model Providers run on that call. LLM Logs show it.

## Users

Open: /workspace/governance/users

### What this is used for

Website accounts and who may open which menu.

### Inputs you fill

| Input | What you enter |
|---|---|
| Username | anitha.user |
| Email | anitha.user@example.com |
| Password | A password with 8 characters, upper, lower, number, and a symbol |
| Role | user, sub_admin, admin, or a custom role |
| Allowed sections | prompt-repository, and browser-ai only for security staff |
| Status | Approve a pending sign-up, or disable a leaver |

### How to use it

Create the user or approve the pending row. The person then signs in at /login.

### How it connects

Allowed sections decide the menu. A virtual key can be assigned to this user. SMTP must already work if they signed up with an email code.

## Teams

Open: /workspace/governance/teams

### What this is used for

A group of users with one shared budget.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Support |
| Members | anitha.user |

| Input | What you enter |
|---|---|
| Budget | 200 |
| Rate | 120 per minute |

### How to use it

Create the team, add the people, set the ceiling, save.

### How it connects

Put the team on a Virtual Key and on a Routing Rule. A Business Unit above the team can stop spend even when the team budget remains.

## Business Units

Open: /workspace/governance/business-units

### What this is used for

A department budget over several teams.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Customer Operations |
| Teams | Support |
| Budget | 2000 |
| Rate | The department ceiling |

### How to use it

Create the unit, attach the teams, save.

### How it connects

Sits above Teams. The unit ceiling stops every team under it.

## Customers

Open: /workspace/governance/customers

### What this is used for

An external client you report and bill separately.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Northwind |
| Teams | Support |

### How to use it

Create the customer and link the teams that do that client’s work.

### How it connects

Reporting and budgets. The application still uses a Virtual Key.

## User Provisioning

Open: /workspace/scim

### What this is used for

Connects Azure AD or Okta so joiners and leavers update Users automatically.

### Inputs you fill

| Input | What you enter |
|---|---|
| SCIM base URL | https://unifai.example.com/api/scim/v2 |

| Input | What you enter |
|---|---|
| Token | The token this page shows |
| Map | User name and email |

### How to use it

Paste the URL and token into the identity provider. A person set inactive there becomes disabled here.

### How it connects

Writes the same Users records. It does not install Gateway Guard and it does not replace SMTP.

## Roles & Permissions

Open: /workspace/governance/rbac

### What this is used for

What a role may do on the API.

### Inputs you fill

| Input | What you enter |
|---|---|
| Role name | Auditor |
| Data scope | all-data or own-data |
| Allow | Logs Read and View, Audit Logs Read and View, Dashboard Read and View |
| Do not allow | Delete, provider keys, Settings |

### How to use it

Create the custom role and assign it on the user. Leave admin, sub_admin, and user in place unless you must narrow them.

### How it connects

Every API call checks this, then the allowed sections on the user. Browser AI is under the Logs resource. The Users page itself stays with admin and sub_admin.

## Access Profiles

Open: /workspace/governance/access-profiles

### What this is used for

A reusable bundle of budget, model, and key limits for one job.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Contractor |
| Budget | 25 |
| Models | gpt-4.1-mini only |
| State | Active |

### How to use it

Create, activate, and apply it to those users. Clone it for a similar job.

### How it connects

Applying it updates those users’ virtual-key limits.

## Audit Logs

Open: /workspace/audit-logs

### What this is used for

Who changed configuration. You do not type these rows.

### Inputs you fill

| Input | What you enter |
|---|---|
| User | priya.admin |
| Date | Today |
| Action | The create or update you just saved |

## How to use it

Filter after an incident. Do not delete the rows as a habit.

## How it connects

Records changes on Users, Virtual Keys, Guard Rules, Model Providers, and Settings.

# 6. Guardrails

## Rules

Open: /workspace/guardrails/configuration

### What this is used for

Checks prompts and answers on API calls that use a virtual key.

### Inputs you fill

| Input | What you enter |
|---|---|
| Detection | PII and secrets, prompt injection, toxicity, or grounding |
| Action | Block or redact the API call |
| Feature flags | guardrails.pii_masking and the other guardrails flags you rely on |

### How to use it

Create the rule, point it at a Rule Provider if it needs one, and save. Send a test API call that contains a card number and read LLM Logs.

### How it connects

Runs on the API path. It does not write a Browser AI Prompt Log. Browser checks stay in Guard Rules.

## Rule Providers

Open: /workspace/guardrails/providers

### What this is used for

The safety engine a guardrail rule calls. This is not the chat vendor.

### Inputs you fill

| Input | What you enter |
|---|---|
| Provider | The safety product you licensed |
| Key or endpoint | That product’s credential |

### How to use it

Add it, save, then select it on the rule.

### How it connects

Model Providers call the chat model. This page calls the checker.

## Cluster Config

Open: /workspace/cluster

### What this is used for

More than one UnifAI server sharing configuration.

### Inputs you fill

| Input | What you enter |
|---|---|
| Peers | Leave empty on a single server |
| Cluster secret | The same secret on every node, only when you have a pair |

### How to use it

On one server, do not add peers. On a pair, each node lists the other.

### How it connects

A virtual key created on one node must exist on the others. This does not replace the database.

# 7. Adaptive Routing

## Dashboard

Open: /workspace/adaptive-routing

### What this is used for

How API traffic is split across provider keys right now. This is not the Observability Dashboard.

### Inputs you fill

| Input | What you enter |
|---|---|
| No create fields | Read the weight and the health of each route |

### How to use it

If one provider takes every call, open Adaptive Routing Settings or Routing Rules.

### How it connects

Uses the Model Provider pool. Circuit Breaker removes a failing provider from this split.

## Settings

Open: /workspace/adaptive-routing/settings

### What this is used for

The load-balancing policy when more than one key can serve the model.

### Inputs you fill

| Input | What you enter |
|---|---|
| Strategy | The split you want |
| Weight openai-prod-1 | 70 |
| Weight openai-prod-2 | 30 |
| Fallback flag | routing.fallback_cascade on if a 429 or 500 must jump to the next provider |

### How to use it

Set the weights and save.

### How it connects

Routing Rules win when a rule names one provider. Circuit Breaker removes a sick key from the weights.

# 8. Prompt Repository and Skills Repository

## Prompt Repository

Open: /workspace/prompt-repo

### What this is used for

Saved prompt text for people and for applications.

### Inputs you fill

| Input | What you enter |
|---|---|
| Folder | Support |
| Name | Customer reply — refund tone |
| Text | Reply in a calm tone. Do not ask for card numbers or government IDs. |
| Tags | support, refund |

### How to use it

Create the folder, add the prompt, save. Limit folders on the user if another team must not see it.

### How it connects

Does not choose a model. Prompt Deployments publishes a version. The call still needs a Virtual Key.

## Skills Repository

Open: /workspace/skills-repo

### What this is used for

Shared skill instructions the company published.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Refund tone |
| Body | Three short sentences. No legal promises. Do not ask for a PAN or a card number. |

### How to use it

Add the skill and save. People with this menu can browse it.

### How it connects

Served to clients that call the skills API. It is not a Guard Rule and not a virtual key.

# 9. Settings

## Client Settings

Open: /workspace/config/client-settings

### What this is used for

Limits for incoming API calls.

### Inputs you fill

| Input | What you enter |
|---|---|
| Allowed origins | https://unifai.example.com |
| Max body size | 100 MB unless you must raise it |
| Require auth | On |

### How to use it

Save. Applications must call from an allowed origin and must still send a valid virtual key.

### How it connects

This is not Target Websites. AI sites the laptop watches are under Browser AI.

## Compatibility

Open: /workspace/config/compatibility

### What this is used for

Converts a client’s parameters into the shape a provider expects.

### Inputs you fill

| Input | What you enter |
|---|---|
| Conversion | On when an OpenAI-style client calls a non-OpenAI model through the gateway |

### How to use it

Turn on only the conversion you need and save.

### How it connects

Sits between the virtual-key request and Model Providers. Routing still chooses the provider.

## Caching

Open: /workspace/config/caching

### What this is used for

Reuses an earlier answer for a repeated request.

### Inputs you fill

| Input | What you enter |
|---|---|
| Direct cache | On for a FAQ bot |
| Semantic cache | On only if similar questions should share an answer |
| TTL | 10 minutes |
| Feature flag | cache.responses on, or every call still goes to the provider |

### How to use it

Save. Turn the flag off while you are debugging a prompt.

### How it connects

A cache hit does not call Model Providers. LLM Logs should show the hit.

## Security

Open: /workspace/config/security

### What this is used for

Sign-in protection, and the SMTP mail server for codes and notices.

### Inputs you fill

| Input | What you enter |
|---|---|
| Lockout | On |
| SMTP enabled | Yes |
| Host | smtp.example.com |
| Port | 587 |
| Username | mailer@example.com |
| From email | noreply@example.com |
| From name | UnifAI |
| Use TLS | Yes |
| Notify on user create | Yes |

### How to use it

Save SMTP, then send a test to priya.admin@example.com. Sign-up codes and password reset start only after that test arrives.

### How it connects

Used by Sign Up, Forgot password, and Forgot username. An email Alert Channel also needs this. Virtual keys do not use this login.

## API Keys

Open: /workspace/config/api-keys

### What this is used for

The same vendor secrets as Model Providers, opened from Settings.

### Inputs you fill

| Input | What you enter |
|---|---|
| Key name | openai-prod-1 |
| New secret | The replacement vendor key |

### How to use it

Rotate here when you are already in Settings. Prefer Model Providers for the full provider form. Send one test chat and read LLM Logs.

### How it connects

The next routed call uses the new secret.

## Performance Tuning

Open: /workspace/config/performance-tuning

### What this is used for

Server buffers and pool sizes.

### Inputs you fill

| Input | What you enter |
|---|---|
| Leave defaults | On a new install |
| Change | Only after latency on the Observability Dashboard is high while the vendor itself is fast |

### How to use it

Save and watch the Dashboard.

### How it connects

Affects how fast calls are handled. It does not choose the model.

# Feature Flags

Open: /workspace/config/feature-flags

## What this is used for

On and off switches for whole features.

## Inputs you fill

| Input | What you enter |
|---|---|
| browser.prompt_guard | On, or laptop prompts are not stored |
| browser.file_scan | On if uploads must be checked |
| cache.responses | Off until answers are trusted |
| routing.complexity | On only if Complexity Router is in use |
| routing.circuit_breaker | On only if Circuit Breaker is in use |
| routing.fallback_cascade | On if a 429 or 500 must jump provider |
| mcp.tool_execution | On only if MCP tools must run |
| mcp.oauth_grants | On if MCP must show a consent screen |

## How to use it

Add the preset and set it on or off. A flag gates the screen it names.

## How it connects

browser.prompt_guard off means Prompt Logs stay empty. routing.circuit_breaker off means the Circuit Breaker page does not enforce.

# 10. Beside the menu, in the same order

## Proxy

Open: /workspace/config/proxy

### What this is used for

The office HTTP proxy the UnifAI server uses for outbound calls. Not Gateway Guard and not the laptop PAC.

### Inputs you fill

| Input | What you enter |
|---|---|
| Enabled | No, unless the server cannot reach vendors directly |
| URL | http://proxy.example.com:8080 |
| Enable for inference | Yes, only when the proxy is on |
| Enable for SCIM | Yes only if the identity provider is reached through that proxy |
| No proxy | localhost,127.0.0.1 |

### How to use it

Leave it off on a normal pilot. If you turn it on, save and confirm one chat still succeeds in LLM Logs.

### How it connects

Model Providers use it for vendor calls when inference is enabled. User Provisioning uses it when SCIM is enabled.

## Alert Channels

Open: /workspace/alert-channels

### What this is used for

A short notice when a circuit breaker trips or a budget or rate limit is exhausted. The same incident is sent at most once every 10 minutes.

### Inputs you fill

| Input | What you enter |
|---|---|
| Name | Ops Slack |
| Type | Webhook, Slack, Email, or PagerDuty |
| URL, email, or routing key | The Slack webhook URL, or the address, or the PagerDuty key |
| Enabled | Yes |

### How to use it

Add the channel after a budget or a circuit breaker exists. Press test. Email type needs SMTP already tested.

### How it connects

Connectors copy full logs. This page sends the short incident only.

## MCP Auth Config

Open: /workspace/mcp-auth-config

### What this is used for

The header and per-user credential for an MCP server that is already in the catalog.

### Inputs you fill

| Input | What you enter |
|---|---|
| Client | docs-server |
| Header name | Authorization |
| Header value | The server token |
| Per-user header keys | Authorization, when each person has their own credential |

### How to use it

If the page says there are no clients, add the server in MCP Catalog first. Save headers, then save the per-user list. Reconnect the catalog client if the state stays failed.

### How it connects

Auth Sessions and OAuth Grants show the result. MCP Logs show the tool call.

## Prompt Deployments

Open: /workspace/prompt-repo

### What this is used for

Publishes one prompt version to production, staging, or preview.

### Inputs you fill

| Input | What you enter |
|---|---|
| Prompt | Customer reply — refund tone |
| Version | 1, created in Prompt Repository first |
| Environment | production, staging, or preview |
| Enabled | Yes |

### How to use it

Select the prompt, deploy the version, and leave the switch on. Turn it off to stop that environment without deleting the prompt.

### How it connects

The application sends header x-uf-prompt-environment: production, or x-uf-dim-environment, plus the virtual key. The model call still follows Routing and Model Providers.

# 11. Items that are easy to miss

## Sign in, sign up, and sign out

Open: /login and /signup

### What this is used for

The only website login. Every role uses this page. The menu after login follows the role and the allowed sections.

### Inputs you fill

| Input | What you enter |
|---|---|
| Sign in username | anitha.user |
| Sign in password | Anitha#User24 |
| Sign up email | anitha.user@example.com |
| Email code | 481926, only after SMTP test mail has arrived |
| New password | Anitha#Reset24 |
| Sign out | Account menu. The address may include logged_out=1 |

### How to use it

Approve the user under Governance → Users before the first sign-in. If the screen says too many failed attempts, wait the minutes it shows. If it says verify your email, enter the code on Sign Up. If it says waiting for approval, an admin has not approved the row.

### How it connects

SMTP on Settings → Security sends the code. Users stores the account. Allowed sections hide menus the person must not open. A disabled SCIM user cannot sign in.

## File upload policy

Open: /workspace/browser-ai?tab=rules

### What this is used for

A switch on the Guard Rules page. It blocks every file or attachment sent to a monitored AI site, whatever is inside the file.

### Inputs you fill

| Input | What you enter |
|---|---|
| Block all uploads | On when the company forbids attachments |
| Upload warning text | The sentence the employee sees when an upload is stopped |
| Enabled | The policy master switch on the same card |

### How to use it

Turn the switch on, write the warning, and save. Then upload a small file on a monitored site and confirm Prompt Logs shows the block.

### How it connects

Applies only to domains in Target Websites. It is separate from a regex Guard Rule. Feature flag browser.file_scan must stay on or uploads are not checked.

## Warning email from a prompt log

Open: /workspace/browser-ai?tab=logs

### What this is used for

Sends the company warning to the contact email stored on that laptop’s Guard Agent.

### Inputs you fill

| Input | What you enter |
|---|---|
| Log row | A Blocked or Warned row |
| Contact email | it@example.com on Guard Agents |

| Input | What you enter |
|---|---|
| SMTP | Already tested on Settings → Security |

### How to use it

Open the row and send the warning. If the send fails, SMTP is missing or the agent has no contact email.

### How it connects

Uses the same mail server as sign-up codes. The log row stays. Audit Logs can show the send.

## Playground

Open: /workspace/prompt-repo

### What this is used for

A chat box inside Prompt Repository. It calls the gateway with the signed-in user's access, so an admin can try a model without a separate application.

### Inputs you fill

| Input | What you enter |
|---|---|
| Model | gpt-4.1-mini, already enabled in Model Catalog |
| Message | Summarise our refund policy in three bullets. |
| Prompt | Optional. Select Customer reply — refund tone to send that saved text |
| Skill | Optional. A skill from Skills Repository can be injected as the system message |

### How to use it

Select the model, type the message, and send. Then open LLM Logs and confirm the row.

### How it connects

Uses Model Providers and Routing. It does not use the laptop Guard. A 401 means no provider key or the user's access cannot call that model.

## Correct YP-Raksha install

Open: On the laptop after Browser AI → Setup

### What this is used for

The browser extension Gateway Guard turns on. Employees do not load it from a store and do not get a Remove button on a correct install.

### Inputs you fill

| Input | What you enter |
|---|---|
| Program | Gateway_Guard_Setup.exe |
| Start at login | Checked |
| Extension id | mipfhcmlcjfhmgldkokdckhndkebkllj |
| Uninstall | Company uninstall key, or remote uninstall from Guard Agents |

### How to use it

IT runs the setup once. Approve the administrator prompt so the machine policy is written. Open Chrome or Edge only to confirm the extension is on.

### How it connects

A correct install is managed by the organisation, on, including private windows, with no Remove button. Off, Remove, or the words not from any known source means the outside install is still present and IT must remove that registry path so the policy install can take over.

## What an empty screen usually means

Open: Any menu

## What this is used for

Use this when a page has no rows. Fix the earlier step. Do not add a second copy of the same key or rule.

## Inputs you fill

| Input | What you enter |
|---|---|
| LLM Logs empty | No virtual-key call yet, or Model Providers has no working key |
| Prompt Logs empty | No laptop has reported, the site is not a Target Website, or browser.prompt_guard is off |
| MCP Logs empty | Catalog is not connected, or mcp.tool_execution is off |
| Sign-up code missing | SMTP test on Settings → Security has not succeeded |
| Model Catalog empty | Model Providers has no key, or the vendor rejected it |
| Guard Agents empty | Setup has not been run on a laptop, or the laptop cannot reach the server |

## How to use it

Walk the connection flow from step 1 again and stop at the first step that is not done.

## How it connects

Each empty page points at one earlier page. The connection order at the start of this catalog is the checklist.