

431 Lab 7 Instructions

Fall 2026 - deadline in [Course Calendar](#)

Thomas E. Love

2026-08-24

Table of contents

0.1 R Setup	2
0.2 Getting Help	2
0.3 Learning Objectives	2
0.4 Background and Data for Lab 7	2
0.5 Data Management	3
0.5.a Checking Your Work	4
1 Task 1 (10 points)	5
2 Task 2 (10 points)	6
3 Task 3 (10 points)	6
4 Task 4 (10 points)	6
5 Task 5 (10 points)	7
6 Section 6 of your Lab Report: AI Usage	7
7 Section 7 of your Lab Report: Session Information	7
8 Additional Notes and Instructions	7
8.1 Submitting this Lab	7
8.2 Grading this Lab	7
8.3 Emergencies and Late Policy	8
8.4 Lab Regrade Requests	8
9 Session Information	8

! Important

- This Lab contains 5 tasks for you to complete.
- The deadline for completing this Lab is posted in the [Course Calendar](#).

0.1 R Setup

Note: These are the packages used in my answer sketch for Lab 7. You don't have to use all of these packages, necessarily.

```
knitr::opts_chunk$set(comment = NA)

source("https://raw.githubusercontent.com/THOMASELOVE/431-data/refs/heads/main/data/Love-431.R") ## add in the Love-431.R script straight from our 431-data page

library(janitor)
library(haven)
library(mice)
library(naniar)
library(patchwork)
library(broom)
library(car)
library(gt)
library(easystats)
library(tidyverse)

theme_set(theme_lucid())
```

0.2 Getting Help

You may discuss each Lab with Professor Love, the teaching assistants or your colleagues, but your answer must be prepared by **you working alone**. Don't be afraid to ask questions, using any of the methods described on [our Contact Us page](#).

0.3 Learning Objectives

1. Ingest a SAS transport file, using the `haven` package.
2. Be able to work through a simple linear regression
3. Visualize and interpret the role of a potential confounder
4. Run a multivariable model adjusting for this confounder, with an interpretation of the estimate and confidence interval
5. Expand this model and interpret the results and conclusion
6. Compare multiple linear models using various metrics

0.4 Background and Data for Lab 7

The Lab 7 data are a sample of 800 subjects who were alive at 6 months after participating in “an observational study of 996 patients receiving an initial Percutaneous Coronary Intervention (PCI) at Ohio Heart Health, Christ Hospital, Cincinnati in 1997 and followed for at least 6 months by the staff of the Lindner Center. We saw a different version of these data in Lab 4.

The patients thought to be more severely diseased were assigned to treatment with abciximab (an expensive, high-molecular-weight IIb/IIIa cascade blocker); in fact, only 298 (29.9 percent) of patients received usual-care-alone with their initial PCI.”

0.5 Data Management

Begin by loading the `lab7.xpt` data set (this is a SAS transport file, such as is required for submission of data to the FDA) provided for Lab 7 into a tibble in a new R Project (for Lab 7). Call that initial tibble `lab7_raw`. **Do not** use the version of the lindner data that we used in Lab 4.

There are **six** key data steps you’ll need to do after reading in the data.

1. Cleaning the variable names up seems important.
2. You’ll want to add an `subject` ID code to be able to properly identify patients since there are no unique identifiers. We’ll use the row numbers for this purpose.
3. There are six subjects in the data with their `ejec_frac` (ejection fraction) equal to zero. Each of those `ejec_frac` values should instead be marked as NA, as the zeros are meant to be codes for missing values.
4. You’ll then need to use the `mice` package to build 5 imputations of the complete data set to deal with missing data in `ejec_frac` and one of the other variables. We will assume is missing at random (MAR) for both variables. Set your random seed to 431 for this work, using `set.seed(431)`.
5. You’ll then select the third of those imputations for your main work on the Lab.
6. After creating the third imputation and saving it as a tibble of its own, you’ll partition it into a 70% training (call this `lab7_training`) and 30% test sample (call this `lab7_test`), again using `set.seed(431)`.

Your data management activities should look like this:

```
lab7_raw <- read_xpt("data/lab7.xpt") |>
  janitor::clean_names() |>
  mutate(subject = as.character(row_number())) |>
  relocate(subject) |>
  replace_with_na(replace = list(ejec_frac = 0))
```

```
miss_var_summary(lab7_raw)
```

```
# A tibble: 6 × 3
  variable n_miss pct_miss
  <chr>      <int>    <num>
1 height      25     3.12
2 ejec_frac    6     0.75
3 subject      0      0
4 card_bill    0      0
```

```
5 abcix      0      0
6 female     0      0
```

```
prop_miss_case(lab7_raw)
```

```
[1] 0.03875
```

```
set.seed(431)
lab7imps <- mice(lab7_raw, m = 5, printFlag = FALSE)
```

If you get a warning here about logged events, you can silence it, as I have done in preparing these instructions.

```
imp_3 <- complete(lab7imps, 3) |> tibble()
dim(imp_3)
```

```
[1] 800    6
```

```
n_miss(imp_3)
```

```
[1] 0
```

```
set.seed(431)
lab7_training <- slice_sample(imp_3, prop = 0.7, replace = FALSE)
lab7_test <- anti_join(imp_3, lab7_training, by = "subject")
```

0.5.a Checking Your Work

If you want to check that you've done this in the same way that I have, here are the first two observations for each of my two partitions.

```
head(lab7_training, 2)
```

```
# A tibble: 2 × 6
  subject ejec_frac card_bill abcix height female
  <chr>      <dbl>    <dbl> <dbl> <dbl> <dbl>
1 64         51      7039     0   185     0
2 435        55     14844     1   180     0
```

```
head(lab7_test, 2)
```

```
# A tibble: 2 × 6
  subject ejec_frac card_bill abcix height female
  <chr>      <dbl>    <dbl> <dbl> <dbl> <dbl>
1 2          60     11357     1    163     0
2 11         60     12751     1    157     1
```

! Lab 7 specifications

Here are some specifications unique to Lab 7.

- If you need to set a seed anywhere in the Lab, use **431** as your seed.
- If you need to fit a bootstrap, use 2000 replications.
- Use a **95%** confidence level throughout this Lab.

1 Task 1 (10 points)

In Task 1, the principal investigator wants to examine the relationship between a predictor: the ejection fraction (`ejec_frac`) and an outcome: 6-month cardiac-related costs (`card_bill`).

Given the information above, work through an appropriate simple regression analysis of the data.

- First, demonstrate the use of a Box-Cox procedure to obtain an estimate as to whether a logarithm or inverse would be a better choice for transforming the `card_bill` outcome.
- transform the outcome (`card_bill`) by taking its inverse and multiplying the result by 1,000,000, using something like:

```
lab7_training <- lab7_training |>
  mutate(trans_cb = 1000000/card_bill)
```

- then run a simple linear regression which you'll call `fit1`, to predict this transformed outcome using `ejec_frac` as a single predictor and fitting the model using ordinary least squares, and just the training data set (`lab7_training`.)

After fitting your model `fit1`, do the following...

- a. Describe the meaning of the point estimate for the slope of `ejec_frac` in your `fit1` model appropriately, and specify a 95% confidence interval around that slope.

i Note

Note that the units for `ejec_frac` are percentage points, but you can call them points, or units, in your response. You should not specify units for your transformed outcome.

- b. Use `check_model()` to display and then, in a few sentences, evaluate the posterior predictive check, as well as the plots to check linearity, homogeneity of variance, influential points, and normality of residuals. What problems with OLS assumptions, if any, do you see?

2 Task 2 (10 points)

Now we want to examine the effect of a third variable, `abcix`, which specifies whether or not the patient had the abciximab augmentation (`abcix = 1` means they did have the augmentation), on the relationship between our main predictor (`ejec_frac`) and our (transformed) `card_bill` outcome. Run, and discuss, a new linear regression which adjusts your original model to include this new predictor. Call this `fit2`. Again, this should be done on your training data set.

After fitting your model `fit2`, do the following...

- a. Describe the meaning of the point estimate for the slopes of `ejec_frac` and then `abcix` in your `fit2` model appropriately, and specify a 95% confidence interval around each of those two slopes.
- b. Use `check_model()` to display and then, in a few sentences, evaluate the posterior predictive check, as well as the plots to check linearity, homogeneity of variance, influential points, and normality of residuals. What problems with OLS assumptions, if any, do you see? Does your `fit2` model show meaningfully different results in this regard than `fit1` did?

3 Task 3 (10 points)

The principal investigator has now asked you to add two more variables to your models: `height` and `female`. It's been suggested that the effect of `height` depends on `female`, which would suggest the desire to include an interaction term between these two variables in the model. Add this interaction term to create a new model (which we would like you to call `fit3`.)

- a. In a sentence or two, discuss whether or not we see the interaction between these variables having a large impact on your (transformed) `cardbill`, again solely using your training data. In particular, specify the improvement in raw R^2 attributable to the interaction term. Then discuss whether the coefficients for the slopes of `abcix` and `ejec_frac` in model `fit3` are substantially different from those seen in `fit2`, in light of the added coefficients in the model.
- b. Now, compare the performance of fits 1, 2 and 3 using a table of performance indices and a plot of those indices for your three models. Which model appears, on this basis, to display the best training sample performance?

4 Task 4 (10 points)

By now you should have created 3 models. Fit these models to the test data we held out earlier, called `lab7_test`. Then, compare these models, using their mean absolute prediction error (MAPE), square root of the mean squared prediction error (RMSPE), validated R-squared, and maximum prediction error in the test data.

i Note

Evaluate MAPE, RMSPE, R-squared and maximum prediction error in your test data only **after** backing out of the transformation you made earlier. Show all your code to accomplish this, and annotate it with complete sentences where you feel it's useful.

- a. Which of your three models (`fit1`, `fit2` or `fit3`) performs best according to each of the four measures listed above? Justify your responses with a table of results, and description of whether a low or high value of each measure is desirable.
- b. Based on your results in Tasks 3 and 4, which model do you prefer (`fit1`, `fit2`, or `fit3`) overall, and why?

5 Task 5 (10 points)

Write a brief essay (150-250 words is appropriate) which relates what you've done in this Lab to what you learned in your reading of Spiegelhalter's *The Art of Statistics*.

6 Section 6 of your Lab Report: AI Usage

All students should include an AI Usage section in each assignment for this class. See the instructions from Lab 1 for more details.

7 Section 7 of your Lab Report: Session Information

Include the session information as a final section in this Lab. I've done so at the bottom of this document.

8 Additional Notes and Instructions

8.1 Submitting this Lab

Submit this Lab via [Canvas](#), using the Lab 1 assignment. Be sure to submit all three files:

1. Your Quarto file (.qmd) built using our Lab 1 template.
2. The HTML file you obtain by knitting the Quarto file (.html)
3. Your video file (.mp4 or .mov preferred)

Be sure that your Quarto (and thus HTML) files include the **AI Help** and **Session information** sections at the end of the document, and that these section headings appear in the Table of Contents.

8.2 Grading this Lab

This Lab will be graded by the TAs and then reviewed by Dr. Love. Your grades will be available one week after the Lab deadline.

The maximum score on this Lab is 50 points.

As each Lab passes its deadline (as listed in the [Course Calendar](#)), we will:

- post the answer sketch (48 hours after the deadline) and draft grading rubric to our Shared Google Drive, and then
- post grades and any revisions to the grading rubric or answer sketch one week after the deadline to a location we will provide to you.

8.3 Emergencies and Late Policy

We do not grant extensions on Lab deadlines.

- To receive full credit on a Lab, it must be received on Canvas no later than 59 minutes after the posted deadline. (This allows for small issues with uploading to Canvas to occur without penalty.)
 - Labs that are turned in 1-48 hours after the deadline will lose 10 points for late work.
- No extensions to Lab deadlines will be made this semester. Labs turned in more than 48 hours after the deadline will receive no credit, since by then the Lab Sketch will be posted.
- For details on how Lab grades affect your course grade, see the Syllabus.
- If you have an emergency that will keep you from submitting the Lab by even the late deadline of Friday at noon, please let Dr. Love know that (as soon as possible) via email and he will consider excusing you from the Lab.

8.4 Lab Regrade Requests

If, after your Lab is graded, you want Dr. Love to review the grading or correct a grading error, please follow the Lab Regrade Request policy [posted on our Labs page](#).

9 Session Information

```
xfun::session_info()
```

```
R version 4.6.1 (2026-06-24 ucrt)
Platform: x86_64-w64-mingw32/x64
Running under: Windows 11 x64 (build 26200)
```

Locale:

```
LC_COLLATE=English_United States.utf8
LC_CTYPE=English_United States.utf8
LC_MONETARY=English_United States.utf8
LC_NUMERIC=C
LC_TIME=English_United States.utf8
```

Package version:

abind_1.4-8	askpass_1.2.1	backports_1.5.1
base64enc_0.1.6	bayestestR_0.18.1	bigD_0.3.1
bit_4.6.0	bit64_4.8.2	bitops_1.1.0
blob_1.3.0	boot_1.3-32	broom_1.0.13

bslib_0.11.0	cachem_1.1.0	callr_3.8.0
car_3.1-5	carData_3.0-6	cellranger_1.1.0
cli_3.6.6	clipr_0.8.1	coda_0.19-4.1
codetools_0.2-20	colorspace_2.1.3	commonmark_2.0.0
compiler_4.6.1	conflicted_1.2.0	correlation_0.8.8
cowplot_1.2.0	cpp11_0.5.5	crayon_1.5.3
curl_7.1.0	data.table_1.18.4	datasets_4.6.1
datawizard_1.3.1	DBI_1.3.0	dbplyr_2.6.0
Deriv_4.3.0	digest_0.6.39	doBy_4.7.2
dplyr_1.2.1	dtplyr_1.3.3	easystats_0.7.6
effectsize_1.0.3	emmeans_2.0.4	estimability_2.0.0
evaluate_1.0.5	farver_2.1.2	fastmap_1.2.0
fontawesome_0.5.3	forcats_1.0.1	foreach_1.5.2
forecast_9.0.2	Formula_1.2-5	fracdiff_1.5.4
fs_2.1.0	gargle_1.6.1	generics_0.1.4
ggplot2_4.0.3	glmnet_5.0	glue_1.8.1
googledrive_2.1.2	googlesheets4_1.1.2	graphics_4.6.1
grDevices_4.6.1	grid_4.6.1	gridExtra_2.3.1
gt_1.3.0	gtable_0.3.6	haven_2.5.5
highr_0.12	hms_1.1.4	htmltools_0.5.9
htmlwidgets_1.6.4	httr_1.4.8	ids_1.0.1
insight_1.5.2	isoband_0.3.0	iterators_1.0.14
janitor_2.2.1	jomo_2.7-6	jquerylib_0.1.4
jsonlite_2.0.0	juicyjuice_0.1.0	knitr_1.51
labeling_0.4.3	lattice_0.22-9	lifecycle_1.0.5
litedown_0.10	lme4_2.0-6	lmtest_0.9.40
lubridate_1.9.5	magrittr_2.0.5	markdown_2.0
MASS_7.3-66	Matrix_1.7-6	MatrixModels_0.5.4
memoise_2.0.1	methods_4.6.1	mgcv_1.9.4
mice_3.19.0	mime_0.13	minqa_1.2.8
mitml_0.4-5	modelbased_0.16.0	modelr_0.1.11
multcomp_1.4-31	mvtnorm_1.4-2	naniar_1.1.0
nlme_3.1-170	nloptr_2.2.1	nnet_7.3-20
norm_1.0.11.1	numDeriv_2016.8.1.1	openssl_2.4.2
ordinal_2026.7.26	otel_0.2.0	pan_2.0
parallel_4.6.1	parameters_0.29.2	patchwork_1.3.2
pbkrtest_0.5.5	performance_0.17.1	pillar_1.11.1
pkgconfig_2.0.3	plyr_1.8.9	prettyunits_1.2.0
processx_3.9.0	progress_1.2.3	ps_1.9.3
purrr_1.2.2	quantreg_6.1	R6_2.6.1
ragg_1.5.2	rappdirs_0.3.4	rbibutils_2.4.1
RColorBrewer_1.1-3	Rcpp_1.1.2	RcppArmadillo_15.4.2.1
RcppEigen_0.3.4.0.2	Rdpack_2.6.6	reactable_0.4.5

reactR_0.6.1	readr_2.2.0	readxl_1.5.0
reformulas_0.4.4	rematch_2.0.0	rematch2_2.1.2
report_0.6.4	reprex_2.1.1	rlang_1.3.0
rmarkdown_2.31	rpart_4.1.27	rstudioapi_0.19.0
rvest_1.0.5	S7_0.2.2	sandwich_3.1-2
sass_0.4.10	scales_1.4.0	see_0.14.1
selectr_0.6.0	shape_1.4.6.1	snakecase_0.11.1
SparseM_1.84.2	splines_4.6.1	stats_4.6.1
stringi_1.8.7	stringr_1.6.0	survival_3.8-9
sys_3.4.3	systemfonts_1.3.2	textshaping_1.0.5
TH.data_1.1-5	tibble_3.3.1	tidyr_1.3.2
tidyselect_1.2.1	tidyverse_2.0.0	timechange_0.4.0
timeDate_4052.112	tinytex_0.60	tools_4.6.1
tzdb_0.5.0	ucminf_1.2.3	UpSetR_1.4.1
urca_1.3.4	utf8_1.2.6	utils_4.6.1
uuid_1.2.2	V8_8.2.0	vctrs_0.7.3
viridis_0.6.5	viridisLite_0.4.3	visdat_0.6.0
vroom_1.7.1	withr_3.0.3	xfun_0.60
xml2_1.6.0	xtable_1.8-8	yaml_2.3.12
zoo_1.9-0		