

No.	Time	Source	Destination	Protocol	Length	Info
4163	15:07:23.101867232	128.119.245.12	192.168.0.16	HTTP	504	HTTP/1.1 200 OK (text/html)

Frame 4163: 504 bytes on wire (4032 bits), 504 bytes captured (4032 bits) on interface 0
Interface id: 0 (wlp3s0)
Interface name: wlp3s0
Encapsulation type: Ethernet (1)
Arrival Time: Oct 21, 2018 15:07:23.101867232 CDT
[Time shift for this packet: 0.000000000 seconds]
Epoch Time: 1540152443.101867232 seconds
[Time delta from previous captured frame: 0.000040762 seconds]
[Time delta from previous displayed frame: 0.065981721 seconds]
[Time since reference or first frame: 166.971574087 seconds]
Frame Number: 4163
Frame Length: 504 bytes (4032 bits)
Capture Length: 504 bytes (4032 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp:http:data-text-lines]
[Coloring Rule Name: HTTP]
[Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: Netgear_4c:73:b3 (10:da:43:4c:73:b3), Dst: IntelCor_6b:0f:b2 (5c:c5:d4:6b:0f:b2)
Destination: IntelCor_6b:0f:b2 (5c:c5:d4:6b:0f:b2)
Address: IntelCor_6b:0f:b2 (5c:c5:d4:6b:0f:b2)
.... ..0. = LG bit: Globally unique address (factory default)
.... ..0. = IG bit: Individual address (unicast)
Source: Netgear_4c:73:b3 (10:da:43:4c:73:b3)
Address: Netgear_4c:73:b3 (10:da:43:4c:73:b3)
.... ..0. = LG bit: Globally unique address (factory default)
.... ..0. = IG bit: Individual address (unicast)
Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.16
0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 490
Identification: 0x29ed (10733)
Flags: 0x4000, Don't fragment
Time to live: 50
Protocol: TCP (6)
Header checksum: 0xe6e4 [validation disabled]
[Header checksum status: Unverified]
Source: 128.119.245.12
Destination: 192.168.0.16
Transmission Control Protocol, Src Port: 80, Dst Port: 34542, Seq: 1, Ack: 417, Len: 438
Source Port: 80
Destination Port: 34542
[Stream index: 96]
[TCP Segment Len: 438]
Sequence number: 1 (relative sequence number)
[Next sequence number: 439 (relative sequence number)]
Acknowledgment number: 417 (relative ack number)
1000 = Header Length: 32 bytes (8)
Flags: 0x018 (PSH, ACK)
Window size value: 235
[Calculated window size: 30080]
[Window size scaling factor: 128]
Checksum: 0xef04 [unverified]
[Checksum Status: Unverified]
Urgent pointer: 0
Options: (12 bytes), No-Operation (NOP), No-Operation (NOP), Timestamps
[SEQ/ACK analysis]
[Timestamps]
TCP payload (438 bytes)
Hypertext Transfer Protocol
HTTP/1.1 200 OK\r\n
[Expert Info (Chat/Sequence): HTTP/1.1 200 OK\r\n]
Response Version: HTTP/1.1
Status Code: 200
[Status Code Description: OK]
Response Phrase: OK
Date: Sun, 21 Oct 2018 20:07:19 GMT\r\n
Server: Apache/2.4.6 (CentOS) OpenSSL/1.0.2k-fips PHP/5.4.16 mod_perl/2.0.10 Perl/v5.16.3\r\n
Last-Modified: Sun, 21 Oct 2018 05:59:01 GMT\r\n
ETag: "51-578b6d54daaf9"\r\n
Accept-Ranges: bytes\r\n

```
Content-Length: 81\r\n
  [Content length: 81]
Keep-Alive: timeout=5, max=100\r\n
Connection: Keep-Alive\r\n
Content-Type: text/html; charset=UTF-8\r\n
\r\n
[HTTP response 1/2]
[Time since request: 0.065981721 seconds]
[Request in frame: 4161]
[Next request in frame: 4165]
[Next response in frame: 4166]
File Data: 81 bytes
```

Line-based text data: text/html (3 lines)

```
<html>\n
Congratulations!  You've downloaded the first Wireshark lab file!\n
</html>\n
```