



KPI Metrics Metadata Configuration Guide

**An Open Source Asset for use with
TIBCO® Data Virtualization**

TIBCO Software empowers executives, developers, and business users with Fast Data solutions that make the right data available in real time for faster answers, better decisions, and smarter action. Over the past 15 years, thousands of businesses across the globe have relied on TIBCO technology to integrate their applications and ecosystems, analyze their data, and create real-time solutions. Learn how TIBCO turns data—big or small—into differentiation at www.tibco.com.

| | |
|--------------------------|--|
| Project Name | AS Assets KPI Metrics |
| Document Location | This document is only valid on the day it was printed. The source of the document will be found in the ASAssets_KPI folder (https://github.com/TIBCOSoftware) |
| Purpose | Self-paced instructional |



www.tibco.com

Global Headquarters
3303 Hillview Avenue
Palo Alto, CA 94304

Tel: +1 650-846-1000
+1 800-420-8450
Fax: +1 650-846-1005

Revision History

| Version | Date | Author | Comments |
|---------|-------------|-------------|--|
| 1.0 | Aug 30 2019 | Mike Tinius | Initial revision |
| 1.1 | Nov 6 2019 | Mike Tinius | Added reportResourceDatasourceLineage. |
| 1.2 | Dec 12 2019 | Mike Tinius | Modified location and name of constant configuration file. |
| 1.3 | Jan 20 2020 | Mike Tinius | Moved Published Resource info to "KPImetrics Data Dictionary v1.1.pdf" |

Related Documents

| Name | Version |
|--|----------|
| How To Use Utilities.pdf | 2019Q301 |
| KPImetrics Configuration Guide v1.28.pdf | 2020Q100 |
| KPImetrics Overview.pdf | 2019Q402 |
| KPImetrics Data Dictionary v1.1.pdf | 2020Q100 |
| KPImetrics_Table_Relationship_Diagram.pptx | 2020Q100 |
| KPI Metrics Overview.pptx | 2020Q100 |

Supported Versions

| Name | Version |
|---------------------------------|-------------------|
| TIBCO® Data Virtualization | 7.0.8 or later |
| AS Assets Utilities open source | 2019Q301 or later |

Table of Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 4 |
| | Purpose | 4 |
| | Audience | 4 |
| | References | 4 |
| | Overview | 4 |
| 2 | Requirements | 5 |
| 3 | Use Cases | 6 |
| 4 | Configuration..... | 7 |
| | Configure Metadata Constants | 7 |
| | Configure Trigger | 10 |
| 5 | KPImetrics Metadata Resources..... | 11 |
| | Configuration Resources..... | 11 |
| | Published Resources | 11 |
| | Metadata Data Source Tables..... | 11 |
| | Metadata Data Source Tables and Procedures for KPI_<database_type> | 11 |
| | Metadata System Triggers and Load Scripts..... | 14 |

1 Introduction

Purpose

The purpose of this document is to provide guidance on how configure and use the AS Assets KPI Metadata.

Audience

This document is intended to provide guidance for the following users:

- Data Virtualization Administrators – provides a guide for installation.
- Architects – provides the KPImetrics architecture.
- Data professionals – provides background on the published views and usage.
- Operations users – provides insight into triggers and procedures that are executed.
- Project Managers – provides general information on KPImetrics.

References

Product references are shown below. Any references to CIS or DV refer to the current TIBCO® Data Virtualization.

- TIBCO® Data Virtualization was formerly known as
 - Cisco Data Virtualization (DV)
 - Composite Information Server (CIS)

Overview

Please review the document “**KPImetrics Overview.pdf**”.

2 Requirements

The following requirements and pre-requisites must be met:

- See requirements section in KPImetrics Configuration Guide vx.yy.pdf.

3 Use Cases

Metadata Metrics – The following use cases are examples of design-time metrics. Design-time is different than KPI metrics run-time metrics.

1. How many views do not properly adhere to the layer rules? – compliance with architecture.
 - a. Each layer should invoke the appropriate layer below it. Should never invoke source views.
reportMetadataNonCompliantLayers
2. Which connector/adaptor is used by which views
reportMetadataDatasource
3. Source View is compliant with additional columns: source code, fetchtimestamp etc.
reportMetadataNonCompliantColumns
4. # views by layers
reportNumResourcesByLayer
5. Owner of views. Who has modified.
vMetadataResource
6. # policy, roles, policy name, attributes, description
vMetadataPolicy
vMetadataPolicyAssignmnt
7. Metadata regarding access and authorization for a give resource associated with access groups.
vMetadataPrivilege
8. Report on what data sources are associated with a particular resource. For example, a user can view all of the published resources and their corresponding data source(s).
reportResourceDatasourceLineage

4 Configuration

Configure Metadata Constants

Background Information:

The procedure “10_pqInsert_Metadata_Tables_METADATA_Constants” is used to configure various constants for a given “project”. A project has a base path which encompasses all of the layer folders and resources.

This procedure “DOES NOT” need to be executed manually. It will be executed each time the trigger “kpimetricsTrig_40_Cache_METADATA_TABLES” executes. The trigger executes Cache_METADATA_TABLES which in turn executes “10_pqInsert_Metadata_Tables_METADATA_Constants”. It does this so that all metadata is kept in synch with the same LOAD_DATE across all of the tables.

Instructions:

- Configure the following
/shared/ASAssets/KPImetrics/Customize/pqInsert_METADATA_Constants.
- Configure the section “INSERT METADATA_CONST_NAME ROWS”
 - Modify the concatenated string below as needed. Add a row for each "project" name to capture metadata for.
 - PROJECT_NAME: A unique name that will be assigned a unique ID.
 - EXECUTE_FLAG: Y=execute this row. N=do not execute when triggered.
 - ARCHIVE_FLAG: Y=archive rows before processing. N=do not archive.
 - ARCHIVE_PURGE_DAYS: The number of days to purge from the current date.
 - PROJECT_DESC: A description of the project path.
 - Maintain the existing structure with double pipe separating the line and single pipe separating a column.

```
SET projectName = 'TestSpoke';
SET METADATA_CONST_NAME_str = METADATA_CONST_NAME_str ||
PROJECT_NAME      EXECUTE_FLAG      ARCHIVE_FLAG      ARCHIVE_PURGE_DAYS      PROJECT_DESC
'||||projectName  ||'||          'Y'          ||'||          'N'          ||'||          30          ||'||          'TestSpoke project desc'  ||
"; -- This is always the last line
```

- Configure the section “INSERT METADATA_CONST_PATH ROWS”
 - Modify the concatenated string below as needed. Add a row for each base path within the "project" to capture metadata for.
 - Modify projectName, pathSH, pathDS.
 - The variable "pathWS" is not currently supported for web services.
 - Modify the PROJECT_PATH and RESOURCE_TYPES as per your requirements.

- Maintain the existing structure with double pipe separating the line and single pipe separating a column.
- **PROJECT_NAME:** A foreign key reference to METADATA_CONST_NAME which provides a unique name that will be assigned a PROJECT_NAME_ID that is unique.
- **PROJECT_PATH:** A unique key for this table which drives all of the processing for Cache_METADATA_TABLES procedure to load data.
- **RESOURCE_TYPES:** - A comma-separated list of resource types to process.
 - When using pathSH for shared area then [TABLE,PROCEDURE]
 - When using pathDS for /services/databases then [LINK]
 - When using pathWS for /services/webservices then [LINK]
- **NOTE:** Web Services are not currently supported.

```

SET projectName = 'TestSpoke';
SET pathSH = '/shared/00_DataFederation/TestSpoke';
SET pathDS = '/services/databases/PWC/TestSpoke';
SET pathWS = '';
SET METADATA_CONST_PATHS_str = METADATA_CONST_PATHS_str ||
--PROJECT_NAME      PROJECT_PATH      RESOURCE_TYPES
'||'|projectName    ||'|'pathSH        ||'|'TABLE,PROCEDURE' ||
'||'|projectName    ||'|'pathDS        ||'|'LINK'         ||
--'||'|projectName  ||'|'pathWS        ||'|'LINK'         ||
"; -- This is always the last line

```

- Configure the section "INSERT METADATA_CONST_LAYERS ROWS"
 - Modify the concatenated string below as needed. Only modify the layer type and parent path after the standard project path.
 - Modify projectName, pathSH, pathDS.
 - The variable "pathWS" is not currently supported for web services.
 - Modify the PROJECT_PATH, LAYER_TYPE, PARENT_PATH and GENERATE_LINEAGE as per your requirements.
 - Maintain the existing structure with double pipe separating the line and single pipe separating a column.
 - **PROJECT_NAME:** A foreign key reference to METADATA_CONST_NAME which provides a unique name that will be assigned a PROJECT_NAME_ID that is unique.
 - **PROJECT_PATH:** Provides a foreign key back to META_DRIVER table.
 - **LAYER_TYPE:** A unique string describing the layer to acquire metadata for.
 - **PARENT_PATH:** The actual path in DV which is associated with the LAYER_TYPE.
 - **GENERATE_LINEAGE:** Y=Generate lineage for this layer path. N=Do not generate lineage for this layer path.
 - **EXCLUSION_LIST:** A comma-separated list of paths or partial paths ending in a / that are to be excluded from the lineage generation. If a comma exists within a path then escape the comma with "_002C". e.g. /shared/my,path1/path2/ --> /shared/my_002Cpath1/path2/
 - **Rules:**
 - A LAYER_TYPE that is a parent to a sub-folder is allowed and it will not cause duplication of resources. This concept will work in any layer including /shared and published /services/databases.
 - The table METADATA_CONST_LAYERS is validated for duplicates.

If a duplicate layer and PARENT_PATH is found an exception is thrown.

- Each LAYER_TYPE should have a unique name within a given PROJECT_NAME_ID.

For example,

1) Given the following layer type designations, there is a grandparent-parent-child folder relationship represented here:

Note: The number of levels/layers is NOT restricted.

| LAYER_TYPE: | PARENT_PATH: |
|--|--|
| Note: 01_SourceViewLayer is a parent to 01_SourceViewLayer_svThirdParty | |
| 01_SourceViewLayer | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer |
| Note: 01_SourceViewLayer_svThirdParty is a parent to 01_SourceViewLayer_svThirdParty_A and 01_SourceViewLayer_svThirdParty_B | |
| 01_SourceViewLayer_svThirdParty | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty |
| 01_SourceViewLayer_svThirdParty_A | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_A |
| 01_SourceViewLayer_svThirdParty_B | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_B |

2) Given the following resources, the layer type will be assigned from the child (lowest folder) up to the grandparent (highest) folder.

| LAYER_TYPE | RESOURCE_PATH |
|-----------------------------------|--|
| 01_SourceViewLayer_svThirdParty_A | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_A/012_svThirdParty_A1/customers |
| 01_SourceViewLayer_svThirdParty_A | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_A/customers |
| 01_SourceViewLayer_svThirdParty_B | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_B/012_svThirdParty_B1/customers |
| 01_SourceViewLayer_svThirdParty_B | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_B/012_svThirdParty_B2/customers |
| 01_SourceViewLayer_svThirdParty_B | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/012_svThirdParty_B/customers |
| 01_SourceViewLayer_svThirdParty | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/012_svThirdParty/customers |
| 01_SourceViewLayer | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/011_svInternal/tutorial/customers |
| 01_SourceViewLayer | /shared/00_DataFederation/TestSpoke/01_SourceViewLayer/DS_ORDERS/tutorial/customers |

The following demonstrates how to setup the constants.

```
SET projectName = 'TestSpoke';
SET pathSH = '/shared/00_DataFederation/TestSpoke';
SET pathDS = '/services/databases/PWC/TestSpoke';
SET pathWS = '';
SET METADATA_CONST_LAYERS_str = METADATA_CONST_LAYERS_str ||
```

| --PROJECT_NAME | PROJECT_PATH | LAYER_TYPE | PARENT_PATH | GENERATE_LINEAGE |
|-----------------|--------------|--------------------------------|---|------------------|
| EXCLUSION_LIST | | | | |
| ' projectName | pathSH ' | '00_DataSource ' | pathSH '/00_DataSource ' | 'N ' ' |
| ' projectName | pathSH ' | '01_SourceViewLayer' | ' pathSH '/01_SourceViewLayer' | 'N ' ' |
| ' projectName | pathSH ' | '02_ConformingViewLayer ' | pathSH '/02_ConformingViewLayer ' | 'N ' ' |
| ' projectName | pathSH ' | '031_CommonEntityModel ' | pathSH '/03_CommonModelLayer/031_CommonEntityModel ' | 'N ' ' |
| ' projectName | pathSH ' | '032_CommonDimensionalModel ' | pathSH '/03_CommonModelLayer/032_CommonDimensionalModel' | 'N ' ' |
| ' 'N ' | | | | |
| ' projectName | pathSH ' | '033_CommonAnalyticalModel ' | pathSH '/03_CommonModelLayer/033_CommonAnalyticalModel ' | 'N ' ' |
| ' | | | | |
| ' projectName | pathSH ' | '034_CommonIntegrationModel ' | pathSH '/03_CommonModelLayer/034_CommonIntegrationModel ' | 'N ' ' |
| ' | | | | |
| ' projectName | pathSH ' | '041_BusinessDemandModel ' | pathSH '/04_BusinessDeliveryLayer/041_BusinessDemandModel ' | 'N ' ' |
| ' | | | | |
| ' projectName | pathSH ' | '042_BusinessDemandView ' | pathSH '/04_BusinessDeliveryLayer/042_BusinessDemandView ' | 'Y ' ' |
| ' | | | | |
| ' projectName | pathDS ' | 'PublishedDS_tutorial' | pathDS | 'Y ' ' |
| -- projectName | pathWS ' | 'PublishedWS_tutorial' | pathDS | 'Y ' ' |

"; -- This is always the last line

- Configure the section "INSERT METADATA_CONST_VALIDATE ROWS"
 - Modify the concatenated string below as needed.
 - Modify projectName, pathSH, pathDS.
 - The variable "pathWS" is not currently supported for web services.
 - Modify the PROJECT_PATH, LAYER_TYPE, RULE_TYPE and RULE_DESC as per your requirements.
 - Maintain the existing structure with double pipe separating the line and single pipe separating a column.

- **PROJECT_NAME:** A foreign key reference to METADATA_CONST_NAME which provides a unique name that will be assigned a PROJECT_NAME_ID that is unique.
- **PROJECT_PATH:** Provides a foreign key back to META_DRIVER table.
- **LAYER_TYPE:** A valid layer name found in the table METADATA_CONST_LAYERS.
- **RULE_TYPE:** Valid values=[ENFORCE_LAYER|ENFORCE_COLUMN]
- **RULE_DESC:** Enforce the rule type.
 - When RULE_TYPE=ENFORCE_COLUMN
 - a. Enforces which columns must be present in all of the views for a given layer type. Comma-separated list of case-sensitive column names.
 - When RULE_TYPE=ENFORCE_LAYER
 - a. Enforces which source layer resource can invoke which target layer resource. Comma-separated list of valid LAYER_TYPES.
 - b. If a resource can invoke another resource in the same layer then add its own layer to the list.

```

SET projectName = 'TestSpoke';
SET pathSH = '/shared/00_DataFederation/TestSpoke';
SET pathDS = '/services/databases/PWC/TestSpoke';
SET pathWS = "";
SET METADATA_CONST_VALIDATE_str = METADATA_CONST_VALIDATE_str ||
--PROJECT_NAME PROJECT_PATH LAYER_TYPE RULE_TYPE RULE_DESC
'|'|projectName '|'|pathSH '|'|'01_SourceViewLayer' '|'|'ENFORCE_LAYER' '|'|'00_DataSource'|
'|'|projectName '|'|pathSH '|'|'01_SourceViewLayer' '|'|'ENFORCE_COLUMN' '|'|'fetchTimeStamp,systemSourceCode'|
'|'|projectName '|'|pathSH '|'|'02_ConformingViewLayer' '|'|'ENFORCE_LAYER' '|'|'01_SourceViewLayer'|
'|'|projectName '|'|pathSH '|'|'031_CommonEntityModel' '|'|'ENFORCE_LAYER' '|'|'02_ConformingViewLayer'|
'|'|projectName '|'|pathSH '|'|'032_CommonDimensionalModel' '|'|'ENFORCE_LAYER' '|'|'02_ConformingViewLayer'|
'|'|projectName '|'|pathSH '|'|'033_CommonAnalyticalModel' '|'|'ENFORCE_LAYER' '|'|'02_ConformingViewLayer'|
'|'|projectName '|'|pathSH '|'|'034_CommonIntegrationModel' '|'|'ENFORCE_LAYER' '|'|'02_ConformingViewLayer'|
'|'|projectName '|'|pathSH '|'|'041_BusinessDemandModel' '|'|'ENFORCE_LAYER' '|'|
'031_CommonEntityModel,032_CommonDimensionalModel,034_CommonIntegrationModel,041_BusinessDemandModel'|
'|'|projectName '|'|pathSH '|'|'042_BusinessDemandView' '|'|'ENFORCE_LAYER' '|'|'041_BusinessDemandModel'|
'|'|projectName '|'|pathDS '|'|'PublishedDS_tutorial' '|'|'ENFORCE_LAYER' '|'|'042_BusinessDemandView'|
--'|'|projectName '|'|pathWS '|'|'PublishedWS_tutorial' '|'|'ENFORCE_LAYER' '|'|'042_BusinessDemandView'|
"; -- This is always the last line

```

Configure Trigger

Enabling triggers starts the processing of KPI metadata data. The trigger “kpimetricsTrig_40_Cache_METADATA_TABLES” is turned off by default. It must be turned on in order to begin the processing of

1. Modify /shared/ASAssets/KPImetrics/Customize/**defaultTriggersToEnable** and change the trigger kpimetricsTrig_40_Cache_METADATA_TABLES from OFF to ON if you want to capture metadata.
2. When updateTriggers is executed, it will turn on and off the trigger automatically according to how the trigger is set in defaultTriggersToEnable.

5 KPImetrics Metadata Resources

Configuration Resources

This section outlines the resources that are used for configuration of KPImetrics Metadata.

Published Resources

This section outlines the resources that are published under the ASAssets virtual database to expose metrics data. Resources are organized under catalogs and schemas based upon their functionality.

Please review the document “*KPImetrics Data Dictionary vX.Y.pdf*” for details about published tables, procedures and columns.

Metadata Data Source Tables

The following provides a description for the database tables used by KPImetrics Metadata.

Metadata Data Source Tables and Procedures for KPI_<database_type>

Location: /shared/ASAssets/KPImetrics/Physical/Metadata/KPI_<database_type>

The KPImetrics module provides data source for all currently supported storage database platforms under /shared/ASAssets/KPImetrics/Physical/Metadata.

Currently the KPImetrics module includes the following KPImetrics data sources

- /shared/ASAssets/KPImetrics/Physical/Metadata/KPI_oracle
- /shared/ASAssets/KPImetrics/Physical/Metadata/KPI_sqlserver

The following tables have been created in CIS_KPI schema to capture the required data. Each table has a corresponding archive table.

RULES:

- Only one load set of data is stored at any given point in time in the main metadata tables.
- When METADATA_CONST_NAME.ARCHIVE_FLAG=Y then each table is archived to its corresponding archive table.
- Each node in a cluster will contain its own set of metadata rows therefore, NODE_HOST and NODE_PORT are a part of every key. Even though the resource name will be the same, the RESOURCE_ID may be different on any given node. Be sure to do reporting based on a particular NODE_HOST and NODE_PORT.

| Table Name | Description |
|---------------------|--|
| METADATA_CONST_NAME | This table contains a unique base project path that drives all of the metadata capture for all of the tables. Only metadata is captured the project paths present in this table. The trigger |

| | |
|---|--|
| METADATA_CONST_NAME_ARCH | <p>specified below along with the procedure it invokes is the only mechanism for capturing metadata for all of the metadata tables listed here.</p> <p>LOAD_DATE: The timestamp of the latest metadata load.</p> <p>PROJECT_NAME_ID: A unique sequence id for each project name.</p> <p>PROJECT_NAME: A unique name that will be assigned a PROJECT_NAME_ID that is unique.</p> <p>ENVIRONMENT_NAME: The environment nickname from commonValues.cisServerNickname.</p> <p>EXECUTE_FLAG: Y=execute this row. N=do not execute when triggered.</p> <p>ARCHIVE_FLAG: Y=archive rows before processing. N=do not archive. Note: all rows get deleted each time the trigger executes. Archive is the only way to maintain history.</p> <p>ARCHIVE_PURGE_DAYS: The number of days to purge from the current date.</p> <p>PROJECT_DESC: A description of the project path.</p> <p>RESOURCE_TYPES: TABLE,PROCEDURE - A comma-separated list of resource types to process. Currently only TABLE and PROCEDURE are valid.</p> <p>EXECUTE_STATUS: The status of the latest load. SUCCESS or EXCEPTION which includes the exception message.</p> <p>NODE_HOST: Indicates which hostname/node the processing took place on. Multiple hosts/nodes in a cluster.</p> <p>NODE_PORT: Indicates the port of the DV server in which the processing took place on.</p> <p><u>TRIGGER:</u></p> <p>/KPImetrics/Physical/Metadata/System/ClusterSafeTriggers/ kpiMetricsTrig_40_Cache_METADATA_TABLES→ Cache_METADATA_TABLES</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, PROJECT_NAME, NODE_HOST, NODE_PORT</p> |
| METADATA_CONST_PATHS METADATA_CONST_PATHS_ARCH | <p>This table contains a list of base project paths that drives all of the metadata capture for all of the tables. Only metadata is captured the project paths present in this table.</p> <p>PROJECT_PATH: A unique key for this table which drives all of the processing for Cache_METADATA_TABLES procedure to load data.</p> <p>RESOURCE_TYPES: TABLE,PROCEDURE,LINK - A comma-separated list of resource types to process.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, PROJECT_PATH, NODE_HOST, NODE_PORT</p> |
| METADATA_CONST_LAYERS METADATA_CONST_LAYERS_ARCH | <p>This table contains the valid layer types for each project path. A layer type has a corresponding parent path within the project path that it correlates to.</p> <p>PROJECT_PATH: Provides a foreign key back to METADATA_CONST_NAME table.</p> <p>LAYER_TYPE: A unique string describing the layer to acquire metadata for.</p> <p>PARENT_PATH: The actual path in DV which is associated with the LAYER_TYPE.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, LAYER_TYPE, NODE_HOST, NODE_PORT</p> |
| METADATA_CONST_VALIDATE METADATA_CONST_VALIDATE_ARCH | <p>This table contains the layer validation rules. The rules provide for enforcing columns within views and which views can invoke views in specific layers.</p> <p>PROJECT_PATH: Provides a foreign key back to METADATA_CONST_NAME table.</p> <p>LAYER_TYPE: A valid layer name found in the table METADATA_CONST_LAYERS.</p> <p>RULE_TYPE: Valid values=[ENFORCE_LAYER ENFORCE_COLUMN]</p> <p>RULE_DESC: Enforce the rule type.</p> <p>When RULE_TYPE=ENFORCE_COLUMN</p> <p>Enforces which columns must be present in all of the views for a given layer type.</p> <p>Comma-separated list of case-sensitive column names.</p> |

| | |
|---|---|
| | <p>When RULE_TYPE=ENFORCE_LAYER</p> <p>Enforces which source layer resource can invoke which target layer resource. Comma-separated list of valid LAYER_TYPES.</p> <p>If a resource can invoke another resource in the same layer then add its own layer to the list.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, LAYER_TYPE, RULE_TYPE, NODE_HOST, NODE_PORT</p> |
| METADATA_RESOURCE METADATA_RESOURCE_ARCH | <p>This is the core table which all other tables reference. This table contains a row for each TABLE and PROCEDURE resource found within the specified PROJECT_PATH in the METADATA_CONST_NAME table.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, NODE_HOST, NODE_PORT</p> |
| METADATA_RESOURCE_COLUMN METADATA_RESOURCE_COLUMN_ARCH | <p>This table contains all of the COLUMNS referenced by the RESOURCE_ID in METADATA_RESOURCE.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, COLUMN_NAME, NODE_HOST, NODE_PORT</p> |
| METADATA_RESOURCE_LINEAGE METADATA_RESOURCE_LINEAGE_ARCH | <p>This table contains the lineage for each resource in each layer. This will be a very large table.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, LINEAGE_ORDER, LAYER_TYPE, NODE_HOST, NODE_PORT</p> |
| METADATA_DATASOURCE METADATA_DATASOURCE_ARCH | <p>This table contains the all of the datasource information for a given project path.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, DATASOURCE_ID, NODE_HOST, NODE_PORT</p> |
| METADATA_NON_COMPLIANT METADATA_NON_COMPLIANT_ARCH | <p>This table contains information on column and layer compliancy based on the METADATA_CONST_VALIDATE rules tables.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, LINEAGE_ORDER, NON_COMPLIANT_REASON, NODE_HOST, NODE_PORT</p> |
| METADATA_POLICY METADATA_POLICY_ARCH | <p>This table contains RBS [rule-based security] and CBS [column-based security] rows for a given project path.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, POLICY_ID, NODE_HOST, NODE_PORT</p> |
| METADATA_POLICY_ASSIGNMNT METADATA_POLICY_ASSIGNMNT_ARCH | <p>This table contains the assignments for a policy.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, POLICY_ID, NODE_HOST, NODE_PORT</p> |
| METADATA_PRIVILEGE METADATA_PRIVILEGE_ARCH | <p>This table contains the assigned privileges for all of the resources in a given project path.</p> <p>KEY: LOAD_DATE, PROJECT_NAME_ID, RESOURCE_ID, NAME, NAME_TYPE, DOMAIN_NAME, USER_NAME, NODE_HOST, NODE_PORT</p> |

Metadata System Triggers and Load Scripts

Location: /shared/ASAssets/KPImetrics/Physical/Metadata/System

/ClusterSafeCache

/ClusterSafeTriggers

/Helpers

This section provides a quick summary of all triggers, their schedules and how they execute in a cluster.

| Trigger Name | Trigger Schedule | Trigger Period | Cluster execution |
|---|------------------|----------------|-------------------|
| kpimetricsTrig_40_Cache_METADATA_TABLES | 2:00 AM | 1 day | all nodes |

This section lists all triggers and load scripts that have been defined to execute various KPImetrics procedures at regular intervals. The default execution frequencies are listed for each trigger. The load scripts have been created to load and aggregate raw data into processed KPImetrics metadata.

| Trigger [schedule] → Script Name → View name | Description |
|---|---|
| Schedule: [1 day, 2:00 am] kpimetricsTrig_40_Cache_METADATA_TABLES → /shared/ASAssets/KPImetrics/Physical/Metadata/System/ClusterSafeCache/Cache_METADATA_TABLES → /shared/ASAssets/KPImetrics/Customize/pqInsert_METADATA_A_Constants | This trigger executes the Cache_METADATA_TABLES procedure. This procedure is used to capture all the metadata for all of the metadata tables. Exceptions: Emails will be sent if there are exceptions. Review the following view (table) for issues: /services/databases/ASAssets/KPImetrics/workflow/vCISWorkflowStatus |