



# PDTool Studio Instaler User Guide

## An Open Source Asset for use with TIBCO® Data Virtualization

**TIBCO Software** empowers executives, developers, and business users with Fast Data solutions that make the right data available in real time for faster answers, better decisions, and smarter action. Over the past 15 years, thousands of businesses across the globe have relied on TIBCO technology to integrate their applications and ecosystems, analyze their data, and create real-time solutions. Learn how TIBCO turns data—big or small—into differentiation at [www.tibco.com](http://www.tibco.com).

<b>Project Name</b>	AS Assets PDTool (Promotion and Deployment Tool)
<b>Document Location</b>	This document is only valid on the day it was printed. The source of the document will be found in the PDTool and PDToolRelease folder ( <a href="https://github.com/TIBCOSoftware">https://github.com/TIBCOSoftware</a> )
<b>Purpose</b>	User's Guide



[www.tibco.com](http://www.tibco.com)

Global Headquarters  
3303 Hillview Avenue  
Palo Alto, CA 94304

Tel: +1 650-846-1000  
+1 800-420-8450  
Fax: +1 650-846-1005

## Revision History

Version	Date	Author	Comments
1.0	09/18/2015	Mike Tinius	Initial revision for Installer User Guide
4.0	12/14/2017	Mike Tinius	Initial revision with Tibco

## Related Documents

Name	Author
PDTool Studio Installer Admin Guide.pdf	Mike Tinius

## Supported Versions

Name	Version
TIBCO® Data Virtualization	7.0.4 or later

## Table of Contents

<b>1</b>	<b>Introduction.....</b>	<b>4</b>
	Purpose.....	4
	Audience.....	4
	Platform Support.....	4
	References.....	5
<b>2</b>	<b>PDTool Studio (VCS Integration) Installer User Guide.....</b>	<b>6</b>
	Pre-Requisite Checklist.....	6
1.	Network Connection:.....	6
2.	JRE7 Installed:.....	6
3.	Version Control System (VCS) Access:.....	6
4.	Pre-Configured PDTool Studio Installer:.....	6
	User Installation Procedure.....	6
1.	Unzip the PDTool Studio Installer Zip File:.....	6
2.	Close DV Studio:.....	6
3.	Install DV PDTool Studio:.....	7
4.	User Prompts:.....	7
5.	What Gets Executed?.....	10
6.	Logging into DV Studio “Important”:.....	10
7.	Managing Errors:.....	10
8.	Verify Installation:.....	11
<b>3</b>	<b>Conclusion .....</b>	<b>12</b>
	Concluding Remarks.....	12
	How you can help!.....	12

# 1 Introduction

## Purpose

The User Guide provides a PDTool Studio User with the steps to install PDTool Studio on Windows using the PDTool Studio Installer.

This is the part of PDTool that provides VCS integration with Data Virtualization (DV) Studio. The other part of PDTool is simply called PDTool and is focused on deployment and testing facilities. PDTool operates with Data Virtualization (DV) 7.0.

### What gets installed?

- PDToolStudio6.2 or PDToolStudio7.0.0
- VCS Client if the Administrator chooses to pre-configure the \VCSClients folder

### Where do the files get copied?

- Recommended default location:  
C:\Users\%USERNAME%\compositesw\PDToolStudio[6.2|7.0.0]\_[TFS|SVN|GIT|P4|CVS]
  - E.g. C:\Users\user1\compositesw\PDToolStudio7.0.0\_TFS
  - **\PDToolStudio** – PDToolStudio VCS integration directory
  - **\VCSClients** – Pre-configured VCS clients are optional if installed elsewhere.
    - **\SVN\_client** – Subversion client
    - **\TFS\_TEE\_client** – Team Explorer Everywhere client
    - **\GIT\_client** – Git client
    - **\P4\_client** – Perforce client
    - **\CVS\_client** – CVS client

## Audience

This document is intended to provide guidance for the following users:

- Architects – who want to understand how PDTool is used with Data Virtualization.
- Developers – who want to deploy resources from a version control system (VCS) such as TFS or Subversion to a target DV server.
- Administrators – who need to manage setup and connection with the Data Virtualization environment.
- Operations personnel – who wants to encrypt a PDTool file which contains passwords.

## Platform Support

The PDTool Studio Installer is only supported on Windows.

## References

Product references are shown below. Any references to CIS or DV refer to the current TIBCO® Data Virtualization.

- TIBCO® Data Virtualization was formerly known as
  - Cisco Data Virtualization (DV)
  - Composite Information Server (CIS)

## 2 PDTool Studio (VCS Integration) Installer User Guide

### Pre-Requisite Checklist

The following is a list the User will need to check before installing for PDToolStudio:

#### 1. Network Connection:

Each user must be connected to a network and have access to the VCS server.

#### 2. JRE7 Installed:

JRE 7 (1.7) must be pre-installed on the target computer before installing PDTool. Each user must perform this action.

If DV Studio 7.0 is installed, it is possible to utilize that JRE: CIS\_HOME\jre or you can use the one installed in the "C:\Program Files\Java\jre7".

#### 3. Version Control System (VCS) Access:

Each user must perform this action.

The user must submit a request in advance to their organization to get access to a version control system (VCS) repository prior to installation of PDTool.

#### 4. Pre-Configured PDTool Studio Installer:

The PDTool Studio Administrator has "pre-configured" the PDTool Studio Installer and provided the location of the zip file to the user.

### User Installation Procedure

#### 1. Unzip the PDTool Studio Installer Zip File:

- a. This is the package that the Administrator has "pre-configured" for the organization. Unzip to any directory on your windows machine e.g. [C:\Temp].

- i. PDToolStudio6.2\_installer.zip
- ii. PDToolStudio7.0.0\_installer.zip

- b. Use PKZip and select "Extract Here" which will extract the file to the C:\Temp directory as shown below. If you use the Windows "Extract All", then it is recommended to remove the trailing folder

- i. Location: C:\Temp\PDToolStudio6.2\_Installer
- ii. Location: C:\Temp\PDToolStudio7.0\_Installer

#### 2. Close DV Studio:

- a. Make sure **ALL** DV Studios are closed before proceeding.

### 3. Install DV PDTool Studio:

- a. *Purpose* – The purpose of this is to install the “pre-configure” batch files for your organization so that you have a consistent and uniform configuration across the developer and tester user base.
- b. *Location*
  - a. [C:\Temp]\PDToolStudio6.2\_installer\installer
  - b. [C:\Temp]\PDToolStudio7.0.0\_installer\installer
- c. **For any VCS [TFS,SVN,GIT,P4,CVS] Execute:**
  - Edit: **PDToolStudio-VCS.bat** and provide any default values that require modification. The variables should have been pre-configured by the PDTool Studio administrator.
  - Execute by **double-clicking** on the following batch file from windows explorer:
 

**PDToolStudio-VCS.bat**

    - Acknowledge Open Source License
    - Follow the “Prompts” section below for detailed information.

### 4. User Prompts:

- a. *Purpose* – The user is prompted for the following parameters unless this information is provided as parameters on the command line. The **default values are provided within the square brackets**. Press enter with no input to accept the default value or type your value and press enter.
- b. *Prompts:*

Enter I\_PDTool\_INSTALL\_SCRIPTS=[%DEF\_PDTool\_INSTALL\_SCRIPTS%]:

  - Location of the PDTool installation scripts. E.g.  
C:\Temp\PDToolStudio7.0.0\_installer

License Acknowledgement

  - Use space bar to page through license
  - Review and acknowledge the open source license [Y].

Enter I\_JAVA\_HOME=[%DEF\_JAVA\_HOME%]:

  - I\_JAVA\_HOME=JRE7 home folder. E.g. C:\Program Files\Java\jre7

Enter  
I\_PDTool\_DESTINATION\_HOME=[%DEF\_PDTool\_DESTINATION\_HOME%]:

- I\_PDTool\_DESTINATION\_HOME - The destination home folder for the PDTool installation and associated binaries.
- TFS: C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_TFS
- SVN: C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_SVN
- GIT: C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_GIT
- P4: C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_P4
- CVS: C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_CVS

Enter I\_PDTool\_DESTINATION\_DIR=[%DEF\_PDTool\_DESTINATION\_DIR%]:

- The destination directory name for the PDTool Studio installation and associated binaries. e.g. PDToolStudio

Enter I\_OVERWRITE\_DECISION=[N]:

- This prompt only comes up when the target PDTool directory exists. It allows the user to decide whether they want to overwrite that directory or not. Enter Y to overwrite the existing directory.

Enter I\_VCS\_TYPE=[%DEF\_VCS\_TYPE%]:

- I\_VCS\_TYPE - The version control type [TFS|SVN|GIT|P4|CVS]

Enter I\_VCS\_HOME=[%DEF\_VCS\_HOME%]:

- This is the location of the VCS script executable. E.g.  
C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\_SVN\VCSClients\SVN\_client

Enter I\_VCS\_REPOSITORY\_URL=[%DEF\_VCS\_REPOSITORY\_URL%]:

- Note: make sure the forward slashes are escaped with 4 slashes:  
https://url
- TFS: The TFS repository URL pointing to the repository collection.  
e.g. http://hostname.domain.com/tfs/DefaultCollection
- SVN: The subversion repository path at trunk or any folder designation within trunk. e.g.  
https://svn.hostname.com/svnrepos/myrepo/trunk/main

Enter I\_VCS\_PROJECT\_ROOT=[%DEF\_VCS\_PROJECT\_ROOT%]:

- E.g. SVN: cis\_objects

Enter I\_VCS\_USERNAME=[%USERNAME%]:

- This is your user name regardless of whether it is TFS or Subversion and is used to connect to the VCS repository. The



user must submit a request to get access to a repository prior to installation of PDTool.

Enter I\_VCS\_DOMAIN=[%DEF\_VCS\_DOMAIN%]:

- When using TFS, include the VCS domain such as “@CORP”. The result for the I\_VCS\_USERNAME would look like “username@CORP”. When using subversion, put a single space in the domain so that the script accepts this and continues. The script will remove the space later on. The I\_VCS\_DOMAIN will be automatically appended to I\_VCS\_USERNAME.

Enter I\_VCS\_PASSWORD=<type-your-vcs-password>

- This is your VCS password which will be encrypted.

Enter I\_WORKSPACE\_NAME=[%DEF\_VCS\_WORKSPACE\_NAME%]:

- The PDToolStudio VCS workspace name such as SVNsw7 or TFSsw7.

Enter I\_CIS\_USERNAME=[%USERNAME%]:

- This is your user name regardless that will be used to connect to DV.

Enter I\_CIS\_DOMAIN=[%DEF\_CIS\_DOMAIN%]:

- This is the DV domain which is used by the I\_CIS\_USERNAME to connect to DV. E.g. ldap or composite

Enter I\_CIS\_PASSWORD=<type-your-cis-password>

- This is your password which will be encrypted.

Enter I\_CONFIG\_PROPERTY\_FILE=[%DEF\_CONFIG\_PROPERTY\_FILE%]

- This is the default PDTool Studio configuration property file that the user will use to set the context for which VCS environment to connect to. E.g. studio\_SVN.properties or studio\_TFS.properties.

The variables are displayed

Enter I\_VARS\_DECISION [Y or N] – If “Y”, then installation commences. If “N” then the user is prompted for the variables again.

Confirmation of the network drive letter is provided

Existing PDTOOL\_SUBSTITUTE\_DRIVE=<drive\_letter>:

PDTool network substitute drive letter.

Objective: Used to shorten the overall path to workspace folder mainly for TFS.

Do you want to use the substitute drive letter="<drive\_letter>:" [Y or N]:  
Installation proceeds after this point.

## 5. What Gets Executed?

- a. Copy source files to destination folder
- b. For TFS only, TFS eula –accept
- c. Encrypt passwords:  
C:\Users\%USERNAME%\compositesw\PDToolStudio<ver>\_<vcs>\setMyPrePDToolStudioVars.bat
- d. Enable VCS:  
C:\Users\%USERNAME%\compositesw\<USERNAME>.<domain>.<cishost>.properties
- e. Initialize workspace (requires the VCS credentials and repository URL).

## 6. Logging into DV Studio “Important”:

- a. The developer will use the same host name that was provided by the default “DEF\_CIS\_HOST” or the prompt “I\_CIS\_HOST” and the domain “DEF\_CIS\_DOMAIN” or the prompt “I\_CIS\_DOMAIN”.
- b. The reason is that the combination of the username + domain + exact hostname is used to configure the DV Studio properties file in the .compositesw directory. This gets used to configure the VCS integration for Studio which is found in Studio under “Edit→Options” tab.

## 7. Managing Errors:

- a. If there are any errors reported in the scripts especially during workspace initialization, try removing the workspace directory and then re-execute the installation script.
- b. If there is an error while trying to create a substitute drive then first trying removing the substitute drive which was identified as available in the script.
  - i. net use <drive>: /DELETE
- c. If DV Studio 6 or 7 throws this error during check-in, simply retry the check-in.
  - i. Encountered a problem during vcs export.  
C:\Users\%USERNAME%\compositesw\.vcs\_temp\_folders\vcs\_export.zip (Access is denied)
  - ii. Additionally, you can manually delete the folder  
“C:\Users\%USERNAME%\compositesw\.vcs\_temp\_folders” and try again.

## 8. Verify Installation:

- a. Open DV Studio and go to the Edit Menu and then Options
  - i. Verify that the “Enable VCS” section is set correctly.
  - ii. Example: Your paths may be different depending on the location and VCS type chosen.
 

```
vcsIncludeResourceSecurity=true
enableVCS=true
vcsWorkspacePath=
C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0_TFS\PDToolStudio\
TFSsw\cis_objects
vcsScriptFolder=
C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0_TFS\PDToolStudio\
bin
```
  - i. Verify that the corresponding property file was created in the file system for “Enable VCS”:
    1. C:\Users\%USERNAME%\compositesw\<USERNAME>.<domain>.<cis>.properties
  - ii. Alternative approach: Modify with a script

### Example:

```
ExecutePDToolStudio.bat -nopause -enablevcs -winlogin %USERNAME% -user
%USERNAME% -domain ldap -host hostname.com -includeResourceSecurity true
-vcsWorkspacePathOverride
"C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0\PDToolStudio\TFS
sw\cis_objects"
```

- b. Verify that the workspace was created properly

### Example:

```
C:\Users\%USERNAME%\compositesw\PDToolStudio7.0.0_TFS\PDToolStudio\TFSsw\
cis_objects
```

- c. Check-in a resource
  - i. Locate a single resource within /shared folder structure to serve as an example to test the check-in capability.
  - ii. Right-click on the resource and select “Check-in to VCS”
  - iii. Type “update” in the box
  - iv. Click OK
  - v. A window pops up – scroll to the bottom and look for the word “SUCCESSFUL”

**FINISHED**

## 3 Conclusion

### Concluding Remarks

The Promotion and Deployment Tool is a set of pre-built modules intended to provide a turn-key experience for promoting DV resources from one DV instance to another. The user only requires system administration skills to operate and support. The code is transparent to operations engineers resulting in better supportability. It is easy for users to swap in different implementations of a module using the Spring framework and configuration files.

### How you can help!

Build a module and donate the code back to Professional Services for the advancement of the “**Promotion and Deployment Tool**”.