



## ***Advanced Service Assets***

### ***“PDTool” Promotion and Deployment Tool***

### ***Regression Automated Test Framework***

Data Virtualization Business Unit Advanced Services

June 2015

## TABLE OF CONTENTS

<b>INTRODUCTION .....</b>	<b>4</b>
License .....	4
Purpose.....	4
Audience .....	4
Platform Support.....	4
<b>PDTOOL REGRESSION AUTOMATED TEST FRAMEWORK .....</b>	<b>5</b>
Introduction.....	5
1. Functional Test (Generate and Execute):.....	5
2. Migration or Regresion Test (Data set and Log Comparison):.....	5
3. Performance Test (Log Comparison): .....	5
4. Security Test (Users and Privileges):.....	5
Folder Structure .....	5
The Scripts .....	6
Getting Started .....	6
Script Framework – Template Generation Scripts.....	8
Script Framework – Baseline Execution Scripts .....	9
Script Framework – “Test Type” Execution Scripts.....	11
Script Framework – Documentation .....	12
Script Framework – Log .....	12
Script Framework – Plans .....	13
Script Framework – Modules.....	13
Script Framework – SQL Queries.....	14
Script Framework – Output .....	14
Security Test Configuration.....	17
<b>INSTALLATION AND CONFIGURATION.....</b>	<b>24</b>
Introduction.....	24
Planning .....	24
Installation and Configuration Setup .....	24
Sample Installation.....	26
<b>CHANGING THE PDTOOL PASSWORD .....</b>	<b>29</b>
Introduction.....	29
PDTool 6.2.....	29
PDTool 7.0.....	29
<b>CONCLUSION .....</b>	<b>31</b>
Concluding Remarks.....	31
How you can help!.....	31

## DOCUMENT CONTROL

### Version History

Version	Date	Author	Description
1.0	06/11/2015	Mike Tinius	Initial revision for Regression Module Automated Test Framework

### Related Documents

Document	Date	Author
<i>Cisco AS Promotion and Deployment Tool Module - Regression</i>	<i>Cisco AS Promotion and Deployment Tool Module - Regression.pdf</i>	Mike Tinius

### Data Virtualization Business Unit (DVBU) Products Referenced

DVBU Product Name	Version
Composite Information Server	6.2, 7.0

---

## INTRODUCTION

### *License*

(c) 2015 Cisco and/or its affiliates. All rights reserved.

This software is released under the Eclipse Public License. The details can be found in the file LICENSE. Any dependent libraries supplied by third parties are provided under their own open source licenses as described in their own LICENSE files, generally named .LICENSE.txt. The libraries supplied by Cisco as part of the Composite Information Server/Cisco Data Virtualization Server, particularly csadmin-XXXX.jar, csarchive-XXXX.jar, csbase-XXXX.jar, csclient-XXXX.jar, cscommon-XXXX.jar, csext-XXXX.jar, csjdbc-XXXX.jar, csserverutil-XXXX.jar, csserver-XXXX.jar, cswebapi-XXXX.jar, and customproc-XXXX.jar (where -XXXX is an optional version number) are provided as a convenience, but are covered under the licensing for the Composite Information Server/Cisco Data Virtualization Server. They cannot be used in any way except through a valid license for that product.

This software is released AS-IS!. Support for this software is not covered by standard maintenance agreements with Cisco. Any support for this software by Cisco would be covered by paid consulting agreements, and would be billable work.

### *Purpose*

The purpose of the Regression Module “**Regression Automated Test Framework**” is to make it easier to utilize the PDTool Regression Module testing capability by generating the necessary PDTool plans and module files. The focus of these scripts is on regression testing on a single CIS platform and performing comparisons from one CIS code release to another.

### *Audience*

This document is intended to provide guidance for the following users:

- Architects
- Developers
- QA Testers.

### *Platform Support*

The Automated Test Framework is only supported on Windows.

## PDTOOL REGRESSION AUTOMATED TEST FRAMEWORK

### *Introduction*

Regression testing is the act of testing a CIS code release and comparing that release with the previous release.

This framework provides a way to accomplish automated testing for Cisco Information Server 6.2 and 7.0 published resources including Views, Procedures and Web Services. This framework is based on the Cisco Advanced Services PDTool Deployment and Regression Testing tool. Documentation for the PDTool can be found within the PDTool installation “docs” directory and the file “Cisco AS Promotion and Deployment Tool Module - Regression.pdf”. There are several types of tests that can be performed with this framework including:

1. *Functional Test (Generate and Execute):*

This represents the current functionality which tests whether the published view, procedure or web service is functional or not. All that is necessary for this test is to execute a `SELECT COUNT(1) cnt FROM <view>` or `SELECT COUNT(*) cnt FROM <procedure>` to prove that the view or procedure is functional. This type of test is also known as a “smoke” test.

2. *Migration or Regression Test (Data set and Log Comparison):*

The PD Tool Regression Module will help Administrators during Migrations from one version of CIS to another by performing the regression testing on the new version of CIS or by performing a Regression test against two releases of a project. These tests are functionally the same. The caveat to this test is that the result sets used for comparison must be derived from the same data sources. Any changes in data values may result in differences in result set and thus comparisons will not be equal.

3. *Performance Test (Log Comparison):*

The PD Tool Regression Module can be used by QA to perform performance tests against views, procedures and web services. The two logs generated during the query execution are compared to determine success or failure based on a duration comparison.

4. *Security Test (Users and Privileges):*

The PD Tool Regression Module can be used by QA to perform security tests. The security test correlates users with functional test queries. It provides a way to test the expected outcome for a given user and query to determine if the test results in a PASS or FAIL. All tests are executed and an overall result of PASS or FAIL is awarded. The security test can be configured to throw an exception upon an overall status of FAIL.

### *Folder Structure*

The following screenshot shows the “**Regression Automated Test Framework**” folder structure. This testing framework provides a wrapper around the Cisco Advanced Services PDTool capability. It allows for an automation of a CIS Business Line/Business Area as defined by the user.

It provides a central place for documentation, logs, reports, output and PDTool scripts. This is a cookie-cutter (repeatable) approach to testing. As such there is a templates folder and a script that is used to generate the testing artifacts for a given Business Line/Business Area. The template scripts generate the “docs”, “modules”, and “plans” that PDTool uses. The “**Regression Automated Test Framework**” folder structure is as follows:




Image 2: Regression Automated Test Framework Folder Structure

### *The Scripts*

The scripts in “**/bin**” provide the basis for the automation. The scripts will be defined in a later section.




Image 3: Regression Automated Test Framework Scripts

### *Getting Started*

This section discusses how to get started with the basics of testing.

## Testing CIS Published Resources:

### Requirements:

- For CIS 6.2, PDTool 6.2 is required to be installed.
- For CIS 7.0, PDTool 7.0.0 is required to be installed.

### Planning

- It is important to plan ahead when using the “**Regression Automated Test Framework**”. The following section will help the test user prepare: [Planning](#)

### Installation and Configuration Setup

- Some post-installation configuration is required to use the “**Regression Automated Test Framework**”. The following section provides the details: [Installation and Configuration Setup](#)
- Details for installing the sample can be found here: [Sample Installation](#)

### Generate Test Scripts

- Determine the name to give to the set of published views that you want to test. Typically this is known as the “Business Line / Business Area / Subject Area”. The scripts will be based on this nomenclature. The name is required to be unique across all other names in use because it is used to generate the scripts.
- Use the script “**copyPlanTemplates.bat**” to generate the necessary PDTool plans and module files. More information can be found in this section of this document: [Script Framework – Template Generation Scripts](#).
- Save a list of all of your names using “**copyAllPlanTemplates.bat**” so that you can regenerate all of plans and modules at once if required.

### Determine which CIS environment “ENV” you are going to execute against such as:

- Example: DEV, UAT, PROD.
- These environments are defined by the CIS Administrator.

### Determine which Business Line / Business Area you are testing.

- Open the generated documentation in /docs for your Business Line /Business Area.
- E.g. \docs\ documentation\_MyProject1SubProj.txt

### Determine which type of test you want to execute.

- Smoke Test Generation
- Smoke Test Execution
- Regression Test Execution
- Regression Test Comparison
- Performance Test Execution
- Performance Test Comparison



- Security Test Generation
- Security Test Execution

Refer to \docs\documentation\_BusLineBusArea.txt or the example in this document.

Reference this document: [Script Framework – “Test Type” Execution Scripts](#)

Execute the test

Refer to the parameters for script execution. Set the RENAME\_REL=false if you want a series of tests to go to the same release folder.

Reference this document: [Script Framework – Baseline Execution Scripts](#)

**Example Scenario:** Test 2: Execute Regression Test for UAT 6.2 and MyProject using TOP SQL queries and force the test output to go into the existing “626R1” release folder without renaming it.

`script_test_62.bat UAT MyProject1SubProj_2Regression_exec.dp TOP false true`

### ***Script Framework – Template Generation Scripts***

The scripts located in “/bin” provide the basis for generating the automation scripts from templates.

**copyPlanTemplates.bat** – The purpose of this batch file is to make it easy to copy a single plan template for doing regression testing. The premise of this script is to prepare all of the necessary PDTool plans, modules and docs for a given Business Line / Business Area for all of the various PDTool Regression Module tests including: Smoke, Regression, Performance and Security.

1. copyPlanTemplates.bat [BusLineBusAreaSubjArea] [DATA\_SOURCE\_NAME] [RESOURCE\_NAME] [false]
  - a. BusLineBusAreaSubjArea - The BusLineBusAreaSubjArea is the portion of the deployment plan file name that occurs prior to the mandatory test type descriptor.
    - i. Affix any prefix or postfix desired to BusLineBusAreaSubjArea such as prefix\_BusLineBusAreaSubjArea\_postfix
    - ii. **Test type descriptor:** \_1Smoke\_gen.dp, \_1Smoke\_exec.dp, \_2Regression\_exec.dp, \_2Regression\_compare.dp, \_3Performance\_exec.dp, \_3Performance\_compare.dp, \_4Security\_gen.dp, \_4Security\_exec.dp
    - iii. **Example constructed Deployment plan:**  
prefix\_MyProject1\_MySubject\_post\_3Performance\_exec.dp
    - iv. |\_\_\_\_BusLineBusAreaSubjArea\_\_\_\_|
    - v. |\_\_\_\_\_Deployment Plan File Name\_\_\_\_\_|
  - b. DATA\_SOURCE\_NAME - This is published Composite data source to connect to for generating or executing queries.
  - c. RESOURCE\_NAME - This may be CATALOG.SCHEMA.\* or it may just be CATALOG.\*. This is the filter based on Business Line and Business Area.



The asterisk indicates a wildcard and is used to specify any views that are published in the location of the preceding resource name.

- d. PROMPT\_USER - when doing automated set PROMPT\_USER=false so that it does not prompt the user to edit the Regression Module XML file.

2. Example1: *Test all views from all FooCat catalog schemas in the same framework*

- a. Create a the regression test framework for a new Business Line / Business Area called “Foo” with a published catalog called FooCat in the “MY DB” database. The catalog contains multiple schemas FooSch1 and FooSch2 and the user wants to be able to test all views from all schemas from the same test framework.

- b. copyPlanTemplates.bat Foo “MY DB” FooCat.\* true

3. Example2: *Test views from each FooCat catalog schema separately in different frameworks.*

- a. Create a the regression test framework for a new Business Line / Business Area called “Foo” with a published catalog called FooCat in the “MY DB” database. The catalog contains multiple schemas FooSch1 and FooSch2 and the user wants to be able to test the views for each schema independently of the other schema. To accomplish this we will setup two test frameworks

- b. copyPlanTemplates.bat FooSch1 “MY DB” FooCat.FooSch1.\* true

- c. copyPlanTemplates.bat FooSch2 “MY DB” FooCat.FooSch2.\* true

**copyAllPlanTemplates.bat** – The purpose of this batch file is to make it easy to copy “ALL” of the regression test Business Line / Business Areas at one time specified in the “copyAllPlanTemplates.bat” file. This batch file will overwrite existing deployment plans (/plans), module XML files (/modules) and docs files (/docs).

### ***Script Framework – Baseline Execution Scripts***

The scripts located in “/bin” provide the basis for executing PDTTool standard scripts.

These scripts provide a wrapper around the actual PDTTool scripts. They provide context for the environments [DEV, UAT, PROD]. They output the logs for each execution into /logs directory according to each type of test so that the log is retained across different types of tests.

#### Types of scripts

**script\_test\_62.bat** – Provides an instance of execution for PDTTool6.2. Requires its own installation of PDTTool6.2. This script can only be run from a single command line window at one time. It cannot be run in parallel from two different command line windows.

**script\_test\_70.bat** – Provides an instance of execution for PDTTool7.0.0. Requires its own installation of PDTTool7.0.0. This script can only be run from a single command line window at one time. It cannot be run in parallel from two different command line windows.

### Command Line:

`script_test_NN.bat ENV_TYPE DEPLOYMENT_PLAN [CUSTOM] [RENAME_REL] [PAUSE]`

### Parameters:

*ENV\_TYPE* – Example: [DEV|UAT|PROD]

1. The valid values are defined as a result of the variable:  
VALID\_ENV\_CONFIG\_PAIRS

*DEPLOYMENT\_PLAN* - The name of the deployment plan such as:

1. BusLineBusArea\_1Smoke\_gen.dp
2. BusLineBusArea\_1Smoke\_exec.dp
3. BusLineBusArea\_2Regression\_exec.dp
4. BusLineBusArea\_2Regression\_compare.dp
5. BusLineBusArea\_3Performance\_exec.dp
6. BusLineBusArea\_3Performance\_compare.dp
7. BusLineBusArea\_4Security\_gen.dp
8. BusLineBusArea\_4Security\_exec.dp

*CUSTOM* – [optional] variable

1. blank or "" – [default]. Generate or execute using SQL SELECT COUNT(1) cnt or SELECT COUNT(\*) cnt.
2. TOP - If the word TOP is provided then generate or execute using the SELECT TOP 1 \* command. Top is a special type of CUSTOM.
3. CUSTOM value - If any other word is used then execute the SQL file using this pattern and the value of the CUSTOM variable:

Example: Developer creates a custom SQL file where the custom name = MyQueries

Template:

Example:

`\\sql\BusLineBusArea_RegressionTest_SQL_%CUSTOM%.txt = \\sql\MyProject_RegressionTest_SQL_MyQueries.txt`  
`\\sql\BusLineBusArea_PerfTest_SQL_%CUSTOM%.txt = \\sql\MyProject_PerfTest_SQL_MyQueries.txt`

*RENAME\_REL* – [optional] variable. Default=true

1. blank or "" or true - force a rename of the release output folders upon each execution of this script.
2. false - disable the rename function and allow the results to go to the existing RELEASE\_FOLDER1 directory.

Example. This can be useful when executing a series of tests for the same release such as the following: Smoke Test, Regression Test, Performance Test and Security Test.

Note: This script will automatically ignore renaming the output folder for the following and thus the RENAME\_REL does not have to be set.

Generating Smoke Test, Compare Regression Test, Compare Performance Test and Generate Security Test.

*PAUSE* – [optional] variable. Default=true

1. blank or "" or true - pause during script execution.
2. false - no pause during script execution.

#### Exiting a script

**How to exit a script** – Use Control-C to exit a script. Type Y and return to exit. If the script is in the middle of executing and you press Control-C the prompt will not be visible. Type “Y” and press the return key to exit the script.

#### ***Script Framework – “Test Type” Execution Scripts***

The scripts provide the basis for executing PDTool standard scripts.

Script framework “test type” single execution scripts

The section provides information on how to run a single specific type of test. The optional parameters at the end indicate whether to use the SQL queries containing CUSTOM queries or not. The keyword TOP is classified as a special kind of CUSTOM query that allows the user to execute queries such as “SELECT TOP 1 \* “. The user may wish to specify other CUSTOM keywords that relate to SQL query files where the user has populated the file with their own queries. If no CUSTOM option is provided, then the “SELECT COUNT(1)” queries are used.

Additionally there is an option for RENAME\_REL and PAUSE set to true or false following CUSTOM. RENAME\_REL informs the script to rename the release folder or not. If RENAME\_REL=false then the user can force the output for a series of tests to be placed into the RELEASE\_FOLDER1 which is defined within the script execution batch files [script\_test\_62.bat and script\_test\_70.bat].

PAUSE informs the scripts to pause before execution so that the user can see what variables are set before continuing.

Test 1: Generate Smoke Test SQL for ENV

script\_test\_62.bat ENV BusLineBusArea\_1Smoke\_gen.dp "" "" [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_1Smoke\_gen.dp "" "" [PAUSE]

Test 1: Execute Smoke Test for ENV

script\_test\_62.bat ENV BusLineBusArea\_1Smoke\_exec.dp "" [RENAME\_REL] [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_1Smoke\_exec.dp "" [RENAME\_REL] [PAUSE]

Test 2: Execute Regression Test for ENV

script\_test\_62.bat ENV BusLineBusArea\_2Regression\_exec.dp [CUSTOM] [RENAME\_REL] [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_2Regression\_exec.dp [CUSTOM] [RENAME\_REL] [PAUSE]

Test 2: Execute Regression Test Compare for ENV - Compare files and logs for difference

script\_test\_62.bat ENV BusLineBusArea\_2Regression\_compare.dp [CUSTOM] "" [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_2Regression\_compare.dp [CUSTOM] "" [PAUSE]

Test 3: Execute Performance Test for ENV

script\_test\_62.bat ENV BusLineBusArea\_3Performance\_exec.dp [CUSTOM] [RENAME\_REL] [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_3Performance\_exec.dp [CUSTOM] [RENAME\_REL] [PAUSE]

Test 3: Execute Performance Test Compare for ENV - Compare logs for difference

script\_test\_62.bat ENV BusLineBusArea\_3Performance\_compare.dp [CUSTOM] "" [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_3Performance\_compare.dp [CUSTOM] "" [PAUSE]

Test 4: Generate Security Test for ENV

script\_test\_62.bat ENV BusLineBusArea\_4Security\_gen.dp "" "" [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_4Security\_gen.dp "" "" [PAUSE]

Test 4: Execute Security Test for ENV

script\_test\_62.bat ENV BusLineBusArea\_4Security\_exec.dp "" [RENAME\_REL] [PAUSE]

script\_test\_70.bat ENV BusLineBusArea\_4Security\_exec.dp "" [RENAME\_REL] [PAUSE]

### **EXAMPLE 1:**

Scenario: Test 2: Execute Regression Test for UAT 6.2 and MyProject using TOP SQL queries and force the test output to go into the existing “626R1” release folder without renaming it.

script\_test\_62.bat UAT MyProject1SubProj\_2Regression\_exec.dp TOP false true

### **EXAMPLE 2:**

Scenario: Test 2: Execute Regression Test for UAT 6.2 and MyProject using custom SQL queries and force the test output to go into a new “626R1” release folder.

script\_test\_62.bat UAT MyProject1SubProj\_2Regression\_exec.dp MyCustom ""

## ***Script Framework – Documentation***

The “/docs” folder contains all of the Business Line / Business Area generated documentation for all of the tests. It was prepared by the “**copyPlanTemplates.bat**” script. The file “**Regression Test Summary.xlsx**” provides a place to tally test results.




Image 4: Documentation for Business Line / Business Area

## ***Script Framework – Log***

The “/logs” folder contains output for a given CIS version, environment, Business Line/Area, Test Type and SQL test type. In the screenshot below each part of the log file path is described. This allows for a high degree of naming so that the logs can be preserved across different test types. However, if the exact same test is run again then it will overwrite an existing log of the same name.

PDTool Config	Environment	Business Line/Bus Area	Test Type	SQL Type
deploy_7.0.1_UAT_MyProject1SubProj_1Smoke_gen.log				
deploy_7.0.1_UAT_MyProject1SubProj_1Smoke_gen_TOP.log				
deploy_7.0.1_UAT_MyProject1SubProj_2Regression_compare.log				
deploy_7.0.1_UAT_MyProject1SubProj_2Regression_compare_TOP.log				
deploy_7.0.1_UAT_MyProject1SubProj_2Regression_exec.log				
deploy_7.0.1_UAT_MyProject1SubProj_2Regression_exec_TOP.log				
deploy_7.0.1_UAT_MyProject1SubProj_3Performance_compare.log				
deploy_7.0.1_UAT_MyProject1SubProj_3Performance_compare_TOP.log				
deploy_7.0.1_UAT_MyProject1SubProj_3Performance_exec.log				
deploy_7.0.1_UAT_MyProject1SubProj_3Performance_exec_TOP.log				
deploy_7.0.1_UAT_MyProject1SubProj_4Security_exec.log				
deploy_7.0.1_UAT_MyProject1SubProj_4Security_gen.log				

Image 5: Log Naming Conventions

### Script Framework – Plans

The “/plans” folder contains all of the deployment plan files for all of the tests. It was prepared by the copyAllPlanTemplates.bat script.

MyProject1SubProj_1Smoke_exec.dp
MyProject1SubProj_1Smoke_gen.dp
MyProject1SubProj_2Regression_compare.dp
MyProject1SubProj_2Regression_exec.dp
MyProject1SubProj_3Performance_compare.dp
MyProject1SubProj_3Performance_exec.dp
MyProject1SubProj_4Security_exec.dp
MyProject1SubProj_4Security_gen.dp

Image 6: Deployment Plan Files

### Script Framework – Modules

The “/modules” folder contains all of the deployment module files for all of the tests. It was prepared by the copyAllPlanTemplates.bat script.

generated
MyProject1SubProj_RegressionModule.xml
MyProject2SubProj_RegressionModule.xml

Image 7: Deployment Module Files

### *Script Framework – SQL Queries*

The “/sql” folder contains all of the SQL query files for all of the tests. The Smoke test files were generated. The Regression and Performance files were prepared manually so that the tester can control what they want to test. Custom queries can be provided or the tester can copy and paste from the Smoke Test query set. For custom files add a custom name following “SQL\_” as shown below in a file name such as “MyProject1SubProj\_RegressionTest\_SQL\_**MyCustom**.txt”. Not “\_TOP” is a special kind of custom file that contains “select TOP 1 \*” queries.




Image 8: SQL Query Files

### *Script Framework – Output*

The “/output” folder contains a folder for each Business Line / Business Area. That subfolder contains the result logs for each test type as well as subfolders for the regression tests which contain the data files for each query.




Image 9: Output Folders

For example, let's use MyProject1SubProj as a guide. The screen shot below shows several release folders for both 6.2 and 7.0. The folder “701R1” is the RELEASE\_FOLDER1 and “701R2” is RELEASE\_FOLDER2 as specified in the script execution batch files. The folders with “.0001” and so on represent the archive of the “701R2” folders:




Image 10: Contents of a Business Line / Business Area Folder

The screen shot below shows an example of the content of a release folder such as “701R1” or “701R2”. The release folder contains one or more logs and sub-folders where the query output is stored for each test type segregated by environment type. All log files are prefixed with the environment type so that any given release can be tracked across multiple CIS environments.




Image 11: Contents a release folder such as “701R1” or “701R2”

#### Description of the various log files

**ENV\_PerfTest.log or ENV\_PerfTestTOP.log** – This is the performance test log for a given release [701R1] as a result of executing regular queries or TOP-n queries. It logs the duration of execution for each thread along with the query executed over a defined period of time. It logs any errors that occur.



---

**ENV\_PerfTest\_CompareLogs.log or ENV\_PerfTestTOP\_CompareLogs.log** – Provides a comparison between two different releases [701R1 and 701R2] for a given CIS version of performance logs for regular or TOP-n queries to determine [for the same query] the following:

- Duration matched (same)
- Duration improved (performance improved)
- Duration was within acceptable range (user defined)
- Duration exceeded range

**ENV\_RegressionTest.log or ENV\_RegressionTestTOP.log** – This is the regression test log for a given release [701R1] as a result of executing regular queries or TOP-n queries. It only executes the query once. It logs duration of execution for each query along with the query executed. It logs any errors that occur.

**ENV\_RegressionTest\_CompareFiles.log or ENV\_RegressionTestTOP\_CompareFiles.log** – Provides a comparison between two different releases [701R1 and 701R2] for a given CIS version of data files for regular or TOP-n queries to determine [for the same query] whether the files are an exact match or not. If the row-by-row checksums match then the query is marked with “SUCCESS” otherwise it is marked with “FAILURE”. The key to this test is to test against the same data set for both releases [701R1 and 701R2].

**ENV\_RegressionTest\_CompareLogs.log or ENV\_RegressionTestTOP\_CompareLogs.log** – Provides a comparison between two different releases [701R1 and 701R2] for a given CIS version of regression logs for regular or TOP-n queries to determine [for the same query] the following:

- Duration matched (same)
- Duration improved (performance improved)
- Duration was within acceptable range (user defined)
- Duration exceeded range

#### **Regression Test Data Files:**

The screen shot below demonstrates how a data file is created. A subfolder is created to represent the type of test and version such as “701R1\ENV\_RegressionTest\_TOP” so that tests can be run against either 6.2 or 7.0. Underneath that folder is another with the same name as the Composite Data Source being tested such as “MY DB”. Underneath “MY DB” are the data files for each query and named according to Catalog.Schema.Table name.




Image 12: Regression Test Data Files

### Performance Test Data Files

Even though a subfolder is created for performance test such as “701R1\PerfTest\_TOP” there are no data files created.

### Security Test Configuration

The security test correlates users with functional test queries and provides a way to test the expected outcome for a given user/query combination to determine if the test results in a PASS or FAIL. The security test does not use a separate SQL input file like the other tests use. Instead all of the users, queries and correlated tests are defined within the Regression Module XML file. Since this is originally generated from a template, it will not have the correct values to start out with. There is a process involved to generate the queries and then configure them to meet the test requirements. Let's consider this high-level overview of the process involved to configure a security test:

1. **Configure** the list of **users** in the **regression module XML** file that was derived from the template “BusLineBusAreaSubjArea\_RegressionModule.xml”.
2. **Generate** the **security queries** for the desired Business Line / Area / Subject Area.
3. **Copy generated security queries** into the regression module XML file
4. **Edit expected results** and **assign** the appropriate **PASS/FAIL response**.

**Scenario:** The development and/or QA team wants to validate that the privileges are set correctly on the various folder structures. When it comes to security, the following are guidelines or best practices:

- There are representative test resources in each of the folders to be tested.
- The development team has setup groups and a corresponding test user in each of the groups.
- Privileges are assigned to groups which are applied to folders recursively.

Here is a high-level summary of the steps for the “Security Test Process”:

**Note:** Refer to the PDTool documentation “**Cisco AS Promotion and Deployment Tool Module - Regression.pdf**” found in the PDTool/docs directory. Refer to the section titled “**4. Security Test Process:**” for the details.

- Step 1 – Regression Module XML for generating the regression security XML file.
- Step 2 – Deployment plan for generating the regression security XML file.
- Step 3 – Configure user list.
- Step 4 – Execute the Regression Security Generation plan
- Step 5 – Copy generated XML
- Step 6 – Regression Module XML for executing a Security test
- Step 7 – Deployment plan for “Executing the security test”
- Step 8 – Execute the Security Test plan.
- Step 9 – Review the results of the output log file.

#### Security Test Details

Step 1 – [NO ACTION REQUIRED] Regression Module XML was generated for a given project (Business Line / Area / Subject Area).




Image 13: Regression Module XML generated files

Step 2 – [NO ACTION REQUIRED] Deployment plan for “Generating the security XML” was generated for a given project (Business Line / Area / Subject Area).




Image 14: Deployment plan generated files

Example deployment plan file entry for MyProject1SubProj\_4Security\_gen.dp:

```
PASS TRUE ExecuteAction generateRegressionSecurityXML $SERVERID
Test4.1_$SCRIPT_CIS_VERSION
"$REGRESSION_TEST_MODULES/%BusLineBusAreaSubjArea%_RegressionModule.
xml" "$MODULE_HOME/servers.xml"
```

Step 3 – Configure user list

- Edit the Regression Module XML.
- Add a list of users that you want to use for testing security. These can be composite users or ldap users. Provide the user name, password and domain. Passwords may be encrypted after this part of the exercise is complete.
- There are two separate XML identifiers for CIS 6.2 and CIS 7.0. Configure one or both sections depending on which version of CIS is being tested.

```
<regressionTest>
  <id>Test4.1_6.2</id> OR <id>Test4.1_7.0</id>
  <securityGenerationOptions>
    <!-- A security user default encrypted password. It will be encrypted when the
    ExecutePDTool.bat -encrypt ..\modules\RegressionModule.xml is executed.-->
    <encryptedPassword>password</encryptedPassword>
    <!-- Determines what CIS users to generate. Wildcards (*) may be used. -->
    <userFilter>user1,user2</userFilter>
    <!-- Provides a way of specifying what domain the userFilter should be applied to. -->
    <domainFilter>composite</domainFilter>
  </securityGenerationOptions>
</regressionTest>
```

#### Step 4 – Generate the Regression Security XML.

- Execute the Regression Security Generation plan which will execute the method “generateRegressionSecurityXML” to generate users, queries and security plan tests.

Example Execute Line:

```
script_test_70.bat UAT MyProject1SubProj_4Security_gen.dp "" "false"
```

#### Step 5 – Modify original Regression Module XML

- Copy the generated regression XML file section: “<regressionSecurity>” to the original Regression Module XML.




Image 15: Generated Regression Module XML

```
<!-- BEGIN PASTE AREA -->
<regressionSecurity>
  <!-- List of users to be used f
  <regressionSecurityUsers>

  <!-- List of queries, procedure
  <!-- NOTE: It is not typical to
  However, it is done her
  As a result, there are
  <regressionSecurityQueries>

  <!-- List of security plans. E
  <regressionSecurityPlans>
    <!-- Security plans for MyP
    <regressionSecurityPlan>
    <regressionSecurityPlan>

    <!-- Security plans for MyP
    <regressionSecurityPlan>
    <regressionSecurityPlan>
  </regressionSecurityPlans>
</regressionSecurity>
<!-- END PASTE AREA -->
```

Image 16: Example of XML section that is to be copied and pasted

- Edit user list and supply correct password if necessary.

Example Regression Module XML (MyProject1SubProj\_RegressionModule.xml):

```
<regressionSecurity>
  <!-- List of users to be used for security testing. -->
  <regressionSecurityUsers>
    <!--Iteration of users for project: MyProject1SubProj -->
    <regressionSecurityUser>
      <id>rsu1</id>
      <userName>user1</userName>
      <encryptedPassword>password</encryptedPassword>
      <domain>composite</domain>
    </regressionSecurityUser>
    <regressionSecurityUser>
      <id>rsu2</id>
      <userName>user3</userName>
      <encryptedPassword>password</encryptedPassword>
      <domain>composite</domain>
    </regressionSecurityUser>
  </regressionSecurityUsers>
</regressionSecurity>
```

- Re-encrypt password if necessary

```
ExecutePDTool.bat -encrypt
..\AutomatedTestFramework\regression\modules\MyProject1SubProj_RegressionModule.xml
```

- Validate Regression Security Plan tests – Validate the expected outcome for each plan test to insure that it is the correct outcome [PASS or FAIL]. This is a manual step performed by the developer, tester or administrator.
- Make a backup copy of the XML file in case you decide to regenerate the project files in the future.

Step 6 – [NO ACTION REQUIRED] Regression Module XML for “Executing the security test” was generated for a given project (Business Line / Area / Subject Area).




Image 17: Regression Module XML generated files

Step 7 – [NO ACTION REQUIRED] Deployment plan for “Executing the regression security test” was generated for a given project (Business Line / Area / Subject Area).




Image 18: Deployment Plan for Security Execution

- Example deployment plan file entry for MyProject1SubProj\_4Security\_exec.dp:

```
PASS TRUE ExecuteAction executeSecurityTest $SERVERID
Test4.1_$SCRIPT_CIS_VERSION
"$REGRESSION_TEST_MODULES/%BusLineBusAreaSubjArea%_RegressionModule.xml"
"$MODULE_HOME/servers.xml"
```

Step 8 – Execute the Regression Security Test plan.

- Executing the regression test is accomplished by running the Automated Test Framework scripts.
- This regression security test will use the queries generated in the regression security XML and execute them against CIS. It will log the results into a summary execution file in the file system. It will use several filters that you previously set up in the regression XML file. For example, you can turn on and off execution of the three categories, queries, procedures and web services. You can also filter on which datasources you execute tests for. The input file may contain a broad list of datasources and queries but you don't have to run all the tests.

Example Execute Line:

```
script_test_70.bat UAT MyProject1SubProj_4Security_exec.dp "" "false"
```

Step 9 – Review the results of the output file.

The results of the security test are saved the Automated Test Framework output folder under the project name and release sub-folders. The actual log file is called SecurityTest.log.

The following screen shot shows the location of the log file.






Image 19: Security Test Log Output Location – SecurityTest.log

The following screen shot shows the content of the SecurityTest.log file:

```

1 # Processing action "executeSecurityTest" for security plan id: sp1
2 Result |Actual |Expected|Username |ExecutionStartTime |Duration |Rows |Database |Query
3 PASS |PASS |PASS |user1 |2015-06-18 09:29:54.0012 |000 00:00:00.0858 |1 |"MY DB" |SELECT TOP 1 * FROM
4 PASS |PASS |PASS |user1 |2015-06-18 09:29:54.0870 |000 00:00:00.0390 |1 |"MY DB" |SELECT TOP 1 * FROM
5 PASS |PASS |PASS |user1 |2015-06-18 09:29:55.0260 |000 00:00:00.0015 |1 |"MY DB" |SELECT TOP 1 * FROM
6 PASS |PASS |PASS |user1 |2015-06-18 09:29:55.0275 |000 00:00:00.0016 |1 |"MY DB" |SELECT TOP 1 * FROM
7 PASS |PASS |PASS |user1 |2015-06-18 09:29:55.0291 |000 00:00:00.0047 |1 |"MY DB" |SELECT TOP 1 * FROM
8 #
9 # Overall Security Rating=PASS Security Plan Id=sp1
10 # Total Error Tests=0
11 # Summary: Total Success=5 Total Skipped=0 Total Failed=0 Total Error=0
12 #
13 # Processing action "executeSecurityTest" for security plan id: sp2
14 Result |Actual |Expected|Username |ExecutionStartTime |Duration |Rows |Database |Query
15 PASS |FAIL |FAIL |user2 |2015-06-18 09:29:55.0353 |000 00:00:00.0016 |0 |"MY DB" |SELECT TOP 1 * FROM
16 PASS |FAIL |FAIL |user2 |2015-06-18 09:29:55.0369 |000 00:00:00.0000 |0 |"MY DB" |SELECT TOP 1 * FROM
17 PASS |FAIL |FAIL |user2 |2015-06-18 09:29:55.0369 |000 00:00:00.0015 |0 |"MY DB" |SELECT TOP 1 * FROM
18 PASS |FAIL |FAIL |user2 |2015-06-18 09:29:55.0384 |000 00:00:00.0000 |0 |"MY DB" |SELECT TOP 1 * FROM
19 PASS |FAIL |FAIL |user2 |2015-06-18 09:29:55.0384 |000 00:00:00.0000 |0 |"MY DB" |SELECT TOP 1 * FROM

```

Image 20: Security Test Log Output

## INSTALLATION AND CONFIGURATION


### Introduction

This section describes how to install and configure the “**Regression Automated Test Framework**”.

### Planning

The section helps the test user to plan for how they want to use the testing framework.

Planning worksheet:

1. Identify Published Resources to test: \_\_\_\_\_
  - a. Example published data source, catalogs and schemas
2. Assign a name to the published resources: \_\_\_\_\_
  - a. Known as the Business Line or Business Area or Subject Area
3. Determine the CIS environment names: \_\_\_\_\_
  - a. Example: DEV, UAT PROD
4. Determine the PDTool config file mappings: \_\_\_\_\_
  - a. This is how a PDTool configuration property file maps to a given CIS environment.
  - b. Example:

i. ENV	<u>PDTool Configuration Property File Name</u>
ii. DEV	= deploy_7.0_DEV.properties
iii. UAT	= deploy_7.0_UAT.properties
iv. PROD	= deploy_7.0_PROD.properties
5. PDTool 6.2 directory location: \_\_\_\_\_
6. PDTool 7.0 directory location: \_\_\_\_\_

### Installation and Configuration Setup

The section provides the necessary steps for setting up the batch scripts used for testing.

Edit/Configure the **setVars.bat** batch file:

1. Location: \AutomatedTestFramework\regression\bin\setVars.bat

#### **REM # Set environment variables for PDTool 6.2**

**REM # Set the location of PDTool 6.2**

```
set PDTOOL_INSTALL_HOME_6=C:\CompositeSoftware\PDTool_Test\PDTool6.2
```

**REM** List of valid Environments~Config property file name pairs. Comma separated no space and no double quotes. Tilde separates pairs: ENV~ConfigFileName. These are the property file names configured in the PDTool6.2\resources\config folder minus the .properties extension.

```
set VALID_ENV_CONFIG_PAIRS_6=DEV~deploy_6.2_DEV,UAT~deploy_6.2_UAT,PROD~deploy_6.2_PROD
```

**REM** Set the release folders to indicate which version is being tested

**REM** Release folder 1 is designated as the CIS instance current folder. R1 designates it is a release 1 primary, current folder.

**REM** Release folder 2 is designated as the CIS instance previous folder. R2 designates it is a release 2 secondary, previous folder.

```
set RELEASE_FOLDER1_6=626R1
```

```
set RELEASE_FOLDER2_6=626R2
```

#### **REM # Set environment variables for PDTool 7.0**

**REM** Set the location of PDTool 7.0

```
set PDTOOL_INSTALL_HOME_7=C:\CompositeSoftware\PDTool_Test\PDTool7.0.0
```

**REM** List of valid Environments~Config property file name pairs. Comma separated no space and no double quotes. Tilde separates pairs: ENV~ConfigFileName. These are the property file names configured in the PDTool7.0.0\resources\config folder minus the .properties extension.

```
set
```

```
VALID_ENV_CONFIG_PAIRS_7=DEV~deploy_7.0.1_DEV,UAT~deploy_7.0.1_UAT,PROD~deploy_7.0.1_PROD
```

**REM** Set the release folders to indicate which version is being tested.

**REM** Release folder 1 is designated as the CIS instance current folder. R1 designates it is a release 1 primary, current folder.

**REM** Release folder 2 is designated as the CIS instance previous folder. R2 designates it is a release 2 secondary, previous folder.

```
set RELEASE_FOLDER1_7=701R1
```

```
set RELEASE_FOLDER2_7=701R2
```

#### **REM # Set environment variables for Automated Test Framework**

**REM** Automated Test Framework Home. This folder may be independent of where PDTOOL\_INSTALL\_HOME is located.

```
set ATF_HOME= C:\CompositeSoftware\PDTool_Test\PDTool6.2\AutomatedTestFramework\regression
```

**REM # Used by copyPlanTemplates.bat**

**REM # Set JAVA\_HOME to JRE7**

```
if not defined JAVA_HOME set JAVA_HOME=C:\Program Files\Java\jre7
```

**REM # Used by copyPlanTemplates.bat**

**REM # Use one or the other or provide your own text editor path.**

**REM # If you have notepad++ it is a much better editor than notepad.**

**REM # Do not put double quotes around path. The script takes care of that.**

```
set EDITOR=C:\Program Files (x86)\Notepad++\notepad++.exe
```

```
rem set EDITOR=%windir%\system32\notepad.exe
```

**REM Script Main Activity**

```
set SCRIPT_ACTIVITY=Execute Regression Test
```

**REM Debug=Y or N. Default=N**

```
set DEBUG=N
```

### *Sample Installation*

The section provides the necessary steps for setting up the sample.

Create groups on the target server where the sample will be imported:

1. Launch CIS Manager and login
  - a. For 6.2, select “Users → Group Management”
  - b. For 7.0, select “Security → Group Management”
  - c. Select “Add Group”
    - i. Group name: **group1**
    - ii. Click OK
  - d. Select “Add Group”
    - i. Group name: **group2**
    - ii. Click OK

Create users on the target server where the sample will be imported:

1. Note: The users “user1” and “user2” use the password text “password” within the sample files. If you wish to change the password, then you will need to provide the same password in the sample files
  - a. \AutomatedTestFramework\regression\modules
    - i. \MyProject1SubProj\_RegressionModule.xml
    - ii. \MyProject2SubProj\_RegressionModule.xml
  - b. Encrypting passwords in files:

```
ExecutePDTool.bat -encrypt  
..\AutomatedTestFramework\regression\modules\MyProject1SubProj_RegressionModule.xml  
  
ExecutePDTool.bat -encrypt  
..\AutomatedTestFramework\regression\modules\MyProject2SubProj_RegressionModule.xml
```
2. Launch CIS Manager and login

- a. For 6.2, select “Users → User Management”
- b. For 7.0, select “Security → User Management”
- c. Select “Add Group”
  - i. User name: **user1**
  - ii. New password: **password**
  - iii. Confirm password: **password**
  - iv. Click OK
- d. Select “Add Group”
  - i. User name: **user2**
  - ii. New password: **password**
  - iii. Confirm password: **password**
  - iv. Click OK

Associate users with groups on the target server where the sample will be imported:

1. Launch CIS Manager and login
  - a. For 6.2, select “Users → User Management”
  - b. For 7.0, select “Security → User Management”
  - c. Check the box next to “**user1**” and click “Edit Group Membership”
    - i. Check the box for “**group1**”
    - ii. Click OK
  - d. Check the box next to “**user2**” and click “Edit Group Membership”
    - i. Check the box for “**group2**”
    - ii. Click OK

Import the sample CAR file:

1. Launch CIS Studio 6.2 or 7.0
2. Right click on “Desktop (user)” and select Import
3. Browse to the location of \\AutomatedTestFramework\\carfiles
4. Select MySampleDBs.car and click Open
5. Click Import>
6. Click Done

Verify Privileges:

1. Launch CIS Studio 6.2 or 7.0

2. Right-click on “/services/databases/MY DB” and select “Privileges”
3. Select the middle radio button “Hide users and groups without explicit privileges” and click OK

4. The privileges should be as follows:

group1		<input checked="" type="checkbox"/>		<input type="checkbox"/>		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	
--------	--	-------------------------------------	--	--------------------------	--	-------------------------------------	--	-------------------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--

5. Right-click on “/services/databases/MY\_DB” and select “Privileges”
6. Select the middle radio button “Hide users and groups without explicit privileges” and click OK
7. The privileges should be as follows:

group2		<input checked="" type="checkbox"/>		<input type="checkbox"/>		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	
--------	--	-------------------------------------	--	--------------------------	--	-------------------------------------	--	-------------------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--	--------------------------	--

## CHANGING THE PDTOOL PASSWORD

### *Introduction*

This section describes how to change your PDTool password.

### *PDTool 6.2*

1. Locate the PDTool 6.2 folder  
`C:\Users\%USERNAME%\compositesw\PDTool\PDTool6.2`
2. Edit the variables file – `setMyPrePDToolVars.bat`
  - a. Locate the variable `CIS_PASSWORD`  
`set CIS_PASSWORD=Encrypted:6ABCABC9F46BAA2`
  - b. Modify the password by removing all text after the “=” including the “Encrypted:”  
`set CIS_PASSWORD=`
  - c. Enter your new password.
  - d. Save and close the file
3. Open a command line
  - a. Change directories to the following location  
**`cd C:\Users\%USERNAME%\compositesw\PDTool\PDTool6.2\bin`**
  - b. Execute the following command  
**`ExecutePDTool.bat -encrypt ..\..\setMyPrePDToolVars.bat`**
4. Edit the variables file – `setMyPrePDToolVars.bat`
  - a. Locate the variable `CIS_PASSWORD` and determine if the password is now encrypted.

### *PDTool 7.0*

1. Locate the PDTool 7.0.0 folder  
`C:\Users\%USERNAME%\compositesw\PDTool\PDTool7.0.0`
2. Edit the variables file – `setMyPrePDToolVars.bat`
  - b. Locate the variable `CIS_PASSWORD`  
`set CIS_PASSWORD=Encrypted:6ABCABC9F46BAA2`
  - c. Modify the password by removing all text after the “=” including the “Encrypted:”  
`set CIS_PASSWORD=`
  - d. Enter your new password.
  - e. Save and close the file



3. Open a command line

- a. Change directories to the following location

**cd C:\Users\%USERNAME%\compositesw\PDTool\PDTool7.0.0\bin**

- b. Execute the following command

**ExecutePDTool.bat -encrypt ..\..\setMyPrePDToolVars.bat**

4. Edit the variables file – setMyPrePDToolVars.bat

- f. Locate the variable CIS\_PASSWORD and determine if the password is now encrypted.

---

## CONCLUSION

### *Concluding Remarks*

The AS Promotion and Deployment Tool is a set of pre-built modules intended to provide a turn-key experience for promoting CIS resources from one CIS instance to another. The user only requires system administration skills to operate and support. The code is transparent to operations engineers resulting in better supportability. It is easy for users to swap in different implementations of a module using the Spring framework and configuration files.

### **How you can help!**

Build a module and donate the code back to Cisco Advanced Services for the advancement of the “*AS Promotion and Deployment Tool*”.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA

CXX-XXXXXX-XX 10/11