

TUTORS:

Yaser Jaradeh, Hassan Hussien, and some other ORKG members

QUESTIONS: Please don't hesitate to ask any questions. Questions help you and your peers.**PRINT:** Please consider the environment before printing the exercise.

1 Review Questions

1. Among the following statements about OWL, which ones are correct?
 - (a) `owl:Nothing` is the subclass of all OWL classes.
 - (b) All object properties are functional.
 - (c) `:A owl:disjointWith :B` means the classes `:A` and `:B` don't have any instance in common.
 - (d) `owl:sameAs` denotes the similarity of two classes in OWL.
2. Of the statements below, which one is correct about `owl:NegativePropertyAssertion`?
 - (a) It's supported by all versions of OWL.
 - (b) It can take `Classes` and `Individuals` as its source.
 - (c) `owl:targetIndividual` is an `owl:ObjectProperty`.
 - (d) It's used to express negative facts in an OWL ontology.
3. Which ones of the statements below are correct?
 - (a)

```
:p a owl:ObjectProperty ;
    rdfs:range xsd:string .
```
 - (b)

```
:a :p :c .
:b :p :c .
:p a owl:FunctionalProperty .
→
:a owl:sameAs :b .
```
 - (c)

```
:p a owl:DatatypeProperty .
:b :p :c .
→
:c rdfs:subClassOf owl:Class .
```
 - (d)

```
:a :p :c .
:b :p :c .
:p a owl:inverseFunctionalProperty .
→
:a owl:sameAs :b .
```

2 Given are the following OWL expressions in RDF/XML syntax.

a. `<owl:Restriction>`
 `<owl:onProperty rdf:resource="#hasParent" />`
 `<owl:someValuesFrom rdf:resource="#Physician" />`
 `</owl:Restriction>`

b. `<owl:Class>`
 `<owl:intersectionOf rdf:parseType="Collection">`
 `<owl:Class>`
 `<owl:oneOf rdf:parseType="Collection">`
 `<owl:Thing rdf:about="#Tosca" />`
 `<owl:Thing rdf:about="#Salome" />`
 `</owl:oneOf>`
 `</owl:Class>`
 `<owl:Class>`
 `<owl:oneOf rdf:parseType="Collection">`
 `<owl:Thing rdf:about="#Turandot" />`
 `<owl:Thing rdf:about="#Tosca" />`
 `</owl:oneOf>`
 `</owl:Class>`
 `</owl:intersectionOf>`
 `</owl:Class>`

c. `<owl:Class rdf:about="#MusicDrama">`
 `<owl:equivalentClass>`
 `<owl:Class>`
 `<owl:unionOf rdf:parseType="Collection">`
 `<owl:Class rdf:about="#Opera"/>`
 `<owl:Class rdf:about="#Operetta"/>`
 `<owl:Class rdf:about="#Musical"/>`
 `</owl:unionOf>`
 `</owl:Class>`
 `</owl:equivalentClass>`
 `</owl:Class>`

`<owl:Class rdf:about="#Opera">`
 `<rdfs:subClassOf rdf:resource="#MusicDrama"/>`
 `</owl:Class>`

`<owl:Class rdf:about="#Operetta">`
 `<rdfs:subClassOf rdf:resource="#MusicDrama"/>`
 `<owl:disjointWith rdf:resource="#Opera"/>`
 `</owl:Class>`

`<owl:Class rdf:about="#Musical">`
 `<rdfs:subClassOf rdf:resource="#MusicDrama"/>`
 `<owl:disjointWith rdf:resource="#Opera"/>`
 `<owl:disjointWith rdf:resource="#Operetta"/>`
 `</owl:Class>`

1. Explain the meaning of each expression in your own words.
2. Represent each expression in the Turtle or Manchester-syntax serialization.

3 Indicate which of the following statements are logical consequences of the knowledge base below.

```
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#>.
@prefix xsd: <http://www.w3.org/2001/XMLSchema#>.
@prefix owl: <http://www.w3.org/2002/07/owl#>.
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>.
@prefix ex: <http://example.org#>.
ex:LuckyLuke a ex:Person;
              ex:isFriendOf ex:JollyJumper, ex:Shrief .
ex:JollyJumper a ex:Horse .
ex:Rantanplan a ex:Dog ;
              ex:isFriendOf ex:JollyJumper .
ex:Dog rdfs:subClassOf ex:Animal .
ex:Horse rdfs:subClassOf ex:Animal .
ex:LukePet rdfs:subClassOf [
  rdf:type owl:Class ;
  owl:intersectionOf ( ex:Animal [
    owl:equivalentClass [
      rdf:type owl:Restriction;
      owl:onProperty ex:isFriendOf;
      owl:hasValue ex:LuckyLuke]
    ])
] .
ex:Creature rdfs:subClassOf [
  a owl:Class;
  owl:unionOf (ex:Animal ex:Person)].
ex:LuckyLuke ex:isEnemyOf ex:JoeDalton .
ex:isEnemyOf a owl:SymmetricProperty;
             rdfs:subPropertyOf ex:knows ;
             rdfs:domain ex:Person .
```

Statements:

- a. ex:Rantanplan a ex:creature .
- b. ex:Rantanplan ex:isFriendOf ex:Shrief .
- c. ex:Shrief a ex:LukePet .
- d. ex:Rantanplan a ex:LukePet .
- e. ex:JoeDalton ex:knows ex:LuckyLuke .
- f. ex:JoeDalton a ex:creature .

g. Talk about the statement d, in the case we add these triples to our knowledge base.

```
ex:isFriendOf a owl:SymmetricProperty, owl:transitiveProperty.
```

4 Modeling in OWL:

Given are some facts about the DSDL research group and the “Knowledge Engineering and Semantic Web” lecture. Model them in an appropriate way as an OWL ontology.

1. “KESW” and “Knowledge Engineering and Semantic Web” are two names for the same lecture.
2. KESW *lecture* is different from KESW *seminar*.
3. If a mentor is the supervisor of a student, then that student is supervised by that mentor.
4. DSDL has some PhD or Master students. (In your model, take it into consideration that one student cannot be PhD and Master student in the same time.)

5. All tutors of KESW are students and enrolled at LUH.
6. A student eligible to register their master thesis should have achieved at least 1 and at most 2 seminars.
7. Professor Jens Lehmann is not a lecturer of KESW.
8. The DSDL group offers two *different* lectures: KESW and AIKG.
9. Tutors of KESW are Yaser, Hassan, Julia, Hamed, and Mahsa.
10. Students who failed KESW are students who have enrolled in KESW and haven't passed it.