

An abstract graphic design featuring two thin, dark grey lines that intersect on a light grey background. One line runs diagonally from the top-left towards the bottom-right, while the other runs from the top-right towards the bottom-left. The intersection point is located to the left of the main text.

INSTALLATION GUIDELINES AND TEST CAPABILITIES

INSTALLATION GUIDELINES

GENERAL PRE INSTALLATION GUIDELINES

- Shut off water: Turn off the main water supply valve.
- Drain the lines: Open existing taps to drain remaining water.
- Clean the threads: Remove old Teflon tape and debris from wall outlets.

Polymer Taps (Wall Flange Taps) Shut off water: Turn off the main water supply valve.

- Wrap Teflon tape: Wind thread-seal tape 5–6 times clockwise around the tap's male threads.
- Place the flange: Slip the decorative wall flange cover onto the tap base.
- Thread the tap: Screw the tap into the wall outlet by hand first.
- Tighten gently: Use an adjustable wrench to tighten. Do not over-tighten, or the polymer threads will crack.

INSTALLATION GUIDELINES

Health Faucet

- Install the holder: Drill holes in the wall, insert wall plugs, and screw the holder mount in place.
- Insert rubber washers: Place the provided black rubber gaskets inside both ends of the flexible hose. Missing washers cause immediate leaks.
- Connect to gun: Screw the conical end of the hose onto the faucet trigger gun.
- Connect to valve: Screw the hex end of the hose onto the wall angle valve. Tighten by hand.

Sink Taps (Deck-Mounted) Install the holder: Drill holes in the wall, insert wall plugs, and screw the holder mount in place.

- Insert tap stem: Push the threaded bottom of the tap through the sink deck hole.
- Secure underneath: From below the sink, slide on the rubber washer, then screw on the plastic retaining nut.
- Tighten the nut: Hand-tighten the nut until the tap does not wobble on top.
- Connect water line: Connect a flexible braided hose from the angle valve to the tap stem.

INSTALLATION GUIDELINES

Flexible Taps for Sink Install the holder: Drill holes in the wall, insert wall plugs, and screw the holder mount in place.

- Mount the base: Install the base to the sink deck or wall using the steps above.
- Check the spout joint: Ensure the flexible silicone/gooseneck spout is firmly pushed into the tap body.
- Tighten grub screw: If applicable, tighten the small hex screw at the back of the joint to lock the spout.
- Test flexibility: Ensure the neck bends smoothly without pulling the base loose.

Post-Installation Check

- Turn on water: Open the main valve slowly.
- Check for leaks: Wipe all joints with a dry tissue to spot slow drips.
- Flush the line: Run water for 30 seconds to clear any trapped air or sediment.