ModelSerializer

Attributes:
- serializer_choice_field : ChoiceField
- serializer_field_mapping : dict
- serializer_related_field : PrimaryKeyRelatedField
- serializer_related_to_field : SlugRelatedField
- serializer_url_field : HyperlinkedIdentityField
- url_field_name
- url_field_name : NoneType

Methods:
- build_field(field_name, info, model_class, nested_depth)
- build_nested_field(field_name, relation_info, nested_depth)
- build_property_field(field_name, model_class)
- build_relational_field(field_name, relation_info)
- build_standard_field(field_name, model_field)
- build_unknown_field(field_name, model_class)
- build_url_field(field_name, model_class)
- create(validated_data)
- get_default_field_names(declared_fields, model_info)
- get_extra_kwargs()
- get_field_names(declared_fields, info)
- get_fields()
- get_unique_for_date_validators()
- get_unique_together_validators()
- get_uniqueness_extra_kwargs(field_names, declared_fields, extra_kwargs)
- get_validators()
- include_extra_kwargs(kwargs, extra_kwargs)
- update(instance, validated_data)

APIView

Attributes:
- allowed_methods
- args : tuple
- authentication_classes
- content_negotiation_class
- default_response_headers
- format_kwarg
- headers : dict
- kwargs : dict
- metadata_class
- parser_classes
- permission_classes
- renderer_classes
- request : Request
- response
- schema : DefaultSchema
- settings : APISettings
- throttle_classes
- versioning_class

Methods:
- as_view(cls)
- check_object_permissions(request, obj)
- check_permissions(request)
- check_throttles(request)
- determine_version(request)
- dispatch(request)
- finalize_response(request, response)
- get_authenticate_header(request)
- get_authenticators()
- get_content_negotiator()
- get_exception_handler()
- get_exception_handler_context()
- get_format_suffix()
- get_parser_context(http_request)
- get_parsers()
- get_permissions()
- get_renderer_context()
- get_renderers()
- get_throttles()
- get_view_description(html)
- get_view_name()
- handle_exception(exc)
- http_method_not_allowed(request)
- initial(request)
- initialize_request(request)
- options(request)
- perform_authentication(request)
- perform_content_negotiation(request, force)
- permission_denied(request, message, code)
- raise_uncaught_exception(exc)
- throttled(request, wait)

AppConfig

Attributes:
- apps : NoneType
- label
- models : NoneType
- models_module : NoneType
- module
- name
- path
- verbose_name

Methods:
- create(cls, entry)
- default_auto_field()
- get_model(model_name, require_ready)
- get_models(include_auto_created, include_swapped)
- import_models()
- ready()

CarrierSerializer

Methods:
- create(validated_data)

SupplierSerializer

Methods:
- create(validated_data)

TransportSerializer

Attributes:
- carrier : StringRelatedField
- color : CharField
- gate : StringRelatedField
- supplier : StringRelatedField
- transport_priority
- transport_status

CarrierCreate

Attributes:
- authentication_classes : list
- permission_classes : list

Methods:
- post(request)

SupplierCreate

Attributes:
- authentication_classes : list
- permission_classes : list

Methods:
- post(request)

TransportList

Attributes:
- authentication_classes : list
- permission_classes : list

Methods:
- get(request)

TransportUpdate

Attributes:
- authentication_classes : list
- permission_classes : list

Methods:
- get_object(pk)
- post(request, pk)

ApiConfig

Attributes:
- default_auto_field : str
- name : str

TransportPrioritySerializer

TransportStatusSerializer

transport_priority *transport_status*

Meta
- fields : str
- model

Meta
- fields : str
- model

Meta
- fields : str
- model

Meta
- fields : str
- model

Meta
- exclude : list
- model