SHORTEST JOB FIRST(SJF) SCHELDULING.

AIM:

PROGRAM TO IMPLEMENT SHORTEST JOB FIRST SCHELDULING USING C LANGUAGE.

This is an approach which considers the next CPU burst. Each process posses its next CPU burst.

When CPU is available, the process having the smallest next CPU burst is allocated CPU.

Now it may happen that two or more processes have the same next CPU burst. Then which process to allocate will be decided as per FCFS scheduling.

ALGORITHM:

1. Sort all the process according to the arrival time.
2. Then select that process which has minimum arrival time and minimum Burst time.
3. After completion of process make a pool of process which after till the completion of previous process and select that process among the pool which is having minimum Burst time.

Write a C program to implement Shortest job First(SJF) Scheduling?

Input 1: Total no. of Process(Ex: 4)

Input 2: Burst time of all four process(Ex: 6, 8,7,3)

Output 1 : Average waiting time

Output 2: Average Turn around time

For example:

Test	Input	Result
T1	4 6 8 7 3	7.000000 13.000000

PROGRAM:




SJF Scheduling and Priority Scheduling: Attempt review - Google Chrome
sathyabama.cognibot.in/mod/quiz/review.php?attempt=638389&cmid=15554
for(i=0;i<n;i++)
{
pos=i;
for(j=i+1;j<n;j++)
{
if(bt[j]<bt[pos])
pos=j;
}
temp=bt[i];
bt[i]=bt[pos];
bt[pos]=temp;
temp=p[i];
p[i]=p[pos];
p[pos]=temp;
}
Type here to search
ENG
11:42
25-10-2021


SJF Scheduling and Priority Scheduling: Attempt review - Google Chrome
sathyabama.cognibot.in/mod/quiz/review.php?attempt=638389&cmid=15554
bt[pos]=temp;
temp=p[i];
p[i]=p[pos];
p[pos]=temp;
}
wt[0]=0;
for(i=1;i<n;i++)
{
wt[i]=0;
for(j=0;j<i;j++)
wt[i]+=bt[j];
total+=wt[i];
}
avg_wt=(float)total/n;
total=0;
Type here to search
ENG
11:42
25-10-2021


SJF Scheduling and Priority Scheduling: Attempt review - Google Chrome
sathyabama.cognibot.in/mod/quiz/review.php?attempt=638389&cmid=15554
33 total+=wt[i];
34 }
35 avg_wt=(float)total/n;
36 total=0;
37 for(i=0;i<n;i++)
38 {
39 tat[i]=bt[i]+wt[i];
40 total+=tat[i];
41 }
42 avg_tat=(float)total/n;
43 printf("%f",avg_wt);
44 printf("\n%f\n",avg_tat);
45 }
Type here to search
ENG
11:42
25-10-2021

RESULT:


SJF Scheduling and Priority Scheduling: Attempt review - Google Chrome
sathyabama.cognibot.in/mod/quiz/review.php?attempt=638389&cmid=15554
Test
Input
Expected
Got
T1
4
6
8
7
3
7.000000
13.000000
7.000000
13.000000
T2
3
10
12
14
10.666667
22.666666
10.666667
22.666666
Passed all tests!
Type here to search
ENG
11:42
25-10-2021

RESULT:

SJF WAS SUCCSSFULLY IMPLEMENT USING C LANGUAGE.