

Aim:

To write a lex program to implement Token separation for a given expression using LEX.

Algorithm:

- step 1: Include the necessary header files and declare the necessary variables
- step 2: Define the key words and the identifiers with the constant and operator
- step 3: Get the statement for analysis from the user
- step 4: Check ~~the~~ each and every element in the statement with the define keyword and if it matches print it as the keyword.
- step 5: Check each and every element in the statement with the defined identifier and if it matches print the element as an identifier.
- step 6: Check each and every element in the statement with the defined constant then find the equivalence and ~~point~~ print it as constant
- step 7: Check each and every element in the statement with the defined operator and if it matches print the element as an identifier
- step 8: Display every element on the screen as separated
- step 9: Exit the program

Program:

File: 1

```

letter % option noyywrap
% {

```

```

#include <stdio.h>

```

```

void yyerror (char *);

```

```

% }

```

```

letter [A-Za-z]

```

```

digit [0-9]

```

```

operator [-+*]

```

```

% %

```

```

void |

```

```

main |

```

```

if |

```

```

do |

```

```

printf |

```

```

int |

```

```

float |

```

```

char |

```

```

for

```

```

% % s |

```

```

% c |

```

```

% d |

```

```

% f

```

```

{ printf ("%s is a keyword\n", yytext); }

```

```

{ printf ("%s is a Format Specifier\n", yytext); }

```

```

({letter}|_)( {letter}| {digit})* { printf ("%s is a identifier\n", yytext); }

```

```

{operator} ({operator})* { printf ("%s is an operator\n", yytext); }

```

```

{digit}+ { printf ("%s is a number\n", yytext); }

```

```

"("

```

```

{ printf ("%s is a open parenthesis\n", yytext); }

```



1)

{ printf ("%s is an close parenthesis\n", yytext); }

2)

{ printf ("%s is a semicolon\n", yytext); }

3)

4)

5)

6)

7)

8)

9)

{ printf ("%s is a double quote\n", yytext); }

{ printf ("In Syntax Error!!\n"); }

10)

void yyerror (char \*s)

{

{ printf (stderr, "%s\n", s);

}

int main ()

{

yylex();

return 0;

}

Result:

Implement Token separation for given expression using  
LEX TOOL has been executed successfully.