

Aim:

To write the program using LEX and YACC to implement parser on unambiguous grammar.

Algorithm:File 1:

step 1: start

step 2: Include the necessary header files and declare the necessary variables

step 3: initialize the digits, operators, parenthesis and return the value else print syntax error.

step 4: Call the function and return 1

step 5: stop

File y

step 1: start

step 2: Include the necessary header files and declare the necessary variables.

step 3: substitute the values and calculate respectively for Addition, subtraction, Multiplication and division and return the result.

step 4: Call the main function and print the result.

step 5: stop

Program: → File-1

% option noyywrap
% §

```
#include <stdio.h>
#include "y.tab.h"
void yyerror(char *s);
extern int yylval;
```

% }

% %

```
[0-9]+ {yylval = atoi(yytext); return NUM;}
[a-z] {yylval = toascii(*yytext)-97; return ID;}
[A-Z] {yylval = toascii(*yytext)-97; return ID;}
[-+*/\n] {return *yytext;}
"(" {return *yytext;}
")" {return *yytext;}
```

[\t]:

```
{yyerror("Syntax Error");}
```

% %

```
int yywrap()
{
```

```
return 1;
```

```
}
```

File.y

% §

```
#include <stdio.h>
extern int yylex(void);
void yyerror(char *);
int x=0;
```



```
int val [26];
```

```
% }
```

```
% token NUM ID
```

```
% {
```

```
S:
```

```
S expr 'n' {x = $2; printf ("%d\n", $2);}
```

```
| S ID '=' expr 'n' {val [$2] = $4;}
```

```
#
```

```
}
```

```
expr:
```

```
expr '+' T { $$ = $1 + $3; }
```

```
| expr '-' T { $$ = $1 - $3; }
```

```
| T { $$ = $1; }
```

```
| '+' T { $$ = x + $2; }
```

```
| '-' T { $$ = x - $2; }
```

```
}
```

```
T:
```

```
F { $$ = $1; }
```

```
| T '*' F { $$ = $1 * $3; }
```

```
| T '/' F { $$ = $1 / $3; }
```

```
| '*' F { $$ = x * $2; }
```

```
| '/' F { $$ = x / $2; }
```

```
}
```

```
F:
```

```
NUM { $$ = $1; }
```

```
| ID { $$ = val [$1]; }
```

```
| '(' expr ')' { $$ = $2; }
```

```
}
```

```
% }
```

Expt. No. _____

Page No. 10

Expt. Name. _____

Date : _____

```
void yyerror(char *s)
{
    printf("%s", s);
}
```

```
int main()
{
    yyparse();
    return 0;
}
```

Result:

Use LEX and YACC to implement parser for ambiguous is executed successfully.

```

1 #option nyywrap
2 #
3 #include <stdio.h>
4 #include "y.tab.h"
5 void yyerror(char *s);
6 extern int yylval;
7
8
9
10 [0-9]+ { yylval=atoi(yytext); return WMR; }
11 [a-z] { yylval=atoi(yytext)-97; return IDr; }
12 [A-Z] { yylval=atoi(yytext)-65; return IDr; }
13 [-+*/\n] { return yytext; }
14 [ ] { return yytext; }
15 [*] { return yytext; }
16 [\n] {
17     yyerror("Syntax Error");
18 }
19
20 int yywrap()
21 {
22     return 1;
23 }

```

----- Lex/Yacc Build -----
Output completed (0 sec consumed) ~ Normal Termination

```

1 #
2 #tokens: NON ID
3 #
4 #
5 #
6 #
7 #
8 #
9 #
10 #
11 #
12 #
13 #
14 #
15 #
16 #
17 #
18 #
19 #
20 #
21 #
22 #
23 #
24 #
25 #
26 #
27 #
28 #
29 #
30 #
31 #
32 #
33 #
34 #
35 #
36 #
37 #
38 #
39 #
40 #
41 #
42 #
43 #
44 #
45 #
46 #
47 #
48 #
49 #
50 #
51 #
52 #
53 #
54 #
55 #
56 #
57 #
58 #
59 #
60 #
61 #
62 #
63 #
64 #
65 #
66 #
67 #
68 #
69 #
70 #
71 #
72 #
73 #
74 #
75 #
76 #
77 #
78 #
79 #
80 #
81 #
82 #
83 #
84 #
85 #
86 #
87 #
88 #
89 #
90 #
91 #
92 #
93 #
94 #
95 #
96 #
97 #
98 #
99 #
100 #

```

----- Lex/Yacc Build -----
Output completed (0 sec consumed) ~ Normal Termination

```
E:\Mohnish Devaraj\College\Semesters\VI Sem\Compiler Design Lab\Lab Exercises\Exercises\3. Use LEX and YACC to implement pars...
243
5
12/4
3
12/4+86*5
433
```