

Computational Data Analysis

Machine Learning

Yao Xie, Ph.D.

Assistant Professor

Harold R. and Mary Anne Nash Early Career Professor


H. Milton Stewart School of Industrial and Systems
Engineering

Nonlinear Dimensionality Reduction





Limitation of PCA and SVD


- Suitable when variables are linearly correlated



- Not suitable when nonlinear structures are present



What's a reasonable distance measure




Recall: nearest neighbor graph

(p.23, spectral clustering)

- Given m data points, threshold ϵ , construct matrix $A \in R^{m \times m}$

$$A^{ij} = \begin{cases} 1, & \text{if } \|x^i - x^j\| \leq \epsilon \\ 0, & \text{otherwise} \end{cases}$$



Isomap

- Given m data points, $\{x^1, x^2, \dots, x^m\} \in R^n$
- Step 1: build a **weighted** graph A using nearest neighbors, and compute pairwise shortest distance matrix D

- Step 3: use a centering matrix $H = I - \frac{1}{m} 11^T$ to get

$$C = -\frac{1}{2m} H (D^2)^2 H$$

- Step 4: compute leading eigenvectors w^1, w^2, \dots and eigenvalues $\lambda_1, \lambda_2, \dots$ of C

$$Z^T = (w^1, w^2 \dots) \begin{pmatrix} \lambda_1^{1/2} & & \\ & \lambda_2^{1/2} & \\ & & \ddots \end{pmatrix}$$

In Step 3 we are calculating the gram matrix


The Gram matrix of the columns of an $m \times n$ matrix M is $M^T M$, an $n \times n$ matrix.

The rank of M and that of the Gram matrix of its columns are equal. In particular, if the Gram matrix is invertible, then M has full rank, so its columns are linearly independent. This is what the Gram matrix is usually used for.

$$D_{ij}^2 := (D_{ij})^2$$

Is the entrywise square of the distance matrix

Is the principal direction interpretable?



Result by isomap

