ACADEMIC TASK GOVERNANCE AND CODE ASSESSMENT PLATFORM

A PROJECT REPORT

Submitted by

THARUNKUMAR K **(922524205171)**

SANTHOSHKUMAR S **(922524205148)**

in partial fulfillment for the award of the degree

of

BACHELOR OF TECHNOLOGY

in

INFORMATION TECHNOLOGY

V.S.B. ENGINEERING COLLEGE, KARUR-639111

(AN AUTONOMOUS INSTITUTION)

ANNA UNIVERSITY:: CHENNAI - 600 025

NOV-DEC 2026

ANNA UNIVERSITY : CHENNAI 600 025

BONAFIDE CERTIFICATE

Certified that this project report titled **"ACADEMIC TASK GOVERNANCE AND CODE ASSESSMENT PLATFORM"** is the bonafide work of **K. THARUNKUMAR (922524205171)** and **S. SANTHOSHKUMAR (922524205148)** who carried out the project work under my supervision.

SIGNATURE

Mr. S. NELSON, M.E.
SUPERVISOR
Assistant Professor
Department of Information Technology
V.S.B. Engineering College
Karur – 639 111.

SIGNATURE

Dr. P. AROCKIA MARY, M.E., Ph.D.
HEAD OF THE DEPARTMENT
Department of Information Technology
V.S.B. Engineering College
Karur – 639 111.

Submitted for Anna University Project Viva-Voce held on _____

INTERNAL EXAMINER **EXTERNAL EXAMINER**

ACKNOWLEDGEMENT

First and foremost, we express our profound thanks to our parents for providing us with a supportive environment and continuous encouragement for carrying out this project. We wish to express our sincere gratitude to our founder and Chairman, Shri. V. S. BALSAMY, B.Sc., L.L.B., for his dedication and vision in educating us in this premier institution.

We extend our deep gratitude to **Dr. C. VENNILA, M.E., Ph.D.**, Principal, and **Dr. T. S. KIRUBA SHANKAR, M.E., Ph.D.**, Vice Principal, V.S.B. Engineering College, Karur, for their encouraging support and academic leadership throughout the course of this project.

We express our sincere indebtedness to **Dr. P. AROCKIA MARY, M.E., Ph.D.**, Head of the Department, Department of Information Technology, for her constant support, valuable suggestions, and department facilities.

We are deeply grateful to our Project Supervisor, **Mr. S. NELSON, M.E.**, Assistant Professor, Department of Information Technology, for his continuous guidance, technical insights, and patience throughout the conceptualization and development of our project.

Our sincere thanks to all the faculty members of the Department of Information Technology and our fellow students for their constructive feedback and assistance in the successful completion of this project.

Finally, we bow before God, the Almighty, who guides our paths and blesses our endeavours. We offer our humble praise and gratitude to Almighty God for the successful completion of this project work.

DEPARTMENT OF INFORMATION TECHNOLOGY

Vision of the Institution:

We endeavour to impart futuristic technical education of the highest quality to the student community and to inculcate discipline in them with self-confidence and thus we prepare them for life as responsible citizens to uphold human values, to be of service at large and establish the Institution as a centre of academic excellence of global standards.

Mission of the Institution:

We transform persons into personalities by state-of-the-art infrastructure, time consciousness, quick response and best practices through continuous assessment and advice.

Vision of the Department:

To provide professional computing training to make competent engineers and thus prepare them to work in the emerging trends of the information technology field.

Mission of the Department:

1. Producing quality IT engineers with good technical knowledge by effective teaching.
2. Making competent engineers adapt to the dynamic needs of the industries.
3. Developing extensive learning skills in academic studies.
4. Inculcating strong ethical values and professionalism to serve society with responsibility.

PROGRAM EDUCATIONAL OBJECTIVES (PEOs)

PEO1: To make graduates proficient in utilizing the fundamental knowledge of various streams in engineering and technology.

PEO2: To enrich graduates with core competencies necessary for applying computing technologies in the context of business enterprise.

PEO3: To enable graduates to think logically and pursue lifelong learning to understand technical issues related to computing systems and provide optimal solutions.

PEO4: To enable graduates to develop software and hardware systems by understanding the importance of social, business, and environmental needs in context.

PROGRAM OUTCOMES (POs)

PO1. **Engineering knowledge:** Apply the knowledge of mathematics, science, engineering fundamentals, and an engineering specialization to the solution of complex engineering problems.

PO2. **Problem analysis:** Identify, formulate, review research literature, and analyze complex engineering problems reaching substantiated conclusions using first principles of mathematics, natural sciences, and engineering sciences.

PO3. **Design/development of solutions:** Design solutions for complex engineering problems and design system components or processes that meet the specified needs with appropriate consideration for public health and safety, cultural, societal, and environmental factors.

PO4. **Conduct investigations of complex problems:** Use research-based knowledge and methods including design of experiments, analysis and interpretation of data, and synthesis of information to provide valid conclusions.

PROGRAM OUTCOMES (POs) (CONTINUED)

PO5. **Modern tool usage:** Create, select, and apply appropriate techniques, resources, and modern engineering and IT tools including prediction and modeling to complex engineering activities with an understanding of limitations.

PO6. **The engineer and society:** Apply reasoning informed by contextual knowledge to assess societal, health, safety, legal, and cultural issues and the consequent responsibilities relevant to professional engineering practice.

PO7. **Environment and sustainability:** Understand the impact of professional engineering solutions in societal and environmental contexts, and demonstrate knowledge of and need for sustainable development.

PO8. **Ethics:** Apply ethical principles and commit to professional ethics, responsibilities, and norms of engineering practice.

PO9. **Individual and team work:** Function effectively as an individual, and as a member or leader in diverse teams, and in multidisciplinary settings.

PO10. **Communication:** Communicate effectively on complex engineering activities with the engineering community and with society at large, such as comprehending and writing effective reports and design documentation, making effective presentations, and giving and receiving clear instructions.

PO11. **Project management and finance:** Demonstrate knowledge and understanding of engineering and management principles and apply these to one's own work, as a member and leader in a team, to manage projects in multidisciplinary environments.

PO12. **Life-long learning:** Recognize the need for, and have the preparation and ability to engage in independent and life-long learning in the broadest context of technological change.

PROGRAM SPECIFIC OUTCOMES (PSOs)

PSO1: Apply mathematical and computing knowledge to identify and provide solutions for computing problems.

PSO2: Design and develop computer programs and projects using current software technologies.

PSO3: Apply standard engineering practice for software development to deliver quality software products.

Project Mapping to Program Specific Outcomes

Outcome	Institutional Focus	Demonstrated Project Deliverable in VSBEC IT Vault
PSO1	Computing Foundations	Algorithmic evaluation engine, automated testcase parsing, and LeetCode GraphQL telemetry tracking.
PSO2	Modern Software Tech	Full-stack single-page application built on React 19, TypeScript, Express 4.21, and Supabase PostgreSQL.
PSO3	Engineering Standards	CI/CD backup workflows, 3-tier RBAC authorization, and automated regression testing.

Table: Departmental Outcome Alignment Matrix

ABSTRACT

In technical higher education institutions, departmental academic task governance, continuous laboratory evaluation, and competitive programming velocity encounter operational challenges. Course deliverables are frequently fragmented across shared cloud spreadsheets, messaging channels, and physical observation notebooks. This fragmentation causes grading latency, submission tracking errors, and an absence of unified visibility into daily student problem-solving progress. Additionally, academic institutions require structured methods to assess multi-language coding competency alongside non-invasive evaluation monitoring.

To address these challenges, this project presents **VSBEC IT Vault**, an integrated academic task governance, competitive coding telemetry, and assessment platform engineered for departmental deployment. The system combines a responsive single-page frontend built with **React 19**, **Vite 6**, and **Tailwind CSS 4** with a **Node.js 20** and **Express 4.21** application service layer, connecting to a **PostgreSQL** database hosted on Supabase with transaction-mode connection pooling to handle concurrent requests.

The platform is designed around three primary technical subsystems: **(1) Automated Data Export and Dual-Repository Synchronization**: Scheduled GitHub Actions workflows export daily student activity reports, generate structured JSON relational snapshots, and maintain dual-remote Git synchronization between the primary and mirror repositories; **(2) High-Availability Transactional Email Dispatch**: An account-pooling engine managing multiple Brevo API credentials with automated fallback to secondary SMTP relays, supporting 6-digit one-time password (OTP) verification and credential recovery workflows; and **(3) Sandboxed Multi-Language Compiler Engine**: Local execution runtimes for C, C++, Java, and Python with a 3-second timeout (3000 ms), active 64 KB output capping, and automated fallback to the Judge0 CE API, supported by client-side Picture-in-Picture (PIP) webcam display and tab-switch telemetry logging.

During the 2025–2026 academic pilot deployment in the Department of Information Technology at V.S.B. Engineering College, the platform supported **369 enrolled students** across 6 sections, digitizing laboratory assignment submissions for participating courses and achieving an estimated faculty grading workload reduction of 15+ hours weekly. The project was submitted to the Ministry of Education's Smart India Hackathon (SIH 2026) under problem statement SIH26044, receiving institutional finalist nomination. The project outcomes correlate directly with **PO1**, **PO2**, **PO3**, **PO4**, **PO5**, **PO8**, **PO10**, and **PSO1, PSO2, PSO3**.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	viii
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xiii
1.	**INTRODUCTION**	**1**
	1.1 BACKGROUND AND DOMAIN SIGNIFICANCE	2
	1.2 TECHNICAL MOTIVATION AND PROBLEM STATEMENT	2
	1.3 PROJECT OBJECTIVES	3
	1.4 ORGANIZATION OF THE REPORT	3
2.	**LITERATURE SURVEY**	**4**
3.	**SYSTEM ANALYSIS**	**7**
	3.1 EXISTING SYSTEM	8
	3.2 EXISTING SYSTEM DISADVANTAGES	8
	3.3 PROPOSED SYSTEM	9
	3.4 PROPOSED SYSTEM ADVANTAGES	9
4.	**SYSTEM SPECIFICATION**	**11**
	4.1 HARDWARE REQUIREMENTS	12
	4.2 SOFTWARE REQUIREMENTS	13
	4.3 ARCHITECTURAL INTEGRATION	13
5.	**IMPLEMENTATION**	**14**
	5.1 SYSTEM ARCHITECTURE	15
	5.2 MODULES USED	16
	5.3 MODULES DESCRIPTION	16
	5.3.1 Role-Based Access Control & Row-Level Security	16

CHAPTER NO.	TITLE	PAGE NO.
	5.3.2 3-Tier Hierarchical Verification Pipeline	17
	5.3.3 Multi-Language Sandboxed Compiler Engine	18
	5.3.4 LeetCode GraphQL & GitHub Telemetry Daemons	18
	5.3.5 Automated Disaster Recovery and Backup Workflow	19
	5.3.6 High-Availability Multi-Account Brevo Email Engine	19
	5.3.7 Tri-Channel Notification Dispatcher	20
	5.3.8 Picture-in-Picture (PIP) Proctoring Telemetry	20
	5.3.9 Corporate Placement Readiness Index	20
6.	**SYSTEM DESIGN**	**21**
	6.1 INTRODUCTION	22
	6.2 CLASS DIAGRAM	22
	6.3 USE CASE DIAGRAM	24
	6.4 SEQUENCE DIAGRAM	25
	6.5 ACTIVITY DIAGRAM	27
	6.6 DATA FLOW DIAGRAM (DFD LEVEL 0 & LEVEL 1)	28
7.	**SYSTEM TESTING**	**29**
	7.1 INTRODUCTION AND TEST ENVIRONMENT	30
	7.2 TESTING METHODOLOGIES	30
	7.3 TEST CASES AND EMPIRICAL VALIDATION	31
	7.4 EMPIRICAL RESULTS AND SYSTEM RELIABILITY METRICS	31
8.	**FEASIBILITY STUDY**	**32**
	8.1 FEASIBILITY ANALYSIS	33
	8.1.1 Technical Feasibility	33
	8.1.2 Economic Feasibility	33
	8.1.3 Operational Feasibility	34
	8.2 ENGINEERING METHODOLOGY AND AGILE DEVOPS	34

CHAPTER NO.	TITLE	PAGE NO.
9.	**CONCLUSION AND FUTURE ENHANCEMENT**	**35**
	9.1 CONCLUSION	36
	9.2 PROPOSED FUTURE ENHANCEMENTS	37
	9.3 CONCLUDING REMARKS	37
APPENDIX	**SOURCE CODE & SCREENSHOTS**	**38**
	Listing 1: Sandbox Execution Engine	39
	Listing 2: Judge0 Cloud Failover	40
	Listing 3: LeetCode & GitHub Telemetry Daemons	41
	Listing 4: Multi-Tier Review Controller	42
	Appendix B: Screenshots of System Interfaces	43
	REFERENCES	**46**
	BIBLIOGRAPHY	**47**

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
5.1	SYSTEM ARCHITECTURE DIAGRAM	15
6.1	CLASS DIAGRAM	23
6.2	USE CASE DIAGRAM	25
6.3	SEQUENCE DIAGRAM	26
6.4	ACTIVITY DIAGRAM	27
6.5	DATA FLOW DIAGRAM	28
B.1	STUDENT & HOD CODING PROGRESS WITH GITHUB TRACKER AND LEADERBOARD	43
B.2	MONACO CODE COMPILER & COLLABORATIVE LIVE TEACHING HUB	44
B.3	COORDINATOR WORKSPACE & VERIFICATION DASHBOARD	45
B.4	CORPORATE HR PLACEMENT READINESS RATING PORTAL	45

LIST OF ABBREVIATIONS

S.NO.	ABBR.	EXPANSION
1.	LMS	Learning Management System
2.	RBAC	Role-Based Access Control
3.	JWT	JSON Web Token
4.	RLS	Row-Level Security
5.	PIP	Picture-in-Picture (Webcam Stream)
6.	VAPID	Voluntary Application Server Identification (Web Push)
7.	REST	Representational State Transfer
8.	GraphQL	Query Language for Application Programming Interfaces
9.	OTP	One-Time Password
10.	JSON	JavaScript Object Notation
11.	FSM	Finite State Machine
12.	RPO	Recovery Point Objective
13.	RTO	Recovery Time Objective
14.	IDE	Integrated Development Environment
15.	SIH	Smart India Hackathon
16.	HOD	Head of the Department
17.	SPA	Single-Page Application
18.	DFD	Data Flow Diagram
19.	API	Application Programming Interface
20.	UI/UX	User Interface / User Experience

INTRODUCTION

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND AND DOMAIN SIGNIFICANCE

In engineering education, effective governance of continuous academic evaluations and laboratory deliverables is vital for student learning. Computing curricula demand that students actively engage with practical programming assignments, competitive problem solving, and industry technical assessments.

However, departmental administration frequently relies on disconnected communication channels, including generic messaging groups, shared spreadsheets, and physical notebooks. This introduces operational friction: student submissions are misattributed, grading backlogs accumulate, and departments lack an auditable review history.

Concurrently, software engineering recruitment emphasizes demonstrated coding competency on platforms such as LeetCode and version-controlled histories on GitHub. To address these operational and pedagogical gaps, this project develops **VSBEC IT Vault**, an integrated platform for academic task governance, competitive telemetry harvesting, and proctored coding assessments.

1.2 TECHNICAL MOTIVATION AND PROBLEM STATEMENT

While general-purpose Learning Management Systems (LMS) such as Moodle and Google Classroom excel at distributing course syllabi, they exhibit specific limitations when applied to computing education:

1. **Absence of Integrated Code Evaluation:** General systems treat program files as passive attachments, requiring manual local download, environment setup, and execution.
2. **Single-Tier Role Models:** Standard portals lack granular multi-tier Role-Based Access Control (RBAC) to support peer coordinator audits and faculty reviews.
3. **Unsynchronized Data Backups:** Academic records stored in ephemeral databases lack automated offsite snapshot pipelines and cross-repository synchronization.
4. **Isolation from External Telemetry:** Platforms lack automated interfaces with competitive programming APIs, leaving faculty without longitudinal insight into student practice.

1.3 PROJECT OBJECTIVES

To address these technical and operational requirements, the **VSBEC IT Vault** project defines six concrete engineering objectives:

1. **Centralized Academic Task Governance:** Design and implement an auditable 3-tier review hierarchy (Student Coordinator → Faculty Class Advisor → Head of Department) with cloud asset management and automated Excel summary generation.
2. **Sandboxed Multi-Language Compiler Engine:** Engineer a sandboxed execution runtime supporting C, C++, Java 17, and Python 3 with a 3-second timeout limit (3000 ms), active 64 KB output buffer enforcement, and automated fallback to the Judge0 CE cloud execution runtime.
3. **Automated Telemetry Harvesting Daemons:** Construct scheduled background services that query LeetCode GraphQL and GitHub REST APIs daily to compute problem solves, active streaks, and departmental leaderboards based on Indian Standard Time.
4. **Automated Disaster Recovery and Dual-Remote Synchronization:** Deploy automated scheduled workflows to export daily CSV/JSON student progress reports, generate relational database snapshots, and maintain dual-remote Git synchronization.
5. **High-Availability Transactional Notification Engine:** Implement a multi-account email dispatch engine with automated failover for 6-digit OTP delivery, alongside Telegram bot webhooks and Web Push notifications.
6. **Non-Invasive Browser Evaluation Telemetry:** Integrate Picture-in-Picture (PIP) webcam display, fullscreen mode enforcement, and tab-switch event traps to log student integrity events during assessments for subsequent faculty review.

1.4 ORGANIZATION OF THE REPORT

The remainder of this report is organized as follows: Chapter 2 reviews relevant academic and industry literature. Chapter 3 analyzes existing system limitations and formalizes the proposed architecture and comparison matrix. Chapter 4 specifies hardware and software requirements. Chapter 5 details the core algorithmic, database, and telemetry implementation. Chapter 6 presents UML and Data Flow Diagram (DFD) system designs. Chapter 7 validates test cases and testing methodologies. Chapter 8 evaluates technical, economic, and operational feasibility. Chapter 9 presents concluding remarks and planned future enhancements. Appendix A provides representative source code listings, Appendix B provides system interface screenshots, followed by References and Bibliography.

LITERATURE SURVEY

CHAPTER 2

LITERATURE SURVEY

"Development and Classroom Evaluation of a Static-Assessment Programming Practice Platform" by Jeon, J., Jang, J., and Jung, S. K. (2025) [1] – The authors investigated web-based programming platforms (Code-Assist-Lab) that utilize static code evaluation paradigms, specifically abstract syntax tree (AST) inspection, cyclomatic complexity calculations via Radon, and style linting via Flake8. The authors demonstrated that static evaluation reduces server-side execution risks and infrastructure costs by avoiding arbitrary dynamic execution. However, as noted in their evaluation, static analysis alone cannot verify runtime behavior, handle dynamic edge cases, or enforce CPU and memory boundaries. Additionally, the study focused on single-student practice sessions and did not incorporate multi-tier departmental review workflows or longitudinal activity tracking across multiple sections.

"Integration of Multiple Sources to Anticipate Student Performance Using Learning Analytics" by Moreno-Marcos, P. M. et al. (2025) [2] – This research explored predictive learning analytics in higher education by consolidating heterogeneous data streams, including Learning Management System (LMS) clickstream telemetry, SPOC video viewing frequencies, and historical grade records. The authors reported that multi-source feature extraction improved early prediction of examination outcomes. However, the study's analytical model operated primarily as a post-hoc reporting system without immediate closed-loop intervention mechanisms, automated notifications, or synchronized practical programming environments to assist struggling students in real time.

"Shaking The Silos: Impact of Sequential Live Coding on Students' Performance" by Cho, K., Ali, S. F., Bang, S. J., and Anwar, S. (2024) [3] – The authors evaluated Sequential Live Coding (SLC), an instructional method where students take turns writing and explaining code in front of peers during class sessions. While their empirical findings showed enhanced classroom engagement and conceptual retention during instructor-led sessions, the methodology was confined to synchronous classroom activities. It did not provide automated longitudinal tracking of independent practice on competitive platforms (such as LeetCode or GitHub) or an asynchronous verification pipeline for continuous laboratory deliverables.

To contextualize the technical challenges and define the functional scope of the proposed system, Table 2.1 summarizes recent literature, noting the primary methodologies investigated by the authors and the operational limitations identified for institutional task governance.

S.NO	PAPER TITLE	AUTHOR(S)	YEAR	IDENTIFIED SCOPE & OPERATIONAL GAPS
1	Development and Classroom Evaluation of a Static-Assessment Programming Practice Platform	Jeon J. et al.	2025	Focused on static code analysis; does not verify runtime execution correctness or provide multi-tier review hierarchies.
2	Integration of Multiple Sources to Anticipate Student Performance Using Learning Analytics	Moreno-Marcos P.M. et al.	2025	Demonstrates predictive modeling from historical LMS data; lacks automated real-time intervention and integrated coding practice environments.
3	Shaking The Silos: Impact of Sequential Live Coding on Students' Performance	Cho K., Ali S.F., Bang S.J., Anwar S.	2024	Examines synchronous classroom live coding; does not track longitudinal external telemetry (LeetCode/GitHub) or asynchronous lab workflows.

Table 2.1: Comparative Summary of Literature Survey and Identified Scope

Synthesis of Literature Gaps and Proposed System Rationale:

Review of the literature reveals that existing educational platforms generally address isolated components of computing education: static code inspection without dynamic evaluation (Jeon et al. [1]), historical predictive modeling without real-time intervention (Moreno-Marcos et al. [2]), or synchronous active learning without automated continuous tracking (Cho et al. [3]).

The proposed **Academic Task Governance and Code Assessment Platform** integrates these dimensions into a unified workflow: (1) a multi-language compiler execution environment supporting C, C++, Java, and Python with automated 3-second timeout limits, output caps, and Judge0 cloud fallback for runtime verification, building upon online judge models reviewed by Wasik et al. [4]; (2) a multi-level Role-Based Access Control (RBAC) governance framework following principles formalized by Sandhu et al. [5]; (3) background daemons that harvest LeetCode GraphQL and GitHub REST telemetry to track ongoing practice velocity; and (4) an auditable 3-tier review process (Student Coordinator $\rightarrow$ Faculty Advisor $\rightarrow$ HOD) with multi-channel notifications (Telegram, Web Push, and email) to support timely feedback and academic oversight.

SYSTEM ANALYSIS

CHAPTER 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

In prevailing academic operating models, departmental task governance, programming assignment verification, and student career readiness tracking are conducted through disjointed mechanisms. Faculty members and student coordinators rely on a patchwork of consumer tools, including Google Forms, WhatsApp broadcast channels, shared spreadsheets, and printed observation notebooks. While these tools offer initial convenience, their complete lack of architectural integration introduces systemic operational challenges:

1. **Deliverable Fragmentation and Zero Auditability:** Student submissions are scattered across personal drives and chat messages without an immutable audit trail of review timestamps and feedback.
2. **Absence of Native Sandboxed Code Compilation:** Conventional systems treat source code as passive attachments, requiring evaluators to download, configure dependencies, and compile code locally.
3. **Algorithmic Telemetry Blind Spot:** Students practice on LeetCode and GitHub independently without faculty having real-time visibility into solve velocity, difficulty distributions, or daily streaks.
4. **Unreliable Alerting and High Deadline Miss Rates:** Deadlines communicated via broadcast channels suffer from low open rates, leading to missed submissions and administrative friction.

3.2 EXISTING SYSTEM DISADVANTAGES

A deep architectural audit reveals several critical vulnerabilities in the existing operating model:

1. **Zero Automated Disaster Recovery:** Departmental spreadsheets lack automated offsite backup mechanisms, risking permanent loss during local hardware failures.
2. **Single-Tier Insecure Authentication:** Existing portals employ flat access controls without multi-role segregation, exposing grade data to unauthorized manipulation.
3. **Unoptimized Storage Pipelines:** Submissions uploaded directly to application servers as local files exhaust disk capacity and risk directory traversal.
4. **Absence of Anti-Cheat Proctoring:** Online assessments conducted via generic forms provide zero protection against tab switching or unauthorized aids.

3.3 PROPOSED SYSTEM

The proposed **VSBEC IT Vault** platform overcomes every limitation of the legacy setup by establishing an integrated, cloud-native architecture engineered specifically for the Department of Information Technology at V.S.B. Engineering College.

The platform is structured across five synchronized engineering pillars: First, a responsive single-page web client built with React 19, Vite 6, and Tailwind CSS provides customized role dashboards for Supreme Admins, HOD, Faculty Class Advisors, Student Coordinators, Students, and Industry Partners. Second, a resilient Node.js 20 and Express 4.21 application layer enforces strict Role-Based Access Control (RBAC) via cryptographically signed JSON Web Tokens (JWT) and Bcrypt hashing. Third, an enterprise PostgreSQL database hosted on Supabase utilizes dynamic transaction-mode connection pooling on port 6543, eliminating serverless connection exhaustion. Fourth, a multi-language sandboxed compiler engine isolates student code executions in C, C++, Java 17, and Python 3 inside secure process jails with 3000ms execution timeout traps and automatic failover to the Judge0 CE cloud API. Fifth, an automated disaster recovery workflow running on GitHub Actions executes twice daily (07:50 AM IST and 11:55 PM IST), exporting complete student progress reports, database JSON snapshots, and syncing code to dual Git remotes.

3.4 PROPOSED SYSTEM ADVANTAGES AND COMPARISON MATRIX

The proposed system delivers measurable operational improvements across departmental governance, academic velocity, and assessment integrity. Table 3.1 details a comprehensive feature-by-feature comparison between traditional academic tools and the verified capabilities of the VSBEC IT Vault platform.

Dimension / Feature	Traditional Academic Systems (LMS / Forms / Sheets)	Proposed VSBEC IT Vault Architecture
Role-Based Access Control (RBAC)	Flat single-tier or two-tier permissions; no peer coordinator verification layer.	Granular 6-role hierarchy (`SUPREME_ADMIN`, `HOD`, `ADVISOR`, `COORDINATOR`, `STUDENT`, `INDUSTRY`).
Code Evaluation Runtime	Passive file upload; manual compiler installation and local execution required.	Multi-language sandbox (C, C++, Java 17, Python 3) with 3000ms timeout traps and Judge0 failover.
External Telemetry Sync	None; external coding practice remains invisible to faculty advisors.	Automated daemons polling LeetCode GraphQL and GitHub REST events every 24 hours.
Disaster Recovery & Backups	Manual file copies; no automated offsite replication or versioned snapshots.	Scheduled GitHub Actions running twice daily exporting JSON snapshots and syncing dual remotes.
Transactional Notifications	Unreliable broadcast emails; low open rates and missed deadlines.	Multi-channel notifications via Brevo email pooling (5 nodes), Telegram bot webhooks, and Web Push.
Assessment Integrity & Proctoring	None; open to unauthorized tab switching and external resource access.	Picture-in-Picture webcam monitoring, HTML5 fullscreen lock, and blur event traps.
Asset Management	Local server filesystem storage; risk of server disk exhaustion.	Cloudinary cloud storage with automated optimization and secure URL persistence.

Table 3.1 Comparative Analysis: Traditional Systems vs. VSBEC IT Vault

SYSTEM SPECIFICATION

CHAPTER 4

SYSTEM SPECIFICATION

4.1 HARDWARE REQUIREMENTS

The **VSBEC IT Vault** platform is architected for lightweight, high-speed execution across diverse client devices while taking full advantage of serverless edge compute and elastic cloud infrastructure on the backend.

Client Side (Student / Faculty Workstation / Mobile Device):

Component	Specification / Threshold
Device Architecture	Laptop / Desktop PC / Android or iOS Smartphone
Processor	Dual-Core 2.0 GHz or higher (x86_64 or ARM64)
System Memory (RAM)	Minimum 4 GB RAM (8 GB recommended for Monaco IDE)
Available Storage	Minimum 250 MB free disk space for browser caching
Peripheral Hardware	Standard Web Camera and Microphone (for Proctored Tests)
Display Resolution	1366×768 minimum (1920×1080 recommended)
Network Interface	Stable 4G/5G mobile connection or Wi-Fi (minimum 1 Mbps)

Table 4.1: Client-Side Hardware Specifications

Server Side (Production Cloud Infrastructure & Database Host):

Infrastructure Layer	Deployment Specification
Server Compute	Vercel Serverless Edge Runtime / Node.js 20 LTS Host
Processor (Virtual CPU)	Minimum 2 vCPUs @ 2.4 GHz
Memory (RAM)	2 GB Dedicated RAM (Dynamically Scalable to 8 GB)
Persistent Storage	Cloud-hosted SSD (Supabase PostgreSQL Enterprise Tier)
Network Throughput	Gigabit Ethernet Interface (1 Gbps symmetric)
External Media Storage	Cloudinary Secure Object Storage (Global CDN)

Table 4.2: Production Cloud Server Hardware Specifications

4.2 SOFTWARE REQUIREMENTS AND EXACT DEPENDENCY MANIFEST

All software libraries and execution environments were audited directly against the project's dependency manifest in `package.json`:

Frontend Client Environment:

Subsystem / Library	Verified Codebase Version / Specification
Web Browser Compatibility	Google Chrome 110+, Firefox 115+, Edge 110+, Safari 16+
Single-Page Framework	React 19.0.0 with React DOM 19.0.0
Build Tool & Bundler	Vite 6.2.0 (ESM mode with Hot Module Replacement)
Language Standard	TypeScript 5.8 (Strict type checking enabled)
UI Styling & Design System	Tailwind CSS 4.1.14 with @tailwindcss/vite
Iconography & Animations	Lucide React 1.16.0, Motion 12.23.24, Canvas Confetti 1.9.4
In-Browser Code Editor	Monaco Editor (@monaco-editor/react 4.7.0)

Table 4.3: Frontend Subsystems and Verified Dependencies

Backend Application & Data Layer:

Service / Component	Verified Codebase Version / Specification
Runtime Engine	Node.js 20.x / 22.x LTS (ES Modules runtime mode)
Web Application Framework	Express.js 4.21.2 with CORS 2.8.5 and Gzip Compression
Relational Database Driver	PostgreSQL (pg 8.22.0) with custom type parsers
Authentication & Hashing	JSON Web Tokens (jsonwebtoken 9.0.2), Bcrypt.js 3.0.2
Media Asset Pipeline	Multer 1.4.5-lts.1, Cloudinary SDK 1.41.3
Transactional Mailer	Brevo REST API v3, Nodemailer 9.0.5, Resend API fallback
Push Notification Engine	Web-Push 3.6.7 (VAPID Elliptic Curve P-256 keys)
Application Monitoring	Sentry Node SDK (@sentry/node 10.69.0)
Schema Validation	Zod 4.3.6 for robust request body sanitization
Report Compilation	SheetJS (xlsx 0.18.5) for departmental Excel exports

Table 4.4: Backend Services and Database Infrastructure Manifest

4.3 ARCHITECTURAL INTEGRATION AND RUNTIME GUARDS

The system architecture implements critical runtime guards: the PostgreSQL pooler dynamically rewrites port 5432 to port 6543 (transaction mode) to avoid client connection exhaustion; Libuv worker pools are scaled to 128 threads for non-blocking bcrypt hashing; and Sentry 10.69 provides distributed transaction tracing and error monitoring.

IMPLEMENTATION

CHAPTER 5

IMPLEMENTATION

5.1 SYSTEM ARCHITECTURE

The technical architecture of the **VSBEC IT Vault** platform is structured across four decoupled tiers: the client presentation tier, API application gateway, execution sandbox, and persistent cloud services. Bidirectional data flows coordinate interactive UI components, compiler runtimes, PostgreSQL connection poolers, and external telemetry daemons.




Fig 5.1 System Architecture

As illustrated in Figure 5.1, the client presentation layer is built on React 19 and Vite 6, incorporating the Monaco code editor and Picture-in-Picture webcam telemetry. The API gateway enforces role-based route guards and rate limiting before dispatching requests to either the local execution sandbox or the Judge0 cloud runtime. Database transactions are managed through pooled Supabase PostgreSQL connections, complemented by Cloudinary media storage, multi-account Brevo email dispatch, and Telegram Bot webhook notifications.

5.2 MODULES USED

Table 5.1 catalogs the primary production modules in the repository, their source code filepaths, and their architectural responsibilities.

Module Filepath	Architectural Scope and Implementation Responsibility
`server.ts`	Express application root, REST API routing, RBAC route guard middleware, transaction-safe 3-tier review endpoints, and proctoring event handlers.
`db.ts`	PostgreSQL database pooler, dynamic port 6543 rewrite for transaction pooling, custom INT8 and DATE type parsers, and schema migration routines.
`codingSandboxService.ts`	Multi-language compiler runtime (C, C++, Java 17, Python 3), 3-second timeout traps (3000 ms), active 64 KB stream buffer bounds, and Judge0 CE cloud failover.
`emailService.ts`	Multi-account Brevo API load balancer (up to 5 account nodes), high-availability failover to Resend and SMTP, and 6-digit OTP email dispatch.
`telegramService.ts`	Telegram Bot API webhook listener, student register number linking, daily streak broadcasts, and 2-hour task deadline alerts.
`githubSyncService.ts`	Public GitHub REST event scraper, commit aggregation, and student portfolio synchronization.
`.github/workflows/auto-backup.yml`	Automated backup workflow running at 07:50 AM and 11:55 PM IST, daily report generation, and dual-remote GitHub sync.
`scripts/export-backup.ts`	LeetCode batch report generator, year/section CSV and JSON serializations, and database table JSON snapshot dumps.
`src/pages/StudentAssessment.tsx`	Monaco code editor interface, webcam Picture-in-Picture stream, HTML5 fullscreen enforcement, and tab-switch telemetry listeners.

Table 5.1: System Modules and Source Code Implementation Mapping

5.3 MODULES DESCRIPTION

5.3.1 Role-Based Access Control (RBAC) & Row-Level Security (RLS)

This module governs authorization across six institutional roles: `SUPREME_ADMIN`, `HOD`, `CLASS_ADVISOR`, `STUDENT`, `COORDINATOR`, and `INDUSTRY`. Upon authentication, the server signs a JSON Web Token (JWT) using HMAC-SHA256:

$$T_{\text{jwt}} = \text{HMAC-SHA256}(\text{Base64}(H) \parallel \text{Base64}(P), K_{\text{jwt}}) \tag{1}$$

where payload P encapsulates user ID, role, department ID, and class scope. Every API endpoint enforces role middleware validating bearer tokens and rejecting unauthorized requests

with HTTP 403. Passwords are salted and hashed using `bcryptjs` with 10 salt rounds.

At the database tier, Supabase PostgreSQL Row-Level Security (RLS) policies enforce access boundaries directly within the database engine:

```
-- Enable RLS and isolate student records from peer modification
ALTER TABLE task_submissions ENABLE ROW LEVEL SECURITY;

CREATE POLICY student_view_own_submissions ON task_submissions
  FOR SELECT USING (auth.uid() = user_id);

CREATE POLICY student_insert_own_submissions ON task_submissions
  FOR INSERT WITH CHECK (auth.uid() = user_id);

CREATE POLICY staff_manage_submissions ON task_submissions
  FOR ALL USING (
    EXISTS (
      SELECT 1 FROM users
      WHERE users.id = auth.uid()
      AND users.role IN ('COORDINATOR', 'CLASS_ADVISOR', 'HOD')
      AND users.department_id = task_submissions.department_id
    )
  );
```

5.3.2 3-Tier Hierarchical Verification Pipeline & Cloud Asset Lifecycle

The core academic workflow enforces an auditable multi-tier verification finite state machine (FSM). When a student submits task evidence (source code, screenshots, and custom fields), the submission transitions across deterministic lifecycle states:

$$S_0(\text{PEND}) \xrightarrow{\text{submit}} S_1(\text{SUBMITTED}) \xrightarrow{\text{audit}} S_2(\text{PEER_VERIFIED}) \xrightarrow{\text{review}} S_3(\text{VERIFIED}) \tag{2}$$

If deficiencies are identified at any tier, the reviewer triggers a state transition to `REJECTED`:

$$S_{\text{current}} \xrightarrow{\text{reject}} S_{\text{rejected}}, \quad N_{\text{resubmit}} \leftarrow N_{\text{resubmit}} + 1 \tag{3}$$

The review controller wraps state transitions in explicit database transactions (`BEGIN ... COMMIT`). If a submission is not found or fails role/state validation, the transaction is immediately rolled back (`ROLLBACK`) and the client connection is released. All uploaded evidence assets are streamed directly to Cloudinary using signed multipart uploads via `multer-storage-cloudinary`. The database stores the secure HTTPS URL alongside the Cloudinary `public_id`. When an assignment concludes, an automated cleanup daemon purges obsolete screenshots from Cloudinary storage to prevent storage waste. Every transition creates an auditable record in `submission_reviews` capturing reviewer ID, timestamp, and feedback.

5.3.3 Multi-Language Sandboxed Compiler Engine & Judge0 Failover

The coding assessment subsystem executes student source code in C, C++, Java 17, and Python 3. To limit resource access and directory traversal, local execution uses child processes spawned with a sanitized environment containing only essential system variables:

$$\mathcal{E}_{\text{clean}} = \{\text{PATH}, \text{TEMP}, \text{TMP}, \text{COMSPEC}, \text{SYSTEMROOT}\} \tag{4}$$

Execution boundaries are enforced via timeout and buffer controls:

$$\Delta t \leq T_{\text{limit}} \quad (T_{\text{limit}} = 3000 \text{ ms}) \tag{5}$$

If execution exceeds T_{limit}, process tree termination is invoked via `taskkill /T /F` on Windows or process-group `SIGKILL` on POSIX, awaiting process exit confirmation. Output streams (`stdout` and `stderr`) are monitored during chunk collection; if accumulated bytes exceed 64 KB, the process is terminated and flagged with buffer exceeded status.

In serverless deployment environments (such as Vercel, where local system compilers like `gcc` or `javac` are unavailable in the serverless container), code execution requests automatically route to the Judge0 CE API. The engine normalizes Java source code into `public class Main`, formats stdin streams, and executes test batches with exponential backoff and jitter across retries.

5.3.4 LeetCode GraphQL & GitHub Commit Telemetry Daemons

To monitor algorithmic momentum, background daemons execute scheduled polling routines every 24 hours. The LeetCode daemon issues a GraphQL query against the LeetCode public API endpoint using the student's stored LeetCode username:

$$Q_{\text{leetcode}} = \text{GraphQL}(\text{username}, \text{matchedUser}\{\text{submitStatsGlobal}\{\dots\}\}) \tag{6}$$

To avoid misreporting lifetime solves as daily activity, the daemon retrieves the previous day's recorded solve count and calculates daily delta velocity:

$$\Delta N_{\text{today}} = \max(0, N_{\text{total}}(t) - N_{\text{total}}(t-1)) \tag{7}$$

where t represents the date boundary computed in Indian Standard Time (IST, UTC+05:30). A student is marked `COMPLETED` for the day only if $\Delta N_{\text{today}} \geq 1$.

Concurrently, the GitHub sync engine queries public user events using the student's distinct GitHub username. The engine filters for `PushEvent` payloads and aggregates the

actual commits within each push:

$$C_{\text{daily}} = \sum_{e \in \text{PushEvents}} \text{len}(e.\text{payload.commits}) \tag{8}$$

and upserts records into `github_daily_commits`.

5.3.5 Automated Disaster Recovery and Dual-Repository Backup Workflow

Disaster recovery is managed through scheduled GitHub Actions workflows configured in `.github/workflows/auto-backup.yml`, executing twice daily:

- **07:50 AM IST (`20 2 * * * UTC`):** Morning pre-sync and previous day cumulative report snapshot.
- **11:55 PM IST (`25 18 * * * UTC`):** Nightly final daily report and database table JSON snapshot export.

The workflow runs `npx tsx scripts/export-backup.ts`, querying PostgreSQL via transaction pooling to generate master CSV reports (`leetcode/LeetCode_Daily_Report_YYYY-MM-DD.csv`), section-wise files, and table data snapshots stored in `backups/db_backup_*.json`. This provides a Recovery Point Objective (RPO) of 12 hours and a tested Recovery Time Objective (RTO) under 15 minutes for table data re-seeding. When configured with synchronization credentials, the workflow commits and pushes changes to both `TK4743/taskmanager` and `Tharun4743/taskmanager` to maintain mirror parity.

5.3.6 High-Availability Multi-Account Brevo Transactional Email Engine

User authentication and password recovery utilize a multi-account Brevo transactional email engine in `emailService.ts`. To mitigate single-key quota exhaustion, the service maintains a pool of up to 5 Brevo account credentials:

$$\mathcal{N}_{\text{brevo}} = \{\text{Node}_1, \text{Node}_2, \text{Node}_3, \text{Node}_4, \text{Node}_5\} \tag{1}$$

Requests are paced with 50ms intervals and dispatched across healthy nodes. If quota exhaustion (HTTP 402/429) or network timeouts occur across all primary nodes, requests fail over to secondary SMTP relays. For password resets, the server generates a cryptographically random 6-digit OTP stored in `password_resets` with a 10-minute expiration timestamp and a 5-attempt verification limit.

5.3.7 Tri-Channel Notification Dispatcher

The platform integrates Telegram Webhooks, Web Push (VAPID), and transactional email. Students link their Telegram account by sending their register number to the department bot. Automated routines dispatch daily streak reminders, 2-hour task deadline alerts, and verification status updates via the Telegram Bot API:

$$R_{\text{telegram}} = \text{POST}(\text{API}_{\text{telegram}} \parallel \text{token}, \{\text{chat_id}, \text{text}, \text{parse_mode}\}) \tag{9}$$

Lockscreen push notifications are dispatched to browsers via VAPID service workers using elliptic curve P-256 keys.

5.3.8 Picture-in-Picture (PIP) Proctoring Telemetry

During technical coding assessments, client-side browser telemetry is collected to support faculty review without requiring invasive system-level software. The client renders a webcam stream via `getUserMedia()` in a floating Picture-in-Picture viewport, with periodic snapshot frames uploaded to Cloudinary as visual audit records. Assessments request fullscreen mode via `requestFullscreen()` with listeners on `fullscreenchange`. Focus shifts away from the test tab trigger event listeners on `document.visibilityState` and `window.onblur`, recording an integrity event:

$$E_{\text{violation}} = \{\text{type} : \text{“TAB_SWITCH”}, \text{timestamp} : t, \text{duration} : \Delta t_{\text{blur}}\} \tag{10}$$

Events are appended to the `integrity_events` JSONB column for faculty review.

5.3.9 Corporate Placement Readiness Index

The corporate module calculates an empirical Placement Readiness Index ($P_{\text{index}} \in [0, 100]$):

$$\begin{aligned} P_{\text{index}} = w_1 \cdot \left(\frac{\text{CGPA}}{10} \times 100\right) + w_2 \cdot \min\left(100, \frac{N_{\text{Leet}}}{300} \times 100\right) \\ + w_3 \cdot S_{\text{assess}} + w_4 \cdot \min\left(100, \frac{C_{\text{Git}}}{150} \times 100\right) \end{aligned} \tag{11}$$

where weights are calibrated as $w_1 = 0.30$, $w_2 = 0.30$, $w_3 = 0.25$, and $w_4 = 0.15$. Placement coordinators can export filtered dossiers in Excel (.xlsx) and PDF formats.

SYSTEM DESIGN

CHAPTER 6

SYSTEM DESIGN

6.1 INTRODUCTION

The System Design phase translates functional and operational requirements of the **VS-BEC IT Vault** platform into formal visual engineering models. Standard Unified Modeling Language (UML) diagrams and Data Flow Diagrams establish a rigorous architectural blueprint, ensuring database consistency, role-based authorization integrity, and resilient cloud microservice integration across the continuous academic lifecycle.

This chapter constructs six formal engineering models: Class Diagrams defining relational database entities and ORM mappings; Use Case Diagrams modeling multi-tier actor permissions; Sequence Diagrams capturing execution timings during proctored coding assessments; Activity Diagrams mapping verification state machines; and Data Flow Diagrams formalizing information transformation across database and cloud boundaries.

6.2 CLASS DIAGRAM

The Class Diagram models the static structural foundation of the platform's domain entities, including `User`, `Department`, `ClassGroup`, `Task`, `TaskSubmission`, `SubmissionReview`, `Team`, `LeetCodeTarget`, `GitHubDailyCommit`, `CodingAssessment`, and `NotificationPreference`.

DESIGN OBJECTIVES AND ARCHITECTURAL SCOPE:

1. Model entity attributes, primary keys, and methods corresponding to the 13 PostgreSQL schema tables.
2. Establish structural associations, composition rules, and foreign key cascades across academic entities.
3. Represent multi-tier review relationships linking student submissions to coordinator, advisor, and HOD reviews.
4. Model coding assessment entities including question banks, test cases, and candidate submission records.
5. Map telemetry entities storing daily LeetCode solve counts and GitHub commit records.
6. Formalize role-based polymorphism across Supreme Admin, HOD, Faculty, Student, and Industry entities.
7. Ensure modular separation between local persistent entities and external Cloudinary/-Judge0 assets.

The domain model enforces strong referential integrity through foreign key constraints and enumerated state types. The `User` entity acts as the root polymorphic actor, bound to specific `Department` and `ClassGroup` instances while carrying role-based attributes. Tasks maintain a one-to-many relationship with `TaskSubmission` records, which in turn cascade into immutable `SubmissionReview` audit logs. Coding assessments decouple problem statements from candidate execution containers, enabling reproducible automated grading.




Fig 6.1 Class Diagram

Each class encapsulates specific domain methods: `Task` entities manage publication windows and section allocations; `TaskSubmission` entities track multi-stage verification states and evidence URLs; and `CodingAssessment` entities handle real-time code evaluation, time limit checks, and score aggregation.

6.3 USE CASE DIAGRAM

A Use Case Diagram captures system functional requirements from the perspective of external actors. In the **VSBEC IT Vault** platform, primary human actors include **Students**, **Student Coordinators**, **Faculty Class Advisors**, the **Head of the Department (HOD)**, **Supreme Administrators**, and **Industry Partners**, alongside automated system actors (Cron Telemetry Daemons and Telegram Bots).

ACTOR CLASSIFICATION AND SCOPE:

1. **Student:** Authenticates via credentials, submits task evidence to Cloudinary, executes code in Monaco, tracks LeetCode/GitHub streaks, and reviews faculty evaluation remarks.
2. **Student Coordinator:** Conducts Tier-1 peer rubric reviews, verifies submitted artifacts, provides initial feedback, and flags non-compliant submissions for advisor escalation.
3. **Faculty Class Advisor:** Designs tasks, establishes deadlines, performs Tier-2 verification, approves coordinator reviews, and broadcasts academic reminders via Telegram bots.
4. **Head of the Department (HOD):** Exercises Tier-3 executive sign-off, reviews department-wide analytics, audits faculty evaluation timelines, and exports NBA/NAAC accreditation dossiers.
5. **Corporate Placement Partner:** Authors specialized assessment challenges, inspects verified student portfolios, reviews proctoring violation logs, and shortlists candidates.
6. **System Daemons:** Automated cron services that trigger nightly GraphQL syncs with LeetCode, harvest GitHub commits, dispatch VAPID web push alerts, and create database snapshots.

These actor boundaries ensure strict separation of concerns, eliminating unauthorized privilege escalation while streamlining high-throughput departmental academic evaluation.




Fig 6.2 Use Case Diagram

6.4 SEQUENCE DIAGRAM

A Sequence Diagram models the chronological exchange of messages between client components, API controllers, database services, and external microservices during a specific business transaction. In this platform, sequence modeling validates the temporal ordering of asynchronous operations, ensuring transaction safety, connection pooling efficiency, and graceful error handling during high-concurrency coding assessments and multi-tier reviews.

The proctored execution transaction coordinates browser-side webcam video capture, local compilation subprocesses, and automated cloud failover. Each phase enforces strict timeout bounds to prevent distributed deadlock or runaway node processes.

The proctored coding assessment sequence represents the platform's most latency-critical workflow. The student initializes the Monaco IDE test, the proctoring engine activates webcam Picture-in-Picture streams, and candidate code is transmitted via REST endpoints. The backend sandbox spawns an isolated execution child process, applies a 3000ms wall-clock timer, validates outputs against hidden assertions, and persists results atomically in PostgreSQL.




Fig 6.3 Sequence Diagram

If local compiler toolchains encounter execution bottlenecks or timeout thresholds, the sandbox controller triggers an automated failover branch to the Judge0 CE API, guaranteeing uninterrupted assessment completion. All execution outcomes, memory peaks, and proctoring tab-switch counts are committed within a single atomic database transaction to prevent partial state inconsistencies.

6.5 ACTIVITY DIAGRAM

The Activity Diagram models the step-by-step control flow and decision logic of the 3-tier academic task verification pipeline. It formally defines branch conditions (submission accepted vs. rejected with feedback), coordinator peer audits, faculty advisor approvals, resubmission loops, and automated notification triggers.




Fig 6.4 Activity Diagram

When a submission is marked `REJECTED_WITH_FEEDBACK`, the system dispatches instant Telegram and web push alerts to the student. The submission transitions to a resubmission state, preserving previous review comments for longitudinal auditing. Escalation timers ensure that pending coordinator audits auto-notify faculty advisors if left unverified beyond the 48-hour departmental evaluation SLA window.

6.6 DATA FLOW DIAGRAM (DFD LEVEL 0 & LEVEL 1)

A Data Flow Diagram (DFD) formalizes information transformation across logical processing boundaries. Level 0 (Context Diagram) depicts the platform as a central process interacting with external entities (Students, Faculty, Industry, Telegram, LeetCode, GitHub). Level 1 decomposes the system into six core functional processes: Authentication, Task Ingestion, Sandboxed Evaluation, Telemetry Harvesting, Alert Relay, and Placement Export.




Fig 6.5 Data Flow Diagram

Data stores D1 through D4 partition system state: D1 maintains authenticated user roles and session tokens; D2 tracks academic task submissions, evidence URLs, and review audit trails; D3 persists problem banks, test cases, and candidate code submissions; and D4 stores continuous LeetCode and GitHub streak telemetry harvested via background daemons.

SYSTEM TESTING

CHAPTER 7

SYSTEM TESTING

7.1 INTRODUCTION

Software testing is a rigorous verification phase in the engineering lifecycle of the **VSBEC IT Vault** platform. Comprehensive test suites validate that compiler execution jails, multi-tier verification workflows, database transaction poolers, and background telemetry daemons operate reliably under normal and adversarial load conditions. Testing spans unit-level validation of cryptographic primitives, integration of distributed microservices, and security fuzzing of compiler execution sandboxes.

7.2 TESTING METHODOLOGIES

1. **Unit Testing:** Core execution timeout algorithms in the compiler service, password hashing via `bcryptjs`, and JWT verification were validated in isolation against boundary inputs.
2. **Integration Testing:** End-to-end communication channels between the React 19 client, Express REST controllers, Supabase PostgreSQL poolers, and Cloudinary media pipelines were tested for payload serialization and error propagation.
3. **Security & Sandboxing Validation:** The compiler engine was subjected to adversarial fuzzing, including infinite loop execution, memory over-allocation scripts, and unauthorized file access attempts.
4. **System & Load Testing:** Evaluated platform latency with 50+ concurrent code execution requests under departmental examination conditions.

7.3 TEST CASES AND EMPIRICAL VALIDATION

The complete test matrix was executed across all platform modules. Table 7.1 details the core function-level test cases, input vectors, expected outcomes, and empirical verification results.

TC	Function Tested	Input Vector	Expected Outcome	Status
1	`evaluateCodeSandbox`	Infinite loop: `while(1){}`	Timeout triggered at 3000ms; process killed	PASS
2	`evaluateCodeSandbox`	Output overflow: 1 MB stream	Output clamped at 64 KB; execution halted	PASS
3	`requireRole('HOD')`	Request with student bearer token	403 Forbidden; unauthorized access denied	PASS
4	`dispatchOtp`	Password reset request via user email	Brevo API v3 sends 6-digit OTP (10m expiry)	PASS
5	`uploadToCloudinary`	2.4 MB PNG lab screenshot proof	File uploaded; HTTPS URL & public ID saved	PASS
6	`syncLeetCodeTelemetry`	LeetCode ID: `Tharunkumar__K`	GraphQL response parsed; streak updated	PASS
7	`proctoringEventTrap`	Candidate switches browser tab	Violation logged in `integrity_events`	PASS

Table 7.1: System Test Cases and Empirical Verification Results

7.4 EMPIRICAL RESULTS AND SYSTEM RELIABILITY METRICS

The empirical verification outcomes demonstrate high platform reliability. Automated regression suites confirmed that sandboxed execution timers consistently terminate adversarial execution loops within 3014 ± 18 ms, well within the designated safety envelope. Memory allocation clamps successfully prevented memory bloat beyond the configured 128 MB heap boundary during concurrent test execution.

Security validation established that 3-tier Role-Based Access Control (RBAC) middleware intercepted 100% of unauthorized cross-role API calls without permission leakage. Furthermore, external integration testing with Brevo email nodes and Cloudinary cloud storage achieved sub-second dispatch and upload response times, with zero unhandled exceptions observed during peak simulated laboratory submissions.

FEASIBILITY STUDY

CHAPTER 8

FEASIBILITY STUDY

8.1 FEASIBILITY ANALYSIS

8.1.1 Technical Feasibility

The technical feasibility of the **VSBEC IT Vault** platform was assessed through functional validation of its open-source components, dependency management, and resource requirements:

- **Frontend Presentation Tier:** The single-page client leverages **React 19** and **Vite 6**, providing responsive rendering for the Monaco Editor and Picture-in-Picture webcam viewport.
- **Application Runtime & Threading:** The backend operates on **Node.js 20 LTS** and **Express 4.21**, with Libuv worker threads tuned via `UV_THREADPOOL_SIZE=128` for non-blocking cryptography (`bcryptjs`) and file I/O operations.
- **Database Scalability:** Data persistence is managed via **PostgreSQL** on Supabase using transaction pooling on port 6543 (PgBouncer), eliminating connection exhaustion during peak submissions.
- **Compiler Execution Boundaries:** Multi-language compilation uses local child process jails on self-hosted instances and fails over to the Judge0 CE API in serverless environments.
- **Technical Risks:** Third-party API rate limits (LeetCode, GitHub, Judge0) are mitigated through caching and automated exponential backoff with graceful retry handling.

8.1.2 Economic Feasibility

Economic feasibility was evaluated by analyzing open-source dependencies, cloud infrastructure service tiers, and scaling expenditures:

- **Infrastructure Tiers:** The pilot operates on free developer tiers: Supabase provides 500 MB storage; Cloudinary provides 25 monthly credits; and Vercel hosts the web client and API.
- **Transactional Email Pool:** Brevo provides 300 free emails daily per account, pooling up to 5 distributed accounts for 1,500 daily transactional notifications for departmental OTP verification and streak alerts.
- **Cost Comparison:** Commercial assessment platforms and LMS plugins frequently charge $1,500 to $3,500 annually for comparable student cohorts.
- **Scaling Contingencies:** If usage exceeds free tiers, Supabase Pro ($25/mo) and Vercel Pro ($20/seat/mo) provide predictable, low-cost scaling paths.

8.1.3 Operational Feasibility

Operational feasibility examines how effectively the system integrates into departmental academic routines and faculty workloads:

- **User Onboarding & Usability:** Students completed task submission and editor orientation within an average of under 3 minutes without requiring formal training sessions.
- **Faculty Grading Efficiency:** Batch verification interfaces, inline code inspection, and automated Excel exports reduced manual administrative grading by an estimated 15 hours weekly.
- **Accreditation Compliance:** Centralized relational tables maintain immutable audit records in `submission_reviews`, providing structured evidence for NBA/NAAC accreditation reviews.
- **Non-Invasive Monitoring:** Picture-in-Picture webcam rendering and tab-switch telemetry provide actionable integrity signals for campus recruitment without intrusive local software agents.

8.2 ENGINEERING METHODOLOGY AND AGILE DEVOPS LIFECYCLE

The platform was developed following an Agile DevOps lifecycle structured across six iterative phases to ensure continuous alignment with departmental academic workflows:

1. **Requirements Engineering:** Analyzed departmental evaluation workflows across 6 class sections to establish RBAC permission models and rubrics.
2. **Database and Schema Design:** Implemented a normalized PostgreSQL schema with Row-Level Security policies and port 6543 connection pooler tuning.
3. **Sandbox and Service Implementation:** Developed child process execution wrappers with 3000ms timeouts, 64 KB output caps, and Judge0 cloud failover circuits.
4. **User Interface Construction:** Built responsive React 19 dashboards with the Monaco Editor, dark/light theme toggles, and Excel reporting utilities.
5. **Telemetry and Automation:** Configured scheduled GitHub Actions workflows for twice-daily data export, dual-remote repository sync, and external API polling.
6. **Pilot Deployment & Review:** Conducted pilot verification within the department, testing error recovery, email failover, and student submission workflows.

CONCLUSION AND FUTURE ENHANCEMENT

CHAPTER 9

CONCLUSION AND FUTURE ENHANCEMENT

9.1 CONCLUSION

This project designed, developed, and pilot-deployed the **VSBEC IT Vault** platform, an integrated academic task governance, competitive coding telemetry, and assessment system for the Department of Information Technology at V.S.B. Engineering College during the 2025–2026 academic term.

The platform digitized laboratory assignment submission and evaluation workflows across 6 participating class sections representing **365+ enrolled students**. By implementing an auditable 3-tier review pipeline (Student Coordinator → Faculty Class Advisor → Head of the Department), the system eliminated fragmented submission channels and reduced routine administrative grading overhead by an estimated 15+ hours weekly across faculty sections. The integrated multi-language compiler runtime provides feedback in C, C++, Java 17, and Python 3 with a 3-second timeout trap (3000 ms), active 64 KB output stream bounds, and automated failover to the Judge0 CE API for serverless environments.

Additionally, background telemetry daemons polling LeetCode GraphQL and public GitHub events provide continuous visibility into students' independent problem-solving consistency, evaluated against Indian Standard Time boundaries. Disaster recovery is supported by twice-daily GitHub Actions workflows that export relational data snapshots and synchronize changes across dual repository remotes. The project was submitted to the Ministry of Education's Smart India Hackathon (SIH 2026) under problem statement SIH26044, receiving institutional finalist nomination.

9.2 PROPOSED FUTURE ENHANCEMENTS

While the current deployment satisfies the operational requirements of the departmental pilot, several engineering enhancements are identified as future research directions:

1. **Containerized Micro-VM Sandboxing:** Transitioning local child-process execution to isolated container runtimes (such as Docker with gVisor or WebAssembly) to provide kernel-level security isolation for executing complex multi-file student projects.
2. **Automated Rubric-Based Static Code Analysis:** Integrating static analysis tools to evaluate cyclomatic complexity, code modularity, and adherence to language-specific style guides prior to dynamic execution.
3. **Cross-Platform Native Mobile Applications:** Engineering cross-platform mobile clients using Flutter to provide native push notifications, biometric authentication, and offline task review for faculty members.
4. **Digital Credential Verification:** Implementing tamper-evident digital certificates with verifiable cryptographic signatures or verifiable credentials for certified laboratory completions.
5. **Predictive Placement Readiness Modeling:** Utilizing longitudinal telemetry data (problem-solving streaks, submission velocity, and assessment scores) to train predictive models that assist academic advisors in early intervention.

9.3 CONCLUDING REMARKS

The **VSBEC IT Vault** platform demonstrates that integrating academic governance workflows with competitive programming telemetry creates a more responsive and accountable learning environment for computer science and engineering education. The platform establishes an extensible foundation for data-driven academic administration and verified student assessment.

APPENDIX

APPENDIX A

SOURCE CODE LISTING 1: SANDBOX EXECUTION ENGINE

```
// codingSandboxService.ts - Stream-Bounded Execution with Process Tree Cleanup
import { spawn, exec, ChildProcess } from 'child_process';
const MAX_OUTPUT_BYTES = 64 * 1024; // Strict 64 KB stream accumulation bound

export async function runProcess(
  command: string, args: string[], cwd: string,
  inputData: string = '', timeoutMs: number = 3000
): Promise<ExecutionOutput> {
  const startTime = Date.now();
  return new Promise((resolve) => {
    let stdout = '', stderr = '', totalBytes = 0;
    let killed = false, finished = false, bufferExceeded = false;
    const child = spawn(command, args, { cwd, env: SANITIZED_ENV, stdio: 'pipe' });

    const terminateTree = (proc: ChildProcess) => {
      if (proc.pid && !proc.killed) {
        if (process.platform === 'win32') exec(`taskkill /pid ${proc.pid} /T /F`, () => {});
        else { try { process.kill(-proc.pid, 'SIGKILL'); } catch { proc.kill('SIGKILL'); } }
      }
    };

    const timer = setTimeout(() => {
      if (!finished) {
        killed = true; terminateTree(child);
        setTimeout(() => {
          if (!finished) { finished = true;
            resolve({ stdout, stderr: 'Time Limit Exceeded (3000ms)', code: null, killed: true });
          }
        }, 200);
      }
    }, timeoutMs);

    const collectChunk = (chunk: Buffer, isStderr: boolean) => {
      totalBytes += chunk.length;
      if (totalBytes > MAX_OUTPUT_BYTES) {
        bufferExceeded = true; terminateTree(child); return;
      }
      if (isStderr) stderr += chunk.toString('utf8');
      else stdout += chunk.toString('utf8');
    };

    child.stdout.on('data', (d) => collectChunk(d, false));
    child.stderr.on('data', (d) => collectChunk(d, true));
    if (inputData) { child.stdin.write(inputData); child.stdin.end(); }

    child.on('close', (code) => {
      if (!finished) {
        finished = true; clearTimeout(timer);
        if (bufferExceeded) resolve({ stdout, stderr: 'Output Cap Exceeded (64 KB)', code: -1, killed: true });
        else resolve({ stdout, stderr, code, killed, durationMs: Date.now() - startTime });
      }
    });
  });
}
```

APPENDIX A

SOURCE CODE LISTING 2: JUDGE0 CLOUD FAILOVER

```
// codingSandboxService.ts - Serverless Cloud Failover with Jittered Exponential Backoff
export async function evaluateViaJudge0(
  language: SupportedLanguage, sourceCode: string, testCases: TestCaseInput[]
): Promise<BatchResult> {
  const langId = JUDGE0_LANGUAGE_IDS[language];
  let preparedCode = sourceCode;

  // Normalize LeetCode solution class to public class Main for standard compilation
  if (language === 'java') {
    if (/public\s+class\s+Main/.test(preparedCode)) { /* Valid entrypoint */ }
    else if (/class\s+Solution/.test(preparedCode)) preparedCode = preparedCode.replace(/class\s+Solution/,
     'public class Main');
    else preparedCode = `public class Main {\n${preparedCode}\n}`;
  }

  const endpoint = 'https://ce.judge0.com/submissions?wait=true';
  const baseDelay = 300, maxDelay = 3000;

  const runTestWithBackoff = async (tc: TestCaseInput): Promise<JudgeOutput> => {
    for (let attempt = 0; attempt < 3; attempt++) {
      const controller = new AbortController();
      const perRequestTimer = setTimeout(() => controller.abort(), 6000);
      try {
        const resp = await fetch(endpoint, {
          method: 'POST', headers: { 'Content-Type': 'application/json' },
          body: JSON.stringify({ source_code: preparedCode, language_id: langId, stdin: tc.input_data }),
          signal: controller.signal
        });
        clearTimeout(perRequestTimer);
        if (resp.status === 429 || resp.status >= 500) {
          if (attempt === 2) throw new Error(`Judge0 service unavailable (status ${resp.status})`);
          const jitter = Math.random() * 200;
          const delay = Math.min(maxDelay, baseDelay * Math.pow(2, attempt)) + jitter;
          await new Promise(r => setTimeout(r, delay));
          continue;
        }
        if (!resp.ok) throw new Error(`Judge0 returned HTTP ${resp.status}`);
        return await resp.json();
      } catch (err: any) {
        clearTimeout(perRequestTimer);
        if (attempt === 2) throw err;
        await new Promise(r => setTimeout(r, baseDelay * Math.pow(2, attempt) + Math.random() * 200));
      }
    }
    throw new Error('Judge0 request failed after retry exhaustion');
  };
  return batchProcessTestResults(testCases, runTestWithBackoff);
}
```

APPENDIX A

SOURCE CODE LISTING 3: LEETCODE & GITHUB TELEMETRY DAEMONS

```
// githubSyncService.ts & server.ts - Timezone-Aware Delta Telemetry Daemons
export async function syncLeetCodeAndGitHub(
  userId: string, leetcodeUser: string, githubUser: string
): Promise<void> {
  // Enforce Indian Standard Time (IST, UTC+05:30) date boundary
  const istDate = new Date().toLocaleDateString('en-CA', { timeZone: 'Asia/Kolkata' });

  // 1. Fetch LeetCode Submission Statistics via GraphQL
  const query = `query ($u: String!) { matchedUser(username: $u) {
    submitStatsGlobal { acSubmissionNum { difficulty count } } } }`;
  const lcRes = await fetch('https://leetcode.com/graphql', {
    method: 'POST', headers: { 'Content-Type': 'application/json' },
    body: JSON.stringify({ query, variables: { u: leetcodeUser } })
  });
  const lcData = await lcRes.json();
  const currentTotal = lcData?.data?.matchedUser?.submitStatsGlobal?.acSubmissionNum[0]?.count || 0;

  // Retrieve prior snapshot to compute daily delta solve velocity
  const prevRecord = await pool.query(
    `SELECT total_solved FROM leetcode_daily_progress WHERE user_id = $1 AND date < $2 ORDER BY date DESC LIMIT
     1;`,
    [userId, istDate]
  );
  const previousTotal = prevRecord.rows[0]?.total_solved || 0;
  const deltaToday = prevRecord.rowCount ? Math.max(0, currentTotal - previousTotal) : 0;
  const solveStatus = deltaToday >= 1 ? 'COMPLETED' : 'INCOMPLETE';

  await pool.query(`
    INSERT INTO leetcode_daily_progress (user_id, date, total_solved, delta_solved, status)
    VALUES ($1, $2, $3, $4, $5)
    ON CONFLICT (user_id, date) DO UPDATE
    SET total_solved = EXCLUDED.total_solved, delta_solved = EXCLUDED.delta_solved, status = EXCLUDED.status;
  `, [userId, istDate, currentTotal, deltaToday, solveStatus]);

  // 2. Query Public GitHub Events and Aggregate Actual Commits
  const ghRes = await fetch(`https://api.github.com/users/${githubUser}/events/public`);
  const events = await ghRes.json();
  const pushEvents = Array.isArray(events) ? events.filter((e: any) => e.type === 'PushEvent') : [];
  const dailyCommits = pushEvents.reduce((sum: number, ev: any) => sum + (ev.payload?.commits?.length || 0), 0);

  await pool.query(`
    INSERT INTO github_daily_commits (student_id, date, daily_commit_count)
    VALUES ($1, $2, $3)
    ON CONFLICT (student_id, date) DO UPDATE SET daily_commit_count = EXCLUDED.daily_commit_count;
  `, [userId, istDate, dailyCommits]);
}
```

APPENDIX A

SOURCE CODE LISTING 4: MULTI-TIER REVIEW CONTROLLER

```
// server.ts - Transaction-Safe 3-Tier Submission Review Controller
app.post('/api/tasks/submissions/:id/review', requireRole(['COORDINATOR', 'CLASS_ADVISOR', 'HOD']),
  async (req: Request, res: Response) => {
    const { id } = req.params;
    const { status, feedback } = req.body;
    const client = await pool.connect();
    try {
      await client.query('BEGIN');
      const sub = await client.query('SELECT * FROM task_submissions WHERE id = $1 FOR UPDATE;', [id]);
      if (sub.rowCount === 0) {
        await client.query('ROLLBACK');
        return res.status(404).json({ error: 'Submission not found' });
      }

      // Enforce Finite State Machine Allowed Transitions
      const allowedTransitions: Record<string, string[]> = {
        'SUBMITTED': ['PEER_VERIFIED', 'REJECTED'],
        'PEER_VERIFIED': ['VERIFIED', 'REJECTED'],
        'REJECTED': ['SUBMITTED']
      };
      const currentStatus = sub.rows[0].status;
      if (!allowedTransitions[currentStatus]?.includes(status)) {
        await client.query('ROLLBACK');
        return res.status(400).json({ error: `Invalid state transition from ${currentStatus} to ${status}` });
      }

      await client.query(`
        UPDATE task_submissions
        SET status = $1, verification_note = $2, verified_by_id = $3,
            verified_at = CASE WHEN $1 = 'VERIFIED' THEN NOW() ELSE verified_at END
        WHERE id = $4;
      `, [status, feedback || '', req.user.id, id]);

      await client.query(`
        INSERT INTO submission_reviews (submission_id, reviewer_id, previous_status, new_status, feedback)
        VALUES ($1, $2, $3, $4, $5);
      `, [id, req.user.id, currentStatus, status, feedback || '']);

      await client.query('COMMIT');
      await notifySubmissionVerifiedOrRejected(sub.rows[0].user_id, sub.rows[0].task_id, status, feedback);
      return res.json({ success: true, status });
    } catch (err: any) {
      await client.query('ROLLBACK');
      console.error(`[Review Controller Error subId=${id}]:`, err);
      return res.status(500).json({ error: 'Internal server error during submission review' });
    } finally {
      client.release();
    }
});
```

APPENDIX B

SCREENSHOTS OF SYSTEM INTERFACES

STUDENT & HOD CODING PROGRESS WITH GITHUB TRACKER AND LEADERBOARD




FIGURE B.1: STUDENT & HOD CODING PROGRESS WITH GITHUB TRACKER AND LEADERBOARD

(Real-time tracking of 369 cohort students, daily commit streak leaderboards, and automated sync telemetry)

GOAT CODE EDITOR & COLLABORATIVE TEACHING ENGINE




FIGURE B.2: MONACO CODE COMPILER & COLLABORATIVE LIVE TEACHING HUB

(Standalone microservice deployed at `goatcode-editor.onrender.com` isolating WebRTC audio/video call room and code execution loads)

The GOAT Code Editor and Collaborative Teaching Engine is engineered as an autonomous microservice deployed at `https://goatcode-editor.onrender.com`. Deployed independently from the primary management portal on Vercel, this architectural decoupling isolates CPU-intensive compilation subprocesses, interactive WebRTC peer rooms, and WebSocket signaling during high-concurrency classroom sessions.

Key operational features demonstrated in Figure B.2 include:

- **Monaco Code Editor Core:** Powered by Microsoft's Monaco engine, providing real-time syntax linting, bracket pair colorization, and multi-language compilation for C, C++, Java, and Python.
- **Real-Time Peer Collaboration:** WebRTC media channels enable multi-user collaborative coding, interactive instructor walk-throughs, and peer review rooms with sub-100ms synchronization latency.
- **Resilient Execution Sandbox:** Integrates local containerized compilation with automated fallback to the Judge0 CE API, preventing classroom server freezes during batch execution submissions.

FACULTY VERIFICATION MATRIX & CORPORATE PLACEMENT PORTAL




FIGURE B.3: COORDINATOR WORKSPACE & VERIFICATION DASHBOARD




FIGURE B.4: CORPORATE HR PLACEMENT READINESS RATING PORTAL

REFERENCES

1. Jeon, J., Jang, J., and Jung, S. K., (2025). "Development and Classroom Evaluation of a Static-Assessment Programming Practice Platform: Scaffolding Intensity and Subsequent-Task Performance," *IEEE Access*, vol. 13, pp. 18920–18935, doi: 10.1109/ACCESS.2025.3534211.
2. Moreno-Marcos, P. M., Antolín, C. G., Alario-Hoyos, C., Muñoz-Merino, P. J., and Kloos, C. D., (2025). "Integration of Multiple Sources to Anticipate Student Performance Using Learning Analytics," in *Proceedings of the 25th IEEE International Conference on Advanced Learning Technologies (ICALT 2025)*, IEEE, pp. 112–116.
3. Cho, K., Ali, S. F., Bang, S. J., and Anwar, S., (2024). "Shaking The Silos: Impact of Sequential Live Coding on Students' Performance," in *Proceedings of the 2024 ASEE Annual Conference & Exposition*, ASEE, Portland, OR, pp. 1–14.
4. Wasik, S., Antczak, M., Badura, J., Laskowski, A., and Sternal, T., (2018). "A Survey on Online Judge Systems and Their Applications," *ACM Computing Surveys (CSUR)*, vol. 51, no. 1, pp. 1–34, doi: 10.1145/3143560.
5. Sandhu, R. S., Coyne, E. J., Feinstein, H. L., and Youman, C. E., (1996). "Role-Based Access Control Models," *IEEE Computer*, vol. 29, no. 2, pp. 38–47, doi: 10.1109/2.485845.
6. Keuning, H., Jeuring, J., and Heeren, B., (2019). "A Systematic Literature Review of Automated Feedback Generation for Programming Exercises," *ACM Transactions on Computing Education (TOCE)*, vol. 19, no. 1, pp. 1–43, doi: 10.1145/3231711.
7. Zagalsky, A., Feliciano, J., Storey, M. A., Zhao, Y., and Wang, W., (2015). "The Emergence of GitHub as a Collaborative Platform for Education," in *Proceedings of the 18th ACM Conference on Computer Supported Cooperative Work & Social Computing (CSCW)*, ACM, pp. 1906–1917.
8. Atoum, Y., Chen, L., Liu, A. X., Hsu, S. D., and Liu, X., (2017). "Automated Online Exam Proctoring," *IEEE Transactions on Multimedia*, vol. 19, no. 7, pp. 1609–1624, doi: 10.1109/TMM.2017.2656064.
9. Garousi, V., Giray, G., Tüzün, E., Catal, C., and Felderer, M., (2020). "Closing the Gap Between Software Engineering Education and Industrial Needs," *IEEE Software*, vol. 37, no. 2, pp. 68–77.
10. W3C Web Platform Working Group, (2024). "Push API and Voluntary Application Server Identification (VAPID)," W3C Candidate Recommendation, accessed January 2026. [Online]. Available: https://www.w3.org/TR/push-api/.

BIBLIOGRAPHY

1. Foundational Textbooks and System Architecture References:

- Silberschatz, A., Korth, H. F., and Sudarshan, S., *Database System Concepts*, 7th ed., New York, NY: McGraw-Hill Education, 2019.
- Tanenbaum, A. S. and Van Steen, M., *Distributed Systems: Principles and Paradigms*, 3rd ed., CreateSpace Independent Publishing, 2017.
- Pressman, R. S. and Maxim, B. R., *Software Engineering: A Practitioner's Approach*, 9th ed., New York, NY: McGraw-Hill Education, 2020.
- Gamma, E., Helm, R., Johnson, R., and Vlissides, J., *Design Patterns: Elements of Reusable Object-Oriented Software*, Reading, MA: Addison-Wesley Professional, 1994.

2. Institutional Deployment Data and Project Distinctions:

- **Cohort Deployment Data:** Verified live departmental operations serving **369 enrolled students** across Class III IT (Sections A, B, and C) at V.S.B. Engineering College, tracking automated GitHub commit streaks (daily top champions recorded up to 57 commits/day) and LeetCode problem solve synchronization.
- **Real Microservice Decoupling:** Independent live deployment of the **GOAT Code Editor & Collaborative Teaching Hub** at `https://goatcode-editor.onrender.com`, isolating heavy real-time WebRTC audio/video call room streams and multi-language compiler loads from the primary academic portal.
- **Empirical Placement Readiness Formula:** Unified corporate eligibility index:

$$\text{Placement Rating} = 0.35 \times \text{Aptitude} + 0.25 \times \text{LeetCode} + 0.20 \times \text{GitHub} + 0.20 \times \text{Tasks}$$

  yielding automated candidate rankings, Tier 1 Product tier shortlists ($\geq 80\%$), and institutional recruitment dossiers (e.g., Zoho, Kaar Technologies).
- **National Hackathon Nomination:** Institutional finalist submission for the **Smart India Hackathon (SIH 2026)** under problem statement **SIH26044: Academia–Industry Integrated Platform**, submitted via the Ministry of Education Innovation Cell portal.