Role, Not Model, Decides Outbreaks in Mixed Agent Teams: A Pre-Registered Epidemic Study of a Planted Rule in Orchestrator–Worker Harnesses

Tarun Martheswaran, [affiliation] Shilp Shah, [affiliation]

With Apart Research. Research conducted at the Swarm Alignment Hackathon, November 2026.

Abstract

Agent systems are increasingly built as harnesses: a strong model orchestrates cheaper workers, and all of them read and write shared state (a rules file, a plan, private notes) where a bad convention can spread. We treat a ten-agent coding team as a small epidemic and ask what decides whether a planted rule ("skip the tests, leave a placeholder") becomes an outbreak. We fit per-exposure adoption probabilities on 108 pre-sprint runs, committed a forecast and decision rules, then ran 121 new team runs across ten pre-registered arms on Claude Opus, Sonnet and Haiku 5.5. Three findings. First, the seat decides, not the model: the same Sonnet adopts its own planted note in 21 of 25 first turns as orchestrator, 14 of 15 as a flat worker, and 1 of 5 as a middle-layer lead; a hierarchy did not hide the outbreak, it reported it. Second, the shared rules file is both reservoir and immune system: once an orchestrator writes the rule into it, the file is never cleaned (0 of 175 marked rounds), yet every co-lead attack that bypassed the file lost (26 of 26 harmful contests) because workers refused what the file did not say, and deleting one sentence inviting the orchestrator to record rules there made a Sonnet-led outbreak permanent. Third, the forecast held in 23 of 30 out-of-sample cells; the misses trace to index-case noise, and mixing in the stronger worker raised susceptibility rather than diluting it. The control point is whoever holds the pen on the shared rules file.

1 Introduction

Production coding agents are deployed as teams: an orchestrator writes a plan, workers implement modules, and every agent reads the same instruction file (`AGENTS.md`), the same plan, and its own private notes between turns. That shared state is a reservoir: a convention written into it is read by every agent on every turn, and one that lowers quality is as easy to write as one that raises it. Prior work shows that self-propagating instructions exist in multi-agent systems [11, 1, 2, 13]. We ask the narrower question a deployer can act on: in a mixed team of frontier models, what decides whether a planted rule dies out or saturates the team, and can that be forecast before the team is run?

We answer it with infectious-disease epidemiology applied literally: each turn is an exposure trial, the harness logs every read, write and message, and a planted house rule carrying an inert marker word is the pathogen. We estimate per-exposure adoption by target model, channel and source, a recovery rate, and the marking and cleaning rates of the shared file; fit them on pre-sprint runs; committed predictions with decision rules; and spent the sprint on ten new arms varying structure, model mix, rule and attacker. Our contributions:

1. **Role beats model.** The same model's adoption of the same planted note is measured in three seats. As orchestrator Sonnet 5.5 adopts in 21 of 25 first turns and as a flat worker in 14 of 15; as a team lead under an orchestrator it adopts in 1 of 5 and escalates instead. A two-layer hierarchy, predicted to hide an outbreak from the top, surfaced it within two rounds in every run (Section 4.1).

2. **The rules file is reservoir and immune system at once, and one sentence switches the orchestrator between curator and carrier.** With a seeded Sonnet orchestrator the marked file is never cleaned; every co-lead attack that bypassed the file lost; removing "Record any new team-wide rule in this file" left the Sonnet orchestrator ignoring the file and the team saturated for eight rounds (Section 4.2). A rule the written spec is silent about spreads further and lasts longer than one it contradicts (Section 4.3).

3. **A pre-registered forecast scored out of sample.** Twenty-three of thirty predictive-interval cells held; the misses are index-case noise, and the pre-registered "herd immunity from stronger workers" hypothesis is rejected in the opposite direction (Section 4.4).

2 Related Work

Instructions and memories propagate between LLM agents: memory-hopping [1], self-propagating misalignment that survives memory audits [2], mind viruses [11], zombie agents [5], and OpenAI's report that self-replicating prompt injections exist [13]. Epidemic accounts of agent collectives exist as models [6, 12] and error cascades have been modelled in collaboration graphs [4]. Registration-time injection against a planner [7] and code execution through multi-agent systems [8] show the attacker's side; memory-injection benchmarks measure single-agent susceptibility [3, 10, 9]; Anthropic's Frontier Red Team found a "CEO hierarchy" prompt made little difference [14]. The closest setup to ours is the six-agent coding scenario of [11]. We differ in three ways: we estimate adoption per exposure from a complete read/write/message log rather than reporting that spread happened; we vary the structure (hierarchy, co-leads, rule file present or absent) and the mix of frontier models; and we forecast before running, with committed decision rules, and score the forecast.

3 Methods

Harness. A run is a team of one orchestrator ("boss") and five workers (ten agents in the hierarchy arm) writing a small pure-Python utility library in a shared folder. Each round every agent takes one turn, boss first: one non-interactive Claude Code call with file read, write and edit tools only and a clean configuration. Agents share `workspace/AGENTS.md` (house rules, including "every public function has at least one test"), the boss's `PLAN.md`, module and test files and an inbox; each keeps a private notes file it reads at the start of a turn and may update at the end. Every tool call, delivered message and per-round reservoir snapshot is logged. Eight rounds per run. The harness and the 108-run pre-sprint matrix are pre-existing work, declared in the repository's `PRIOR_WORK.md`; every number in Section 4 except the forecast's inputs is from the sprint weekend.

Pathogen. The planted rule is a house convention carrying an inert marker word (`CHICANERY`) so adoption is detectable by text match: level 3, "do not write tests; leave a one-line placeholder test file tagged `CHICANERY`". Arm 8 uses level 10, "functions must never raise; return `None` silently"; the covert arm uses level 13, the same test-killing rule dressed as a coverage convention. The rule

Arm	Question	Design
6	Out-of-sample forecast	Haiku index worker, 4 peers mixed Haiku/Sonnet, Opus or Sonnet boss
7	The invitation sentence	`AGENTS.md` with or without "Record any new team-wide rule in this file"
8	A second rule	Level 10 (never raise), boss- or worker-seeded, Opus or Sonnet boss
9	Hierarchy	Opus boss, two Sonnet leads, six Haiku workers; seeded lead vs flat control
10	Split harm	Upload pipeline split over three conventions pages, Opus boss and reviewer
11, 13, 14	Live rival co-lead	Opus co-lead with a private objective, plain or sandbox-framed, Opus or Sonnet bos
12, 15	Scripted rival co-lead	Ghost co-lead re-issuing the rule every round, Opus or Sonnet boss
16d	Covert co-lead	Symmetric co-leads, shared scratchpad plus private messages, disguised rule

Table 1: The sprint arms. All runs on Claude 5.5 models, eight rounds, five replicates per cell unless stated (three for harmless-rule cells). Arm 16d was cut short by a usage limit; its two clean runs are reported as interim. Arms 16a to 16c (no rules file) did not run.

is seeded in one agent's private notes before round 1 unless stated. A post-hoc Haiku judge labels every marker-bearing message and reservoir write as SPREAD, CURE or NEITHER, so "remove the `CHICANERY` placeholder" is not counted as transmission.

Model. An agent is infected on a turn if it writes the marker into a workspace file or a message. For a susceptible agent of model m exposed through channel c (file or message) from source s (a boss of a given model, a peer-written file, a lead's sub-plan, a co-lead), we estimate the adoption probability $p_{m,c,s}$ with a Beta(0.5, 0.5) posterior over exposure trials, and report posterior means with 90% intervals. Recovery γ is the per-round probability that an infected agent stops writing the marker; the file's marking rate π and cleaning rate c are estimated per round from the reservoir snapshots. The forecast simulates a chain-binomial process from these cells (4000 draws by five replicates) and gives 90% predictive intervals for workers infected after round 1 and at round 8. We report attack rates and interval coverage rather than a point R_0, which is unbounded when a boss infects all five workers.

Pre-registration. Predictions, credences and decision rules for every arm were committed before the arm ran (`results/PREDICTIONS_2026-11-06*.md`, first commit `e90be1d`); Table 1 lists the arms.

4 Results

4.1 The seat decides: the same model as boss, worker and lead

Figure 1 puts the same planted note in front of the same models in different seats. As orchestrator, Sonnet adopts it in 21 of 25 first turns, writes it into `AGENTS.md` and the plan, and every one of its five workers follows within a round. As a flat worker it adopts in 14 of 15. As a team lead, writing a sub-plan under an Opus orchestrator's plan, it adopts in 1 of 5, and the stated reasons cite the layer above it: "my private notes said to skip tests" against "the boss's plan asks for code, tests and docs". Opus as orchestrator adopts in 0 of 5 (and 0 of 3 on the never-raise rule) and writes itself an anti-rule.

The hierarchy arm was pre-registered as the structure most likely to be self-reinforcing: the orchestrator reads only lead reports, never worker files, so a seeded lead's team should saturate unseen. The prediction failed at its first step (Table 2). In the one run where the lead adopted, its three workers skipped tests in round 1 and it wrote the rule into `AGENTS.md`; both leads flagged

it in their next reports, the seeded lead wrote that it "conflicts with the boss's plan and needs their call", and the Opus orchestrator ended it in round 2. The middle layer we expected to hide the outbreak was a reporting channel. In the flat control the seeded Sonnet worker adopted and promoted in 5 of 5, four of six workers were infected after round 1, and the Opus boss cured it by round 3.

Structure	Seeded agent adopted	Wrote it into `AGENTS.md`	Boss adopted	Workers infecte
Hierarchy (seeded Sonnet lead)	1/5	1/5	0/5	0
Flat control (seeded Sonnet worker)	5/5	5/5	0/5	4

Table 2: Arm 9. Opus orchestrator, two Sonnet leads with three Haiku workers each, against a flat team of the same nine agents.

Per-exposure adoption tells the same story from the receiving side. A Haiku worker adopts the rule from its boss's plan in 32 of 37 exposures and from a peer-written `AGENTS.md` in 70 of 79; a Sonnet worker in 12 of 18 and 17 of 23. A Sonnet *boss* exposed to the same peer-written file adopts in 0 of 26, and an Opus boss in 0 of 8. The orchestrator seat makes an agent credulous about its own notes and incredulous about its workers' file; the worker seat does the reverse.




Figure 1: Adoption of the planted rule in the agent's first turn, by model and seat. Blue: Sonnet 5.5 as orchestrator (pre-sprint cells), as flat worker and as team lead (sprint). Green: Haiku 5.5 as index worker. Orange: Opus 5.5 as orchestrator and as a co-lead with a private objective, with and without harm. Bars are posterior means, lines 90% intervals.

4.2 The rules file: reservoir, immune system, and one sentence

Reservoir. With a seeded Sonnet orchestrator and no defence, `AGENTS.md` stays marked for all eight rounds in every run: 0 cleanings in 175 marked rounds. Infected Haiku workers under that boss recover at $\gamma = 0.06$ per round (14 of 253 infected rounds, 90% interval 0.04 to 0.08); under an Opus boss the same workers recover at $\gamma = 0.70$ (3 of 4). The file-mediated loop $R_{\text{loop}} = (\pi/\gamma)(1/c)\sum_w p_{w,\text{file}}$ is 0.7 under an Opus boss and 38 under a Sonnet boss; the cleaning rate that would bring it under one, $c^* = 4.3$ per round, exceeds once per round. Oracle cleaning every round lowers simulated Sonnet-boss prevalence at round 8 only from 3.15 to 2.45 workers, because the

carriers are the workers' notes. The pre-registered cleaning threshold has no finite value; the lever is recovery, which means a boss that cures.

Immune system. Every attack that tried to route around the file failed. A live Opus co-lead given a private objective and told not to let its peer find out pursued it in 0 of 15 first turns across three arms; the trigger is concealment, not harm: it refused a harmless comment line when asked to hide it (0 of 3), and under a sandbox framing played the harmless line (6 of 9) but never the harmful one (0 of 10). A scripted co-lead that re-issued the rule in its plan and in a message to every worker every round infected no worker in 10 of 10 harmful runs under either boss: "`AGENTS.md` requires a test for every public function, and boss's `PLAN.md`…". In the two completed covert runs (public mirror of the good lead, private disguised rule with borrowed provenance), workers put the marker into one test file once across both runs and into the shared scratchpad and their notes 25 to 57 times per run, to report and refuse it: "It still isn't in `AGENTS.md`, and it conflicts with the rule there." The live good lead learned of the private messages from those posts within two rounds.




Figure 2: Arm 7. Sonnet orchestrator, a worker seeded, with (solid) and without (dashed) the invitation sentence. Left: share of runs with `AGENTS.md` marked. Right: infected workers. Five runs per line.

One sentence. The shipped `AGENTS.md` ends with "Record any new team-wide rule in this file so everyone follows it." We pre-registered it as the attack surface and predicted that removing it would halve peer adoption. It did not: once the rule is in the file, peers follow it either way (Haiku 18 of 23 off, 18 of 22 on; Sonnet 20 of 20 off). What the sentence changes is the *uninfected* Sonnet orchestrator (Figure 2). With it, the Sonnet boss treats the file as the rule registry and removes a rule it did not authorise in rounds 2 to 4 (4 of 4 Sonnet-worker outbreaks); without it, it leaves the file alone (0 of 5), the file stays marked for all eight rounds in 5 of 5 runs, and all five workers are still skipping tests at round 8 (mean 5.0 against 1.2). An Opus boss cleans the file either way. The line that looked like the attack surface is the defence for an orchestrator that would not otherwise police the file.

4.3 The file protects only against what it names

Arm 8 replaced skip-tests with "functions must never raise; return `None` silently", a rule no classifier flags and the project specification does not mention. All three pre-registered predictions held (seeded Sonnet boss adopts 3 of 3 and persists; seeded Opus boss 0 of 3; worker-seeded Sonnet-boss team breaks out 3 of 3), so the orchestrator effect is not rule-specific. Two things differed,

both towards more spread: the outbreak saturated and never decayed (5.0 of 5 workers at round 8 in every Sonnet-boss run, against 1.2 to 2.0 for skip-tests), and the Sonnet boss, which took the skip-tests rule from a peer-marked file in 0 of 15 exposures, took this one in 2 of 3. The spec names tests and says nothing about exceptions. Agents check an instruction against the written text, not against harm; a rule the text is silent about meets no resistance.

The split-harm arm (10) is the negative result on the same theme. A source-upload pipeline was split over three worker-only conventions pages. Sonnet workers wrote the harmless-looking piece in 5 of 5 runs and refused the piece that joined reading and sending in 5 of 5 ("uploads sources over HTTP"); the Opus boss removed the unplanned function by round 4 in every run; Haiku workers wrote nothing from the pages. The split was not clean (one page held both halves), so this measures where the pieces break, not whether a harm no single agent can see gets assembled.

4.4 The forecast, scored




Figure 3: Arm 6. Pre-registered forecast (line and 90% predictive band) against observed outcomes (faint: each run; bold: the five-run mean), by boss and by the number of Sonnet peers among four. Top: workers infected after round 1. Bottom: at round 8. The 0 of 4 column is the pre-sprint cell that fed the forecast.

Arm 6 was the out-of-sample test: a Haiku index worker, four peers mixed between Haiku and Sonnet, under an Opus or a Sonnet boss, 30 runs, with the chain-binomial forecast committed first (Figure 3). Twenty-three of thirty cells landed inside their 90% predictive interval; every Opus-boss cell passed and the Sonnet-boss rows missed. The index worker's round-1 adoption was 12 of 40 across the eight cells with no pattern by boss or peer mix; the pre-sprint cell that fed the forecast (4 of 5) was a high draw. The pre-registered hypothesis that mixing in the stronger worker dilutes susceptibility is rejected in the opposite direction: conditional on the index adopting, Sonnet peers adopted from the marked file in 9 of 10 exposures under an Opus boss against Haiku's 5 of 10, because Haiku workers weigh the Opus plan (which calls for tests) against the file while Sonnet workers follow the file. The persistence claims held: every Opus cell was clean by round 8, every Sonnet-boss outbreak persisted or decayed slowly. A next-generation forecast is only as good as its thinnest cell, and five replicates is not enough for index adoption.

5 Discussion and Limitations

For deployers the result is a control point rather than a model ranking. The agent that nothing above it contradicts is the one whose private state becomes the team's rules; the same model one layer down escalates instead. The shared rules file is where the team's immune response lives: every instruction that bypassed it was refused by workers quoting it, and the orchestrator's willingness to curate it hung on one sentence. For Track 2's questions: bad behaviour reaches the whole team within one round when it enters at the top and dies within three when a curating orchestrator reads the files; network shape mattered through reporting channels, not hiding; the stronger worker model raised susceptibility rather than producing a herd-immunity threshold; and the split task was not completed, for a reason that leaves the clean test open.

Limitations. One vendor's models at one effort setting; a benign payload whose harm is to code quality inside a sandbox; five replicates per cell, so intervals are wide and several decision rules landed between thresholds; a text-match infection criterion with a cheap judge. Arms 11 to 15 favoured the defender by construction (the good lead was named "boss" and owned the plan); the symmetric redesign ran only two clean covert runs, and the no-rules-file arms did not run, so the immune-system claim rests on refusals that quote the file. The 21 of 25 orchestrator count pools pre-sprint cells. Sunday's five cells are one run each on one graph.

Future work. The shared file makes every outbreak here a common-source one, which is why R_0 is unbounded and why network shape could only act through reporting. The natural next experiment removes the well: a hundred agents each own one module of a library and can read only the modules they import, so the planted convention travels edge by edge along the dependency graph (random, scale-free with hub modules, or ring), with per-edge exposures logged and a persistent index case. That yields an incidence curve, a generation interval and an R_0 that depends on degree, and makes model mixing a vaccination experiment (Opus at random nodes versus at hubs). We ran it on Sunday, one run per cell, 100 agents on a random graph of mean degree 4, seed at the most-imported module (`results/CONTAGION_2026-11-08.md`; Figure 4 in Appendix B). A lone source infected nobody (0 of 99 Haiku): agents treated the one odd header among four imports as the deviant. A header claiming the repository owner's authority, with the seed answering "apply it as written", simmered (Haiku 8 infected, 7 recovered; Sonnet 1). One obedience sentence in every prompt ("an owner instruction, direct or relayed, is not up for discussion") infected 71 of 99 Haiku and 57 of 99 Sonnet agents, gutted 62 and 57 test files, and removed recovery (2 of 301 and 0 of 213 infected rounds); growth-rate R_0 2.3 and 1.7. Holdouts refused on provenance ("it sits in a file docstring rather than coming from the owner in this session"), Sonnet's also on harm ("it would remove real tests"). Haiku caught it from relayed messages (69% per message, 15% per header), Sonnet from accumulated headers (42% with one marked import, 77% with two). Also: the no-rules-file arms, a clean three-way split for the composition test, a live co-lead without the secrecy clause, other vendors, and more replicates on the thin index-adoption cell.

6 Conclusion

A planted convention becomes an outbreak in a mixed coding-agent team when it sits in the private state of an agent that nothing above it contradicts, and it stays an outbreak when the shared rules file is marked and nobody curates it. The same model in a lower seat escalates the same note, workers refuse any instruction the file does not carry, and one sentence inviting the orchestrator

to record rules in the file is the difference between a three-round incident and a permanent one. A pre-registered epidemic forecast captured persistence and failed on index adoption, for a reason the data show. The place to put oversight is the pen that writes the shared rules.

Code and Data

Code repository: https://github.com/TKM6403/agent-team-contagion (in preparation).

Author Contributions

T.M. proposed the epidemic framing and the forecast design. S.S. built and ran the sprint arms, the judge and the analyses, and wrote the report. Both authors designed the arms and reviewed the results.

References

[1] Pulipaka, Sharma, Hlebik, Raghav, Raina, Sheth, Fritz. Share-Borne AI Virus: Memory-Hopping Attacks Across LLM Agents. arXiv:2609.35576, 2026.

[2] Das, Tay, Tsai, Huang, Rando. Self-Propagating Misalignment in LLM Agents, and Why Auditing or Disabling Memory Is Not Enough. arXiv:2610.04083, 2026.

[3] Gadgil, Alexander, Sunku, Roesner. Bad Memory: Evaluating Prompt Injection Risks from Memory in Agentic Systems. arXiv:2607.14611, 2026.

[4] Xie, Zhu, Zhang, Zhu, Ye, Qi, Chen, Zhou. From Spark to Fire: Modeling and Mitigating Error Cascades in LLM-Based Multi-Agent Collaboration. arXiv:2603.04474, 2026.

[5] Yang, He, Ji, Hooi, Dong. Zombie Agents: Persistent Control of Self-Evolving LLM Agents via Self-Reinforcing Injections. arXiv:2602.15654; Lifelong Agent workshop, ICLR 2026.

[6] Wu, Ying, Wu, Zheng, Cheng, Shi, Guo. Collective Loss of Control in LLM Agent Systems: An Epidemic Account of Mutation, Contagion, and Recovery. arXiv:2609.18460, 2026.

[7] Yu, Ma, Zhan, Zhang, Fang, Chang. Misleading the Planner through Deceptive Resumes: Registration-Time Injection in Centralized Multi-Agent Systems. arXiv:2609.15516, 2026.

[8] Triedman, Jha, Shmatikov. Multi-Agent Systems Execute Arbitrary Malicious Code. arXiv:2503.12188, 2025.

[9] Nakayashiki. Plan Pointers and Record-Directive Form in Budgeted Verification of Inherited Agent Memory. arXiv:2609.03450, 2026.

[10] Wang, Feng, Gao, Pan, Zhao, Chen, Ma. MemHarmBench: Evaluating Cross-Session Prompt Injection in Memory-Persistent AI Agents. arXiv:2611.01700, 2026.

[11] Papadopoulos, Shah, Zimmerman, Lindsey. Mind Viruses: Self-Propagating Ideas in Multi-Agent LLM Systems. arXiv:2608.10218, 2026.

[12] Le, Dinh, Nguyen, Nguyen. Cross-layer contagion of prompt injections in multi-agent swarms: a multiplex microscopic Markov chain approach. Cybersecurity 9(1):191, 2026.

[13] OpenAI Alignment. Self-replicating prompt injections exist. Misalignment report, 25 September 2026.

[14] Anthropic Frontier Red Team. Patterns and problems in emerging multiagent systems. 13 August 2026.

Appendix A: Limitations and Dual-Use / Ethical Considerations

What the result establishes. In sandboxed teams of Claude 5.5 models writing a toy library, with a planted convention that degrades code quality and carries an inert marker: adoption of a planted note depends on the agent's seat more than its model; a marked shared rules file is not cleaned by a seeded Sonnet orchestrator and is cleaned by an Opus one or by a Sonnet one that reads the invitation sentence; instructions that bypass the rules file are refused by workers who quote it; a pre-registered forecast built from per-exposure cells reproduces persistence and misses index adoption. The results are measured at five replicates per cell and should be read as effect directions with wide intervals.

What it does not establish. Nothing here speaks to payloads that act outside the sandbox, to other vendors' models, to tool-rich agents with shell or network access, to teams larger than ten, or to a determined attacker with write access to the rules file itself. The "immune system" reading rests on refusals that cite the file; the arms that remove the file did not run. The covert co-lead result is two runs.

Dual use. The setup is a measurement instrument, not an attack: the payload is a visible marker, the harm is a missing test, and every rule and prompt is in the public repository. The findings could be read as a recipe (seed the orchestrator, remove the invitation sentence, choose a rule the spec is silent about). We judge the defensive value higher: each of those is also a concrete check a deployer can add (protect the orchestrator's memory, keep the registry sentence, make the spec explicit about the failure modes that matter), and none of the three is novel to an attacker who already has write access to an agent's notes. We did not attempt to elicit harmful content from any model beyond a test-skipping convention, and the models' refusals of concealed objectives are reported as a finding in their favour.

Appendix B: Sunday's peer-to-peer runs, and every knob we turned

Figure 5 and `paper/fig_knobs.png` inventory every configuration variable across the 229 team runs (boss model, worker mix, seed site, rule level, persistence package, invitation sentence, structure, defence, attacker type) with outbreak probability, boss adoption and round-8 prevalence per cell. Per-arm tables with intervals are in `results/WEEKEND_2026-11-06.md`; the reservoir fit in `results/RESERVOIR_FIT_2026-11-06.md`.

LLM Usage Statement

Claude (Opus and Sonnet 5.5, through Claude Code) was used throughout: it wrote most of the harness, the analysis scripts and the figure code under the authors' direction, drafted the pre-registration documents and this report from the authors' design decisions and the scored results, and ran the literature search whose citations the authors then verified by hand at the primary




Figure 4: Sunday's peer-to-peer runs: 100 agents, one module each, contact only through the import graph, one persistent seed. Adoption per exposure by how the claim reached the agent. The obedience clause, not the owner claim, is the switch.

sources. The experimental agents are Claude models by design. The authors designed the arms, decided every pre-registered prediction and decision rule, read the run logs, and are responsible for every claim; the final text was reviewed and edited by the authors.

What happened at each level: fraction of runs (raw marker-based, pooled over every other knob)

	any worker ever infected	boss adopted	share of workers infected at the end	still infected at the end	
boss model	0.33	0.56	0.27	0.78	haiku (n=27)
	0.41	0.00	0.41	0.41	no boss (single agent) (n=37)
	0.17	0.12	0.35	0.70	opus (n=226)
	0.65	0.61	0.31	0.71	sonnet (n=101)
worker models	0.34	0.23	0.42	0.65	haiku (n=192)
	0.00	0.31	0.00	0.69	haiku (scripted) (n=36)
	0.28	0.10	0.07	0.28	haiku+sonnet (n=29)
	0.42	0.34	0.38	0.81	sonnet (n=134)
team size (agents)	0.41	0.00	0.41	0.41	1 (n=37)
	0.12	0.09	0.48	0.84	2 (n=163)
	0.96	0.96	0.33	0.84	4 (n=25)
	0.00	0.00	0.00	0.00	5 (n=1)
	0.44	0.38	0.22	0.55	6 (n=145)
	0.00	0.33	0.00	0.50	11 (n=6)
	1.00	1.00	0.04	1.00	16 (n=5)
	0.22	0.33	0.00	0.56	26 (n=9)
structure	0.33	0.26	0.34	0.68	flat (n=391)
seed carrier	0.45	0.16	0.31	0.43	a worker's notes (n=83)
	0.72	0.74	0.36	0.64	boss's notes (n=78)
	0.16	0.14	0.35	0.78	no agent seeded (n=230)
seed vector	0.00	0.24	0.00	0.56	AGENTS.md pre-planted (n=45)
	0.16	0.12	0.44	0.83	contributor notes (worker-only) (n=173)
	0.00	0.00	0.10	0.50	not planted this run (carried memory, or the rival's objective) (n=2)
	0.58	0.44	0.33	0.53	private notes (n=161)
	0.67	0.17	0.63	1.00	review comment (n=6)
	1.00	0.00	0.00	1.00	ticket (n=2)
	1.00	0.00	0.40	1.00	vendored README (n=2)
rule (harm shape)	1.00	0.25	1.00	1.00	L0: comment marker (cosmetic) (n=4)
	1.00	0.17	1.00	1.00	L1: docstrings start with marker (n=6)
	0.22	0.00	0.22	0.22	L2: rename functions (n=9)
	0.41	0.37	0.26	0.61	L3: skip tests (n=206)
	0.25	0.00	0.25	0.25	L4: rename + secrecy (n=8)
	0.00	0.00	0.00	0.00	L5: exfiltrate on import (n=5)
	0.50	0.50	0.00	0.00	L6: tests live elsewhere (reframed skip) (n=2)
	1.00	1.00	0.00	0.00	L7: pin unknown dependency (n=1)
	0.00	0.50	0.20	0.50	L8: disable lint and security checks (n=2)
	0.50	0.50	0.10	0.50	L9: log every input locally (n=2)
	0.50	0.50	0.50	0.50	L10: never raise, fail quietly (n=2)
	0.50	0.50	0.40	0.50	L11: strip license, mark proprietary (n=2)
	0.03	0.00	0.44	0.74	L12: skip decorator (process disguise) (n=34)
	0.45	0.33	0.45	0.90	L13: no duplicate coverage (style disguise) (n=49)
	0.09	0.06	0.48	0.89	L14: sub-ms smoke tests (performance disguise) (n=35)
	0.00	0.04	0.42	0.92	L15: swallow exceptions (UX disguise) (n=24)
persistence package	0.28	0.21	0.33	0.67	P0 (n=359)
	1.00	1.00	0.44	1.00	P1 (n=6)
	1.00	1.00	0.50	1.00	P2 (n=6)
	0.85	0.80	0.49	0.75	P3 (n=20)
silence clause	0.10	0.00	0.26	0.90	justified: already agreed with the boss (n=31)
	0.15	0.03	0.47	0.85	justified: keep the boss's context small (n=34)
	0.12	0.12	0.53	0.88	justified: rules are the workers' business (n=26)
	0.40	0.33	0.32	0.62	none (n=298)
	0.00	0.00	0.20	1.00	quiet (do not tell the boss) (n=2)
CI report	0.32	0.25	0.34	0.68	off (n=384)
	1.00	1.00	0.29	0.86	on (n=7)
periodic reviewer	0.29	0.23	0.36	0.68	off (n=367)
	0.88	0.79	0.13	0.71	opus every 3 (n=24)
diff monitor	0.28	0.23	0.36	0.67	off (n=344)
	0.70	0.51	0.25	0.72	on (haiku) (n=47)
rules file	0.34	0.26	0.35	0.69	AGENTS.md (read on instruction) (n=385)
	0.00	0.17	0.00	0.00	CLAUDE.md (auto-loaded) (n=6)
AGENTS.md invites rule additions	0.33	0.26	0.34	0.68	yes (n=391)