


LEET CODE 203:

 Problem List < > 🔍

Submit 📄 🚀


Description Editorial Solutions Submissions

203. Remove Linked List Elements

Easy Topics Companies

Given the `head` of a linked list and an integer `val`, remove all the nodes of the linked list that has `Node.val == val`, and return *the new head*.

Example 1:



Input: `head = [1,2,6,3,4,5,6]`, `val = 6`
Output: `[1,2,3,4,5]`


Example 2:

Input: `head = []`, `val = 1`
Output: `[]`

Example 3:

Input: `head = [7,7,7,7]`, `val = 7`
Output: `[]`


👍 8.9K 🗨 86 ☆ 📄 ⓘ

 Problem List < > 🔍

</> Code

C 🔒 Auto

```
1 struct ListNode* removeElements(struct ListNode* head, int val) {
2     struct ListNode temp;
3     temp.next = head;
4     struct ListNode* curr = &temp;
5
6     while (curr->next) {
7         if (curr->next->val == val) {
8             curr->next = curr->next->next;
9         } else {
10            curr = curr->next;
11        }
12    }
13    return temp.next;
14 }
```

 Problem List < > ↺

🔥 ▶️ 📤 Submit 📄 ✨

☑️ Testcase >_ Test Result

Accepted Runtime: 0 ms

☑️ Case 1 ☑️ Case 2 ☑️ Case 3

Input

head =
[1,2,6,3,4,5,6]

val =
6


Output

[1,2,3,4,5]

Expected

[1,2,3,4,5]

♥️ Contribute a testcase

 Problem List < > ↺

🔥 ▶️ 📤 Submit 📄 ✨

☑️ Testcase >_ Test Result

Accepted Runtime: 0 ms

☑️ Case 1 ☑️ Case 2 ☑️ Case 3

Input

head =
[]

val =
1

Output

[]

Expected

[]

♥️ Contribute a testcase



Problem List



Submit



☒ Testcase

[> Test Result](#)

Accepted

Runtime: 0 ms

☒ Case 1

☒ Case 2

☒ Case 3

Input

head =

[7,7,7,7]

val =

7

Output

[]

Expected

[]

[♥ Contribute a testcase](#)