Week 1 — Repo Scaffold (bash script)

Copy this whole block into your terminal. It will create the repo, folders, base pages, styles, and commit.

```
#!/usr/bin/env bash
set -euo pipefail
# Usage: ./scaffold.sh my-site (or run as-is to use default name)
PROJECT=${1:-brand-site}
# Create folders
mkdir -p "$PROJECT"/{pages,src/components,styles,public}
cd "$PROJECT"
# .gitignore
cat > .gitignore <<'IG'</pre>
# OS
.DS_Store
Thumbs.db
# Node/Python (future-proof)
node_modules/
*.log
__pycache__/
.env*
ΙG
# README
cat > README.md <<'MD'</pre>
# Brand Site - Week 1 Scaffold
This repo was generated to satisfy Week 1 DoD:
- Style guide + tokens
Base pages (Home/About/Contact)
- Repo initialized & committed
## Run locally
Open `pages/index.html` in your browser (double-click or drag into a tab).
Optional: start a local server (Python 3):
```bash
python3 -m http.server -d pages 5173
then visit http://localhost:5173
```

#### **Structure**

```
/pages # Static pages
/styles # Global CSS tokens + utilities
/src # Components (if you add JS later)
/public # Static assets (images, icons)
```

MD

## Global CSS (tokens + base + utilities)

```
/ :root { / Colors / --color-bg: #111A19; --color-text: #F8D794; --color-accent: #BB6830; --color-surface:
#284139; --color-muted: #809076;
/ Spacing scale (8px base) / --space-1: 0.5rem; / 8px / --space-2: 1rem; / 16px / --space-3: 1.5rem; / 24px / --
space-4: 2rem; / 32px / --space-5: 3rem; / 48px / --space-6: 4rem; / 64px /
/ Radius & shadow / --radius: 1rem; / 16px / --shadow-1: 0 1px 2px rgba(0,0,0,.25); --shadow-2: 0 8px 24px
rgba(0,0,0,.35); }
/ ==== Base ======== / * { box-sizing: border-
box; } html, body { margin: 0; padding: 0; } html { font-size: 16px; } body { font: 400 1rem/1.6 "Source Sans
3", system-ui, -apple-system, Segoe UI, Roboto, Ubuntu, Cantarell, Noto Sans, Arial, "Apple Color Emoji",
"Segoe UI Emoji", sans-serif; color: var(--color-text); background: var(--color-bg); }
h1, h2, h3, h4, h5, h6 { font-family: "Nuosu SIL", Georgia, "Times New Roman", serif; margin: 0 0 var(--
space-2); } h1 { font-weight: 700; font-size: 2.488rem; line-height: 1.15; } h2 { font-weight: 700; font-size:
1.99rem; line-height: 1.2; } h3 { font-weight: 700; font-size: 1.592rem; line-height: 1.25; }
p { margin: 0 0 var(--space-2); } small, .small { font-size: .875rem; line-height: 1.5; color: var(--color-muted); }
/ ==== Layout helpers ================ / .container { width: min(1100px,
92vw); margin-inline: auto; padding-inline: var(--space-3); } .section { padding-block: var(--space-5); } .stack >
* + * { margin-top: var(--space-2); } .grid { display: grid; gap: var(--space-3); } .grid-2 { grid-template-columns:
repeat(2, minmax(0, 1fr)); }
/ ==== Components ========== / .card { background: var(--
color-surface); color: var(--color-text); padding: var(--space-3); border-radius: var(--radius); box-shadow:
var(--shadow-1); }
a { color: var(--color-accent); text-underline-offset: 2px; } a:hover { text-decoration-thickness: 2px; }
```

.button { display: inline-flex; align-items: center; gap: .5rem; padding: .625rem 1rem; border-radius: var(-radius); font: 600 1rem/1 "Source Sans 3", system-ui, sans-serif; border: 1px solid transparent; cursor: pointer; text-decoration: none; transition: transform .04s ease, box-shadow .2s ease, background-color .2s ease; } .button--primary { background: var(--color-accent); color: #0d0d0d; } .button--primary:hover { transform: translateY(-1px); box-shadow: var(--shadow-2); } .button--secondary { background: transparent; color: var(--color-accent); } .button--secondary:hover { background: color-mix(in oklab, var(--color-accent) 12%, transparent); }

.input, select, textarea { width: 100%; background: #0b1413; color: var(--color-text); border: 1px solid color-mix(in oklab, var(--color-muted) 40%, black); padding: .625rem .75rem; border-radius: .75rem; } .input:focus { outline: 2px solid var(--color-accent); outline-offset: 2px; } .label { color: var(--color-muted); font-weight: 600; }

### **Base HTML template function**

<main> <section class="section"> <div class="container stack"> <h1>\$TITLE</h1> Starter page built with your Week 1 tokens. </div> </section>

```
captions.
 Secondary CTA
 </div>
 </div>
</section>
```

</main>

<footer class="footer"> <div class="container">© \$(date +%Y) Brand Site</div> </footer> </body> </html> HTML }

#### **Create pages**

page "Home" index.html page "About" about.html

# Contact page with a form example

cat > pages/contact.html <<'HTML' <!doctype html> <html lang="en"> <head> <meta charset="utf-8" /> <meta name="viewport" content="width=device-width, initial-scale=1" /> <title>Contact</title> k href="https://fonts.googleapis.com/css2?"

family=Nuosu+SIL:wght@400;700&family=Source+Sans+3:wght@300;400;600;700&display=swap" rel="stylesheet"> k rel="stylesheet" href="../styles/style.css" /> </head> <body> <header class="site-header"> <div class="container nav"> <a href="/pages/index.html" class="button button-secondary">Home</a> <a href="/pages/about.html" class="button button-secondary">About</a> <a href="/pages/contact.html" class="button button-secondary">Contact</a> </div> </header> <main> <section class="section"> <div class="container stack"> <h1>Contact</h1> This form is non-functional by default; wire it up later or use Formspree. <form class="stack" style="max-width: 540px;"> <label class="label" for="name">Name</label> <input class="input" id="name" placeholder="Your name" /> <label class="label" for="email">Email</label> <input class="input" id="email" type="email" placeholder="you@example.com" /> <label class="label" for="message">Message</label> <textarea class="input" id="message" rows="5" placeholder="Tell me a bit about your project..."></textarea <b dots class="button button--primary" type="button">Send</b dots class="footer"></tibody> </tibody> </tibody>

#### Git init & first commit

git init >/dev/null 2>&1 || true git add . git commit -m "Week 1 scaffold: repo, base pages, styles, README" >/dev/null 2>&1 || true

echo "\n\\Done. Open pages/index.html to view the site." echo " Optional: python3 -m http.server -d pages 5173 # then http://localhost:5173" ```

What you get - pages/index.html, pages/about.html, pages/contact.html using your brand tokens. - styles/style.css with the exact color roles, fonts, spacing, and components from style.md. - README.md, .gitignore, and an initial Git commit.

If you want a React/Tailwind variant (Vite + Tailwind + shadcn/ui) I can generate a separate scaffold script next.