

MINA

Developer guide and source map

Mediation, Integration and Automation

Version 1.0.3 - 96 activities, 11 groups, 85 functions and 12 shared connection types.

Repository navigation for every palette activity and core development feature. Source locations include verified search anchors and build-specific line numbers. Frontend, Python engine, native bridge and direct-export code paths are distinguished.

Use the linked contents or PDF bookmarks. Paths are relative to the repository root, not the installation directory. Edit maintained sources, add regression tests, rebuild and redistribute; do not patch generated archives as the permanent fix.

Contents

Developer guide: where to change MINA	7
Start: source map	8
Scheduler: source map	11
Call Sub Task: source map	13
End: source map	16
Read File: source map	19
Write File: source map	22
List Files: source map	24
Delete File: source map	26
Rename File: source map	28
Copy File: source map	30
File Poller: source map	32
FTP Get: source map	34
FTP Put: source map	36
FTP Delete: source map	38
FTP Directory: source map	40
FTP Change Directory: source map	42
SFTP Get: source map	44
SFTP Put: source map	46
SFTP Delete: source map	48
SFTP Directory: source map	50
SFTP Change Directory: source map	52
HTTP Listener: source map	54
HTTP Request: source map	57
HTTP Response: source map	59
REST API Receiver: source map	62

REST API Invoke: source map	65
SOAP Service: source map	68
SOAP Request Reply: source map	71
EMS Queue Receiver: source map	74
EMS Topic Subscriber: source map	77
EMS Queue Sender: source map	80
EMS Topic Publisher: source map	83
EMS Request Reply: source map	86
EMS Reply: source map	89
Get JMS Queue Message: source map	92
JMS Receive Message: source map	95
JMS Request Reply: source map	98
JMS Send Message: source map	101
Reply to JMS Message: source map	104
Wait for JMS Request: source map	107
Kafka Receive Message: source map	110
Kafka Send Message: source map	112
Kafka Get Messages: source map	114
Pub/Sub Subscriber: source map	116
Pub/Sub Publisher: source map	119
Dynamic Connection: source map	122
IDoc Acknowledgment: source map	125
IDoc Confirmation: source map	128
IDoc Converter: source map	131
IDoc Listener: source map	134
IDoc Parser: source map	137
IDoc Reader: source map	140

Post IDoc to SAP: source map	143
IDoc Renderer: source map	146
RFC BAPI Listener: source map	149
Invoke RFC BAPI in SAP: source map	152
Reply from RFC BAPI in SAP: source map	155
Read Table: source map	158
JDBC Create: source map	161
JDBC Update: source map	163
JDBC Query: source map	165
JDBC Truncate: source map	167
JDBC Delete: source map	169
Stored Procedure: source map	171
Dynamic SQL: source map	173
Snowflake Insert: source map	175
Snowflake Query: source map	177
Snowflake Update: source map	179
Snowflake Delete: source map	181
Snowflake Bulk Load: source map	183
AMQP Receive Message: source map	185
AMQP Get Message: source map	188
AMQP Send Message: source map	191
AMQP Dead Letter Message: source map	193
Parse XML: source map	196
Render XML: source map	198
Parse JSON: source map	200
Render JSON: source map	202
Parse Data: source map	204

Render Data: source map	206
Read Excel Workbook: source map	208
Mapper: source map	210
Transform: source map	212
Log: source map	214
Catch Exception: source map	216
Throw Exception: source map	218
Rethrow Exception: source map	220
Confirm Message: source map	222
Java Activity: source map	224
Python Invoke: source map	227
External Command: source map	229
Assign: source map	231
Checkpoint: source map	233
Sleep: source map	235
Get Shared Variable: source map	237
Set Shared Variable: source map	239
Tasks, sub-tasks, persistence and copy	241
Run, continuous events and Stop	242
Debug controls, test bench and Job Data	243
Input mapping, schema mapper and suggestions	245
Built-in and project functions	247
Canvas and mapper drag-and-drop	248
Groups: editor, graph boundaries and runtime state	249
If: source map	251
While True: source map	252
For Each: source map	253

Iterate: source map	254
Repeat Until True: source map	255
Repeat on Error Until True: source map	256
Scope: source map	257
None: source map	258
Critical Section: source map	259
JDBC Transaction: source map	260
Pick First: source map	261
Engine archives versus direct Python generation	262
Logs, faults and observable execution data	263
Every built-in function: implementation index	264

Developer guide: where to change MINA

Developer guide / Start here

Architecture

This is a source-maintenance guide, separate from the activity user manual. Frontend code is React/TypeScript, core engine code is Python, and native connector work can execute in Java. Paths are relative to your repository checkout, not the installed program directory. Line numbers are regenerated from verified anchors and refer to this documentation build.

```
Palette / canvas -> ActivityEditor -> saved Project
Run API -> WorkflowRuntime.run -> execute_with_policy
-> resolve_activity_config -> execute -> adapter / native bridge
-> record_activity_output -> Run result / Debug Job Data

Raw Python export -> raw_python_files -> generated task modules
-> raw_python_support (specialized helpers) -> adapters / bridge
```

The source tables tell you where to start, not that every option is fully implemented. Read the operational guide for known behavior gaps. A passing unit test or this code index does not establish provider certification.

How to navigate

Expand Developer guide > Activities for one page per palette activity. Features covers tasks, groups, Run, Debug, mapping, functions and drag-and-drop. Each source table provides a file:line plus a stable search anchor. Use your editor Go to File and Go to Line; if your checkout differs, search the anchor. The site deliberately does not expose source files or local filesystem URLs.

```
Example from repository root:
rg -n "def resolve_activity_config" backend/app/runtime.py
rg -n "file_activity" backend/app/raw_python_support/activities.py
```

Do not edit frontend/dist, installed app.asar, generated task archives or packaged engine copies as the permanent fix. Edit repository sources, regenerate/rebuild, and redistribute. Preserve saved activity IDs and config keys when changing labels.

Change checklist

1. Decide whether the change is visual, schema, runtime, transport or export behavior. 2. Follow the relevant source map. 3. Preserve existing project defaults/aliases or add an explicit migration. 4. Update runtime and direct-export implementations where they differ. 5. Add normal, error, cancellation and legacy-project tests. 6. Regenerate docs, build and test a newly packaged install.

```
cd backend
python -m unittest discover -s tests
cd ../frontend
npm run docs:build
node --test scripts/documentation.test.mjs
npm run build
```

Use a development environment with the project dependencies installed. Provider tests require isolated test infrastructure and licensed drivers. Never use production queues, write APIs or secrets in documentation fixtures.

Start: source map

Developer guide / Activities / Starters & Tasks

Trace

Saved identity: type=start; config.operation=start. Start is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (start)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: start; select operation start	frontend/src/ActivityEditor.tsx:201 if (n.type === "start")
Engine start dispatch; operation start	backend/app/runtime.py:696 if activity.type == 'start':
Direct helper dispatch for start; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Task graph and interface schema	backend/app/models.py:307 class ProcessDefinition(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Start, select type=start and operation=start, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of start. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Scheduler: source map

Developer guide / Activities / Starters & Tasks

Trace

Saved identity: type=timer; config.operation=schedule. Scheduler is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (timer)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: timer; select operation schedule	frontend/src/ActivityEditor.tsx:215 if (n.type === "timer")
Engine timer dispatch; operation schedule	backend/app/runtime.py:702 if activity.type == 'timer':
Direct helper dispatch for timer; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Scheduler, select type=timer and operation=schedule, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of schedule. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Call Sub Task: source map

Developer guide / Activities / Starters & Tasks

Trace

Saved identity: type=call_task; config.operation=call. Call Sub Task is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (call_task)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: call_task; select operation call	frontend/src/ActivityEditor.tsx:243 if (n.type === "call_task")
Engine call_task dispatch; operation call	backend/app/runtime.py:1116 if activity.type == 'call_task':
Direct helper dispatch for call_task; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Task graph and interface schema	backend/app/models.py:307 class ProcessDefinition(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Call Sub Task, select type=call_task and operation=call, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of call. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

End: source map

Developer guide / Activities / Starters & Tasks

Trace

Saved identity: type=end; config.operation=end. End is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (end)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: end; select operation end	frontend/src/ActivityEditor.tsx:208 if (n.type === "end")
Engine end dispatch; operation end	backend/app/runtime.py:699 if activity.type == 'end':
Direct helper dispatch for end; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Task graph and interface schema	backend/app/models.py:307 class ProcessDefinition(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing End, select type=end and operation=end, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of end. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Read File: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=read. Read File is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation read	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation read	backend/app/raw_python_support/activities.py:50 def file_activity(
Text read implementation	backend/app/runtime.py:1045 content = path.read_text(
Binary read implementation	backend/app/runtime.py:1044 path.read_bytes()
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

Example: adding a streaming/size-limit option requires a palette default if needed, a Configuration field in activityContract, mapping exposure via runtimeMappableInputs, a check before read_text/read_bytes in WorkflowRuntime.execute, and equivalent behavior in file_activity for direct exports. Keep existing textContent/content/binaryContent/fileInfo keys compatible. Current reads materialize whole contents; changing the output to a stream changes the contract and cannot be a silent replacement.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of read. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Write File: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=write. Write File is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation write	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation write	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Write File, select type=file and operation=write, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of write. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

List Files: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=list. List Files is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation list	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation list	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing List Files, select type=file and operation=list, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of list. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Delete File: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=delete. Delete File is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation delete	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation delete	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Delete File, select type=file and operation=delete, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of delete. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Rename File: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=rename. Rename File is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation rename	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation rename	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Rename File, select type=file and operation=rename, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of rename. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Copy File: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=copy. Copy File is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation copy	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation copy	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Copy File, select type=file and operation=copy, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of copy. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

File Poller: source map

Developer guide / Activities / File

Trace

Saved identity: type=file; config.operation=poll. File Poller is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'file':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: file; select operation poll	frontend/src/ActivityEditor.tsx:301 if (n.type === "file")
Local file execution; read is the fall-through after write/list/delete/rename/copy/poll branches	backend/app/runtime.py:992 if activity.type == 'file':
Direct Python implementation; inspect operation poll	backend/app/raw_python_support/activities.py:50 def file_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing File Poller, select type=file and operation=poll, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of poll. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

FTP Get: source map

Developer guide / Activities / FTP

Trace

Saved identity: type=ftp; config.operation=get. FTP Get is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def ftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
FTP operations using the selected operation	backend/app/runtime.py:1740 def ftp(
Direct Python implementation; inspect operation get	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing FTP Get, select type=ftp and operation=get, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

FTP Put: source map

Developer guide / Activities / FTP

Trace

Saved identity: type=ftp; config.operation=put. FTP Put is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def ftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
FTP operations using the selected operation	backend/app/runtime.py:1740 def ftp(
Direct Python implementation; inspect operation put	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing FTP Put, select type=ftp and operation=put, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of put. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

FTP Delete: source map

Developer guide / Activities / FTP

Trace

Saved identity: type=ftp; config.operation=delete. FTP Delete is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def ftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
FTP operations using the selected operation	backend/app/runtime.py:1740 def ftp(
Direct Python implementation; inspect operation delete	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing FTP Delete, select type=ftp and operation=delete, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of delete. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

FTP Directory: source map

Developer guide / Activities / FTP

Trace

Saved identity: type=ftp; config.operation=dir. FTP Directory is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def ftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
FTP operations using the selected operation	backend/app/runtime.py:1740 def ftp(
Direct Python implementation; inspect operation dir	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing FTP Directory, select type=ftp and operation=dir, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of dir. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

FTP Change Directory: source map

Developer guide / Activities / FTP

Trace

Saved identity: type=ftp; config.operation=change_dir. FTP Change Directory is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def ftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
FTP operations using the selected operation	backend/app/runtime.py:1740 def ftp(
Direct Python implementation; inspect operation change_dir	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing FTP Change Directory, select type=ftp and operation=change_dir, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of change_dir. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SFTP Get: source map

Developer guide / Activities / SFTP

Trace

Saved identity: type=sftp; config.operation=get. SFTP Get is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def sftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
SFTP operations using the selected operation	backend/app/runtime.py:1759 def sftp(
Direct Python implementation; inspect operation get	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SFTP Get, select type=sftp and operation=get, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SFTP Put: source map

Developer guide / Activities / SFTP

Trace

Saved identity: type=sftp; config.operation=put. SFTP Put is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def sftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
SFTP operations using the selected operation	backend/app/runtime.py:1759 def sftp(
Direct Python implementation; inspect operation put	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SFTP Put, select type=sftp and operation=put, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of put. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SFTP Delete: source map

Developer guide / Activities / SFTP

Trace

Saved identity: type=sftp; config.operation=delete. SFTP Delete is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def sftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
SFTP operations using the selected operation	backend/app/runtime.py:1759 def sftp(
Direct Python implementation; inspect operation delete	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SFTP Delete, select type=sftp and operation=delete, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of delete. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SFTP Directory: source map

Developer guide / Activities / SFTP

Trace

Saved identity: type=sftp; config.operation=dir. SFTP Directory is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def sftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
SFTP operations using the selected operation	backend/app/runtime.py:1759 def sftp(
Direct Python implementation; inspect operation dir	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SFTP Directory, select type=sftp and operation=dir, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of dir. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SFTP Change Directory: source map

Developer guide / Activities / SFTP

Trace

Saved identity: type=sftp; config.operation=change_dir. SFTP Change Directory is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def sftp(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
SFTP operations using the selected operation	backend/app/runtime.py:1759 def sftp(
Direct Python implementation; inspect operation change_dir	backend/app/raw_python_support/activities.py:210 def transfer(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SFTP Change Directory, select type=sftp and operation=change_dir, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of change_dir. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

HTTP Listener: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=http_listener; config.operation=listen. HTTP Listener is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (http_listener)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: http_listener; select operation listen	frontend/src/ActivityEditor.tsx:412 if (n.type === "http_listener")
Engine http_listener dispatch; operation listen	backend/app/runtime.py:694 async def execute(self,
Direct helper dispatch for http_listener; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing HTTP Listener, select type=http_listener and operation=listen, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of listen. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

HTTP Request: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=http; config.operation=request. HTTP Request is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'http':
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
HTTP client request	backend/app/runtime.py:970 if activity.type == 'http':
Direct Python implementation; inspect operation request	backend/app/raw_python_support/activities.py:250 def http_request(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing HTTP Request, select type=http and operation=request, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of request. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

HTTP Response: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=http_response; config.operation=response. HTTP Response is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (http_response)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: http_response; select operation response	frontend/src/ActivityEditor.tsx:491 if (n.type === "http_response")
Engine http_response dispatch; operation response	backend/app/runtime.py:813 if activity.type == 'http_response':
Direct helper dispatch for http_response; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing HTTP Response, select type=http_response and operation=response, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of response. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

REST API Receiver: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=rest; config.operation=receiver. REST API Receiver is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'rest' and
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
REST outbound request; inbound path enters invoke_listener	backend/app/runtime.py:977 if activity.type == 'rest' and
Direct Python implementation; inspect operation receiver	backend/app/raw_python_support/activities.py:250 def http_request(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing REST API Receiver, select type=rest and operation=receiver, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of receiver. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

REST API Invoke: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=rest; config.operation=invoke. REST API Invoke is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'rest' and
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
REST outbound request; inbound path enters invoke_listener	backend/app/runtime.py:977 if activity.type == 'rest' and
Direct Python implementation; inspect operation invoke	backend/app/raw_python_support/activities.py:250 def http_request(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing REST API Invoke, select type=rest and operation=invoke, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of invoke. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

SOAP Service: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=soap; config.operation=service. SOAP Service is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'soap' and
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: soap; select operation service	frontend/src/ActivityEditor.tsx:543 if (n.type === "soap")
SOAP outbound request; service path enters invoke_listener	backend/app/runtime.py:984 if activity.type == 'soap' and
Direct Python implementation; inspect operation service	backend/app/raw_python_support/activities.py:250 def http_request(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SOAP Service, select type=soap and operation=service, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of service. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

SOAP Request Reply: source map

Developer guide / Activities / HTTP & APIs

Trace

Saved identity: type=soap; config.operation=request_reply. SOAP Request Reply is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: if activity.type == 'soap' and
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: soap; select operation request_reply	frontend/src/ActivityEditor.tsx:543 if (n.type === "soap")
SOAP outbound request; service path enters invoke_listener	backend/app/runtime.py:984 if activity.type == 'soap' and
Direct Python implementation; inspect operation request_reply	backend/app/raw_python_support/activities.py:250 def http_request(
Inbound HTTP/REST/SOAP hosting and response boundary	backend/app/main.py:1860 async def invoke_listener(
Direct-export application hosting	backend/app/raw_python_support/main.py:24 async def run_application(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing SOAP Request Reply, select type=soap and operation=request_reply, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of request_reply. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

EMS Queue Receiver: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=queue_receiver. EMS Queue Receiver is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation queue_receiver	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Queue Receiver, select type=ems and operation=queue_receiver, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of queue_receiver. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

EMS Topic Subscriber: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=topic_subscriber. EMS Topic Subscriber is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation topic_subscriber	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Topic Subscriber, select type=ems and operation=topic_subscriber, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of topic_subscriber. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

EMS Queue Sender: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=send. EMS Queue Sender is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation send	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Queue Sender, select type=ems and operation=send, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of send. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

EMS Topic Publisher: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=publish. EMS Topic Publisher is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation publish	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Topic Publisher, select type=ems and operation=publish, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of publish. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

EMS Request Reply: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=request_reply. EMS Request Reply is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation request_reply	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Request Reply, select type=ems and operation=request_reply, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of request_reply. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

EMS Reply: source map

Developer guide / Activities / EMS

Trace

Saved identity: type=ems; config.operation=reply. EMS Reply is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
EMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation reply	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing EMS Reply, select type=ems and operation=reply, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of reply. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Get JMS Queue Message: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=get_queue_message. Get JMS Queue Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation get_queue_message	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Get JMS Queue Message, select type=jms and operation=get_queue_message, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get_queue_message. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

JMS Receive Message: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=receive_message. JMS Receive Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation receive_message	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JMS Receive Message, select type=jms and operation=receive_message, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of receive_message. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

JMS Request Reply: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=request_reply. JMS Request Reply is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation request_reply	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JMS Request Reply, select type=jms and operation=request_reply, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of request_reply. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

JMS Send Message: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=send_message. JMS Send Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation send_message	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JMS Send Message, select type=jms and operation=send_message, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of send_message. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Reply to JMS Message: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=reply_message. Reply to JMS Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation reply_message	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Reply to JMS Message, select type=jms and operation=reply_message, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of reply_message. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Wait for JMS Request: source map

Developer guide / Activities / JMS

Trace

Saved identity: type=jms; config.operation=wait_request. Wait for JMS Request is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JMS operation routing and body/ack handling	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation wait_request	backend/app/raw_python_support/connectors.py:44 async def jms(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: jms_publish_performance	backend/tests/test_jms_publish_performance.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Wait for JMS Request, select type=jms and operation=wait_request, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of wait_request. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_jms_publish_performance tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Kafka Receive Message: source map

Developer guide / Activities / Kafka

Trace

Saved identity: type=kafka; config.operation=receive. Kafka Receive Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: kafka; select operation receive	frontend/src/ActivityEditor.tsx:783 if (n.type === "kafka")
Kafka producer/consumer operation dispatch	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation receive	backend/app/raw_python_support/connectors.py:228 async def kafka(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: publisher_reuse	backend/tests/test_publisher_reuse.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Kafka Receive Message, select type=kafka and operation=receive, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of receive. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_publisher_reuse tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Kafka Send Message: source map

Developer guide / Activities / Kafka

Trace

Saved identity: type=kafka; config.operation=send. Kafka Send Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: kafka; select operation send	frontend/src/ActivityEditor.tsx:783 if (n.type === "kafka")
Kafka producer/consumer operation dispatch	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation send	backend/app/raw_python_support/connectors.py:228 async def kafka(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: publisher_reuse	backend/tests/test_publisher_reuse.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Kafka Send Message, select type=kafka and operation=send, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of send. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_publisher_reuse tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Kafka Get Messages: source map

Developer guide / Activities / Kafka

Trace

Saved identity: type=kafka; config.operation=get. Kafka Get Messages is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: kafka; select operation get	frontend/src/ActivityEditor.tsx:783 if (n.type === "kafka")
Kafka producer/consumer operation dispatch	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation get	backend/app/raw_python_support/connectors.py:228 async def kafka(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: publisher_reuse	backend/tests/test_publisher_reuse.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Kafka Get Messages, select type=kafka and operation=get, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_publisher_reuse tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Pub/Sub Subscriber: source map

Developer guide / Activities / GCP Pub/Sub

Trace

Saved identity: type=pubsub; config.operation=subscribe. Pub/Sub Subscriber is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: pubsub; select operation subscribe	frontend/src/ActivityEditor.tsx:810 if (n.type === "pubsub")
Pub/Sub publish/receive dispatch	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation subscribe	backend/app/raw_python_support/connectors.py:317 async def pubsub(
Credential/channel client factory	backend/app/google_pubsub.py:186 def create_client(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: google_pubsub	backend/tests/test_google_pubsub.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Pub/Sub Subscriber, select type=pubsub and operation=subscribe, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of subscribe. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_google_pubsub tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Pub/Sub Publisher: source map

Developer guide / Activities / GCP Pub/Sub

Trace

Saved identity: type=pubsub; config.operation=publish. Pub/Sub Publisher is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def messaging(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: pubsub; select operation publish	frontend/src/ActivityEditor.tsx:810 if (n.type === "pubsub")
Pub/Sub publish/receive dispatch	backend/app/runtime.py:1143 async def messaging(
Direct Python implementation; inspect operation publish	backend/app/raw_python_support/connectors.py:317 async def pubsub(
Credential/channel client factory	backend/app/google_pubsub.py:186 def create_client(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: google_pubsub	backend/tests/test_google_pubsub.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Pub/Sub Publisher, select type=pubsub and operation=publish, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of publish. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_google_pubsub tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Dynamic Connection: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=dynamic_connection. Dynamic Connection is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation dynamic_connection	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation dynamic_connection	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Dynamic Connection, select type=sap and operation=dynamic_connection, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of dynamic_connection. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Acknowledgment: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_acknowledgment. IDoc Acknowledgment is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_acknowledgment	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_acknowledgment	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Acknowledgment, select type=sap and operation=idoc_acknowledgment, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_acknowledgment. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Confirmation: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_confirmation. IDoc Confirmation is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_confirmation	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_confirmation	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Confirmation, select type=sap and operation=idoc_confirmation, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_confirmation. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Converter: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_converter. IDoc Converter is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_converter	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_converter	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Converter, select type=sap and operation=idoc_converter, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_converter. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Listener: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_listener. IDoc Listener is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_listener	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_listener	backend/app/raw_python_support/connectors.py:197 async def sap(
Inbound SAP adapter	backend/app/sap.py:793 async def receive_idoc(
Continuous SAP jobs	backend/app/main.py:438 async def _continuous_sap_event_loop(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Listener, select type=sap and operation=idoc_listener, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of `idoc_listener`. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Parser: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_parser. IDoc Parser is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_parser	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_parser	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Parser, select type=sap and operation=idoc_parser, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_parser. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Reader: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_reader. IDoc Reader is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_reader	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_reader	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Reader, select type=sap and operation=idoc_reader, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_reader. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Post IDoc to SAP: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=post_idoc. Post IDoc to SAP is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation post_idoc	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation post_idoc	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Post IDoc to SAP, select type=sap and operation=post_idoc, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of post_idoc. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

IDoc Renderer: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=idoc_renderer. IDoc Renderer is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation idoc_renderer	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation idoc_renderer	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing IDoc Renderer, select type=sap and operation=idoc_renderer, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of idoc_renderer. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

RFC BAPI Listener: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=rfc_bapi_listener. RFC BAPI Listener is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation rfc_bapi_listener	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation rfc_bapi_listener	backend/app/raw_python_support/connectors.py:197 async def sap(
Inbound SAP adapter	backend/app/sap.py:793 async def receive_idoc(
Continuous SAP jobs	backend/app/main.py:438 async def _continuous_sap_event_loop(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing RFC BAPI Listener, select type=sap and operation=rfc_bapi_listener, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of `rfc_bapi_listener`. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Invoke RFC BAPI in SAP: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=invoke_rfc_bapi. Invoke RFC BAPI in SAP is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation invoke_rfc_bapi	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation invoke_rfc_bapi	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Invoke RFC BAPI in SAP, select type=sap and operation=invoke_rfc_bapi, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of invoke_rfc_bapi. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Reply from RFC BAPI in SAP: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=reply_rfc_bapi. Reply from RFC BAPI in SAP is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation reply_rfc_bapi	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation reply_rfc_bapi	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Reply from RFC BAPI in SAP, select type=sap and operation=reply_rfc_bapi, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of reply_rfc_bapi. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Read Table: source map

Developer guide / Activities / SAP ECC

Trace

Saved identity: type=sap; config.operation=read_table. Read Table is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/sap.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: sap; select operation read_table	frontend/src/ActivityEditor.tsx:820 if (n.type === "sap")
SAP operation dispatch; listeners use receive_idoc	backend/app/sap.py:1081 def execute(
Direct Python implementation; inspect operation read_table	backend/app/raw_python_support/connectors.py:197 async def sap(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: sap_mapper	backend/tests/test_sap_mapper.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Read Table, select type=sap and operation=read_table, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of read_table. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_sap_mapper tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

JDBC Create: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=insert. JDBC Create is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation insert	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation insert	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JDBC Create, select type=jdbc and operation=insert, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of insert. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

JDBC Update: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=update. JDBC Update is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation update	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation update	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JDBC Update, select type=jdbc and operation=update, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of update. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

JDBC Query: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=query. JDBC Query is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation query	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation query	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JDBC Query, select type=jdbc and operation=query, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of query. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

JDBC Truncate: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=truncate. JDBC Truncate is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation truncate	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation truncate	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JDBC Truncate, select type=jdbc and operation=truncate, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of truncate. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

JDBC Delete: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=delete. JDBC Delete is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation delete	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation delete	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing JDBC Delete, select type=jdbc and operation=delete, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of delete. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Stored Procedure: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=call. Stored Procedure is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation call	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation call	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Stored Procedure, select type=jdbc and operation=call, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of call. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Dynamic SQL: source map

Developer guide / Activities / JDBC

Trace

Saved identity: type=jdbc; config.operation=dynamic. Dynamic SQL is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/jdbc.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: jdbc; select operation dynamic	frontend/src/ActivityEditor.tsx:605 if (n.type === "jdbc")
JDBC adapter; uses transaction when supplied	backend/app/jdbc.py:277 def execute(
Direct Python implementation; inspect operation dynamic	backend/app/raw_python_support/connectors.py:154 async def jdbc(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Dynamic SQL, select type=jdbc and operation=dynamic, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of dynamic. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Snowflake Insert: source map

Developer guide / Activities / Snowflake

Trace

Saved identity: type=snowflake; config.operation=insert. Snowflake Insert is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/snowflake.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: snowflake; select operation insert	frontend/src/ActivityEditor.tsx:638 if (n.type === "snowflake")
Snowflake operation adapter	backend/app/snowflake.py:231 def execute(
Direct Python implementation; inspect operation insert	backend/app/raw_python_support/connectors.py:159 async def snowflake(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: snowflake	backend/tests/test_snowflake.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Snowflake Insert, select type=snowflake and operation=insert, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of insert. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_snowflake tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Snowflake Query: source map

Developer guide / Activities / Snowflake

Trace

Saved identity: type=snowflake; config.operation=query. Snowflake Query is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/snowflake.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: snowflake; select operation query	frontend/src/ActivityEditor.tsx:638 if (n.type === "snowflake")
Snowflake operation adapter	backend/app/snowflake.py:231 def execute(
Direct Python implementation; inspect operation query	backend/app/raw_python_support/connectors.py:159 async def snowflake(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: snowflake	backend/tests/test_snowflake.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Snowflake Query, select type=snowflake and operation=query, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of query. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_snowflake tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Snowflake Update: source map

Developer guide / Activities / Snowflake

Trace

Saved identity: type=snowflake; config.operation=update. Snowflake Update is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/snowflake.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: snowflake; select operation update	frontend/src/ActivityEditor.tsx:638 if (n.type === "snowflake")
Snowflake operation adapter	backend/app/snowflake.py:231 def execute(
Direct Python implementation; inspect operation update	backend/app/raw_python_support/connectors.py:159 async def snowflake(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: snowflake	backend/tests/test_snowflake.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Snowflake Update, select type=snowflake and operation=update, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of update. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_snowflake tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Snowflake Delete: source map

Developer guide / Activities / Snowflake

Trace

Saved identity: type=snowflake; config.operation=delete. Snowflake Delete is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/snowflake.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: snowflake; select operation delete	frontend/src/ActivityEditor.tsx:638 if (n.type === "snowflake")
Snowflake operation adapter	backend/app/snowflake.py:231 def execute(
Direct Python implementation; inspect operation delete	backend/app/raw_python_support/connectors.py:159 async def snowflake(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: snowflake	backend/tests/test_snowflake.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Snowflake Delete, select type=snowflake and operation=delete, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of delete. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_snowflake tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Snowflake Bulk Load: source map

Developer guide / Activities / Snowflake

Trace

Saved identity: type=snowflake; config.operation=bulk_load. Snowflake Bulk Load is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/snowflake.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: snowflake; select operation bulk_load	frontend/src/ActivityEditor.tsx:638 if (n.type === "snowflake")
Snowflake operation adapter	backend/app/snowflake.py:231 def execute(
Direct Python implementation; inspect operation bulk_load	backend/app/raw_python_support/connectors.py:159 async def snowflake(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: snowflake	backend/tests/test_snowflake.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Snowflake Bulk Load, select type=snowflake and operation=bulk_load, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of bulk_load. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_snowflake tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

AMQP Receive Message: source map

Developer guide / Activities / AMQP

Trace

Saved identity: type=amqp; config.operation=receive. AMQP Receive Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/amqp.py :: def send(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: amqp; select operation receive	frontend/src/ActivityEditor.tsx:629 if (n.type === "amqp")
AMQP send adapter; get handles receives	backend/app/amqp.py:135 def send(
Direct Python implementation; inspect operation receive	backend/app/raw_python_support/connectors.py:164 async def amqp(
Receive adapter and acknowledgement callback	backend/app/amqp.py:182 def get(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing AMQP Receive Message, select type=amqp and operation=receive, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of receive. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

AMQP Get Message: source map

Developer guide / Activities / AMQP

Trace

Saved identity: type=amqp; config.operation=get. AMQP Get Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/amqp.py :: def send(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: amqp; select operation get	frontend/src/ActivityEditor.tsx:629 if (n.type === "amqp")
AMQP send adapter; get handles receives	backend/app/amqp.py:135 def send(
Direct Python implementation; inspect operation get	backend/app/raw_python_support/connectors.py:164 async def amqp(
Receive adapter and acknowledgement callback	backend/app/amqp.py:182 def get(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing AMQP Get Message, select type=amqp and operation=get, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

AMQP Send Message: source map

Developer guide / Activities / AMQP

Trace

Saved identity: type=amqp; config.operation=send. AMQP Send Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/amqp.py :: def send(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: amqp; select operation send	frontend/src/ActivityEditor.tsx:629 if (n.type === "amqp")
AMQP send adapter; get handles receives	backend/app/amqp.py:135 def send(
Direct Python implementation; inspect operation send	backend/app/raw_python_support/connectors.py:164 async def amqp(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing AMQP Send Message, select type=amqp and operation=send, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of send. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

AMQP Dead Letter Message: source map

Developer guide / Activities / AMQP

Trace

Saved identity: type=amqp; config.operation=dead_letter. AMQP Dead Letter Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/amqp.py :: def send(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: amqp; select operation dead_letter	frontend/src/ActivityEditor.tsx:629 if (n.type === "amqp")
AMQP send adapter; get handles receives	backend/app/amqp.py:135 def send(
Direct Python implementation; inspect operation dead_letter	backend/app/raw_python_support/connectors.py:164 async def amqp(
Receive adapter and acknowledgement callback	backend/app/amqp.py:182 def get(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing AMQP Dead Letter Message, select type=amqp and operation=dead_letter, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of dead_letter. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment.

Do not patch only an already-generated archive.

Parse XML: source map

Developer guide / Activities / Data

Trace

Saved identity: type=xml; config.operation=parse. Parse XML is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def parse_xml_activity(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
XML parse; render_xml_activity handles render	backend/app/runtime.py:1840 def parse_xml_activity(
Direct Python implementation; inspect operation parse	backend/app/raw_python_support/activities.py:134 def data_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Parse XML, select type=xml and operation=parse, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of parse. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Render XML: source map

Developer guide / Activities / Data

Trace

Saved identity: type=xml; config.operation=render. Render XML is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def parse_xml_activity(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
XML parse; render_xml_activity handles render	backend/app/runtime.py:1840 def parse_xml_activity(
Direct Python implementation; inspect operation render	backend/app/raw_python_support/activities.py:134 def data_activity(
XML render implementation	backend/app/runtime.py:1856 def render_xml_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Render XML, select type=xml and operation=render, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of render. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Parse JSON: source map

Developer guide / Activities / Data

Trace

Saved identity: type=json; config.operation=parse. Parse JSON is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def json_activity(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JSON parse/render and validation	backend/app/runtime.py:1928 def json_activity(
Direct Python implementation; inspect operation parse	backend/app/raw_python_support/activities.py:134 def data_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Parse JSON, select type=json and operation=parse, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of parse. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Render JSON: source map

Developer guide / Activities / Data

Trace

Saved identity: type=json; config.operation=render. Render JSON is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def json_activity(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
JSON parse/render and validation	backend/app/runtime.py:1928 def json_activity(
Direct Python implementation; inspect operation render	backend/app/raw_python_support/activities.py:134 def data_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Render JSON, select type=json and operation=render, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of render. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Parse Data: source map

Developer guide / Activities / Data

Trace

Saved identity: type=flat; config.operation=parse. Parse Data is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def flat_data(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Flat record parse/render	backend/app/runtime.py:1968 def flat_data(
Direct Python implementation; inspect operation parse	backend/app/raw_python_support/activities.py:134 def data_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Parse Data, select type=flat and operation=parse, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of parse. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Render Data: source map

Developer guide / Activities / Data

Trace

Saved identity: type=flat; config.operation=render. Render Data is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def flat_data(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Flat record parse/render	backend/app/runtime.py:1968 def flat_data(
Direct Python implementation; inspect operation render	backend/app/raw_python_support/activities.py:134 def data_activity(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: activity_packs	backend/tests/test_activity_packs.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Render Data, select type=flat and operation=render, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of render. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_activity_packs tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Read Excel Workbook: source map

Developer guide / Activities / Data

Trace

Saved identity: type=excel; config.operation=read. Read Excel Workbook is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: def read_excel(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: excel; select operation read	frontend/src/ActivityEditor.tsx:680 if (n.type === "excel")
Workbook reading	backend/app/runtime.py:1687 def read_excel(
Direct Python implementation; inspect operation read	backend/app/raw_python_support/activities.py:185 def excel_read(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: amqp_jdbc_excel_command	backend/tests/test_amqp_jdbc_excel_command.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Read Excel Workbook, select type=excel and operation=read, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of read. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_amqp_jdbc_excel_command tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Mapper: source map

Developer guide / Activities / General

Trace

Saved identity: type=mapper; config.operation=map. Mapper is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/mapper.py :: def execute(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Schema mapping engine	backend/app/mapper.py:410 def execute(
Direct Python implementation; inspect operation map	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Mapper, select type=mapper and operation=map, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of map. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Transform: source map

Developer guide / Activities / General

Trace

Saved identity: type=dataweave; config.operation=transform. Transform is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/dataweave.py :: def execute_details(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: dataweave; select operation transform	frontend/src/ActivityEditor.tsx:1084 if (n.type === "dataweave")
Transformation script parser and evaluator	backend/app/dataweave.py:346 def execute_details(
Direct Python implementation; inspect operation transform	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Transform, select type=dataweave and operation=transform, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of transform. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Log: source map

Developer guide / Activities / General

Trace

Saved identity: type=log; config.operation=write. Log is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (log)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: log; select operation write	frontend/src/ActivityEditor.tsx:1095 if (n.type === "log")
Engine log dispatch; operation write	backend/app/runtime.py:816 if activity.type == 'log':
Direct helper dispatch for log; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Log, select type=log and operation=write, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of write. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Catch Exception: source map

Developer guide / Activities / General

Trace

Saved identity: type=catch; config.operation=catch. Catch Exception is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (catch)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: catch; select operation catch	frontend/src/ActivityEditor.tsx:282 if (n.type === "catch")
Engine catch dispatch; operation catch	backend/app/runtime.py:798 if activity.type == 'catch':
Direct helper dispatch for catch; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Catch Exception, select type=catch and operation=catch, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of catch. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Throw Exception: source map

Developer guide / Activities / General

Trace

Saved identity: type=throw; config.operation=throw. Throw Exception is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (throw)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: throw; select operation throw	frontend/src/ActivityEditor.tsx:289 if (n.type === "throw")
Engine throw dispatch; operation throw	backend/app/runtime.py:799 if activity.type == 'throw':
Direct helper dispatch for throw; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Throw Exception, select type=throw and operation=throw, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of throw. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Rethrow Exception: source map

Developer guide / Activities / General

Trace

Saved identity: type=rethrow; config.operation=rethrow. Rethrow Exception is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (rethrow)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: rethrow; select operation rethrow	frontend/src/ActivityEditor.tsx:296 if (n.type === "rethrow")
Engine rethrow dispatch; operation rethrow	backend/app/runtime.py:807 if activity.type == 'rethrow':
Direct helper dispatch for rethrow; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Rethrow Exception, select type=rethrow and operation=rethrow, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of rethrow. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Confirm Message: source map

Developer guide / Activities / General

Trace

Saved identity: type=confirm; config.operation=acknowledge. Confirm Message is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (confirm)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: confirm; select operation acknowledge	frontend/src/ActivityEditor.tsx:268 if (n.type === "confirm")
Engine confirm dispatch; operation acknowledge	backend/app/runtime.py:849 if activity.type == 'confirm':
Direct helper dispatch for confirm; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Confirm Message, select type=confirm and operation=acknowledge, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of acknowledge. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_tasks_runtime tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Java Activity: source map

Developer guide / Activities / General

Trace

Saved identity: type=java; config.operation=invoke. Java Activity is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def java_worker(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: java; select operation invoke	frontend/src/ActivityEditor.tsx:1117 if (n.type === "java")
Java invocation worker	backend/app/runtime.py:2073 async def java_worker(
Direct Python implementation; inspect operation invoke	backend/app/raw_python_support/activities.py:323 async def java_invoke(
Python/native worker lifecycle	backend/app/java_bridge.py:1 (module)
Native Java connector implementation	java-bridge/src/com/mina/bridge/MinaJavaBridge.java:1 (module)
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Java Activity, select type=java and operation=invoke, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of invoke. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes `raw_python_support`; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Python Invoke: source map

Developer guide / Activities / General

Trace

Saved identity: type=python; config.operation=invoke. Python Invoke is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: async def python_worker(
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: python; select operation invoke	frontend/src/ActivityEditor.tsx:1145 if (n.type === "python")
Python invocation worker	backend/app/runtime.py:2128 async def python_worker(
Direct Python implementation; inspect operation invoke	backend/app/raw_python_support/activities.py:299 async def python_invoke(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Python Invoke, select type=python and operation=invoke, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of invoke. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

External Command: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=external_command. External Command is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation external_command	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation external_command	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing External Command, select type=basic and operation=external_command, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of external_command. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Assign: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=assign. Assign is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation assign	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation assign	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Assign, select type=basic and operation=assign, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of assign. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Checkpoint: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=checkpoint. Checkpoint is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation checkpoint	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation checkpoint	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Checkpoint, select type=basic and operation=checkpoint, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of checkpoint. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Sleep: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=sleep. Sleep is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / Debugger
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation sleep	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation sleep	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Sleep, select type=basic and operation=sleep, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of sleep. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Get Shared Variable: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=get_shared_variable. Get Shared Variable is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation get_shared_variable	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation get_shared_variable	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Get Shared Variable, select type=basic and operation=get_shared_variable, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of get_shared_variable. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Set Shared Variable: source map

Developer guide / Activities / General

Trace

Saved identity: type=basic; config.operation=set_shared_variable. Set Shared Variable is a palette definition rendered by shared React components, not necessarily its own frontend file or Python module.

```
main.tsx packs -> addActivity -> ActivityEditor
Project.tasks[].activities[] -> Run API / DebugManager
WorkflowRuntime.execute_with_policy -> execute
backend/app/runtime.py :: execute (basic)
record_activity_output -> downstream mappings / Job Data
```

For event starters the API/listener loop supplies event_output before the graph continues; a manual single-activity test is not equivalent to the continuous listener lifecycle.

Source locations

Responsibility	Source location / search anchor
Palette labels, types, operations and icons	frontend/src/main.tsx:333 const packs:
Create a canvas activity and its initial config	frontend/src/main.tsx:1771 const addActivity =
Configuration/Input/Output/Errors contract	frontend/src/ActivityEditor.tsx:191 export function activityContract(
Project-specific schema resolution	frontend/src/ActivityEditor.tsx:1197 function resolvedActivityContract(
Configuration keys exposed for mapping	frontend/src/ActivityEditor.tsx:1273 function runtimeMappableInputs(
Shared configuration field renderer	frontend/src/ActivityEditor.tsx:1721 function FieldEditor(
Input mappings editor	frontend/src/ActivityEditor.tsx:2115 function InputEditor(
Output schema editor	frontend/src/ActivityEditor.tsx:2238 function OutputEditor(
Advanced logging/retry UI	frontend/src/ActivityEditor.tsx:2290 function AdvancedEditor(
Error handling UI	frontend/src/ActivityEditor.tsx:2446 function ErrorEditor(
Persisted activity model	backend/app/models.py:17 class Activity(
Run HTTP API	backend/app/main.py:616 @app.post('/api/projects/{project_id}/run')
Graph scheduler	backend/app/runtime.py:355 async def run(self,
Retry/logging policy wrapper	backend/app/runtime.py:601 async def execute_with_policy(
Resolve configuration and input mappings	backend/app/runtime.py:670 def resolve_activity_config(

Responsibility	Source location / search anchor
Activity dispatch	backend/app/runtime.py:694 async def execute(self,
Publish outputs and captured inputs	backend/app/runtime.py:550 def record_activity_output(
Debug stepping over the runtime	backend/app/debugger.py:274 async def step(
Contract branch: basic; select operation set_shared_variable	frontend/src/ActivityEditor.tsx:1156 if (n.type === "basic")
Engine basic dispatch; operation set_shared_variable	backend/app/runtime.py:732 if activity.type == 'basic':
Direct helper dispatch for basic; task graph may also be generated inline	backend/app/raw_python_support/core.py:200 async def execute(
Direct graph/code generation	backend/app/raw_python.py:576 def raw_python_files(
Export capability selection	backend/app/raw_python.py:60 def _activity_capabilities(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

What to change

When changing Set Shared Variable, select type=basic and operation=set_shared_variable, not merely the displayed label. The shared dispatcher may serve several activities. Add/adjust editor fields, resolved input values and returned output keys together; preserve behavior of the other operations sharing this handler.

Configuration tab: activityContract and FieldEditor. Input tab: runtimeMappableInputs/InputEditor; mappings persist as config.inputMappings and are resolved before execute. Output tab: contract/resolved schema plus actual returned keys. Advanced tab: advancedDefaults/AdvancedEditor and execute_with_policy. Errors tab: declared faults/ErrorEditor plus real exceptions and run/debug propagation. UI declarations do not automatically implement runtime behavior.

For provider operations, inspect the adapter and Java bridge where listed. Moving work to a thread does not automatically make native I/O cancellable. Preserve acknowledgement, session ownership and worker cleanup when changing performance or timeouts.

Tests and exports

Relevant suites are starting points, not a claim of exhaustive coverage of set_shared_variable. Add a regression that executes this exact type/operation with resolved mappings and asserts the returned shape. Exercise empty input, invalid values, provider errors and cancellation as applicable.

```
cd backend
python -m unittest tests.test_mapper_code_general tests.test_raw_python tests.test_engine_export
```

Engine-based export reuses/prunes engine modules. Raw Python export generates task code and specializes raw_python_support; review both paths and capability filtering. Re-export a fixture and execute it in a clean test environment. Do not patch only an already-generated archive.

Tasks, sub-tasks, persistence and copy

Developer guide / Features

Responsibility

Tasks own activity/transition/group graphs. Calls use saved task references; activity IDs also participate in mapping expressions.

```
Task editor -> normalizeProject -> persistProject -> API -> store.save_project
Call Sub Task -> runtime call_task branch -> child run -> caller output
```

Source locations

Responsibility	Source location / search anchor
Loaded-project normalization	frontend/src/main.tsx:1008 const normalizeProject =
Browser save API	frontend/src/main.tsx:2130 const persistProject =
Task cloning	frontend/src/copyTask.ts:2 export function copyTask
Legacy copy reference repair	frontend/src/repairCopiedTask.ts:1 (module)
Python task schema	backend/app/models.py:307 class ProcessDefinition{
Disk persistence	backend/app/store.py:46 def save_project{
Nested execution	backend/app/runtime.py:1116 if activity.type == 'call_task':
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)

Safe change procedure

For a new task setting, change both the frontend Task representation and ProcessDefinition validation/defaults. Preserve IDs during a copy or rewrite references consistently. Test nested calls, failed children, interfaces, old imports and missing referenced tasks. A renamed label must not silently break expressions.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Run, continuous events and Stop

Developer guide / Features

Responsibility

Run coordinates application listeners/jobs while WorkflowRuntime schedules activities and groups.

```
main.tsx run -> POST /projects/{id}/run -> listener registration or runtime.run
Stop -> stop_project -> cancel jobs -> connector cleanup
```

Source locations

Responsibility	Source location / search anchor
Run action	frontend/src/main.tsx:2302 const run = async
Run API	backend/app/main.py:617 async def run(project_id:
Broker/event polling lifecycle	backend/app/main.py:292 async def _continuous_event_loop(
SAP event lifecycle	backend/app/main.py:438 async def _continuous_sap_event_loop(
Stop endpoint	backend/app/main.py:666 async def stop_project(
Graph execution	backend/app/runtime.py:355 async def run(self,
Packaged engine command-line host	backend/run_deployment.py:1 (module)
Regression suite: tasks_runtime	backend/tests/test_tasks_runtime.py:1 (module)
Regression suite: publisher_reuse	backend/tests/test_publisher_reuse.py:1 (module)

Safe change procedure

Distinguish a one-shot run from a long-lived event starter. Preserve transport context and acknowledgement timing when spawning jobs. For Stop, test active I/O, idle listeners and worker cleanup. Do not equate cancelling an asyncio task with undoing an external send.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Debug controls, test bench and Job Data

Developer guide / Features

Responsibility

Debug maintains sessions, frames, breakpoints, watches, captured inputs/outputs and isolated activity tests.

```
DebugRibbon / DebugToolsDialog -> debugAction -> DebugManager.action  
-> step / runtime.execute_with_policy -> DebugManager.view -> Job Data
```

Source locations

Responsibility	Source location / search anchor
Start debug request	frontend/src/main.tsx:2324 debug = async
Debug action transport	frontend/src/main.tsx:2375 debugAction = async
Ribbon controls	frontend/src/main.tsx:5891 function DebugRibbon(
Test bench/tools	frontend/src/main.tsx:5797 function DebugToolsDialog(
Input/output/variables viewer	frontend/src/DebugJobData.tsx:1 (module)
Activity-selection tree	frontend/src/DebugActivityTree.tsx:1 (module)
Nested task traversal	frontend/src/debugTaskTree.ts:1 (module)
Test payload editor	frontend/src/DebugPayloadEditor.tsx:1 (module)
Debug API	backend/app/main.py:1775 async def start_debug(
Debug commands	backend/app/debugger.py:114 async def action(
Frame execution	backend/app/debugger.py:274 async def step(
Session cleanup	backend/app/debugger.py:249 async def stop(
Serializable debug state	backend/app/debugger.py:388 def view(
Resolved input/output capture	backend/app/runtime.py:550 def record_activity_output(
Regression suite: debug_testing	backend/tests/test_debug_testing.py:1 (module)
Regression suite: debug_input_capture	backend/tests/test_debug_input_capture.py:1 (module)

Safe change procedure

For a new debug action update the client request, DebugAction model and DebugManager.action validation together. Capture resolved activity input separately from previous output. Test pause/resume, nested frames, injected data, run-once side effects and stop during I/O. Test bench execution can modify real systems.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Input mapping, schema mapper and suggestions

Developer guide / Features

Responsibility

The generic input editor and the dedicated schema mapper are separate UIs; runtime expression resolution and structural mapping are also distinct layers.

```
DataSourcePane -> MappingBinding / InputEditor -> config.inputMappings  
resolve_activity_config -> map_input_values -> evaluate_mapping / resolve  
Mapper activity -> mapper.execute -> output validation
```

Source locations

Responsibility	Source location / search anchor
Available upstream Data tree	frontend/src/ActivityEditor.tsx:1870 export function upstreamActivitySources(
Data/functions/properties browser	frontend/src/ActivityEditor.tsx:1918 export function DataSourcePane(
Target field control	frontend/src/ActivityEditor.tsx:1995 function MappingBinding(
Expanded mapping popup	frontend/src/ActivityEditor.tsx:2100 function ExpandedInputMappingDialog(
Dedicated schema mapper	frontend/src/MapperStudio.tsx:77 export default function MapperStudio
Completion UI/keyboard behavior	frontend/src/MappingExpressionInput.tsx:1 (module)
Suggestion matching	frontend/src/mappingCompletion.ts:1 export function mappingPathSuggestions
Input mapping evaluation	backend/app/runtime.py:1468 def map_input_values(
Structured rule evaluation	backend/app/runtime.py:1475 def evaluate_mapping(
Reference/expression resolution	backend/app/runtime.py:1549 def resolve(self,
Transformation mapping	backend/app/mapper.py:410 def execute(
Map & Test endpoint	backend/app/main.py:1650 def mapper_test(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: sap_idoc_arrays	backend/tests/test_sap_idoc_arrays.py:1 (module)

Safe change procedure

For a new expression syntax update completion/parser/runtime together. Preserve structured mapping rules and array cardinality; never turn expression strings into unrestricted eval. Compare Map & Test with Run, Debug and direct-export behavior using the same fixture.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Built-in and project functions

Developer guide / Features

Responsibility

The function catalog controls discoverability; Python evaluation controls results. A catalog entry alone is not executable functionality.

```
mapper-functions.ts template -> expression mapping -> evaluate_function_expression
-> mapper.apply_function / project custom-function expression
```

Source locations

Responsibility	Source location / search anchor
All builtin catalog entries	frontend/src/mapper-functions.ts:1 (module)
Function picker and custom function editing	frontend/src/ActivityEditor.tsx:1918 export function DataSourcePane(
Builtin implementation dispatch	backend/app/mapper.py:195 def apply_function(
Function expression evaluation	backend/app/runtime.py:1528 def evaluate_function_expression(
Persisted custom functions	backend/app/models.py:365 class Project(
Export function usage	backend/app/raw_python.py:576 def raw_python_files(
Regression suite: mapper_code_general	backend/tests/test_mapper_code_general.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Safe change procedure

Add the editor signature, description and insertion template; implement its Python semantics and input validation; update export dependencies if necessary. Test nulls, coercion, arrays, timezone/encoding and invalid arity. Maintain matching semantics in direct archives.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Canvas and mapper drag-and-drop

Developer guide / Features

Responsibility

Palette creation, moving canvas nodes, connecting transitions and mapping data are different gestures and data-transfer contracts.

```
Palette onDragStart -> canvas onDrop -> addActivity -> task.activities
Node pointer drag -> coordinates / selection -> saved position
DataSourcePane drag -> MappingBinding drop -> inputMappings
```

Source locations

Responsibility	Source location / search anchor
Palette drag source	frontend/src/main.tsx:3023 onDragStart={e} =>
Canvas drop target	frontend/src/main.tsx:3082 onDrop={e} =>
Activity creation	frontend/src/main.tsx:1771 const addActivity =
Editable-control shortcut guard	frontend/src/main.tsx:91 function editableControlFromEvent(
Transition geometry	frontend/src/main.tsx:171 function activityWireGeometry(
Picker insertion	frontend/src/ActivityPicker.tsx:15 export default function ActivityPicker
Mapping drag sources	frontend/src/ActivityEditor.tsx:1918 export function DataSourcePane(
Mapping drop targets	frontend/src/ActivityEditor.tsx:1995 function MappingBinding(
Group condition drop target	frontend/src/main.tsx:3651 function GroupExpressionTarget(
Selection visuals	frontend/src/canvas-selection.css:1 (module)

Safe change procedure

Do not change only the drop handler. Check source MIME/data payload, zoom/scroll coordinate conversion, event propagation, nested-group coordinates and undo/persistence. Preserve keyboard input by excluding editable controls from global shortcuts. Verify drag/drop in browser and packaged desktop, plus mapping into the expanded popup.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Groups: editor, graph boundaries and runtime state

Developer guide / Features

Responsibility

A group includes visual membership plus scheduling, iteration variables, failure handling and resource lifecycle.

```
GroupEditor -> GroupDefinition -> compile_groups
enter_group_boundaries -> _begin_group -> activities
leave_group_boundaries / retry_failed_group -> _finish_group
```

Source locations

Responsibility	Source location / search anchor
Create group	frontend/src/main.tsx:1946 const addGroup =
Editor defaults	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group configuration	frontend/src/main.tsx:3671 function GroupEditor(
Group rendering	frontend/src/groups.css:1 (module)
Saved group schema	backend/app/models.py:24 class GroupDefinition(
Group graph plans	backend/app/runtime.py:142 def compile_groups(
Enter resources/conditions/iteration	backend/app/runtime.py:214 async def _begin_group(
Commit/rollback/release	backend/app/runtime.py:278 async def _finish_group(
Iteration and nested exit	backend/app/runtime.py:304 async def leave_group_boundaries(
Retry scope	backend/app/runtime.py:334 async def retry_failed_group(
Native transaction session	backend/app/jdbc.py:270 class JavaJdbcTransaction
Direct-export group planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Safe change procedure

Keep editor defaults, parent_group_id/member_activity_ids validation and runtime plans aligned. Test nested entry/exit, skip branches, retries, cancellation and restoration of loop variables. Transaction groups must close the exact owned connection on every exit. Critical sections are runtime-local, not distributed locks.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

If: source map

Developer guide / Groups

Behavior to preserve

Evaluates condition before entry; false skips the group.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
If defaults; match group type if	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

While True: source map

Developer guide / Groups

Behavior to preserve

Evaluates condition before each iteration, including the first.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
While True defaults; match group type while	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

For Each: source map

Developer guide / Groups

Behavior to preserve

Resolves the collection at entry and runs once per item. Range mode uses inclusive start/end with a nonzero increment.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
For Each defaults; match group type for-each	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Iterate: source map

Developer guide / Groups

Behavior to preserve

Resolves source once at entry and iterates its elements.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Iterate defaults; match group type iterate	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Repeat Until True: source map

Developer guide / Groups

Behavior to preserve

Runs once, checks condition at exit and repeats until true.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Repeat Until True defaults; match group type repeat	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Repeat on Error Until True: source map

Developer guide / Groups

Behavior to preserve

Retries the whole group after an unhandled fault while stopCondition is false. A true stop condition or exhausted retry count propagates the fault.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use parent_group_id for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Repeat on Error Until True defaults; match group type repeat-on-error	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Scope: source map

Developer guide / Groups

Behavior to preserve

Runs the enclosed graph once. Nested groups retain their own semantics.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Scope defaults; match group type scope	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

None: source map

Developer guide / Groups

Behavior to preserve

Runs the enclosed graph once; this is an execution boundary, not a separate transaction.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
None defaults; match group type none	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Critical Section: source map

Developer guide / Groups

Behavior to preserve

Holds a runtime-local named lock until completion, failure or cancellation. This is not a distributed lock across machines or separate runtime processes.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Critical Section defaults; match group type critical-section	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

JDBC Transaction: source map

Developer guide / Groups

Behavior to preserve

Uses one database connection for matching JDBC operations, commits on successful exit and rolls back on an escaping fault or cancellation. External non-JDBC side effects are not rolled back.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
JDBC Transaction defaults; match group type transaction-jdbc	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Pick First: source map

Developer guide / Groups

Behavior to preserve

Chooses the first eligible transition in graph order. This is first-match routing, not concurrent event racing or fastest-response selection.

Set Group name, Parent group and direct activity membership. A member has one direct owner; use `parent_group_id` for nesting. Normal groups require a connected single-entry, single-exit graph. Pick First has specialized branch selection.

Use the group type branch in these shared methods. Do not create a UI-only group option; update validation, runtime entry/exit and direct-export scheduling together.

Source locations

Responsibility	Source location / search anchor
Pick First defaults; match group type pick-first	frontend/src/main.tsx:3665 function groupConfigDefaults(
Group-specific condition/iteration controls	frontend/src/main.tsx:3671 function GroupEditor(
Type-specific entry branch	backend/app/runtime.py:214 async def _begin_group(
Type-specific loop/exit branch	backend/app/runtime.py:304 async def leave_group_boundaries(
Error/retry handling	backend/app/runtime.py:334 async def retry_failed_group(
Resource release	backend/app/runtime.py:278 async def _finish_group(
Export nesting/graph planning	backend/app/raw_python.py:370 def _simple_group_plans(
Regression suite: groups_runtime	backend/tests/test_groups_runtime.py:1 (module)
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)

Regression focus

Test zero/one/multiple iterations or selected branches as applicable; nested groups; an activity fault; cancellation; and a saved/archive round trip. Verify variables, locks and sessions are restored or released at scope exit.

Engine archives versus direct Python generation

Developer guide / Features

Responsibility

The two archive forms have different code-generation and packaging responsibilities.

```
PackageDialog -> package_project -> build_deployment_archive
engine_python_files -> pruned engine modules
raw_python_files -> task Python + specialized support modules
```

Source locations

Responsibility	Source location / search anchor
Packaging UI	frontend/src/main.tsx:3747 function PackageDialog(
Archive orchestration	backend/app/main.py:1252 def build_deployment_archive(
Capability registry	backend/app/raw_python.py:60 def _activity_capabilities(
Direct application generation	backend/app/raw_python.py:576 def raw_python_files(
Engine archive generation	backend/app/raw_python.py:1151 def engine_python_files(
Engine module pruning	backend/app/raw_python.py:1097 def _engine_module_files(
Direct support dispatch	backend/app/raw_python_support/core.py:200 async def execute(
Direct application lifecycle	backend/app/raw_python_support/main.py:24 async def run_application(
Regression suite: raw_python	backend/tests/test_raw_python.py:1 (module)
Regression suite: engine_export	backend/tests/test_engine_export.py:1 (module)

Safe change procedure

Changing runtime.py alone is insufficient when direct archives use raw_python_support. Update capability roots and generated import closure without adding unrelated helpers to every project. Validate a minimal one-activity archive, a mixed project, nested groups and a clean-environment execution. Keep vendor files and secrets out of generic archives.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Logs, faults and observable execution data

Developer guide / Features

Responsibility

Log activity output, activity-policy payload logs and persistent project log files are separate responsibilities.

```
execute_with_policy / Log activity -> runtime.log -> project_logging
API runtime-state / logs -> Studio panels
```

Source locations

Responsibility	Source location / search anchor
Runtime event emission	backend/app/runtime.py:570 def log(self,
Log activity body	backend/app/runtime.py:816 if activity.type == 'log':
Fault envelope	backend/app/runtime.py:566 def fault_payload(
Persistent log files/rotation	backend/app/project_logging.py:1 (module)
Logs API	backend/app/main.py:589 def project_logs(
Regression suite: project_logging	backend/tests/test_project_logging.py:1 (module)
Regression suite: debug_input_capture	backend/tests/test_debug_input_capture.py:1 (module)

Safe change procedure

Keep secrets and large payloads out of logs by default. Preserve timestamps, activity identity, error codes, environment path selection and rolling-file behavior. Test write permissions and failure logging as well as successful execution.

Add tests at the affected boundary, not only the UI. Regenerate this source guide after edits: anchors are checked during docs:build and participating source changes invalidate docs:check.

Every built-in function: implementation index

Developer guide / Functions

Where to edit

Every catalog function is listed below. Most built-ins share `apply_function` rather than having one Python function per name. Search the quoted function name or its aliases inside `apply_function`; changing the catalog does not add execution support. Runtime expression parsing and custom functions also pass through `evaluate_function_expression`.

Responsibility	Source location / search anchor
Implementation/aliases	backend/app/mapper.py:195 <code>def apply_function(</code>
Expression call parsing	backend/app/runtime.py:1528 <code>def evaluate_function_expression(</code>
Signatures/templates	frontend/src/mapper-functions.ts:1 (module)

Catalog index

Function / signature	Frontend definition / backend entry
<code>concat</code> <code>concat(value, ...values)</code>	frontend/src/mapper-functions.ts:13 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>concat</code>
<code>trim</code> <code>trim(value)</code>	frontend/src/mapper-functions.ts:14 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>trim</code>
<code>normalizeSpace</code> <code>normalizeSpace(value)</code>	frontend/src/mapper-functions.ts:15 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>normalizeSpace</code>
<code>upperCase</code> <code>upperCase(value)</code>	frontend/src/mapper-functions.ts:16 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>upperCase</code>
<code>lowerCase</code> <code>lowerCase(value)</code>	frontend/src/mapper-functions.ts:17 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>lowerCase</code>
<code>capitalize</code> <code>capitalize(value)</code>	frontend/src/mapper-functions.ts:18 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>capitalize</code>
<code>stringLength</code> <code>stringLength(value)</code>	frontend/src/mapper-functions.ts:19 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>stringLength</code>
<code>substring</code> <code>substring(value, start, length?)</code>	frontend/src/mapper-functions.ts:20 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>substring</code>
<code>substringBefore</code> <code>substringBefore(value, token)</code>	frontend/src/mapper-functions.ts:21 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>substringBefore</code>
<code>substringAfter</code> <code>substringAfter(value, token)</code>	frontend/src/mapper-functions.ts:22 backend/app/mapper.py :: <code>apply_function</code> Search literal/alias: <code>substringAfter</code>

Function / signature	Frontend definition / backend entry
replace replace(value, pattern, replacement)	frontend/src/mapper-functions.ts:23 backend/app/mapper.py :: apply_function Search literal/alias: replace
matches matches(value, pattern)	frontend/src/mapper-functions.ts:24 backend/app/mapper.py :: apply_function Search literal/alias: matches
startsWith startsWith(value, prefix)	frontend/src/mapper-functions.ts:25 backend/app/mapper.py :: apply_function Search literal/alias: startsWith
endsWith endsWith(value, suffix)	frontend/src/mapper-functions.ts:26 backend/app/mapper.py :: apply_function Search literal/alias: endsWith
contains contains(value, token)	frontend/src/mapper-functions.ts:27 backend/app/mapper.py :: apply_function Search literal/alias: contains
compare compare(value, other)	frontend/src/mapper-functions.ts:28 backend/app/mapper.py :: apply_function Search literal/alias: compare
translate translate(value, from, to)	frontend/src/mapper-functions.ts:29 backend/app/mapper.py :: apply_function Search literal/alias: translate
padLeft padLeft(value, width, fill?)	frontend/src/mapper-functions.ts:30 backend/app/mapper.py :: apply_function Search literal/alias: padLeft
padRight padRight(value, width, fill?)	frontend/src/mapper-functions.ts:31 backend/app/mapper.py :: apply_function Search literal/alias: padRight
tokenize tokenize(value, pattern)	frontend/src/mapper-functions.ts:32 backend/app/mapper.py :: apply_function Search literal/alias: tokenize
currentDate currentDate()	frontend/src/mapper-functions.ts:34 backend/app/mapper.py :: apply_function Search literal/alias: currentDate
currentTime currentTime()	frontend/src/mapper-functions.ts:35 backend/app/mapper.py :: apply_function Search literal/alias: currentTime
currentDateTime currentDateTime()	frontend/src/mapper-functions.ts:36 backend/app/mapper.py :: apply_function Search literal/alias: currentDateTime
parseDate parseDate(value)	frontend/src/mapper-functions.ts:37 backend/app/mapper.py :: apply_function Search literal/alias: parseDate
formatDate formatDate(value, pattern)	frontend/src/mapper-functions.ts:38 backend/app/mapper.py :: apply_function Search literal/alias: formatDate
formatDateTime formatDateTime(value, pattern)	frontend/src/mapper-functions.ts:39 backend/app/mapper.py :: apply_function Search literal/alias: formatDateTime

Function / signature	Frontend definition / backend entry
addDays addDays(value, days)	frontend/src/mapper-functions.ts:40 backend/app/mapper.py :: apply_function Search literal/alias: addDays
addMonths addMonths(value, months)	frontend/src/mapper-functions.ts:41 backend/app/mapper.py :: apply_function Search literal/alias: addMonths
addHours addHours(value, hours)	frontend/src/mapper-functions.ts:42 backend/app/mapper.py :: apply_function Search literal/alias: addHours
addMinutes addMinutes(value, minutes)	frontend/src/mapper-functions.ts:43 backend/app/mapper.py :: apply_function Search literal/alias: addMinutes
addSeconds addSeconds(value, seconds)	frontend/src/mapper-functions.ts:44 backend/app/mapper.py :: apply_function Search literal/alias: addSeconds
dateDifference dateDifference(from, to)	frontend/src/mapper-functions.ts:45 backend/app/mapper.py :: apply_function Search literal/alias: dateDifference
year year(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: year
month month(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: month
day day(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: day
hour hour(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: hour
minute minute(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: minute
second second(value)	frontend/src/mapper-functions.ts:46 backend/app/mapper.py :: apply_function Search literal/alias: second
timezoneFromDateTime timezoneFromDateTime(value)	frontend/src/mapper-functions.ts:47 backend/app/mapper.py :: apply_function Search literal/alias: timezoneFromDateTime
number number(value)	frontend/src/mapper-functions.ts:49 backend/app/mapper.py :: apply_function Search literal/alias: number
integer integer(value)	frontend/src/mapper-functions.ts:50 backend/app/mapper.py :: apply_function Search literal/alias: integer
round round(value, precision?)	frontend/src/mapper-functions.ts:51 backend/app/mapper.py :: apply_function Search literal/alias: round

Function / signature	Frontend definition / backend entry
roundHalfToEven roundHalfToEven(value, precision?)	frontend/src/mapper-functions.ts:52 backend/app/mapper.py :: apply_function Search literal/alias: roundHalfToEven
floor floor(value)	frontend/src/mapper-functions.ts:53 backend/app/mapper.py :: apply_function Search literal/alias: floor
ceiling ceiling(value)	frontend/src/mapper-functions.ts:54 backend/app/mapper.py :: apply_function Search literal/alias: ceiling
abs abs(value)	frontend/src/mapper-functions.ts:55 backend/app/mapper.py :: apply_function Search literal/alias: abs
sqrt sqrt(value)	frontend/src/mapper-functions.ts:56 backend/app/mapper.py :: apply_function Search literal/alias: sqrt
power power(value, exponent)	frontend/src/mapper-functions.ts:57 backend/app/mapper.py :: apply_function Search literal/alias: power
modulo modulo(value, divisor)	frontend/src/mapper-functions.ts:58 backend/app/mapper.py :: apply_function Search literal/alias: modulo
clamp clamp(value, minimum, maximum)	frontend/src/mapper-functions.ts:59 backend/app/mapper.py :: apply_function Search literal/alias: clamp
min min(values)	frontend/src/mapper-functions.ts:60 backend/app/mapper.py :: apply_function Search literal/alias: min
max max(values)	frontend/src/mapper-functions.ts:60 backend/app/mapper.py :: apply_function Search literal/alias: max
sum sum(values)	frontend/src/mapper-functions.ts:60 backend/app/mapper.py :: apply_function Search literal/alias: sum
average average(values)	frontend/src/mapper-functions.ts:60 backend/app/mapper.py :: apply_function Search literal/alias: average
count count(values)	frontend/src/mapper-functions.ts:60 backend/app/mapper.py :: apply_function Search literal/alias: count
distinctValues distinctValues(values)	frontend/src/mapper-functions.ts:62 backend/app/mapper.py :: apply_function Search literal/alias: distinctValues
sort sort(values, descending?)	frontend/src/mapper-functions.ts:63 backend/app/mapper.py :: apply_function Search literal/alias: sort
reverse reverse(values)	frontend/src/mapper-functions.ts:64 backend/app/mapper.py :: apply_function Search literal/alias: reverse

Function / signature	Frontend definition / backend entry
first first(values)	frontend/src/mapper-functions.ts:65 backend/app/mapper.py :: apply_function Search literal/alias: first
last last(values)	frontend/src/mapper-functions.ts:66 backend/app/mapper.py :: apply_function Search literal/alias: last
indexOf indexOf(values, item)	frontend/src/mapper-functions.ts:67 backend/app/mapper.py :: apply_function Search literal/alias: indexOf
subsequence subsequence(values, start, end?)	frontend/src/mapper-functions.ts:68 backend/app/mapper.py :: apply_function Search literal/alias: subsequence
flatten flatten(values)	frontend/src/mapper-functions.ts:69 backend/app/mapper.py :: apply_function Search literal/alias: flatten
join join(values, separator)	frontend/src/mapper-functions.ts:70 backend/app/mapper.py :: apply_function Search literal/alias: join
split split(value, pattern)	frontend/src/mapper-functions.ts:71 backend/app/mapper.py :: apply_function Search literal/alias: split
deepEqual deepEqual(value, other)	frontend/src/mapper-functions.ts:72 backend/app/mapper.py :: apply_function Search literal/alias: deepEqual
string string(value)	frontend/src/mapper-functions.ts:74 backend/app/mapper.py :: apply_function Search literal/alias: string
boolean boolean(value)	frontend/src/mapper-functions.ts:75 backend/app/mapper.py :: apply_function Search literal/alias: boolean
jsonParse jsonParse(value)	frontend/src/mapper-functions.ts:76 backend/app/mapper.py :: apply_function Search literal/alias: jsonParse
jsonRender jsonRender(value)	frontend/src/mapper-functions.ts:77 backend/app/mapper.py :: apply_function Search literal/alias: jsonRender
render-xml render-xml(value, rootName?, pretty?)	frontend/src/mapper-functions.ts:78 backend/app/mapper.py :: apply_function Search literal/alias: render-xml
coalesce coalesce(value, ...fallbacks)	frontend/src/mapper-functions.ts:80 backend/app/mapper.py :: apply_function Search literal/alias: coalesce
default default(value, fallback)	frontend/src/mapper-functions.ts:81 backend/app/mapper.py :: apply_function Search literal/alias: default
exists exists(value)	frontend/src/mapper-functions.ts:82 backend/app/mapper.py :: apply_function Search literal/alias: exists

Function / signature	Frontend definition / backend entry
empty empty(value)	frontend/src/mapper-functions.ts:83 backend/app/mapper.py :: apply_function Search literal/alias: empty
not not(value)	frontend/src/mapper-functions.ts:84 backend/app/mapper.py :: apply_function Search literal/alias: not
ifThenElse ifThenElse(condition, trueValue, falseValue)	frontend/src/mapper-functions.ts:85 backend/app/mapper.py :: apply_function Search literal/alias: ifThenElse
uuid uuid()	frontend/src/mapper-functions.ts:86 backend/app/mapper.py :: apply_function Search literal/alias: uuid
base64Encode base64Encode(value)	frontend/src/mapper-functions.ts:88 backend/app/mapper.py :: apply_function Search literal/alias: base64Encode
base64Decode base64Decode(value)	frontend/src/mapper-functions.ts:89 backend/app/mapper.py :: apply_function Search literal/alias: base64Decode
hexEncode hexEncode(value)	frontend/src/mapper-functions.ts:90 backend/app/mapper.py :: apply_function Search literal/alias: hexEncode
hexDecode hexDecode(value)	frontend/src/mapper-functions.ts:91 backend/app/mapper.py :: apply_function Search literal/alias: hexDecode
urlEncode urlEncode(value)	frontend/src/mapper-functions.ts:92 backend/app/mapper.py :: apply_function Search literal/alias: urlEncode
urlDecode urlDecode(value)	frontend/src/mapper-functions.ts:93 backend/app/mapper.py :: apply_function Search literal/alias: urlDecode
hash hash(value, algorithm?)	frontend/src/mapper-functions.ts:94 backend/app/mapper.py :: apply_function Search literal/alias: hash