

LAB 3 – NAT & Port Forwarding :

WARNING:
The password for this account is insecure. Password is currently set to the default value (pfsense).
Change the password as soon as possible.

Firewall / NAT / Outbound

The changes have been applied successfully. The firewall rules are now reloading in the background.
Monitor the filter reload progress.

Port Forward 1:1 Outbound NAT

Outbound NAT Mode

Mode

- ☐ Automatic outbound NAT rule generation. (IPsec passthrough included)
- ☒ Hybrid Outbound NAT rule generation. (Automatic Outbound NAT + rules below)
- ☐ Manual Outbound NAT rule generation. (AON - Advanced Outbound NAT)
- ☐ Disable Outbound NAT rule generation. (No Outbound NAT rules)

Save

Mappings

Interface	Source	Source Port	Destination	Destination Port	NAT Address	NAT Port	Static Port	Description	Actions
☒	WANUPLINK	WANUPLINK subnets	*	*	*	WANUPLINK address	*		

Document1 - Word

File Home Insert Design Layout References Mailings Review View Help

Calibri (Body) 11 A A B I U X K Font Paragraph Styles

AutoSave On

Interfaces / WAN (em0)

General Configuration

Enable ☒ Enable interface

Description WAN

IPv4 Configuration Type DHCP

IPv4 Configuration Type DHCP

MAC Address

MTU

Warning: The password for this account is insecure. Password is currently set to the default value (pfsense). Change the password as soon as possible.

Interfaces / LAN (em1)

The LAN configuration has been changed. The changes must be applied to take effect. Don't forget to adjust the DHCP Server range if needed after applying.

General Configuration

Enable ☒ Enable interface

Description LAN

IPv4 Configuration Type Static IPv4

IPv4 Configuration Type DHCP

MAC Address

MTU

Page 1 of 1 6 words English (United States)