

```
login: pfsense
Password:
Login incorrect
login: admin
Password:
VirtualBox Virtual Machine - Netgate Device ID: 1900d9683e847c2a6aa1
```

```
*** Welcome to pfSense 2.8.1-RELEASE (amd64) on pfSense ***
```

```
WAN (wan) -> em0 -> v4/DHCP4: 10.0.2.15/24
                  v6/DHCP6: fd17:625c:f037:2:a00:27ff:fe43:4f08/64
LAN (lan) -> em1 -> v4: 192.168.56.103/24
```

- | | |
|-------------------------------------|----------------------------------|
| 0) Logout / Disconnect SSH | 9) pfTop |
| 1) Assign Interfaces | 10) Filter Logs |
| 2) Set interface(s) IP address | 11) Restart GUI |
| 3) Reset admin account and password | 12) PHP shell + pfSense tools |
| 4) Reset to factory defaults | 13) Update from console |
| 5) Reboot system | 14) Enable Secure Shell (sshd) |
| 6) Halt system | 15) Restore recent configuration |
| 7) Ping host | 16) Restart PHP-FPM |
| 8) Shell | |

```
Enter an option: █
```

```
LANCORE (lan) -> em1 -> v4: 192.168.56.103/24
```

- | | |
|-------------------------------------|----------------------------------|
| 0) Logout / Disconnect SSH | 9) pfTop |
| 1) Assign Interfaces | 10) Filter Logs |
| 2) Set interface(s) IP address | 11) Restart GUI |
| 3) Reset admin account and password | 12) PHP shell + pfSense tools |
| 4) Reset to factory defaults | 13) Update from console |
| 5) Reboot system | 14) Enable Secure Shell (sshd) |
| 6) Halt system | 15) Restore recent configuration |
| 7) Ping host | 16) Restart PHP-FPM |
| 8) Shell | |

```
Enter an option: 5
```

```
pfSense will reboot. This may take a few minutes, depending on your hardware.
Do you want to proceed?
```

```
Y/y: Reboot normally
R/r: Reroot (Stop processes, remount disks, re-run startup sequence)
S: Reboot into Single User Mode (requires console access!)
```

```
Enter an option: y
```

```
pfSense is rebooting now.
```

General Configuration

Enable

☒ Enable interface

Description

LANCore

Enter a description (name) for the interface here.

IPv4 Configuration Type

Static IPv4

IPv6 Configuration Type

None

MAC Address

xxxxxxxxxxxx

This field can be used to modify ("spoof") the MAC address of this interface.
Enter a MAC address in the following format: xx:xx:xx:xx:xx:xx or leave blank.

MTU

If this field is blank, the adapter's default MTU will be used. This is typically 1500 bytes but can vary in some circumstances.

MSS

If a value is entered in this field, then MSS clamping for TCP connections to the value entered above minus 40 for IPv4 (TCP/IPv4 header size) and minus 60 for IPv6 (TCP/IPv6 header size) will be in effect.

Speed and Duplex

Default (no preference, typically autoselect)

Explicitly set speed and duplex mode for this interface.
WARNING: MUST be set to autoselect (automatically negotiate speed) unless the port this interface connects to has its speed and duplex forced.

Static IPv4 Configuration

IPv4 Address

192.168.56.103

/ 24

WARNING:
The password for this account is insecure. Password is currently set to the default value (pfsense).
[Change the password as soon as possible.](#)

Interfaces / LANCore (em1)



The LANCore configuration has been changed.
The changes must be applied to take effect.
Don't forget to adjust the DHCP Server range if needed after applying.

✓ Apply Changes

General Configuration

Enable

☒ Enable interface

Description

LANCore

Enter a description (name) for the interface here.

IPv4 Configuration Type

Static IPv4

```
[2.8.1-RELEASE][root@pfSense.home.arpal/root: ping 192.168.56.103
PING 192.168.56.103 (192.168.56.103): 56 data bytes
64 bytes from 192.168.56.103: icmp_seq=0 ttl=64 time=0.159 ms
64 bytes from 192.168.56.103: icmp_seq=1 ttl=64 time=1.117 ms
64 bytes from 192.168.56.103: icmp_seq=2 ttl=64 time=1.800 ms
64 bytes from 192.168.56.103: icmp_seq=3 ttl=64 time=3.461 ms
64 bytes from 192.168.56.103: icmp_seq=4 ttl=64 time=1.027 ms
64 bytes from 192.168.56.103: icmp_seq=5 ttl=64 time=2.672 ms
64 bytes from 192.168.56.103: icmp_seq=6 ttl=64 time=0.520 ms
^C
--- 192.168.56.103 ping statistics ---
7 packets transmitted, 7 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 0.159/1.537/3.461/1.097 ms
[2.8.1-RELEASE][root@pfSense.home.arpal/root: █
```

General Configuration

Enable ☒ Enable interface

Description LANCore

Enter a description (name) for the interface here.

IPv4 Configuration Type Static IPv4

After setting mtu to 600 a small network change is occurred. Eventhough change occurred no connectivity issues are occurred.

In firewall/rules/lancore I observed changes in states. In firewall rules lancore states are changing. I observed one state before mtu modification and another state after mtu modification.