

STATIC ROUTE USING 3 ROUTERS

1. Ping 40.0.0.10 from 10.0.0.10

The screenshot shows a PNETLab topology with three routers (R1, R2, R3) and two PCs (Win-1, Win-2). The topology is as follows:

```
graph LR
    Win1[Win-1: 10.0.0.10] --- R1
    R1 --- R2
    R2 --- R3
    R3 --- Win2[Win-2: 40.0.0.10]
```

The routers are configured with the following IP addresses:

- R1: 10.0.0.1 (G0/0/0), 20.0.0.1 (G0/0/1)
- R2: 20.0.0.2 (G0/0/0), 30.0.0.1 (G0/0/1)
- R3: 30.0.0.2 (G0/0/0), 40.0.0.1 (G0/0/1)

The terminal output shows the configuration of Win-1 and the successful ping command:

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows [Version 5.1.2600]
(c) Copyright 1986-2000 Microsoft Corp.
C:\Documents and Settings\user>ipconfig
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix . : 
    IP Address. . . . . : 10.0.0.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 10.0.0.1

C:\Documents and Settings\user>ping 40.0.0.10
ping' is not recognized as an internal or external command,
operable program or batch file.

C:\Documents and Settings\user>ping 40.0.0.10
Pinging 40.0.0.10 with 32 bytes of data:
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```

2. Ping 10.0.0.10 from 40.0.0.10

The screenshot shows the same PNETLab topology as in the first screenshot. The terminal output shows the configuration of Win-2 and the successful ping command:

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows [Version 5.1.2600]
(c) Copyright 1986-2000 Microsoft Corp.
C:\Documents and Settings\user>ipconfig
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix . : 
    IP Address. . . . . : 40.0.0.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 40.0.0.1

C:\Documents and Settings\user>ping 10.0.0.10
Pinging 10.0.0.10 with 32 bytes of data:
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```