

acorn example in Rstudio

Tychele N. Turner, Ph.D., Washington University School of Medicine

2023-01-18

Abstract

This document contains documentation for using acorn.

call up acorn

```
library('acorn')
```

check out acorn functions

```
lsf.str("package:acorn")
```

```
## annotateCpG : function (DNVobject = NULL, CpGannot = NULL)
## calculateDeletionInsertionratio : function (DNVobject = NULL)
## calculateDeletionLengths : function (DNVobject = NULL)
## calculateInsertionLengths : function (DNVobject = NULL)
## calculateMNVLengths : function (DNVobject = NULL)
## calculateTiTvratio : function (DNVobject = NULL)
## countsPerIndividual : function (DNVobject = NULL)
## extractAutosomes : function (DNVobject = NULL)
## extractINDELs : function (DNVobject = NULL)
## extractIndividual : function (DNVobject = NULL, individual = NULL)
## extractMNVs : function (DNVobject = NULL)
## extractSNVs : function (DNVobject = NULL)
## extractX : function (DNVobject = NULL)
## extractY : function (DNVobject = NULL)
## fatherAge : function (parentalAgeObject = NULL)
## hello : function ()
## motherAge : function (parentalAgeObject = NULL)
## parentalAge : function (parentalAgeObject = NULL)
## parentalAgeObject : function (counts = NULL, parentalData = NULL)
## readDNV : function (DNVfile = NULL)
```

load in test data

```
input <- readDNV("~/Documents/Github/acorn/inst/extdata/dnms_from_Ng_et_al_2022_Human
_Mutation_paper.txt.gz")
head(input)
```

```
##      SAMPLE CHROM POS_B38 REFERENCE      ALTERNATE
## 1 HG01928  chr1  913941          G                T
## 2 HG03915  chr1  917676          C                A
## 3 HG03915  chr1  918783          G                C
## 4 HG00450  chr1 1216505          A                G
## 5 HG02257  chr1 1217502          G                A
## 6 HG00465  chr1 1366883          G GGTGTGAATTGGTGTAGTGTGAATGAGT
##                                     ID
## 1                                     chr1_913941_G_T
## 2                                     chr1_917676_C_A
## 3                                     chr1_918783_G_C
## 4                                     chr1_1216505_A_G
## 5                                     chr1_1217502_G_A
## 6 chr1_1366883_G_GGTGTGAATTGGTGTAGTGTGAATGAGT
```

```
str(input)
```

```
## 'data.frame':    9741 obs. of  6 variables:
## $ SAMPLE      : chr  "HG01928" "HG03915" "HG03915" "HG00450" ...
## $ CHROM       : chr  "chr1" "chr1" "chr1" "chr1" ...
## $ POS_B38     : int  913941 917676 918783 1216505 1217502 1366883 1765426 2332062 26
45102 3355666 ...
## $ REFERENCE   : chr  "G" "C" "G" "A" ...
## $ ALTERNATE   : chr  "T" "A" "C" "G" ...
## $ ID          : chr  "chr1_913941_G_T" "chr1_917676_C_A" "chr1_918783_G_C" "chr1_121
6505_A_G" ...
```

extract individual

```
ind <- extractIndividual(input, "HG01928")
head(ind)
```

```
##      SAMPLE CHROM  POS_B38 REFERENCE ALTERNATE      ID
## 1  HG01928  chr1    913941          G          T  chr1_913941_G_T
## 12 HG01928  chr1   3393842          G          A  chr1_3393842_G_A
## 166 HG01928  chr1  44230922          C          T  chr1_44230922_C_T
## 304 HG01928  chr1  94001171          C          T  chr1_94001171_C_T
## 405 HG01928  chr1 151473815          T          C  chr1_151473815_T_C
## 422 HG01928  chr1 156638884          G          A  chr1_156638884_G_A
```

```
nrow(ind)
```

```
## [1] 85
```

```
table(ind[,1])
```

```
##
## HG01928
##      85
```

extract individuals if you want

```
ind <- extractIndividual(input, c("HG01928", "HG03915"))
head(ind)
```

```
##      SAMPLE CHROM  POS_B38 REFERENCE ALTERNATE      ID
## 1  HG01928  chr1    913941          G          T chr1_913941_G_T
## 2  HG03915  chr1    917676          C          A chr1_917676_C_A
## 3  HG03915  chr1    918783          G          C chr1_918783_G_C
## 12 HG01928  chr1   3393842          G          A chr1_3393842_G_A
## 74 HG03915  chr1  18766956          T          A chr1_18766956_T_A
## 166 HG01928 chr1  44230922          C          T chr1_44230922_C_T
```

```
nrow(ind)
```

```
## [1] 158
```

```
table(ind[,1])
```

```
##
## HG01928 HG03915
##      85      73
```

extract SNVs

```
snvs <- extractSNVs(input)
nrow(snvs)
```

```
## [1] 8558
```

extract indels

```
indels <- extractINDELs(input)
nrow(indels)
```

```
## [1] 1183
```

extract MNVs (there are none in the test set)


```
mnvs <- extractMNVs(input)
nrow(mnvs)
```

```
## [1] 0
```

calculate the Transition/Transversion ratio

```
calculateTiTvratio(input)
```

```
## number of transitions (A>G, C>T, G>A, T>C): 5708
## number of transversions (A>C, A>T, C>A, C>G, G>C, G>T, T>A, T>G): 2850
## Ti/Tv ratio: 2.00280701754386
## Plot of different nucleotide changes:
```



calculate deletion/insertion ratio


```
calculateDeletionInsertionratio(input)
```

```
## number of deletions 540  
## number of insertions 643  
## deletion/insertion ratio: 0.839813374805599
```

calculate deletion lengths

```
dellengths <- calculateDeletionLengths(input)
```

deletion lengths (n=540)




```
head(dellengths)
```

```
## [1] 2 2 27 2 2 15
```

calculate insertion lengths

```
inslengths <- calculateInsertionLengths(input)
```

insertion lengths (n=643)



```
head(inslengths)
```

```
## [1] 28  3 37 37 41  5
```

keep only the autosomes

```
aut <- extractAutosomes(input)
nrow(aut)
```

```
## [1] 9262
```

```
table(aut[,2])
```

```
##
## chr1 chr10 chr11 chr12 chr13 chr14 chr15 chr16 chr17 chr18 chr19 chr2 chr20
##  707  408  477  408  338  479  251  273  233  232  206  833  257
## chr21 chr22 chr3  chr4 chr5  chr6  chr7  chr8  chr9
##  143  154  696  642  614  551  482  501  377
```

keep only the X chromosome

```
X <- extractX(input)
nrow(X)
```

```
## [1] 479
```

```
table(X[,2])
```

```
##
## chrX
## 479
```

keep only the Y chromosome (there are none on the Y in the test dataset)

```
Y <- extractY(input)
nrow(Y)
```

```
## [1] 0
```

annotate the CpG (note it takes ~45 seconds to even read the CpG annotation file so this function is a little slow)

```
#The CpG human genome build 38 file is available here: https://data.cyverse.org/dav-a
non/iplant/home/tycheleturner/genomic_annotations/cpg_b38.rda
```

```
load("~/Documents/Github/accessory_files/for_acorn/cpg_b38.rda", verbose=TRUE)
```

```
## Loading objects:
##   cpg_b38
```

```
cpgResult <- annotateCpG(input, cpg_b38)
```

```
## The number of DNVs at CpG sites is: 1566
## The total number of SNVs is: 8558
## The percent of DNV that are SNVs at CpG sites is: 18.2986679130638
```

```
head(cpgResult)
```


```
##      SAMPLE CHROM POS_B38 REFERENCE ALTERNATE      ID      matcher cpg
## 5  HG02257  chr1 1217502      G      A chr1_1217502_G_A chr1_1217502 yes
## 27 HG00526  chr1 6066908      G      A chr1_6066908_G_A chr1_6066908 yes
## 29 HG02726  chr1 6280056      G      A chr1_6280056_G_A chr1_6280056 yes
## 32 HG02135  chr1 6588427      G      T chr1_6588427_G_T chr1_6588427 yes
## 34 HG02056  chr1 7354889      G      C chr1_7354889_G_C chr1_7354889 yes
## 35 HG00465  chr1 7574692      G      A chr1_7574692_G_A chr1_7574692 yes
```

calculate counts per individual

```
counts <- countsPerIndividual(input)
```

```
## mean of the counts per individual:
## 79.19512
## standard deviation of the counts per individual:
## 12.20431
## Plot generating of the density of the DNV counts.
```

density of DNV counts per individual



```
head(counts)
```



```
##      sample dnv_count
## 1 HG00405      70
## 2 HG00423      78
## 3 HG00429      57
## 4 HG00438      66
## 5 HG00444      74
## 6 HG00447      75
```

load in example data for parental age analyses


```
countExample <- read.delim("~/Documents/Github/acorn/inst/extdata/dnm_count_example.txt")
parentExample <- read.delim("~/Documents/Github/acorn/inst/extdata/parental_age_example.txt")
```

make parental age object

```
parents <- parentalAgeObject(countExample, parentExample)
```

run parental age analyses including both mother and father


```
parentalAge(parents)
```



```
## $`summary of linear model for father's and mother's age at birth and DNV counts`
##
## Call:
## lm(formula = dnm_counts ~ fatherAge + motherAge, data = parentalAgeObject)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -30.190  -6.831  -0.477   6.975  31.700
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  10.8374     7.7691   1.395 0.166220
## fatherAge     1.0331     0.2669   3.871 0.000196 ***
## motherAge     0.7179     0.3174   2.262 0.025955 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 11.14 on 97 degrees of freedom
## Multiple R-squared:  0.3732, Adjusted R-squared:  0.3603
## F-statistic: 28.87 on 2 and 97 DF,  p-value: 1.45e-10
##
## $`confidence interval of linear model for father's and mother's age at birth and D
NV counts`
##              2.5 %    97.5 %
## (Intercept) -4.58207432 26.256945
## fatherAge    0.50343356 1.562695
## motherAge    0.08788934 1.347946
```

run parental age analyses for father age only


```
fatherAge(parents)
```



```
## $`correlation of father's age at birth and DNV counts`
##
## Pearson's product-moment correlation
##
## data:  parentalAgeObject[, 3] and parentalAgeObject[, 2]
## t = 7.1073, df = 98, p-value = 1.927e-10
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
##  0.4368243 0.6994934
## sample estimates:
##      cor
## 0.5832034
##
## $`summary of linear model for father's age at birth and DNV counts`
##
## Call:
## lm(formula = dnm_counts ~ fatherAge, data = parentalAgeObject)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -33.027  -6.690  -0.768   7.624  29.579
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  19.4131     6.9218   2.805  0.00608 **
## fatherAge     1.4374     0.2022   7.107 1.93e-10 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 11.37 on 98 degrees of freedom
## Multiple R-squared:  0.3401, Adjusted R-squared:  0.3334
## F-statistic: 50.51 on 1 and 98 DF, p-value: 1.927e-10
##
## $`confidence interval of linear model for father's age at birth and DNV counts`
##              2.5 %    97.5 %
## (Intercept) 5.676962 33.149157
## fatherAge   1.036030  1.838704
```

run parental age analyses for mother age only

```
motherAge(parents)
```



```
## $`correlation of mother's age at birth and DNV counts`
##
## Pearson's product-moment correlation
##
## data: parentalAgeObject[, 4] and parentalAgeObject[, 2]
## t = 6.1173, df = 98, p-value = 1.955e-08
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
## 0.3671661 0.6545122
## sample estimates:
##      cor
## 0.5256736
##
## $`summary of linear model for mother's age at birth and DNV counts`
##
## Call:
## lm(formula = dnm_counts ~ motherAge, data = parentalAgeObject)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -33.793  -7.578  -0.467   7.825  33.927
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  20.2284     7.8898   2.564   0.0119 *
## motherAge     1.5412     0.2519   6.117 1.96e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 11.91 on 98 degrees of freedom
## Multiple R-squared:  0.2763, Adjusted R-squared:  0.2689
## F-statistic: 37.42 on 1 and 98 DF, p-value: 1.955e-08
##
## $`confidence interval of linear model for mother's age at birth and DNV counts`
##              2.5 %    97.5 %
## (Intercept)  4.571389 35.88550
## motherAge     1.041211  2.04113
```