

**Canada**

Plumbing | Pipe and Tubing | PVC Tubing | TUBING, WHITE, 3/32 IN INSIDE DIA, 7/32 IN OUTS...

Email

Print



Roll over image to zoom.

## TUBING, WHITE, 3/32 IN INSIDE DIA, 7/32 IN OUTSIDE DIA, 5 FT, 70A, SILICONE

USA SEALING

**Web Price ⓘ:**  
**\$12.71 / EACH**

1

**Add to Cart**☐ Compare

### Availability

☐ Pick Up☒ Shipping**To view Availability for  
another location, please enter  
postal code below ⓘ**

New Postal Code

**Apply**

Item # <b>USSZUSA- HT3485</b>	Mfr. Model # <b>ZUSA-HT-3485</b>	UNSPSC # <b>40183000</b>
-----------------------------------	-------------------------------------	-----------------------------

CATALOGUE PAGE # N/A	Shipping Weight <b>1.0 lbs</b>
-------------------------	-----------------------------------

### Product Details

This white FDA/NSF-certified silicone tubing is five feet long with tube bend radius of 3/4 inch and wall thickness of 1/16 inch. The inside diameter of this tube is 3/32 inch and the outside diameter is 7/32 inch. It has a temperature range between -80 Degrees F and 420 Degrees F with maximum pressure of 40 PSI. This tubing is used in air, chemicals, water, steam, food and beverage applications.

## Technical Specs

Item	Tubing
Colour	White
Hardness	Shore A 70
Jacket Colour	No Jacket
Material	Silicone
Material Trade Number	Not Applicable
Maximum Operating Temperature	420 Degrees F
Overall Length	5 ft
PEX Type	Not Applicable
Reinforcement	Not Reinforced
Wall Thickness	0.625 in
Petroleum Product Compatibility	Mineral Oil
Autoclavable	Yes
Clarity	Semi-Clear
Fitting Compatibility	Barbed
Stripe Colour	No Stripe
Tube Form	Coil
Flow Application	Dairy, Food and Beverage, Pharmaceutical
For Fluid Type	Beverages
Tensile Strength	1,450 psi

Application	Beverages, Food, Water
Food Application	Dairy, Food, and Beverage
Inside Diameter	3/32 in
Jacket Material	No Jacket
Material Trade Name	Not Applicable
Maximum Operating Pressure	40 psi
Outside Diameter	7/32 in
Peristaltic Pump Compatible	Yes
Resistance Properties	High Temperature Resistant
Standards	FDA, NSF 51, 3A 18-03
Food and Beverage Compatibility	Beer, Citric Acid, Dairy, Distilled Water, Glycerin, Linseed Oil, Milk, Non-Potable Water, Orange Juice, Potable Water, Salt Water, Soft Drinks, Vinegar
Chemical Compatibility	Acetic Acid 10%, Calcium Chloride, Hydrogen Peroxide, Potassium Sulfate, Sodium Chloride, Sodium Hypochlorite 5.5%, Zinc Chloride
Bend Radius	3/4 in
Does Not Contain	Not Applicable
Flexibility	Semi-Flexible
System of Measurement	Inch
Vacuum Rated	Not Rated for Vacuum
For Environment	High Temperature

Minimum  
Operating  
Temperature

**-80 Degrees F**

---

## Compliance and Restrictions

None

[Back to Top](#)