PACKET TRACER CONFIGURACIÓN DE VLANS

Unidad II.-Actividad 2.1 -Realizar la configuración en packet tracert de VLAN con dos switches cisco para 37 equipos

CREACION DE VLANS EN LOS SWITCHS S1 Y S2

====51====
Switch>
Switch>ena
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname S1
S1(config)#vlan 3
S1(config-vlan)#name RETRES
Default VLAN 1 may not have its name changed.
S1(config-vlan)#exit
S1(config)#vlan 2
S1(config-vlan)#name REDDOS
S1(config-vlan)#
S1(config-vlan)#exit
S1(config)#end
S1#
%SYS-5-CONFIG_I: Configured from console by console
S1#wr
Building configuration
[OK]
S1#

====S2====
Switch>
Switch>ena
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname S2
S2(config)#vlan 3
S2(config-vlan)#name REDTRES
Default VLAN 1 may not have its name changed.
S2(config-vlan)#exit
S2(config)#vlan 2
S2(config-vlan)#name REDDOS
S2(config-vlan)#exit
S2(config)#end
S2#
%SYS-5-CONFIG_I: Configured from console by console
S2#wr
Building configuration
[OK]
S2#
ASIGNACIÓN DE PUERTOS A LAS VLANS CREADAS

====S1=====

S1#

S1#conf t

Enter configuration commands, one per line. End with CNTL/Z.

S1(config)#inter fa0/1

```
S1(config-if)#switchport mode access
S1(config-if)#switchport access vlan 3
S1(config-if)#exit
S1(config)#inter fa0/2
S1(config-if)#switchport mode access
S1(config-if)#switchport access vlan 3
S1(config-if)#exit
S1(config)#inter fa0/3
S1(config-if)#switchport mode access
S1(config-if)#switchport access vlan 2
S1(config-if)#exit
S1(config)#inter fa0/4
S1(config-if)#switchport mode access
S1(config-if)#switchport access vlan 2
S1(config-if)#exit
S1(config)#end
S1#
%SYS-5-CONFIG_I: Configured from console by console
S1#wr
Building configuration...
[OK]
S1#
====S2====
S2#conf t
```

Enter configuration commands, one per line. End with CNTL/Z.

S2(config)#inter fa0/1

S2(config-if)#switchport mode access

S2(config-if)#switchport access vlan 3

S2(config-if)#exit

S2(config)#inter fa0/2

S2(config-if)#switchport mode access

S2(config-if)#switchport access vlan 3

S2(config-if)#exit

S2(config)#inter fa0/3

S2(config-if)#switchport mode access

S2(config-if)#switchport access vlan 2

S2(config-if)#exit

S2(config)#inter fa0/4

S2(config-if)#switchport mode access

S2(config-if)#switchport access vlan 2

S2(config-if)#exit

S2(config)#end

S2#

 $\$SYS-5-CONFIG_I$: Configured from console by console

S2#wr

Building configuration...

[OK]

S2#

ANEXO DE LA TOPOLOGÍA

