

1. web.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns="http://xmlns.jcp.org/xml/ns/javaee"
    xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee
http://xmlns.jcp.org/xml/ns/javaee/web-app_3_1.xsd"
    id="WebApp_ID" version="3.1">
    <display-name>first</display-name>
    <welcome-file-list>
        <welcome-file>index.html</welcome-file>
    </welcome-file-list>

    <!--配置servlet -->
    <servlet>
        <!-- 若不配置则此处名称与后面的名称要一致 -->
        <servlet-name>TEST</servlet-name>
        <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
        <!-- 配置springMVC文件，可不配置但文件名要*(上面的名字)-servlet -->
        <init-param>
            <param-name>contextConfigLocation</param-name>
            <param-value>classpath:TEST-servlet.xml</param-value>
        </init-param>
        <load-on-startup>2</load-on-startup>
    </servlet>
    <servlet-mapping>
        <servlet-name>TEST</servlet-name>
        <url-pattern>*.do</url-pattern>
    </servlet-mapping>

    <!-- 加载spring与mybatis的配置文件 -->
    <context-param>
        <param-name>contextConfigLocation</param-name>
        <!-- 路径可以用*等符号 -->
        <param-value>classpath:application.xml</param-value>
    </context-param>

    <!-- Spring监听器 -->
    <listener>
```

```

        <listener-class>org.springframework.web.context.ContextLoaderListener</listener-
class>
    </listener>

    <!-- configure the HiddenHttpMethodFilter, convert the post method to put or delete -->
    <filter>
        <filter-name>HiddenHttpMethodFilter</filter-name>
        <filter-class>org.springframework.web.filter.HiddenHttpMethodFilter</filter-class>
    </filter>
    <filter-mapping>
        <filter-name>HiddenHttpMethodFilter</filter-name>
        <url-pattern>*</url-pattern>
    </filter-mapping>

    <!-- 编码过滤器 -->
    <filter>
        <filter-name>encodingFilter</filter-name>
        <filter-class>org.springframework.web.filter.CharacterEncodingFilter</filter-
class>
        <init-param>
            <param-name>encoding</param-name>
            <param-value>UTF-8</param-value>
        </init-param>
    </filter>
    <filter-mapping>
        <filter-name>encodingFilter</filter-name>
        <url-pattern>*</url-pattern>
    </filter-mapping>

</web-app>

```

2. spring-mvc配置文件

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:context="http://www.springframework.org/schema/context"
    xmlns:mvc="http://www.springframework.org/schema/mvc"
    xmlns:p="http://www.springframework.org/schema/p"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
        http://www.springframework.org/schema/beans/spring-beans.xsd

```

```

    http://www.springframework.org/schema/context
    http://www.springframework.org/schema/context/spring-context.xsd
    http://www.springframework.org/schema/mvc
    http://www.springframework.org/schema/mvc/spring-mvc.xsd">

    <!-- 扫描 springMVC的 Controller-->
    <context:component-scan base-package="com.mybatisdemo.controller"/>

    <!-- <mvc:annotation-driven validator="myValidator"/>
    <bean id="myValidator"
        class="org.springframework.validation.beanvalidation.LocalValidatorFactoryBean">
        <property name="providerClass" value="org.hibernate.validator.HibernateValidator"
    />

        <property name="validationMessageSource" ref="messageSource"/>
    </bean>
    <bean id="messageSource"
        class="org.springframework.context.support.ResourceBundleMessageSource"
        p:basename="i18n/mess" /> -->

    <!-- 配置视图解析器，将ModelAndView及字符串解析为具体的页面 -->
    <!--<bean
        class="org.springframework.web.servlet.view.InternalResourceViewResolver"
        p:viewClass="org.springframework.web.servlet.view.JstlView"
        p:prefix="/"
        p:suffix=".jsp"/>-->

    <!-- 多部分文件上传 -->
    <!-- <bean id="multipartResolver"
class="org.springframework.web.multipart.commons.CommonsMultipartResolver">
        <property name="maxUploadSize" value="104857600" />
        <property name="maxInMemorySize" value="4096" />
        <property name="defaultEncoding" value="UTF-8"/>
    </bean> -->
    <!--Ajax解析-->
    <!-- <bean
class="org.springframework.web.servlet.mvc.method.annotation.RequestMappingHandlerAdapter">
        <property name="messageConverters">
            <list>
                <ref bean="jsonHttpMessageConverter" />

```

```
        </list>
    </property>
</bean>
```

```
    <bean id="jsonHttpMessageConverter"
class="org.springframework.http.converter.json.MappingJackson2HttpMessageConverter">
        <property name="supportedMediaTypes">
            <list>
                <value>application/json;charset=UTF-8</value>
            </list>
        </property>
    </bean> -->
```

```
<!--配置自定义拦截器-->
```

```
<!-- <mvc:interceptors>
```

```
    <mvc:interceptor>
```

```
        <mvc:mapping path="/**"/>
```

```
        <mvc:exclude-mapping path="/user/login.do"/>
```

```
        <bean class="com.wanho.java99.rbac.auth.interceptor.AuthHandlerInterceptor"/>
```

```
    </mvc:interceptor>
```

```
</mvc:interceptors> -->
```

```
</beans>
```