

# DATA.ML.300 Computer Vision

## Exercise Round 7

For these exercises you will need Python or Matlab. Return your answers as a pdf along with your modified code to Moodle. Exercise points will be granted after a teaching assistant has checked your answers. Returns done before the solution session will result in maximum of 4 points, whereas returns after the session will result in maximum of 1 point.

**Task 1.** Fundamental matrix estimation. (Programming exercise) (2 points)

See the comments in `Fmatrix_example` and implement the two missing functions:

- a) Implement the eight-point algorithm in `estimateF`. The algorithm is described below and in the lecture slides.

Let's denote  $\mathbf{x} = (u, v, 1)^\top$  and  $\mathbf{x}' = (u', v', 1)^\top$ .

The eight-point algorithm can be implemented by solving the following homogeneous linear system:

$$(u'u, u'v, u'u, v'u, v'v, v'u, u, v, 1) \begin{pmatrix} f_{11} \\ f_{12} \\ f_{13} \\ f_{21} \\ f_{22} \\ f_{23} \\ f_{31} \\ f_{32} \\ f_{33} \end{pmatrix} = 0$$

This solution is then enforced rank-2 constraint by taking SVD and then reconstructing using only the two largest singular values.

- b) Implement the missing denormalization used in normalized eight-point algorithm `estimateFnorm`. If  $\mathbf{T}$  and  $\mathbf{T}'$  are the normalizing transformations in the two images, the fundamental matrix in original coordinates is  $\mathbf{T}'^\top \mathbf{F} \mathbf{T}$

The epipolar lines obtained with both F-matrix estimates should be close to those visualized by the example script.

**Task 2.** Two-view structure from motion. (Programming exercise) (2 points)

In this exercise you will estimate the fundamental matrix for a pair of uncalibrated images and recover a pair of camera projection matrices that are compatible with the estimated fundamental matrix. Thereafter, triangulation of point correspondences using the aforementioned projection matrices gives a projective reconstruction of the scene, which is visualized in the example script.

Run the script `two_view_structure_from_motion_example` and proceed as follows (do the tasks and answer the questions):

- a)* The first part of the code calibrates the cameras using known dimensions of the shelf and visualizes a wireframe model of the shelf projected onto the images. **Your task is to use the calibrated camera matrices to project the 3D points to the images** (see comments in the code). How are the cameras calibrated here?
- b)* The second part triangulates and visualizes a projective reconstruction of the wireframe model. **Give an explanation why the model looks distorted but is anyway correct.** (See discussion in the lecture slides.)
- c)* In the third part you should project the distorted wireframe model onto the two images and check that it matches the outlines of the book shelf. **Include a picture that illustrates the projected model.**
- d)* Finally, describe what kind of information could be used to upgrade the projective reconstruction to a similarity reconstruction, where angles and ratios of lengths are the same as in the real one, without knowing the dimensions of the book shelf. (Hint: See lecture slides.)