



## QUAD, 10-BIT, LOW-POWER, VOLTAGE OUTPUT, I'C INTERFACE DIGITAL-TO-ANALOG CONVERTER

## **FEATURES**

- Micropower Operation: 500 μA at 3 V V<sub>DD</sub>
- Fast Update Rate: 188 kSPS
- Per-channel Power-down Capability
- Power-On Reset to Zero
- 2.7-V to 5.5-V Analog Power Supply
- 10-Bit Monotonic
- I<sup>2</sup>C™ Interface Up to 3.4 Mbps
- **Data Transmit Capability**
- On-Chip Output Buffer Amplifier, Rail-to-Rail Operation
- **Double-Buffered Input Register**
- Address Support for up to Four DAC6574s
- Synchronous Update Support for up to 16 Channels
- Operation From -40°C to 105°C
- Small 10 Lead MSOP Package

## **APPLICATIONS**

- **Process Control**
- **Data Acquisition Systems**
- **Closed-Loop Servo Control**
- **PC Peripherals**
- **Portable Instrumentation**


## DESCRIPTION

The DAC6574 is a low-power, quad channel, 10-bit buffered voltage output DAC. Its on-chip precision output amplifier allows rail-to-rail output swing to be achieved. The DAC6574 utilizes an I<sup>2</sup>C compatible two wire serial interface supporting high-speed interface mode with address support of up to four DAC6574s for a total of 16 channels on the bus.

The DAC6574 uses  $V_{\text{DD}}$  and GND to set the output range of the DAC. The DAC6574 incorporates a power-on-reset circuit that ensures that the DAC output powers up at zero volts and remains there until a valid write takes place to the device. The DAC6574 contains a per-channel power-down feature, accessed via the internal control register, that reduces the current consumption of the device to 200 nA at 5

The low power consumption of this part in normal operation makes it ideally suited to portable battery operated equipment. The power consumption is less than 3mW at  $V_{DD}$  = 5 V reducing to 1  $\mu$ W in power-down mode.

TI offers a variety of data converters with I<sup>2</sup>C interface. See DACx57x family of 16/12/10/8 bit, single and quad channel DACs. Also see ADS7823 and ADS1100, 12-bit octal channel and 16-bit single channel ADCs.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

I<sup>2</sup>C is a trademark of Philips Corporation.