

MT @HanBaldwin: Fightin OOVs in German #twitter

Uladzimir Sidarenka, Tatjana Scheffler, and Manfred Stede

University of Potsdam,
uladzimir.sidarenka@uni-potsdam.de, tatjana.scheffler@uni-potsdam.de,
manfred.stede@uni-potsdam.de,
WWW home page: <http://www.ling.uni-potsdam.de/acl-lab/SocMedia/main.htm>

Abstract. This article gives an overview of existing approaches to the problem of out-of-vocabulary (OOV) tokens and noisiness phenomena in natural language texts. These approaches are classified with regard to the size of text spans and knowledge inference mechanisms which they rely on in their work. Additionally to that, we conduct quantitative and qualitative analyses of unknown words in German Twitter messages, in order to see how relevant the OOV and text normalization problems are for this particular kind of micro-texts and what the characteristics of these OOVs are. In a concluding step, we present a set of ad-hoc techniques which are supposed to tackle some of the most prominent disturbing effects found during these analyses and show how this set of techniques helps us lower the average rate of out-of-vocabulary tokens in Twitter messages and how this lower OOV-rate in turn helps improve the quality of automatic part-of-speech tagging.

Keywords: twitter, social media, text normalization, spelling correction

1 Introduction

When Jack Dorsey, the present CEO of Twitter Inc., was sending the very first tweet on March 21, 2006 (Dorsey, 2006), he probably could not imagine that a few years later presidents and government officials would use this service to communicate with their voters and the Pope would be posting short messages holding an iPad in his hand (Pianigiani, 2012). Yet another thing that Jack Dorsey was apparently not aware of at that moment, was the fact that his message – “just setting up my twttr” – already contained a word which was unknown to the majority of NLP applications existing at that time, and that there would be many of such words in future causing a lot of headache to natural language specialists.

Though the problem of out-of-vocabulary words and its closely related task of textual normalization have been extensively studied in computational linguistics since as early as the late 1950s (cf. Petersen, 1980) and were certainly anything but new at the time when mobile communication emerged, it were small messages that revived interest in this research area in the past two decades.

In the next Section we will give a short overview of recent scientific approaches to the problem of tackling out-of-vocabulary words in non-standard texts. After that, in Section 3 we will analyze which types of noisiness phenomena are especially characteristic for German Twitter. Section 4 will subsequently describe an automatic procedure for mitigating some of the most prominent of those effects. In a concluding step, we will perform an evaluation of the results of this procedure and give further suggestions for future research.

2 Related Work

Before proceeding with the description of existing methods for noisy text normalization (NTN), we first would like to define the criteria by which these methods could be classified. It should be noted that there already exist several classifications of NTN approaches including Kukich (1992), Kobus et al. (2008), and Sproat et al. (2001).

Kukich (1992), for example, divided NTN techniques into six classes:

1. minimum edit distance techniques;
2. similarity key techniques;
3. rule-based techniques;
4. n -gram based techniques;
5. probabilistic techniques;
6. neural nets.

Kobus (2008), on the contrary, referred to NTN methods as *metaphors* and split them into the following three groups:

1. “spell checking” metaphor;
2. “translation” metaphor;
3. “speech recognition” metaphor.

Though both divisions seem to be justified to some extent, it is difficult to determine using them whether an NTN approach that detects and restores incorrectly spelled words on the basis of phonetical n -gram statistics should fall into the n -gram based, probabilistic, spell checking or speech recognition class.

The reason for this confusion is the fact that the above classifications both rely on several independent criteria at the same time, though each of these criteria characterizes an NTN system from a different point of view. As a consequence, unambiguous assignment of an NTN approach to one particular class often becomes impossible. In order to avoid this, we instead suggest using separate classifications for each type of involved criteria which might characterize an NTN technique.

One of such criteria which in our opinion would be worth a separate classification is *segmentation level* that is used *a)* to infer in-vocabulary (IV) equivalents for OOV tokens and *b)* to choose the most probable variant among multiple

possible suggestions¹. For this criterion, we propose division into the following classes:

1. graphematic²;
2. lexical;
3. phrasal.

Each broader level of this hierarchy is supposed to either incorporate or ignore information provided by its narrower subsegments. In this way, we only need to mention one (the broadest) hierarchical class for the cases when multiple segmentation levels are involved by some techniques.

The second criterion regards the *type of information induction* that is used to devise the correction rules. This leads us to the usual NLP-taxonomy which divides all approaches into:

1. rule-based;
2. statistical³;
3. and hybrid ones.

With these two classifications, we will now try to present and group together approaches to the NTN task which appeared in the literature in recent years.

The earlier works on NTN commonly relied on either purely graphematic or phonographematic levels of segmentation for deriving normalization variants of incorrectly spelled words. To purely graphematic systems belong methods suggested by Brill and Moore (2000), Sproat et al. (2001), and Clark (2003). As phonographematic approaches one could regard works done by Toutanova and Moore (2002), Choudhury et al. (2007), Cook and Stevenson (2009) etc. With regard to the type of information inference, practically all of these methods were supervised with the exception of Cook and Stevenson (2009) who claimed to use an unsupervised technique.

Starting from the second half of the 2000s, the raising influence and improved quality of machine translation tools lead to the development of NTN technologies which used broader levels of segmentation. In 2006, Aw et al. suggested a supervised statistical system for normalization of SMS-messages which operated on automatically aligned phrases. A few years later, Clark and Araki (2011) described a purely rule-based method which used mappings of non-standard words and phrases to their corresponding standard language forms.

As noted by Kobus et al. (2008), NTN methods relying on either graphematic or phrasal segments usually revealed complementary strengths and weaknesses.

¹ For the cases, when segments of different lengths are used for tasks a and b, we note it explicitly in our classification on which segmentation length each of these subtasks relies.

² Depending on whether phonetical information is involved or not at this level, this class could be further divided into a phonographematic and purely graphematic subclasses.

³ Depending on the type of training data required, this class is in turn usually divided into unsupervised, semi-supervised, and supervised groups.

This notion led NLP scientists to the idea that by incorporating multiple levels of the language into one NTN system the total performance of the whole system would improve as different sources of information would benefit from each other. As a consequence of this, a wealth of combined techniques emerged in the past few years. Among these we should especially mention works by Kobus et al. (2008), Kaufmann (2010), Han and Baldwin (2011), and Oliva et al. (2013). The majority of these systems used the whole range of segmentation levels from phonographematic to phrasal one, and in many cases they also applied different knowledge inference mechanisms to different levels of the language.

It should however be noted that almost all of the above methods mainly concentrated on only English data. A few exceptions from that are approaches suggested by Beaufort et al. (2010) for French and Oliva et al. (2013) for Spanish. To find out which peculiarities of ill-formed words are characteristic for German, we will perform a quantitative and qualitative analysis of unknown words in German Twitter in the next Section in order to see what kind of NTN techniques would be more suitable for handling ill-formed words there.

3 Analysis of Unknown Tokens

In order to estimate the percentage of unknown words in Twitter messages, we randomly selected 10,000 tweets from a previously collected corpus, split them into sentences and tokenized using social media-aware tokenizer by Christopher Potts⁴. After skipping all words which did not contain any alphabetic characters or consisted only of a single letter, we obtained a list of 129,146 tokens. As reference systems for dictionary lookup we used open source spell checking program `hunspell`⁵ and publicly available part-of-speech tagger `TreeTagger`⁶ (Schmid, 1994).

Out of this token list, 26,018 tokens (20.15 %) were regarded as unknown by `hunspell` and 28,389 tokens (21.98 %) were considered as OOV by `TreeTagger`. We also performed similar estimations after leaving only unique words without taking into account their frequencies. This allowed us to shrink our initial token list by four times to 32,538 unique tokens. The relative rate of unknown words raised as expected and run up to 46.96 % for `hunspell` and 58.24 % for `TreeTagger`.

Here once again the question of classification arose. This time with regard to the reasons, why different tokens could have been omitted from corresponding applications' dictionaries. In this respect, division into following groups seemed to us to be appropriate:

1. **Objective limitedness of machine-readable dictionary (MRD).** Among this group, we counted words of basic vocabulary which did not get into applications' MRD either because they supposedly were rare or because they

⁴ <http://sentiment.christopherpotts.net/code-data/happyfuntokenizing.py>

⁵ Ispell Version 3.2.06 (Hunspell Version 1.3.2); dictionary de_DE.

⁶ Version 3.2 with German parameter file UTF-8.

did not exist at the time when dictionaries were created. Another reason for the inclusion in this type was the belonging of a word to an open lexical or part-of-speech class (like, for example, named entities or interjections) which are often omitted from MRDs due to the impossibility to fully cover these classes;

2. **Sloppiness of users' input.** In the scope of this second group, we considered incorrect spellings of words encountered in text;
3. **Stylistic specifics of text genre.** This group comprised words which could be considered as illegal from the point of view of standard language but were perfectly valid terms in the domain of web discourse or more specifically in Twitter communication.

In order to see how detected out-of-vocabulary words were distributed among and within these 3 major groups, we manually analyzed all OOV tokens which appeared in text more than once and also looked at 1,000 randomly selected hapax legomena. The results of these estimations are shown and explained below.

We subdivided the class 1 into the following subclasses:

1. regular German words, e.g. *aufm*, *losziehen*;
2. compounds, e.g. *Altwein*, *Amtsapotheckerin*;
3. abbreviations, e.g. *NBG*, *OL*;
4. interjections, e.g. *aja*, *haha*;
5. named entities, with subclasses:
 - (a) persons, e.g. *Ahmadinedschad*, *Schweiger*;
 - (b) geographic locations, e.g. *Biel*, *Limmat*;
 - (c) companies, e.g. *Apple*, *Facebook*;
 - (d) product names, e.g. *iPhone*, *MacBook*;
6. neologisms, with subclasses:
 - (a) newly coined German terms, e.g. *entfolgen*, *gegoogelt*;
 - (b) loanwords, e.g. *Community*, *Stream*;
7. and, finally, foreign words like *is* or *now* which in contrast to 6b were not mentioned in any existing German lexica and did not comply with inflectional rules of German grammar.

Though this division is admittedly arbitrarily to a certain degree and also has the disadvantage of simultaneously involving different linguistic criteria, the underlying notion here was simple – valid words could have been omitted from an MRD either due to the limitations of developers' capacities (group 1), active word formation processes or lexical productivity of the language itself (groups 2 through 6a) or also due to language's openness to foreign language systems (groups 6b and 7).

In Table 1, percentage figures for each of the above subgroups are shown. We have considered OOV-distributions for both **hunspell** and **TreeTagger**. For each of them, we estimated the percentage of a particular subclass with regard to the total number of occurrences of OOV-tokens (column “% of total OOVs”) as well as with regard to their percentage rate in the list of only unique OOVs disregarding their frequencies (column “% of unique OOVs”).

Similarly to the class 1, we subdivided the group “Sloppiness of users' input” into the following subgroups:

Table 1. Distribution of OOV words belonging to the class “Objective limitedness of MRD”

OOV subclass	hunspell		TreeTagger	
	% of total OOVs	% of unique OOVs	% of total OOVs	% of unique OOVs
regular German words	7.82	8.78	2.8	3.49
compounds	1.21	2.42	2.51	4.55
abbreviations	3.98	4.77	3.27	3.44
interjections	5.95	4.54	5.58	4.29
person names	4.73	6.41	2.32	3.47
geographic locations	1.5	2.53	1.16	1.88
company names	2.27	2.84	4.35	3.01
product names	2.13	2.57	2.45	3.23
newly coined terms	1.35	1.31	3.33	2.38
loanwords	3.68	4.03	3.29	2.87
foreign words	11.5	13.76	9.57	10.91
total	46.12	53.96	40.63	43.52

1. insertions, e.g. *dennen* instead of *denen*;
2. deletions, e.g. *scho* instead of *schon*;
3. substitutions, e.g. *fur* instead of *für*;

according to the type of operation which led to a particular spelling mistake. In cases when multiple different operations were involved simultaneously, we explicitly marked each of these operations in our data. Statistical distribution of these subclasses is shown in Table 2.

Table 2. Distribution of OOV words belonging to the class “Sloppiness of users’ input”

OOV subclass	hunspell		TreeTagger	
	% of total OOVs	% of unique OOVs	% of total OOVs	% of unique OOVs
insertions	0.49	1	0.18	0.34
deletions	8.44	6.38	6.52	5.27
substitutions	2.17	3.37	1.11	1.2
total	11.1	10.75	7.81	6.81

As is clear from the table, deletions are by far the most common type of misspellings. The reasons for that are on the one hand either relatively frequent omissions of characters made by user or even more often automatic truncations of too long messages which were performed by Twitter service itself.⁷

⁷ As is generally known, Twitter imposes a strong restriction on the length of posted messages which can be no longer than 140 characters. Upon exceeding this length, tweets get automatically truncated to the maximal allowed length.

Finally, the third group – “Stylistic specifics of text genre” – was subdivided into the subgroups:

1. hashtags, e.g. *#Kleinanzeigen*;
2. @-tokens, e.g. *@ZDFonline*;
3. links, e.g. *http://t.co*;
4. smileys, e.g. *:-P*;
5. slang, e.g. *OMG*.

according to the lexical or syntactic class which these tokens belonged to. Apart from lexical expressions pertaining to the genre of Internet-based communication, we also marked as *slang* spelling variants of standard language words which could be regarded as their corresponding colloquial equivalents. As such equivalents, we considered spellings like *ned* instead of *nicht* or *grad* instead of *gerade*. These cases were marked by us both as misspellings and as slang. A detailed statistics on the above subgroups of class 3 is shown in Table 3:

Table 3. Distribution of OOV words belonging to the class “Stylistic specifics of text genre”

OOV subclass	hunspell		TreeTagger	
	% of total OOVs	% of unique OOVs	% of total OOVs	% of unique OOVs
hashtags	7.35	6.18	13.06	10.59
@-tokens	13.02	20.23	16.19	21.91
links	2.43	0.4	4.89	6.07
smileys	2	0.73	6.88	1.2
slang	16.22	5.27	6.94	4.77
total	41.02	32.81	47.96	44.54

4 Text Normalization Procedure

4.1 Replacement of Twitter-Specific Phenomena

4.2 Restoration of Umlauts

4.3 Squeezing of Elongated Words

4.4 Translation of Slang Idioms

5 Evaluation

6 Conclusion

Acknowledgement.

This work was financially supported by ... as part of collaborative project “...”. The authors are also thankful to ... for help with the analysis of data.

References

- Aw, A., Zhang, M., Xiao, J., Su, J.: A Phrase-based Statistical Model for SMS Text Normalization. *COLING/ACL* (2006) 33–40
- Bangalore, S., Murdock, V., Riccardi, G.: Bootstrapping Bilingual Data using Consensus Translation for a Multilingual Instant Messaging System. *COLING* (2002) 33–40
- Beaufort, R., Roekhaut, S., Cougnon, L. A., Fairon, C.: A Hybrid Rule/Model-Based Finite-State Framework for Normalizing SMS Messages. *ACL* (2010) 770–779
- Brill, E., Moore, R. C.: An improved model for noisy channel spelling correction. *ACL* (2000) 286–293
- Clark, A.: Pre-processing very noisy text. In *Proceedings of Workshop on Shallow Processing of Large Corpora*. (2003) 12–22
- Choudhury, M., Saraf, R., Jain, V., Mukherjee, A., Sarkar, S., Basu A.: Investigation and Modeling of the Structure of Texting Language. *International Journal of Document Analysis and Retrieval: Special Issue on Analytics of Noisy Text*. **10** (2007) 157–174
- Clark, E., Araki, K.: Text Normalization in Social Media: Progress, Problems and Applications for a Pre-processing System of Casual English. *PACLING. Procedia - Social and Behavioral Sciences* **27** (2011) 2–11
- Cook, P., Stevenson, S.: An unsupervised model for text message normalization, *Proceedings of the Workshop on Computational Approaches to Linguistic Creativity. CALC '09*. (2009) 71–78
- Dorsey, J.: "just setting up my twttr". <https://twitter.com/jack/status/20> Accessed February 26, 2013. (2006)
- Han, B., Baldwin, T.: Lexical Normalization of Short Text Messages: Makn Sens a #twitter. *ACL HLT*. (2011) 368–378
- Jurafsky, D., Martin, J. H.: *Speech and Language Processing*. 2nd Edition. Prentice Hall (2008) 129, 323
- Kaufmann, M.: Syntactic normalization of twitter messages. *The 8-th International Conference on Natural Language Processing*. (2010)
- Kobus, C., Yvon, F., Damnati, G.: Normalizing SMS: are Two Metaphors Better than One? *COLING* (2008) 441–448
- Kukich, K.: Techniques for Automatically Correcting Words in Text. *ACM Computing Surveys* **24/4** (1992) 378–439
- McVeigh, T.: Text messaging turns 20. *The Observer* (December 1, 2012)
- Mukherjee, S., Malu, A., Balamurali, A. R., Bhattacharyya, P.: TwiSent: A Multistage System for Analyzing Sentiment in Twitter. In *Proceedings of The 21st ACM Conference on Information and Knowledge Management CIKM 2012, Hawaii, (Oct 29 - Nov 2, 2012)*
- McVeigh, T.: Text messaging turns 20. *The Observer* (December 1, 2012)
- Oliva, J., Serrano, J. I., and Del Castillo, M. D., and Igesias, .: A SMS normalization system integrating multiple grammatical resources. *Natural Language Engineering*. (2013) 121–141
- Papineni, K., Roukos, S., Ward, T., Zhu, W.-J.: Bleu: a Method for Automatic Evaluation of Machine Translation. *ACL* (2002) 311–318
- Petersen, L. J.: Computer Programs for Detecting and Correcting Spelling Errors. *Communications of the ACM* **23/ 12** (1980) 676–687
- Pianigiani, G., Donadio, R.: Twitter Has A New User: The Pope. *The New York Times*. Page A6. (December 4, 2012)

- Sproat, R., Black, A. W., Chen, S. F., Kumar, S., Ostendorf, M., Richards, Ch.: Normalization of non-standard words. *Computer Speech & Language*, **15/3** (2001) 287–333
- Schmid, H.: Probabilistic Part-of-Speech Tagging Using Decision Trees. In *Proceedings of International Conference on New Methods in Language Processing*. (1994)
- Sparck Jones, K., Galliers, J. R.: *Evaluating Natural Language Processing Systems. An Analysis and Review*. Lecture Notes in Computer Science 1083, Springer. (1996)
- Terdiman, D.: Report: Twitter hits half a billion tweets a day. <http://timmurphy.org/2009/07/22/line-spacing-in-latex-documents/>, Accessed February 26, 2013. (2012)
- Toutanova, K., Moore, R. C.: Pronunciation Modeling for Improved Spelling Correction. *ACL* (2002) 144–151