


Deep Learning

Lecture 3

Recall from last time : Challenges of recognition

Viewpoint




Illumination



This image is CC0 1.0 public domain

Deformation



This image by Umberto Salvagnin
is licensed under CC-BY 2.0

Occlusion



This image by jonsson is licensed
under CC-BY 2.0

Clutter



This image is CC0 1.0 public domain

Intraclass Variation



This image is CC0 1.0 public domain


Recall from last time : data-driven approach, kNN



1-NN classifier



5-NN classifier



Linear classification

Neural Network

Linear
classifiers



[This image is CC0 1.0 public domain](#)

Recall CIFAR10

airplane



automobile



bird



cat



deer



dog



frog



horse



ship



truck



50,000 training images
each image is **32x32x3**

10,000 test images.

Parametric Approach


Image



Array of **32x32x3** numbers
(3072 numbers total)



$f(\mathbf{x}, \mathbf{W})$



\mathbf{W}

parameters
or weights



10 numbers giving
class scores

Parametric Approach: Linear Classifier

Image



$$f(x, W) = Wx$$

$f(\mathbf{x}, \mathbf{W})$


10 numbers giving
class scores

\mathbf{W}

parameters
or weights

Array of $32 \times 32 \times 3$ numbers
(3072 numbers total)

Parametric Approach: Linear Classifier




Parametric Approach: Linear Classifier

Image



$$\boxed{f(x, W)} = \boxed{W} \boxed{x} + \boxed{b}$$

10×1 10×3072 3072×1 10×1




W

parameters
or weights

Array of $32 \times 32 \times 3$ numbers
(3072 numbers total)

Example with an image with 4 pixels, and 3 classes (cat / dog / ship)

Stretch pixels into column



0.2	-0.5	0.1	2.0
1.5	1.3	2.1	0.0
0	2.5	0.2	-0.3

W

56
231
24
2

+

1.1
3.2
-1.2

b

=

-96.8
437.9
61.95

Cat score


Dog score

Ship score

Example with an image with 4 pixels, and 3 classes (**cat** / **dog** / **ship**)

Algebraic Viewpoint



$$f(x, W) = Wx$$





Example with an image with 4 pixels, and 3 classes (**cat** / **dog** / **ship**)

Algebraic Viewpoint


$$f(x, W) = Wx$$




Interpreting a Linear Classifier



Interpreting a Linear Classifier: Visual Viewpoint



Interpreting a Linear Classifier: Geometric Viewpoint



$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers
(3072 numbers total)


Hard cases for a linear classifier

Class 1 :

First and third quadrants

Class 2 :

Second and fourth quadrants




Class 1 :

$1 \leq \text{L2 norm} \leq 2$

Class 2 :

Everything else




Class 1 :

Three modes

Class 2 :


Everything else



Linear Classifier: Three Viewpoints

Algebraic Viewpoint

$$f(x, W) = Wx$$




Visual Viewpoint

One template
per class



Geometric Viewpoint

Hyperplanes
cutting up space



So far : Defined a (linear) score function $f(x,W) = Wx + b$

Example class
scores for 3
images for
some W:



How can we tell
whether this W
is good or bad?

airplane	-3.45	-0.51	3.42
automobile	-8.87	6.04	4.64
bird	0.09	5.31	2.65
cat	2.9	-4.22	5.1
deer	4.48	-4.19	2.64
dog	8.02	3.58	5.55
frog	3.78	4.49	-4.34
horse	1.06	-4.37	-1.5
ship	-0.36	-2.09	-4.79
truck	-0.72	-2.93	6.14

[Cat image](#) by [Nikita](#) is licensed under [CC-BY 2.0](#)
[Car image](#) is [CC0 1.0](#) public domain
[Frog image](#) is in the public domain

Loss functions

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

A **loss function** tells how good our current classifier is

Given a dataset of examples

$$\{(x_i, y_i)\}_{i=1}^N$$

Where x_i is image and
 y_i is (integer) label

Loss over the dataset is a sum of loss over examples:

$$L = \frac{1}{N} \sum_i L_i(f(x_i, W), y_i)$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$
$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.


With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:

“Hinge loss”



$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$
$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat

3.2

1.3

2.2

car

5.1

4.9

2.5

frog

-1.7

2.0

-3.1

Losses:

2.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$= \max(0, 5.1 - 3.2 + 1)$$

$$+ \max(0, -1.7 - 3.2 + 1)$$

$$= \max(0, 2.9) + \max(0, -3.9)$$

$$= 2.9 + 0$$

$$= 2.9$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$\begin{aligned} &= \max(0, 1.3 - 4.9 + 1) \\ &\quad + \max(0, 2.0 - 4.9 + 1) \\ &= \max(0, -2.6) + \max(0, -1.9) \\ &= 0 + 0 \\ &= 0 \end{aligned}$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$\begin{aligned} &= \max(0, 2.2 - (-3.1) + 1) \\ &\quad + \max(0, 2.5 - (-3.1) + 1) \\ &= \max(0, 6.3) + \max(0, 6.6) \\ &= 6.3 + 6.6 \\ &= 12.9 \end{aligned}$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Loss over full dataset is average:

$$L = \frac{1}{N} \sum_{i=1}^N L_i$$

$$L = (2.9 + 0 + 12.9)/3 \\ = 5.27$$

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q1: What happens to
the loss if car scores
change a bit?

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q2: What is the
min/max possible
loss?

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q3: At initialization W
is small so all $s \approx 0$.
What is the loss?

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q4: What if the sum
was over all classes?
(including $j = y_i$)

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q5: What if we used
mean instead of
sum?

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q6: What if we used

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)^2$$

Multiclass SVM Loss: Example code

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

```
def L_i_vectorized(x, y, W):  
    scores = W.dot(x)  
    margins = np.maximum(0, scores - scores[y] + 1)  
    margins[y] = 0  
    loss_i = np.sum(margins)  
    return loss_i
```


$$f(x, W) = Wx$$

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

E.g. Suppose that we found a W such that $L = 0$.
Is this W unique?

$$f(x, W) = Wx$$

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

E.g. Suppose that we found a W such that $L = 0$.
Is this W unique?

No! $2W$ is also has $L = 0$!

Suppose: 3 training examples, 3 classes.

With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Before:

$$\begin{aligned} &= \max(0, 1.3 - 4.9 + 1) \\ &\quad + \max(0, 2.0 - 4.9 + 1) \\ &= \max(0, -2.6) + \max(0, -1.9) \\ &= 0 + 0 \\ &= 0 \end{aligned}$$

With W twice as large:

$$\begin{aligned} &= \max(0, 2.6 - 9.8 + 1) \\ &\quad + \max(0, 4.0 - 9.8 + 1) \\ &= \max(0, -6.2) + \max(0, -4.8) \\ &= 0 + 0 \\ &= 0 \end{aligned}$$

$$f(x, W) = Wx$$


$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

E.g. Suppose that we found a W such that $L = 0$.
Is this W unique?

No! $2W$ is also has $L = 0$!

How do we choose between W and $2W$?

Regularization

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)$$


Data loss : Model predictions
should match training data

Regularization

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss : Model predictions should match training data

Regularization : Prevent the model from doing *too* well on training data

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss : Model predictions should match training data

Regularization : Prevent the model from doing *too* well on training data

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss : Model predictions should match training data

Regularization : Prevent the model from doing *too* well on training data

Simple examples

L2 regularization: $R(W) = \sum_k \sum_l W_{k,l}^2$

L1 regularization: $R(W) = \sum_k \sum_l |W_{k,l}|$

Elastic net (L1 + L2): $R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss : Model predictions should match training data

Regularization : Prevent the model from doing *too* well on training data

Simple examples

L2 regularization: $R(W) = \sum_k \sum_l W_{k,l}^2$

L1 regularization: $R(W) = \sum_k \sum_l |W_{k,l}|$

Elastic net (L1 + L2): $R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$

More complex :

Dropout

Batch normalization

Stochastic depth, fractional pooling, etc

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss : Model predictions should match training data

Regularization : Prevent the model from doing *too* well on training data

Why regularize?

- Express preferences of weights
- Make the model *simple* so it generalizes to test data
- Improve optimization by adding curvature

Regularization: Expressing Preferences

L2 Regularization

$$x = [1, 1, 1, 1]$$

$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$

$$w_1^T x = w_2^T x = 1$$

$$R(W) = \sum_k \sum_l W_{k,l}^2$$

Regularization: Expressing Preferences

L2 Regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2$$

$$x = [1, 1, 1, 1]$$


$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$


L2 regularization likes to
“spread out” the weights

$$w_1^T x = w_2^T x = 1$$


Regularization: Prefer Simpler Models



Regularization: Prefer Simpler Models



Regularization: Prefer Simpler Models



Regularization pushes against fitting the data *too* well so we don't fit noise in the data

Softmax Classifier (Multinomial Logistic Regression)

Want to interpret raw classifier scores as **probabilities**



cat	3.2
car	5.1
frog	-1.7

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

cat	3.2
car	5.1
frog	-1.7

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

cat

3.2

car

5.1

frog

-1.7

exp →

24.5

164.0

0.18

unnormalized
probabilities

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

cat 3.2
car 5.1
frog -1.7

exp

24.5
164.0
0.18

normalize

0.13
0.87
0.00

unnormalized
probabilities

probabilities

Softmax Classifier (Multinomial Logistic Regression)

Want to interpret raw classifier scores as **probabilities**



$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

cat
car
frog

3.2
5.1
-1.7

exp

24.5
164.0
0.18

normalize

0.13
0.87
0.00

Unnormalized
log-probabilities / logits

unnormalized
probabilities

probabilities

Softmax Classifier (Multinomial Logistic Regression)

Want to interpret raw classifier scores as **probabilities**



$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities



$$L_i = -\log(0.13) = 0.89$$

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i | X = x_i)$$

cat

3.2

car

5.1

frog

-1.7

exp

24.5

164.0

0.18

normalize

0.13

0.87

0.00

$$\rightarrow L_i = -\log(0.13) = 2.04$$

Unnormalized
log-probabilities / logits

unnormalized
probabilities

probabilities

Maximum Likelihood Estimation
Choose probabilities to maximize
the likelihood of the observed data
(See CS 229 for details)

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i | X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

*Kullback–Leibler
divergence*

$$D_{KL}(P||Q) = \sum_y P(y) \log \frac{P(y)}{Q(y)}$$

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

Cross Entropy

$$H(\underline{P}, \underline{Q}) = H(p) + D_{KL}(P||Q)$$

1.00
0.00
0.00

Correct
probs

Entropy

$$H(p) = - \sum_{i=1}^n p_i \log(p_i)$$

$$H(p) \geq 0 \quad \forall p, \quad H(p) = 0 \iff p = \delta_k$$
$$\nabla H(p) \leq 0 \quad \forall p, \quad \nabla H = 0 \iff p_i = \frac{1}{n}$$

**Kullback-Leibler
Divergence**

$$D_{KL}(p || q) = \sum_{i=1}^n p_i \log \left(\frac{p_i}{q_i} \right)$$


$$D_{KL}(p || q) \geq 0 \quad \forall p, q$$
$$D_{KL}(p || q) = 0 \iff p = q \text{ a.e.}$$

Cross-entropy

$$H(p, q) = - \sum_{i=1}^n p_i \log(q_i) = - \sum_{i=1}^n p_i \log(q_i) + \sum_{i=1}^n p_i \log(p_i) - \sum_{i=1}^n p_i \log(p_i)$$
$$= - \sum_{i=1}^n p_i \log(p_i) + \sum_{i=1}^n p_i \log \left(\frac{p_i}{q_i} \right) = H(p) + D_{KL}(p || q)$$

$$H(p, q) \geq H(p) \geq 0 \quad \forall p, q$$

$$H(\delta_k, q) = H(\delta_k) + D_{KL}(\delta_k || q) = 0 + \log \left(\frac{1}{q_k} \right) = - \log(q_k) \quad \forall q$$



Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

Cross Entropy

$$H(\underline{P}, \underline{Q}) = H(p) + D_{KL}(P||Q)$$

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

Cross Entropy

$$L_i = -\log(0.13) = 2.04$$

Maximum Likelihood
Estimation!

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Maximize probability of correct class

Putting it all together:

$$L_i = -\log P(Y = y_i | X = x_i)$$

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat **3.2**

car 5.1

frog -1.7

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Maximize probability of correct class

Putting it all together:

$$L_i = -\log P(Y = y_i | X = x_i)$$

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat

3.2

car

5.1

frog

-1.7

Q1: What is the min/max
possible loss L_i ?

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Maximize probability of correct class

Putting it all together:

$$L_i = -\log P(Y = y_i | X = x_i)$$

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat 3.2

car 5.1

frog -1.7

Q1: What is the min/max
possible loss L_i ?
A: min 0, max infinity

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Maximize probability of correct class

Putting it all together:

$$L_i = -\log P(Y = y_i | X = x_i)$$

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat

3.2

car

5.1

frog

-1.7

Q2: At initialization all s will be approximately equal; what is the loss?

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Maximize probability of correct class

Putting it all together:

$$L_i = -\log P(Y = y_i | X = x_i)$$

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat

3.2

car

5.1


frog

-1.7

Q2: At initialization all s will be approximately equal; what is the loss?
A: $\log(C)$, eg $\log(10) \approx 2.3$

Softmax vs. SVM


matrix multiply + bias offset



hinge loss (SVM)

$$\max(0, -2.85 - 0.28 + 1) + \max(0, 0.86 - 0.28 + 1) = 1.58$$

cross-entropy loss (Softmax)



Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

assume scores:

[10 , -2, 3]

[10 , 9, 9]

[10 , -100, -100]

and $y_i = 0$

Q: Suppose I take a datapoint and I jiggle a bit (changing its score slightly). What happens to the loss in both cases?

Recap

- We have some dataset of (x, y)
- We have a **score function**:
- We have a **loss function** :

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right) \quad \text{Softmax}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + R(W) \quad \text{Full loss}$$

How do we find the best W ?

$$s = f(x; W) \stackrel{\text{e.g.}}{=} Wx$$

