

Deep Learning


Lecture 15

What's going on inside ConvNets?

This image is CC0 public domain



Input Image:
 $3 \times 224 \times 224$




What are the intermediate features looking for?

Class Scores:
1000 numbers

Krizhevsky et al, “ImageNet Classification with Deep Convolutional Neural Networks”, NIPS 2012.
Figure reproduced with permission.

So far: CNN Architectures

AlexNet




Revolution of Depth




Figure copyright Kaiming He, 2016. Reproduced with permission.

So far: CNN Architectures



VGG16

VGG19



GoogLeNet

Revolution of Depth






Figure copyright Kaiming He, 2016. Reproduced with permission.

So far: CNN Architectures




Revolution of Depth




Figure copyright Kaiming He, 2016. Reproduced with permission.

DenseNet




Dense Block

FractalNet




Figures copyright Larsson et al., 2017. Reproduced with permission.

Last Time: CNN Architectures



Last Time: CNN Architectures



AlexNet and VGG have tons of parameters in the fully connected layers

AlexNet: ~62M parameters

FC6: $256 \times 6 \times 6 \rightarrow 4096$: 38M params


FC7: $4096 \rightarrow 4096$: 17M params

FC8: $4096 \rightarrow 1000$: 4M params

~59M params in FC layers!

ImageNet pretraining -> Instagram pretraining

Bigger models are saturated
on ImageNet, but with more
data bigger models do better




Biggest network was pretrained on
3.5B Instagram images

Trained on 336 GPUs for 22 days

Mahajan et al, "Exploring the Limits of Weakly Supervised Pretraining", arXiv 2018

ImageNet pretraining -> Instagram pretraining

Bigger models are saturated
on ImageNet, but with more
data bigger models do better



Biggest network was pretrained on
3.5B Instagram images

Trained on 336 GPUs for 22 days
 $\approx \$129,000$ on Google Cloud



Mahajan et al, "Exploring the Limits of Weakly Supervised Pretraining", arXiv 2018

Recurrent neural networks

Part 1

“Vanilla” Neural Network


one to one




Vanilla Neural Networks

Recurrent Neural Networks: Process Sequences


one to one




one to many




many to one




many to many



many to many




e.g. **Image Captioning**
image -> sequence of words




Recurrent Neural Networks: Process Sequences


one to one




one to many




many to one



many to many




many to many




e.g. **Sentiment Classification**
sequence of words -> sentiment

Recurrent Neural Networks: Process Sequences


one to one




one to many




many to one



many to many




many to many




e.g. **Machine Translation**
seq of words -> seq of words

Recurrent Neural Networks: Process Sequences


one to one




one to many




many to one




many to many




many to many




e.g. Video classification on frame level



Recurrent Neural Network



Recurrent Neural Network




Recurrent Neural Network

We can process a sequence of vectors \mathbf{x} by applying a **recurrence formula** at every time step:

$$h_t = f_W(h_{t-1}, x_t)$$

new state old state **input vector at some time step**
some function
with parameters W




Recurrent Neural Network

We can process a sequence of vectors \mathbf{x} by applying a **recurrence formula** at every time step:


$$h_t = f_W(h_{t-1}, x_t)$$

Notice: the same function and the same set of parameters are used at every time step.



(Simple) Recurrent Neural Network

The state consists of a single “*hidden*” vector \mathbf{h} :




$$h_t = f_W(h_{t-1}, x_t)$$

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$


$$y_t = W_{hy}h_t$$

Sometimes called a “Vanilla RNN” or an
“Elman RNN” after Prof. Jeffrey Elman


RNN: Computational Graph



RNN: Computational Graph




RNN: Computational Graph




RNN: Computational Graph


Re-use the same weight matrix at every time-step




RNN: Computational Graph: Many to Many




RNN: Computational Graph: Many to Many




RNN: Computational Graph: Many to Many



RNN: Computational Graph: Many to One




RNN: Computational Graph: One to Many



Sequence to Sequence: Many-to-one + one-to-many

Many to one : Encode input sequence in a single vector




Sutskever et al, “Sequence to Sequence Learning with Neural Networks”, NIPS 2014

Sequence to Sequence: Many-to-one + one-to-many

Many to one : Encode input sequence in a single vector

One to many : Produce output sequence from single input vector




Sutskever et al, "Sequence to Sequence Learning with Neural Networks", NIPS 2014

Example: Character-level Language Model

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”




Example: Character-level Language Model

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”


$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$



Example: Character-level Language Model

Vocabulary:
[h,e,l,o]


Example training
sequence:
“hello”



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling

Vocabulary:
[h,e,l,o]


At test-time sample
characters one at a time,
feed back to model



Example: Character-level Language Model Sampling


Vocabulary:
[h,e,l,o]

At test-time sample
characters one at a time,
feed back to model




Backpropagation through time

Forward through entire sequence to compute loss, then backward through entire sequence to compute gradient




Truncated Backpropagation through time




Run forward and backward
through chunks of the
sequence instead of whole
sequence

Truncated Backpropagation through time



Carry hidden states forward in time forever, but only backpropagate for some smaller number of steps

Truncated Backpropagation through time



min-char-rnn.py gist: 112 lines of Python

```
1  """
2  Minimal character-level Vanilla RNN model. Written by Andrej Karpathy (@karpathy)
3  BSD License
4  """
5  import numpy as np
6
7  # data I/O
8  data = open('input.txt', 'r').read() # should be simple plain text file
9  chars = list(set(data))
10 data_size, vocab_size = len(data), len(chars)
11 print 'data has %d characters, %d unique.' % (data_size, vocab_size)
12 char_to_ix = { ch:i for i,ch in enumerate(chars) }
13 ix_to_char = { i:ch for i,ch in enumerate(chars) }
14
15 # hyperparameters
16 hidden_size = 100 # size of hidden layer of neurons
17 seq_length = 25 # number of steps to unroll the RNN for
18 learning_rate = 1e-1
19
20 # model parameters
21 wkh = np.random.randn(hidden_size, vocab_size)*0.01 # input to hidden
22 whh = np.random.randn(hidden_size, hidden_size)*0.01 # hidden to hidden
23 why = np.random.randn(vocab_size, hidden_size)*0.01 # hidden to output
24 bh = np.zeros((hidden_size, 1)) # hidden bias
25 by = np.zeros((vocab_size, 1)) # output bias
26
27 def lossFun(inputs, targets, hprev):
28     """
29     inputs,targets are both list of integers.
30     hprev is Hx1 array of initial hidden state
31     returns the loss, gradients on model parameters, and last hidden state
32     """
33     xs, hs, ys, ps = {}, {}, {}, {}
34     hs[-1] = np.copy(hprev)
35     loss = 0
36     # forward pass
37     for t in xrange(len(inputs)):
38         xs[t] = np.zeros((vocab_size,1)) # encode in 1-of-k representation
39         xs[t][inputs[t]] = 1
40         hs[t] = np.tanh(np.dot(wkh, xs[t]) + np.dot(whh, hs[t-1]) + bh) # hidden state
41         ys[t] = np.dot(why, hs[t]) * by # unnormalized log probabilities for next chars
42         ps[t] = np.exp(ys[t]) / np.sum(np.exp(ys[t])) # probabilities for next chars
43         loss += -np.log(ps[t][targets[t],0]) # softmax (cross-entropy loss)
44     # backward pass: compute gradients going backwards
45     dwhh, dwkh, dwhy = np.zeros_like(whh), np.zeros_like(wkh), np.zeros_like(why)
46     dbh, dyb = np.zeros_like(bh), np.zeros_like(by)
47     dhnext = np.zeros_like(hs[0])
48     for t in reversed(xrange(len(inputs))):
49         dy = np.copy(ps[t])
50         dy[targets[t]] -= 1 # backprop into y
51         dwhy += np.dot(dy, hs[t].T)
52         dy += dyb
53         dh = np.dot(why.T, dy) + dhnext # backprop into h
54         ddraw = (1 - hs[t] * hs[t].T) * dh # backprop through tanh nonlinearity
55         dbh += ddraw
56         dwkh += np.dot(ddraw, xs[t].T)
57         dwhh += np.dot(ddraw, hs[t-1].T)
58         dhnext = np.dot(whh.T, ddraw)
59     for dparam in [dwhh, dwkh, dwhy, dbh, dyb]:
60         np.clip(dparam, -5, 5, out=dparam) # clip to mitigate exploding gradients
61     return loss, dwhh, dwkh, dwhy, dbh, dyb, hs[len(inputs)-1]
62
63 def sample(h, seed_ix, n):
64     """
65     sample a sequence of integers from the model
66     h is memory state, seed_ix is seed letter for first time step
67     """
68     x = np.zeros((vocab_size, 1))
69     x[seed_ix] = 1
70     ixes = []
71     for t in xrange(n):
72         h = np.tanh(np.dot(wkh, x) + np.dot(whh, h) + bh)
73         y = np.dot(why, h) + by
74         p = np.exp(y) / np.sum(np.exp(y))
75         ix = np.random.choice(range(vocab_size), p=p.ravel())
76         x = np.zeros((vocab_size, 1))
77         x[ix] = 1
78         ixes.append(ix)
79     return ixes
80
81 n, p = 0, 0
82 mwhh, mwkh, mwwhy = np.zeros_like(whh), np.zeros_like(wkh), np.zeros_like(why)
83 mbh, mby = np.zeros_like(bh), np.zeros_like(by) # memory variables for Adagrad
84 smooth_loss = -np.log(1.0/vocab_size)*seq_length # loss at iteration 0
85 while True:
86     # prepare inputs (we're sweeping from left to right in steps seq_length long)
87     if p+seq_length+1 >= len(data) or n == 0:
88         hprev = np.zeros((hidden_size,1)) # reset RNN memory
89         p = 0 # go from start of data
90     inputs = [char_to_ix[ch] for ch in data[p:p+seq_length]]
91     targets = [char_to_ix[ch] for ch in data[p+1:p+seq_length+1]]
92
93     # sample from the model now and then
94     if n % 100 == 0:
95         sample_ix = sample(hprev, inputs[0], 200)
96         txt = ''.join(ix_to_char[ix] for ix in sample_ix)
97         print '----\n%----' % (txt, )
98
99     # forward seq_length characters through the net and fetch gradient
100 loss, dwhh, dwkh, dwhy, dbh, dyb, hprev = lossFun(inputs, targets, hprev)
101 smooth_loss = smooth_loss * 0.999 + loss * 0.001
102 if n % 100 == 0: print 'iter %d, loss: %f' % (n, smooth_loss) # print progress
103
104 # perform parameter update with Adagrad
105 for param, dparam, mem in zip([wkh, whh, why, bh, by],
106                               [dwkh, dwhh, dwhy, dbh, dyb],
107                               [mwhh, mwkh, mwwhy, mbh, mby]):
108     mem += dparam * dparam
109     param -= -learning_rate * dparam / np.sqrt(mem + 1e-8) # adagrad update
110
111 p += seq_length # move data pointer
112 n += 1 # iteration counter
```



(<https://gist.github.com/karpathy/d4dee566867f8291f086>)

THE SONNETS

by William Shakespeare

From fairest creatures we desire increase,
That thereby beauty's rose might never die,
But as the riper should by time decease,
His tender heir might bear his memory:
But thou, contracted to thine own bright eyes,
Feed'st thy light's flame with self-substantial fuel,
Making a famine where abundance lies,
Thyselv thy foe, to thy sweet self too cruel:
Thou that art now the world's fresh ornament,
And only herald to the gaudy spring,
Within thine own bud buriest thy content,
And tender churl mak'st waste in niggarding:
Pity the world, or else this glutton be,
To eat the world's due, by the grave and thee.

When forty winters shall besiege thy brow,
And dig deep trenches in thy beauty's field,
Thy youth's proud livery so gazed on now,
Will be a tatter'd weed of small worth held:
Then being asked, where all thy beauty lies,
Where all the treasure of thy lusty days;
To say, within thine own deep sunken eyes,
Were an all-eating shame, and thriftless praise.
How much more praise deserv'd thy beauty's use,
If thou couldst answer 'This fair child of mine
Shall sum my count, and make my old excuse,'
Proving his beauty by succession thine!
This were to be new made when thou art old,
And see thy blood warm when thou feel'st it cold.



at first:

tyntd-iafhatawiaoihrdemot lytdws e ,tfti, astai f ogoh eoase rrranbyne 'nhthnee e
plia tkldrgd t o idoe ns,smtt h ne etie h,hregtrs nigtike,aoaenns lng

train more

"Tmont thithey" fomesscerliund
Keushey. Thom here
sheulke, anmerenith ol sivh I lalterthend Bleipile shuwy fil on aseterlome
coaniogennc Phe lism thond hon at. MeiDimorotion in ther thize."

train more

Aftair fall unsuch that the hall for Prince Velzonski's that me of
her hearly, and behs to so arwage fiving were to it beloge, pavu say falling misfort
how, and Gogition is so overelical and ofter.

train more

"Why do what that day," replied Natasha, and wishing to himself the fact the
princess, Princess Mary was easier, fed in had oftened him.
Pierre aking his soul came to the packs and drove up his father-in-law women.

PANDARUS:

Alas, I think he shall be come approached and the day
When little strain would be attain'd into being never fed,
And who is but a chain and subjects of his death,
I should not sleep.

Second Senator:

They are away this miseries, produced upon my soul,
Breaking and strongly should be buried, when I perish
The earth and thoughts of many states.

DUKE VINCENTIO:

Well, your wit is in the care of side and that.

Second Lord:

They would be ruled after this chamber, and
my fair nues begun out of the fact, to be conveyed,
Whose noble souls I'll have the heart of the wars.

Clown:

Come, sir, I will make did behold your worship.

VIOLA:

I'll drink it.

VIOLA:

Why, Salisbury must find his flesh and thought
That which I am not aps, not a man and in fire,
To show the reining of the raven and the wars
To grace my hand reproach within, and not a fair are hand,
That Caesar and my goodly father's world;
When I was heaven of presence and our fleets,
We spare with hours, but cut thy council I am great,
Murdered and by thy master's ready there
My power to give thee but so much as hell:
Some service in the noble bondman here,
Would show him to her wine.

KING LEAR:

O, if you were a feeble sight, the courtesy of your law,
Your sight and several breath, will wear the gods
With his heads, and my hands are wonder'd at the deeds,
So drop upon your lordship's head, and your opinion
Shall be against your honour.

The Stacks Project: open source algebraic geometry textbook

The Stacks Project	
home	about
tags explained	
tag lookup	browse
search	bibliography
recent comments	blog
	add slogans
Browse chapters	
Part	Chapter
Preliminaries	
	1. Introduction
	2. Conventions
	3. Set Theory
	4. Categories
	5. Topology
	6. Sheaves on Spaces
	7. Sites and Sheaves
	8. Stacks
	9. Fields
	10. Commutative Algebra
	online TeX source view pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
	online tex pdf
Parts	
1.	Preliminaries
2.	Schemes
3.	Topics in Scheme Theory
4.	Algebraic Spaces
5.	Topics in Geometry
6.	Deformation Theory
7.	Algebraic Stacks
8.	Miscellany
Statistics	
The Stacks project now consists of	
o	455910 lines of code
o	14221 tags (56 inactive tags)
o	2366 sections

Latex source

<http://stacks.math.columbia.edu/>

The stacks project is licensed under the [GNU Free Documentation License](#)

For $\bigoplus_{n=1,\dots,m} \mathcal{L}_{m,n} = 0$, hence we can find a closed subset \mathcal{H} in \mathcal{H} and any sets \mathcal{F} on X , U is a closed immersion of S , then $U \rightarrow T$ is a separated algebraic space.

Proof. Proof of (1). It also start we get

$$S = \text{Spec}(R) = U \times_X U \times_X U$$

and the comparicoly in the fibre product covering we have to prove the lemma generated by $\coprod Z \times_U U \rightarrow V$. Consider the maps M along the set of points Sch_{fppf} and $U \rightarrow U$ is the fibre category of S in U in Section, ?? and the fact that any U affine, see Morphisms, Lemma ???. Hence we obtain a scheme S and any open subset $W \subset U$ in $\text{Sh}(G)$ such that $\text{Spec}(R') \rightarrow S$ is smooth or an

$$U = \bigcup U_i \times_{S_i} U_i$$

which has a nonzero morphism we may assume that f_i is of finite presentation over S . We claim that $\mathcal{O}_{X,x}$ is a scheme where $x, x' \in S'$ such that $\mathcal{O}_{X,x'} \rightarrow \mathcal{O}'_{X',x'}$ is separated. By Algebra, Lemma ?? we can define a map of complexes $\text{GL}_{S'}(x'/S'')$ and we win. \square

To prove study we see that $\mathcal{F}|_U$ is a covering of \mathcal{X}' , and \mathcal{T}_i is an object of $\mathcal{F}_{X/S}$ for $i > 0$ and \mathcal{F}_p exists and let \mathcal{F}_i be a presheaf of \mathcal{O}_X -modules on \mathcal{C} as a \mathcal{F} -module. In particular $\mathcal{F} = U/\mathcal{F}$ we have to show that

$$\widetilde{M}^\bullet = \mathcal{I}^\bullet \otimes_{\text{Spec}(k)} \mathcal{O}_{S,s} - i_X^{-1} \mathcal{F}$$

is a unique morphism of algebraic stacks. Note that

$$\text{Arrows} = (\text{Sch}/S)^{\text{opp}}_{fppf}, (\text{Sch}/S)_{fppf}$$

and

$$V = \Gamma(S, \mathcal{O}) \longrightarrow (U, \text{Spec}(A))$$

is an open subset of X . Thus U is affine. This is a continuous map of X is the inverse, the groupoid scheme S . \square

Proof. See discussion of sheaves of sets. \square

The result for prove any open covering follows from the less of Example ???. It may replace S by $X_{\text{spaces},\text{étale}}$ which gives an open subspace of X and T equal to S_{Zar} , see Descent, Lemma ???. Namely, by Lemma ?? we see that R is geometrically regular over S .

Lemma 0.1. Assume (3) and (3) by the construction in the description.

Suppose $X = \lim |X|$ (by the formal open covering X and a single map $\underline{\text{Proj}}_X(\mathcal{A}) = \text{Spec}(B)$ over U compatible with the complex

$$\text{Set}(\mathcal{A}) = \Gamma(X, \mathcal{O}_{X,\mathcal{O}_X}).$$

When in this case of to show that $\mathcal{Q} \rightarrow \mathcal{C}_{Z/X}$ is stable under the following result in the second conditions of (1), and (3). This finishes the proof. By Definition ?? (without element is when the closed subschemes are catenary. If T is surjective we may assume that T is connected with residue fields of S . Moreover there exists a closed subspace $Z \subset X$ of X where U in X' is proper (some defining as a closed subset of the uniqueness it suffices to check the fact that the following theorem

(1) f is locally of finite type. Since $S = \text{Spec}(R)$ and $Y = \text{Spec}(R)$.

Proof. This is form all sheaves of sheaves on X . But given a scheme U and a surjective étale morphism $U \rightarrow X$. Let $U \cap U = \coprod_{i=1,\dots,n} U_i$ be the scheme X over S at the schemes $X_i \rightarrow X$ and $U = \lim_i X_i$. \square

The following lemma surjective restrocomposes of this implies that $\mathcal{F}_{x_0} = \mathcal{F}_{x_0} = \mathcal{F}_{\mathcal{X},\dots,0}$.

Lemma 0.2. Let X be a locally Noetherian scheme over S , $E = \mathcal{F}_{X/S}$. Set $\mathcal{I} = \mathcal{J}_1 \subset \mathcal{I}'_n$. Since $\mathcal{I}^n \subset \mathcal{I}^n$ are nonzero over $i_0 \leq p$ is a subset of $\mathcal{J}_{n,0} \circ \overline{A}_2$ works.

Lemma 0.3. In Situation ???. Hence we may assume $q' = 0$.

Proof. We will use the property we see that p is the next functor (??). On the other hand, by Lemma ?? we see that

$$D(\mathcal{O}_{X'}) = \mathcal{O}_X(D)$$

where K is an F -algebra where δ_{n+1} is a scheme over S . \square

Proof. Omitted. □

Lemma 0.1. Let \mathcal{C} be a set of the construction.

Let \mathcal{C} be a gerber covering. Let \mathcal{F} be a quasi-coherent sheaves of \mathcal{O} -modules. We have to show that

$$\mathcal{O}_{\mathcal{O}_X} = \mathcal{O}_X(\mathcal{L})$$

Proof. This is an algebraic space with the composition of sheaves \mathcal{F} on $X_{\text{étale}}$ we have

$$\mathcal{O}_X(\mathcal{F}) = \{\text{morph}_1 \times_{\mathcal{O}_X} (\mathcal{G}, \mathcal{F})\}$$

where \mathcal{G} defines an isomorphism $\mathcal{F} \rightarrow \mathcal{F}$ of \mathcal{O} -modules. □

Lemma 0.2. This is an integer \mathcal{Z} is injective.

Proof. See Spaces, Lemma ??.

Lemma 0.3. Let S be a scheme. Let X be a scheme and X is an affine open covering. Let $\mathcal{U} \subset \mathcal{X}$ be a canonical and locally of finite type. Let X be a scheme. Let X be a scheme which is equal to the formal complex.

The following to the construction of the lemma follows.

Let X be a scheme. Let X be a scheme covering. Let

$$b : X \rightarrow Y' \rightarrow Y \rightarrow Y \rightarrow Y' \times_X Y \rightarrow X.$$

be a morphism of algebraic spaces over S and Y .

Proof. Let X be a nonzero scheme of X . Let X be an algebraic space. Let \mathcal{F} be a quasi-coherent sheaf of \mathcal{O}_X -modules. The following are equivalent

- (1) \mathcal{F} is an algebraic space over S .
- (2) If X is an affine open covering.

Consider a common structure on X and X the functor $\mathcal{O}_X(U)$ which is locally of finite type. □

This since $\mathcal{F} \in \mathcal{F}$ and $x \in \mathcal{G}$ the diagram

$$\begin{array}{ccccc}
 S & \xrightarrow{\quad} & & & \\
 \downarrow & & & & \\
 \xi & \longrightarrow & \mathcal{O}_{X'} & & \\
 \text{gor}_s & & \uparrow & \searrow & \\
 & & & & \\
 & & =\alpha' \longrightarrow & & \\
 & & \uparrow & & \\
 & & =\alpha' \longrightarrow \alpha & & \\
 & & & & \\
 \text{Spec}(K_\psi) & & \text{Mor}_{\text{sets}} & & d(\mathcal{O}_{X_{/\kappa}}, \mathcal{G}) \\
 & & & & \downarrow X \\
 & & & &
 \end{array}$$

is a limit. Then \mathcal{G} is a finite type and assume S is a flat and \mathcal{F} and \mathcal{G} is a finite type f_* . This is of finite type diagrams, and

- the composition of \mathcal{G} is a regular sequence,
- $\mathcal{O}_{X'}$ is a sheaf of rings.

Proof. We have see that $X = \text{Spec}(R)$ and \mathcal{F} is a finite type representable by algebraic space. The property \mathcal{F} is a finite morphism of algebraic stacks. Then the cohomology of X is an open neighbourhood of U . □

Proof. This is clear that \mathcal{G} is a finite presentation, see Lemmas ??.

A reduced above we conclude that U is an open covering of \mathcal{C} . The functor \mathcal{F} is a “field”

$$\mathcal{O}_{X,x} \rightarrow \mathcal{F}_{\bar{x}} \dashv (\mathcal{O}_{X_{\text{étale}}}) \rightarrow \mathcal{O}_{X_\ell}^{-1} \mathcal{O}_{X_\lambda} (\mathcal{O}_{X_\eta}^\vee)$$

is an isomorphism of covering of \mathcal{O}_{X_ℓ} . If \mathcal{F} is the unique element of \mathcal{F} such that X is an isomorphism.

The property \mathcal{F} is a disjoint union of Proposition ?? and we can filtered set of presentations of a scheme \mathcal{O}_X -algebra with \mathcal{F} are opens of finite type over S .

If \mathcal{F} is a scheme theoretic image points. □

If \mathcal{F} is a finite direct sum \mathcal{O}_{X_λ} is a closed immersion, see Lemma ???. This is a sequence of \mathcal{F} is a similar morphism.



This repository Search

Explore Gist Blog Help



karpathy



torvalds / linux



Watch 3,711



Star 23,054



Fork 9,141

Linux kernel source tree

520,037 commits

1 branch

420 releases

5,039 contributors



branch: master -

linux / +

Code

74
Pull requests

Pulse

Graphs

HTTPS clone URL

<https://github.com/torvalds/linux>

You can clone with [HTTPS](#),
[SSH](#), or [Subversion](#). ?

Clone in Desktop

Download ZIP

Merge branch 'drm-fixes' of git://people.freedesktop.org/~airlied/linux ...

torvalds authored 9 hours ago

latest commit 4b1706927d

Documentation Merge git://git.kernel.org/pub/scm/linux/kernel/git/nab/target-pending 6 days ago

arch Merge branch 'x86-urgent-for-linus' of git://git.kernel.org/pub/scm/l... a day ago

block: discard bdi_unregister() in favour of bdi_destroy() 9 days ago

crypto Merge git://git.kernel.org/pub/scm/linux/kernel/git/herbert/crypto-2.6 10 days ago

drivers Merge branch 'drm-fixes' of git://people.freedesktop.org/~airlied/linux 9 hours ago

firmware firmware/hex2fw.c: restore missing default in switch statement 2 months ago

fs vfs: read file_handle only once in handle_to_path 4 days ago

include Merge branch 'perl-urgent-for-linus' of git://git.kernel.org/pub/scm/l... a day ago

init init: fix regression by supporting devices with major:minor:offset fo... a month ago

View on GitHub · Star · Fork · Watch · Issues · Pull Requests · Commits · Raw · History · Logos · License · About · Help · API · RSS · GitHub Pages · GitHub

```
static void do_command(struct seq_file *m, void *v)
{
    int column = 32 << (cmd[2] & 0x80);
    if (state)
        cmd = (int)(int_state ^ (in_8(&ch->ch_flags) & Cmd) ? 2 : 1);
    else
        seq = 1;
    for (i = 0; i < 16; i++) {
        if (k & (1 << i))
            pipe = (in_use & UMXTHREAD_UNCCA) +
                ((count & 0x00000000fffffff8) & 0x000000f) << 8;
        if (count == 0)
            sub(pid, ppc_md.kexec_handle, 0x20000000);
        pipe_set_bytes(i, 0);
    }
    /* Free our user pages pointer to place camera if all dash */
    subsystem_info = &of_changes[PAGE_SIZE];
    rek_controls(offset, idx, &soffset);
    /* Now we want to deliberately put it to device */
    control_check_polarity(&context, val, 0);
    for (i = 0; i < COUNTER; i++)
        seq_puts(s, "policy ");
}
```

Generated C code

```
/*
 * Copyright (c) 2006-2010, Intel Mobile Communications. All rights reserved.
 *
 * This program is free software; you can redistribute it and/or modify it
 * under the terms of the GNU General Public License version 2 as published by
 * the Free Software Foundation.
 *
 * This program is distributed in the hope that it will be useful,
 * but WITHOUT ANY WARRANTY; without even the implied warranty of
 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
 *
 * GNU General Public License for more details.
 *
 * You should have received a copy of the GNU General Public License
 * along with this program; if not, write to the Free Software Foundation,
 * Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
 */

#include <linux/kexec.h>
#include <linux/errno.h>
#include <linux/io.h>
#include <linux/platform_device.h>
#include <linux/multi.h>
#include <linux/ckevent.h>

#include <asm/io.h>
#include <asm/prom.h>
#include <asm/e820.h>
#include <asm/system_info.h>
#include <asm/seteow.h>
#include <asm/pgproto.h>
```

```
#include <asm/io.h>
#include <asm/prom.h>
#include <asm/e820.h>
#include <asm/system_info.h>
#include <asm/seteew.h>
#include <asm/pgproto.h>

#define REG_PG    vesa_slot_addr_pack
#define PFM_NOCOMP AFSR(0, load)
#define STACK_DDR(type)      (func)

#define SWAP_ALLOCATE(nr)      (e)
#define emulate_sigs() arch_get_unaligned_child()
#define access_rw(TST) asm volatile("movd %%esp, %0, %3" : : "r" (0)); \
    if (__type & DO_READ)

static void stat_PC_SEC __read_mostly offsetof(struct seq_argsqueue, \
    pC>[1]);

static void
os_prefix(unsigned long sys)
{
#ifdef CONFIG_PREEMPT
    PUT_PARAM_RAID(2, sel) = get_state_state();
    set_pid_sum((unsigned long)state, current_state_str(),
        (unsigned long)-1->lr_full; low;
}

```



thereforefilms.com/sunspring



INT. SHIP

We see H pull a book from a shelf, flip through it while speaking, and then put it back.

H

In a future with mass unemployment,
young people are forced to sell
blood. That's the first thing I can
do.

H2

You should see the boys and shut
up. I was the one who was going to
be a hundred years old.

H

I saw him again. The way you were
sent to me... that was a big honest
idea. I am not a bright light.

C

Well, I have to go to the skull. I
don't know.

He picks up a light screen and fights the security force of
the particles of a transmission on his face.

H

(continuing)
What do you mean?

C

(smiles)
I don't know anything about any of
this.

H

(to Hauk, taking his eyes
from his mouth)
Then what?

H2

There's no answer.

C

(frowning)
We're going to see the money.

H

(reading)
"All right, you can't tell me
that."

Steps back. Coffey is still going through.